

Power Control API

Development Documentation

V1.1.0

Update Records

Date	Description
2023-04-23	First Edition Release
2023-12-19	Update the API
2024-06-20	Update API and documentation

Contents

- 1 Introduction
- 1.1 Power Control Class
 - 1.1.1 Fingerprint device power on/off
 - 1.1.2 Iris power on/off
 - 1.1.3 Passport power on/off
 - 1.1.4 Ethernet power on/off
 - 1.1.5 USB camera power on/off
 - 1.1.6 ID Card power on/off
 - 1.1.7 IC Card power on/off
 - 1.1.8 Psam Card power on/off
 - 1.1.9 UHF power on/off
 - 1.1.10 QR Code power on/off
 - 1.1.11 Zink Printer power on/off
 - 1.1.12 Self-developed printer power on/off
 - 1.1.13 USB/OTG Switch
 - 1.1.14 USB/NFC power on/off
 - 1.1.15 Other device power on/off
 - 1.1.16 Buzzer power on/off
 - 1.1.17 USB power on/off
 - 1.1.18 Lan power on/off
 - 1.1.19 HDMI power on/off
 - 1.1.20 MPos power on/off
 - 1.1.21 Crypto card power on/off
 - 1.1.22 Get the DIP switch status
 - 1.1.23 Get the case box switch status

1 Introduction

Package: (com.common.apiutil.powercontrol)

Support control of fingerprint reader, 2D reading head, iris, passport, Ethernet and USB

1.1 Power Control Class

1.1.1 Fingerprint device power on/off

```
/**
 * @Function Fingerprint device power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int fingerPrintPower(int status)
```

1.1.2 Iris power on/off

```
/**
 * @Function Iris power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int irisPower(int status)
```

1.1.3 Passport power on/off

```
/**
 * @Function Passport power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
```

```
* */  
  
public synchronized int pspPower(int status)
```

1.1.4 Ethernet power on/off

```
/**  
 * @Function Ethernet power on/off  
 *  
 * @Parameter  
 * 1.status: 0, Power off; 1, Power on  
 *  
 * @Return ResultCode: please refer the quick guidance document.  
 *  
 * */  
  
public synchronized int ethernetPower(int status)
```

1.1.5 USB camera power on/off

```
/**  
 * @Function USB camera power on/off  
 *  
 * @Parameter  
 * 1.status: 0, Power off; 1, Power on  
 *  
 * @Return ResultCode: please refer the quick guidance document.  
 *  
 * */  
  
public synchronized int usbCameraPower(int status)
```

1.1.6 ID Card power on/off

```
/**  
 * @Function ID Card power on/off  
 *  
 * @Parameter  
 * 1.status: 0, Power off; 1, Power on  
 *  
 * @Return ResultCode: please refer the quick guidance document.  
 *  
 * */  
  
public synchronized int idcardPower(int status)
```

1.1.7 IC Card power on/off

```
/**
 * @Function IC Card power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int iccardPower(int status)
```

1.1.8 Psam Card power on/off

```
/**
 * @Function Psam Card power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int psamcard(int status)
```

1.1.9 UHF power on/off

```
/**
 * @Function UHF power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int uhfPower(int status)
```

1.1.10 QR Code power on/off

```

/**
 * @Function QR Code power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int decodePower(int status)

```

1.1.11 Zink Printer power on/off

```

/**
 * @Function Zink Printer power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int zinkPower(int status)

```

1.1.12 Self-developed printer power on/off

```

/**
 * @Function Self-developed printer power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public synchronized int printerPower(int status)

```

1.1.13 USB/OTG Switch

```

/**
 * @Function USB/OTG switch
 *
 * @Parameter

```

```

* 1.status: 0, ADB; 1, OTG
*
* @Return ResultCode: please refer the quick guidance document.
*
* */

```

```

public synchronized int usbPower(int status)

```

1.1.14 USB/NFC power on/off

```

/**
 * @Function NFC power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

```

```

public synchronized int nfcPower(int status)

```

1.1.15 Other device power on/off

```

/**
 * @Function Other device power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 * 2.device: Device identification character
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

```

```

public synchronized int miscPower(String device, int status)

```

1.1.16 Buzzer power on/off

```

/**
 * @Function Buzzer power on/off
 *
 * @Parameter
 * 1.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.

```



```

*
* */

public synchronized int beepPower(int status)

```

1.1.17 USB power on/off

```

/**
 * @Function USB power on/off
 *
 * @Parameter
 * 1.which: Start with 1
 * 2.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public int usbPower(int which, int status)

```

1.1.18 Lan power on/off

```

/**
 * @Function Lan power on/off
 *
 * @Parameter
 * 1.which: Start with 1
 * 2.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *
 * */

public int lanPower(int which, int status)

```

1.1.19 HDMI power on/off

```

/**
 * @Function HDMI power on/off
 *
 * @Parameter
 * 1.which: Start with 1
 * 2.status: 0, Power off; 1, Power on
 *
 * @Return ResultCode: please refer the quick guidance document.
 *

```

```
* */  
  
public int hdmiPower(int which, int status)
```

1.1.20 MPos power on/off

```
/**  
 * @Function MPos power on/off  
 *  
 * @Parameter  
 * 1.which: Start with 1  
 * 2.status: 0, Power off; 1, Power on  
 *  
 * @Return ResultCode: please refer the quick guidance document.  
 *  
 * */  
  
public int mposPower(int which, int status)
```

1.1.21 Crypto card power on/off

```
/**  
 * @Function Crypto card power on/off  
 *  
 * @Parameter  
 * 1.status: 0, Power off; 1, Power on  
 *  
 * @Return ResultCode: please refer the quick guidance document.  
 *  
 * */  
  
public int cryptoCardPower(int status)
```

1.1.22 Get the DIP switch status

```
/**  
 * @Function Get the DIP switch status  
 *  
 * @Return 0, close; 1, open; ResultCode: please refer the quick guidance  
 document.  
 *  
 * */  
  
public int getDialSwitchStatus()
```

1.1.23 Get the case box switch status

```
/**
 * @Function Get the case box switch status
 *
 * @Return 0, close; 1, open; ResultCode: please refer the quick guidance
document.
 *
 * */

public int getCaseSwitchStatus()
```