Status	Finished
Started	Thursday, 15 October 2026, 9:22 PM
Completed	Thursday, 15 October 2026, 9:31 PM
Duration	8 mins 52 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write_list()
b. write_all()
c. writelines() ✓
d. write()

The correct answer is: writelines()

Question **2**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Write
b. Read ✓
c. Append
d. Binary

The correct answer is: Read

Question **3**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and write, w+ is for append only
b. r+ is for read and write without truncating, w+ is for read and write with truncating ✓
c. r+ is for binary read and write, w+ is for text read and write
d. r+ is for read and append, w+ is for read and write

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. write() ✓
b. insert()
c. read()
d. append()

The correct answer is: write()

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. reduce()
b. shrink()
c. truncate() ✓
d. resize()

The correct answer is: truncate()

Question **6**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

- True ✓
- False

The correct answer is 'True'.

Question **7**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. 2
- b. 1
- c. garbage
- d. 0 ✓
- e. null

The correct answer is:
0

Question **8**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. moves the file pointer to the end of a file

b. move the file pointer five characters behind from the current position

c. move the file pointer five characters ahead from the current position ✓

d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **9**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. current()

b. locate()

c. position()

d. tell() ✓

The correct answer is: tell()

Question **10**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. open_file()

b. file()

c. open() ✓

d. openfile()

The correct answer is: open()

Question **11**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

- a. sets the file's current position at the offset ✓
- b. sets the file's current position within the file
- c. none of the mentioned
- d. sets the file's previous position at the offset

The correct answer is:
sets the file's current position at the offset

Question **12**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

- a. An empty string ✓
- b. EOFError
- c. 0
- d. None

The correct answer is: An empty string

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

- a. r
- b. r+ ✓
- c. w
- d. a

The correct answer is: r+

Question **14**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.is_closed()
b. file.isclosed()
c. file.closed()
d. file.closed ✓

The correct answer is: file.closed

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open("c:\\scores.txt", "rw")
b. outfile = open("c:\\scores.txt", "a") ✓
c. outfile = open(file = "c:\\scores.txt", "w")
d. outfile = open(file = "c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "a")