



VeloxMail

A simple HTTP-based API to queue and send emails using JSON and Bearer token authentication.

Base URL

<https://veloxmail.xyz/api/v1.0/>

Authentication

All requests must include a Bearer token in the `Authorization` header.

Headers

Authorization: Bearer YOUR_API_TOKEN

Content-Type: application/json

Queue Email

Queue an email for delivery.

Endpoint

POST /queueEmail

Request Body

Send a JSON payload with the email details.

Example

```
{  
  "sender_name": "Aware",  
  "recipients": "reeaz@ramoly.info",  
  "subject": "A Test Email",  
  "content": "This is an html test message."  
}
```

Parameters:

sender_name: optional

recipients: email of recipient. Currently only one email is accepted

subject: the subject of your email

content: is the content of the email you are sending

Responses

Success

HTTP 200

```
{  
  "status": true,  
  "email_id": "1234"  
}
```

Usage Examples:

PHP (cURL)

```
$base_url = "https://veloxmail.xyz/api/v1.0/";
```

```
$payload = [  
  "recipients" => "john@example.com",  
  "sender_name" => "John Doe",  
  "subject" => "Hello",  
  "content" => "<p>This is a test email</p>"  
];
```

```
$ch = curl_init($base_url . "queueEmail");
```

```
curl_setopt_array($ch, [  
  CURLOPT_RETURNTRANSFER => true,  
  CURLOPT_POST => true,  
  CURLOPT_HTTPHEADER => [  
    "Content-Type: application/json",  
    "Authorization: Bearer YOUR_API_TOKEN"  
  ],  
  CURLOPT_POSTFIELDS => json_encode($payload),
```

```
]);
```

```
$response = curl_exec($ch);
```

```
$httpcode = curl_getinfo($ch, CURLINFO_HTTP_CODE);
```

```
curl_close($ch);
```

cURL (CLI)

```
curl -X POST https://mailer.example.com/queueEmail \
```

```
-H "Authorization: Bearer YOUR_API_TOKEN" \
```

```
-H "Content-Type: application/json" \
```

```
-d '{
```

```
  "to": "john@example.com",
```

```
  "subject": "Hello",
```

```
  "body": "<p>This is a test email</p>"
```

```
}'
```