SINGLE-CHIP USB-TO-UART BRIDGE

For newer designs, the CP2102N devices offer compatible footprints and are recommended for use instead of the CP2102/9. See the Silicon Labs website (www.silabs.com/usbxpress) for more information.

Single-Chip USB to UART Data Transfer

- Integrated USB transceiver; no external resistors required
- Integrated clock; no external crystal required
- Internal 1024-byte programmable ROM for vendor ID, product ID, serial number, power descriptor, release number, and product description strings
  - EEPROM (CP2102)
  - EPROM (One-time programmable) (CP2109)
- On-chip power-on reset circuit
- On-chip voltage regulator
  - 3.3 V output (CP2102)
  - 3.45 V output (CP2109)
- 100% pin and software compatible with CP2101

USB Function Controller

- USB Specification 2.0 compliant; full-speed (12 Mbps)
- USB suspend states supported via SUSPEND pins

Asynchronous Serial Data BUS (UART)

- All handshaking and modem interface signals
- Data formats supported:
  - Data bits: 5, 6, 7, and 8
  - Stop bits: 1, 1.5, and 2
  - Parity: odd, even, mark, space, no parity
- Baud rates: 300 bps to 1 Mbps
- 576 Byte receive buffer; 640 byte transmit buffer
- Hardware or X-On/X-Off handshaking supported
- Event character support
- Line break transmission

Virtual COM Port Device Drivers

- Works with existing COM port PC Applications
- Royalty-free distribution license
- Windows 8/7/Vista/Server 2003/XP/2000
- Mac OS-X/OS-9
- Linux

USBXpress™ Direct Driver Support

- Royalty-Free Distribution License
- Windows 7/Vista/XP/Server 2003/2000
- Windows CE

Example Applications

- Upgrade of RS-232 legacy devices to USB
- Cellular phone USB interface cable
- USB interface cable
- USB to RS-232 serial adapter

Supply Voltage

- Self-powered: 3.0 to 3.6 V
- USB bus powered: 4.0 to 5.25 V

Package

- RoHS-compliant 28-pin QFN (5x5 mm)

Ordering Part Numbers

- CP2102-GM
- CP2109-A01-GM

Temperature Range: –40 to +85 °C



Figure 1. Example System Diagram

TABLE OF CONTENTS

1. System Overview

The CP2102/9 is a highly-integrated USB-to-UART Bridge Controller providing a simple solution for updating RS-232 designs to USB using a minimum of components and PCB space. The CP2102/9 includes a USB 2.0 full-speed function controller, USB transceiver, oscillator, EEPROM or EPROM, and asynchronous serial data bus (UART) with full modem control signals in a compact 5 x 5 mm QFN-28 package. No other external USB components are required.

The on-chip programmable ROM may be used to customize the USB Vendor ID, Product ID, Product Description String, Power Descriptor, Device Release Number, and Device Serial Number as desired for OEM applications. The programmable ROM is programmed on-board via the USB, allowing the programming step to be easily integrated into the product manufacturing and testing process.

Royalty-free Virtual COM Port (VCP) device drivers provided by Silicon Laboratories allow a CP2102/9-based product to appear as a COM port to PC applications. The CP2102/9 UART interface implements all RS-232 signals, including control and handshaking signals, so existing system firmware does not need to be modified. In many existing RS-232 designs, all that is required to update the design from RS-232 to USB is to replace the RS-232 level-translator with the CP2102/9. Direct access driver support is available through the Silicon Laboratories USBXpress driver set.

An evaluation kit for the CP2102 (Part Number: CP2102EK) is available. The kit includes a CP2102-based USB-to-UART/RS-232 evaluation board, a complete set of VCP device drivers, USB and RS-232 cables, and full documentation. Contact a Silicon Labs sales representative or go to www.silabs.com to order the CP2102 Evaluation Kit. The CP2102 Evaluation Kit serves as an evaluation kit for both the CP2102 and CP2109.

2. Ordering Information

Table 1. Product Selection Guide

Ordering Part Number	Internal Programmable ROM (Byte)	EEPROM	EPROM	Calibrated Internal 48 MHz Oscillator	Supply Voltage Regulator	Lead-free (RoHS-Compliant)	Package
CP2102-GM*	1024	Y	N	Y	Y	Y	QFN28
CP2109-A01-GM*	1024	N	Y	Y	Y	Y	QFN28
***Note:** Pin compatible with the CP2101-GM.							

3. Electrical Specifications

Table 2. Absolute Maximum Ratings

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Ambient Temperature under Bias	T_{BIAS}		–55	—	125	°C
Storage Temperature	T_{STG}		–65	—	150	°C
Voltage on V_{DD} with respect to GND	V_{DD}		–0.3	—	4.2	V
Maximum Total Current through V_{DD} and GND			—	—	500	mA
Maximum Output Current sunk by $\overline{RST}$ or any I/O pin			—	—	100	mA
CP2102						
Voltage on any I/O Pin, VBUS, or $\overline{RST}$ with respect to GND 相对于GND的任何I / O引脚，VBUS或RST上的电压			–0.3	—	5.8	V
CP2109						
Voltage on any I/O Pin, VBUS, or $\overline{RST}$ with respect to GND		$V_{DD} \geq 3.0$ V V_{DD} not powered	–0.3 –0.3	— —	5.8 V_{DD} + 3.6	V

Note: Stresses above those listed may cause permanent device damage. This is a stress rating only, and functional operation of the devices at or exceeding the conditions in the operation listings of this specification is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

Table 3. Recommended Operating Conditions

V_{DD} = 3.0 to 3.6 V, –40 to +85 °C unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Supply Voltage	V_{DD}		3.0	3.3	3.6	V
Supply Current - USB Pull-up[1]	I_{PU}		—	200	230	µA
Specified Operating Temperature Range	T_A		–40	—	+85	°C
Thermal Resistance[2]	θ_{JA}		—	32	—	°C/W
CP2102						
Supply Current—Normal[3]	I_{REGIN}	Normal Operation; V_{REG} Enabled	—	20	26	mA
Supply Current—Suspended[3]		Bus Powered; V_{REG} Enabled	—	80	100	µA
CP2109						
Supply Current—Normal[3]	I_{REGIN}	Normal Operation; V_{REG} Enabled	—	17	23	mA
Supply Current—Suspended[3]		Bus Powered; V_{REG} Enabled	—	90	230	µA

Notes:

1. The USB Pull-up supply current values are calculated values based on USB specifications. USB Pull-up supply current is current flowing from V_{DD} to GND through USB pull-down/pull-up resistors on D+ and D-.
2. Thermal resistance assumes a multi-layer PCB with any exposed pad soldered to a PCB pad.
3. USB Pull-up current should be added for total supply current. Normal and suspended supply current is current flowing into V_{REGIN}. Normal and suspended supply current is guaranteed by characterization.

Table 4. UART and Suspend I/O DC Electrical Characteristics

V_{DD} = 3.0 to 3.6 V, –40 to +85 °C unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Baud Rate			—	—	921600	bps
Input Leakage Current	I_L		—	25	50	µA
CP2102						
Output High Voltage	V_{OH}	I_{OH} = –10 µA I_{OH} = –3 mA I_{OH} = –10 mA	V_{DD} – 0.1 V_{DD} – 0.7 —	— — V_{DD} – 0.8	— — —	V
Output Low Voltage	V_{OL}	I_{OL} = 10 µA I_{OL} = 8.5 mA I_{OL} = 25 mA	— — —	— — 1.0	0.1 0.6 —	V
Input High Voltage	V_{IH}		2.0	—	—	V
Input Low Voltage	V_{IL}		—	—	0.8	V
CP2109						
Output High Voltage	V_{OH}	I_{OH} = –10 µA I_{OH} = –3 mA I_{OH} = –10 mA	V_{DD} – 0.1 V_{DD} – 0.2 —	— — V_{DD} – 0.4	— — —	V
Output Low Voltage	V_{OL}	I_{OL} = 10 µA I_{OL} = 8.5 mA I_{OL} = 25 mA	— — —	— — 0.6	0.1 0.4 —	V
Input High Voltage	V_{IH}		0.7 x V_{DD}	—	—	V
Input Low Voltage	V_{IL}		—	—	0.6	V

Table 5. Reset Electrical Characteristics

–40 to +85 °C unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
V_{DD} Ramp Time	t_{RMP}	Time to V_{DD} ≥ 2.7 V	—	—	1	ms
$\overline{RST}$ Low Time to Generate a System Reset	t_{RSTL}		15	—	—	µs
CP2102						
$\overline{RST}$ Input High Voltage	$V_{IHRESET}$		0.7 x V_{DD}	—	—	V
$\overline{RST}$ Input Low Voltage	$V_{ILRESET}$		—	—	0.25 x V_{DD}	V
CP2109						
$\overline{RST}$ Input High Voltage	$V_{IHRESET}$		0.75 x V_{DD}	—	—	V
$\overline{RST}$ Input Low Voltage	$V_{ILRESET}$		—	—	0.6	V

Table 6. Voltage Regulator Electrical Specifications

–40 to +85 °C unless otherwise specified.

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
CP2102						
Input Voltage Range	V_{REGIN}		4.0	—	5.25	V
Output Voltage	V_{DDOUT}	Output Current = 1 to 100 mA*	3.0	3.3	3.6	V
VBUS Detection Input Threshold	V_{VBUSTH}		1.0	1.8	2.9	V
Bias Current			—	90	—	µA
CP2109						
Input Voltage Range	V_{REGIN}		3.0	—	5.25	V
Output Voltage	V_{DDOUT}	Output Current = 1 to 100 mA*	3.3	3.45	3.6	V
VBUS Detection Input Threshold	V_{VBUSTH}		2.5	—	—	V
Bias Current			—	83	99	µA
***Note:** The maximum regulator supply current is 100 mA.						

Table 7. USB Transceiver Electrical Specifications

V_{DD} = 3.0 V to 3.6 V, –40 to +85 °C unless otherwise specified.

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Transmitter						
Output High Voltage	V_{OH}		2.8	—	—	V
Output Low Voltage	V_{OL}		—	—	0.8	V
Output Crossover Point	V_{CRS}		1.3	—	2.0	V
Output Impedance (CP2102)	Z_{DRV}	Driving High Driving Low	— —	38 38	— —	Ω
Output Impedance (CP2109)		Driving High Driving Low	— —	36 36	— —	Ω
Pull-up Resistance	R_{PU}	Full Speed (D+ Pull-up) Low Speed (D- Pull-up)	1.425	1.5	1.575	kΩ
Output Rise Time	T_R	Low Speed Full Speed	75 4	— —	300 20	ns
Output Fall Time	T_F	Low Speed Full Speed	75 4	— —	300 20	ns
Receiver						
Differential Input Sensitivity	V_{DI}	| (D+) - (D-) |	0.2	—	—	V
Differential Input Common Mode Range	V_{CM}		0.8	—	2.5	V
Input Leakage Current	I_L	Pullups Disabled	—	< 1.0	—	µA
***Note:** Refer to the USB Specification for timing diagrams and symbol definitions.						

Table 8. EPROM Electrical Characteristics

Parameter	Test Condition	Min	Typ	Max	Unit
CP2109					
Voltage on V_{PP} with respect to GND during a ROM programming operation	$V_{DD} \geq 3.3$ V	5.75	—	V_{DD} + 3.6	V
Capacitor on V_{PP} for In-system Programming		—	4.7	—	µF

4. Pinout and Package Definitions

Table 9. CP2102/9 Pin Definitions

Name	Pin #	Type	Description
V_{DD}	6	Power In Power Out	3.0–3.6 V Power Supply Voltage Input. 3.3 V Voltage Regulator Output. See "10. Voltage Regulator" on page 19.
GND	3		Ground
RST	9	D I/O	Device Reset. Open-drain output of internal POR or V_{DD} monitor. An external source can initiate a system reset by driving this pin low for at least 15 µs.
REGIN	7	Power In	5 V Regulator Input. This pin is the input to the on-chip voltage regulator.
VBUS	8	D In	VBUS Sense Input. This pin should be connected to the VBUS signal of a USB network. A 5 V signal on this pin indicates a USB network connection.
NC[1] / V_{PP}[2]	18	 A Power	This pin should be left unconnected or tied to V_{DD}. This pin is unused on the CP2102 and may be connected to the Vpp programming capacitor to maintain board compatibility with the CP2109. V_{PP} Programming Supply Voltage
D+	4	D I/O	USB D+
D–	5	D I/O	USB D–
TXD	26	D Out	Asynchronous data output (UART Transmit)
RXD	25	D In	Asynchronous data input (UART Receive)
CTS	23[3]	D In	Clear To Send control input (active low)
RTS	24[3]	D Out	Ready to Send control output (active low)
DSR	27[3]	D in	Data Set Ready control input (active low)
DTR	28[3]	D Out	Data Terminal Ready control output (active low)
DCD	1[3]	D In	Data Carrier Detect control input (active low)
RI	2[3]	D In	Ring Indicator control input (active low)
SUSPEND	12[3]	D Out	This pin is driven high when the CP2102/9 enters the USB suspend state.
$\overline{\text{SUSPEND}}$	11[3]	D Out	This pin is driven low when the CP2102/9 enters the USB suspend state.
NC	10, 13–22		These pins should be left unconnected or tied to V_{DD}.

Notes:
1. For CP2102, pin is no connect (NC).
2. For CP2109, pin is V_{PP}. V_{PP} can be left unconnected when not used for in-application programming.
3. Pins can be left unconnected when not used.



Figure 2. QFN-28 Pinout Diagram (Top View)

5. QFN-28 Package Specifications



Figure 3. QFN-28 Package Drawing

Table 10. QFN-28 Package Dimensions

Dimension	Min	Typ	Max
A	0.80	0.90	1.00
A1	0.00	0.02	0.05
A3		0.25 REF	
b	0.18	0.23	0.30
D		5.00 BSC.	
D2	2.90	3.15	3.35
e		0.50 BSC.	
E		5.00 BSC.	
E2	2.90	3.15	3.35

Dimension	Min	Typ	Max
L	0.35	0.55	0.65
L1	0.00	—	0.15
aaa		0.15	
bbb		0.10	
ddd		0.05	
eee		0.08	
Z		0.44	
Y		0.18	

Notes:

1. All dimensions shown are in millimeters (mm) unless otherwise noted.
2. Dimensioning and Tolerancing per ANSI Y14.5M-1994.
3. This drawing conforms to the JEDEC Solid State Outline MO-220, variation VHHD except for custom features D2, E2, Z, Y, and L, which are toleranced per supplier designation.
4. Recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components.



Figure 4. QFN-28 Recommended PCB Land Pattern

Table 11. QFN-28 PCB Land Pattern Dimensions

Dimension	Min	Max
C1	4.80	
C2	4.80	
E	0.50	
X1	0.20	0.30

Dimension	Min	Max
X2	3.20	3.30
Y1	0.85	0.95
Y2	3.20	3.30

Notes:

General

1. All dimensions shown are in millimeters (mm) unless otherwise noted.
2. Dimensioning and Tolerancing is per the ANSI Y14.5M-1994 specification.
3. This Land Pattern Design is based on the IPC-7351 guidelines.

Solder Mask Design

4. All metal pads are to be non-solder mask defined (NSMD). Clearance between the solder mask and the metal pad is to be 60 µm minimum, all the way around the pad.

Stencil Design

5. A stainless steel, laser-cut and electro-polished stencil with trapezoidal walls should be used to assure good solder paste release.
6. The stencil thickness should be 0.125 mm (5 mils).
7. The ratio of stencil aperture to land pad size should be 1:1 for all perimeter pins.
8. A 3x3 array of 0.90 mm openings on a 1.1 mm pitch should be used for the center pad to assure the proper paste volume (67% Paste Coverage).

Card Assembly

9. A No-Clean, Type-3 solder paste is recommended.
10. The recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components.

6. USB Function Controller and Transceiver

The Universal Serial Bus function controller in the CP2102/9 is a USB 2.0 compliant full-speed device with integrated transceiver and on-chip matching and pull-up resistors. The USB function controller manages all data transfers between the USB and the UART as well as command requests generated by the USB host controller and commands for controlling the function of the UART.

The USB Suspend and Resume signals are supported for power management of both the CP2102/9 device as well as external circuitry. The CP2102/9 will enter Suspend mode when Suspend signaling is detected on the bus. On entering Suspend mode, the CP2102/9 asserts the SUSPEND and $\overline{\text{SUSPEND}}$ signals. SUSPEND and $\overline{\text{SUSPEND}}$ are also asserted after a CP2102/9 reset until device configuration during USB Enumeration is complete.

The CP2102/9 exits Suspend mode when any of the following occur: (1) Resume signaling is detected or generated, (2) a USB Reset signal is detected, or (3) a device reset occurs. On exit of Suspend mode, the SUSPEND and $\overline{\text{SUSPEND}}$ signals are de-asserted.

Both SUSPEND and $\overline{\text{SUSPEND}}$ temporarily float high during a CP2102/9 reset. If this behavior is undesirable, a strong pulldown (10 kΩ) can be used to ensure $\overline{\text{SUSPEND}}$ remains low during reset. See Figure 5 for other recommended options.



Option 1: A 4.7 kΩ pull-up resistor can be added to increase noise immunity.
Option 2: A 4.7 µF capacitor can be added if powering other devices from the on-chip regulator.
Option 3: Avalanche transient voltage suppression diodes should be added for ESD protection. Use Littlefuse p/n SP0503BAHT or equivalent.
Option 4: 10 kΩ resistor to ground to hold $\overline{\text{SUSPEND}}$ low on initial power on or device reset.
Option 5: A 4.7 µF capacitor can be added for in-system programming (CP2109 only).

Figure 5. Typical Connection Diagram

选项1：可以添加一个4.7k?的上拉电阻，以提高抗扰度。
选项2：如果通过片上稳压器为其他器件供电，则可以添加4.7 µF电容器。
选项3：应添加雪崩瞬态电压抑制二极管以提供ESD保护。
选项3：使用Littlefuse p / n SP0503BAHT或等效产品。
选项4：接地时将10kΩ电阻接地，以将SUSPEND保持在低电平，以确保初始电源接通或器件复位。
选项5：可以添加一个4.7 µF电容器用于系统内编程（仅CP2109）。

7.异步串行数据总线（UART）接口CP2102 / 9 UART接口由TX（发送）和RX（接收）数据信号以及RTS，CTS，DSR，DTR，DCD和RI控制信号组成。 UART支持RTS / CTS，DSR / DTR和X-On / X-Off握手。

UART可编程以支持各种数据格式和波特率。 如果使用了虚拟COM端口驱动程序，则在PC上配置COM端口时会设置数据格式和波特率。 如果使用USBXpress驱动程序，则通过USBXpress API配置CP2102 / 9。 表12列出了可用的数据格式和波特率。

7. Asynchronous Serial Data Bus (UART) Interface

The CP2102/9 UART interface consists of the TX (transmit) and RX (receive) data signals as well as the RTS, CTS, DSR, DTR, DCD, and RI control signals. The UART supports RTS/CTS, DSR/DTR, and X-On/X-Off handshaking.

The UART is programmable to support a variety of data formats and baud rates. If the Virtual COM Port drivers are used, the data format and baud rate are set during COM port configuration on the PC. If the USBXpress drivers are used, the CP2102/9 is configured through the USBXpress API. The data formats and baud rates available are listed in Table 12.

Table 12. Data Formats and Baud Rates

Data Bits	5, 6, 7, and 8
Stop Bits	1, 1.5[1], and 2
Parity Type	None, Even, Odd, Mark, Space
Baud Rates[2]	300, 600, 1200, 1800, 2400, 4000, 4800, 7200, 9600, 14400, 16000, 19200, 28800, 38400, 51200, 56000, 57600, 64000, 76800, 115200, 128000, 153600, 230400, 250000, 256000, 460800, 500000, 576000, 921600[3]

Notes:
1. 5-bit only.
2. Additional baud rates are supported. See “AN721: CP210x/CP211x Device Customization Guide”.
3. 7 or 8 data bits only.

8. Internal Programmable ROM

The CP2102 includes an internal electrically erasable programmable read-only memory (EEPROM), and the CP2109 includes an internal one-time programmable (OTP) erasable programmable read-only memory (EPROM). Either may be used to customize the USB Vendor ID (VID), Product ID (PID), Product Description String, Power Descriptor, Device Release Number and Device Serial Number as desired for OEM applications. If the EEPROM/EPROM is not programmed with OEM data, the default configuration data shown in Table 13 is used. The EEPROM has a typical endurance of 100,000 write cycles with a data retention of 100 years. The EPROM can only be written one time and cannot be erased.

While customization of the USB configuration data is optional, it is recommended to customize the VID/PID combination. A unique VID/PID combination will prevent the driver from conflicting with any other USB driver. A vendor ID can be obtained from http://www.usb.org/ or Silicon Laboratories can provide a free PID for the OEM product that can be used with the Silicon Laboratories VID. It is also recommended to customize the serial number if the OEM application is one in which it is possible for multiple CP2102/9-based devices to be connected to the same PC.

The internal programmable ROM is programmed via the USB. This allows the OEM's USB configuration data and serial number to be written to the CP2102/9 on-board ROM during the manufacturing and testing process. A stand-alone utility for programming the internal programmable ROM is available from Silicon Laboratories. A library of routines provided in the form of a Windows® DLL is also available. This library can be used to integrate the programmable ROM programming step into custom software used by the OEM to streamline testing and serial number management during manufacturing.

USB descriptors can be locked to prevent future modification on the CP2102. The CP2109 can be programmed in-system over the USB interface by adding a capacitor to the PCB. If configuration ROM is to be programmed in-system, a 4.7 µF capacitor must be added between the V_{PP} pin and ground. **No other circuitry should be connected to V_{PP} during a programming operation, and V_{DD} must remain at 3.3 V or higher to successfully write to the configuration ROM.**

Table 13. Default USB Configuration Data

Name	Value
Vendor ID	10C4h
Product ID	EA60h
Power Descriptor (Attributes)	80h
Power Descriptor (Max. Power)	32h
Release Number	0100h
CP2102 Serial Number	0001 (63 characters maximum)
CP2109 Serial Number	Unique 8 character ASCII string (63 characters maximum)
CP2102 Product Description String	“CP2102 USB to UART Bridge Controller” (126 characters maximum)
CP2109 Product Description String	“CP2109 USB to UART Bridge Controller” (126 characters maximum)

8.内部可编程ROM

CP2102包括一个内部电可擦可编程只读存储器（EEPROM），CP2109包括一个内部一次性可编程（OTP）可擦可编程只读存储器（EPROM）。

可以使用这两种方法自定义USB供应商ID（VID），产品ID（PID），产品描述字符串，电源描述符，设备版本号和设备序列号，这是OEM应用程序所需的。 如果未使用OEM数据对EEPROM / EPROM进行编程，则使用表13中所示的默认配置数据。 EEPROM通常具有100,000个写入周期的耐久性，数据保留时间为100年。 EPROM只能写入一次，并且不能擦除。

虽然自定义USB配置数据是可选的，但建议自定义VID / PID组合。 独特的VID / PID组合将防止驱动程序与任何其他USB驱动程序冲突。 可以从http://www.usb.org/获得供应商ID，或者Silicon Laboratories可以为可与Silicon Laboratories VID一起使用的OEM产品提供免费的PID。 如果OEM应用程序可以将多个基于CP2102 / 9的设备连接到同一台PC，则还建议自定义序列号。

内部可编程ROM通过USB进行编程。 这样就可以在制造和测试过程中将OEM的USB配置数据和序列号写入CP2102 / 9板载ROM。 Silicon Laboratories提供了一个用于对内部可编程ROM进行编程的独立实用程序。 也可以使用以Windows®DLL形式提供的例程库。 该库可用于将可编程ROM编程步骤集成到OEM使用的定制软件中，以简化制造过程中的测试和序列号管理。

可以锁定USB描述符，以防止将来在CP2102上进行修改。 通过在PCB上增加一个电容器，可以通过USB接口在系统中对CP2109进行编程。 如果要在系统中对配置ROM进行编程，则必须在VPP引脚和地之间添加一个4.7 F电容。 在编程操作期间，不得将任何其他电路连接到VPP，并且VDD必须保持在3.3 V或更高电压才能成功写入配置ROM。

9. CP2102/9 Device Drivers

There are two sets of device drivers available for the CP2102/9 devices: the Virtual COM Port (VCP) drivers and the USBXpress Direct Access drivers. Only one set of drivers is necessary to interface with the device.

The latest drivers are available at http://www.silabs.com/support/Pages/software-downloads.aspx.

9.1. Virtual COM Port Drivers

The CP2102/9 Virtual COM Port (VCP) device drivers allow a CP2102/9-based device to appear to the PC's application software as a COM port. Application software running on the PC accesses the CP2102/9-based device as it would access a standard hardware COM port. However, actual data transfer between the PC and the CP2102/9 device is performed over the USB interface. Therefore, existing COM port applications may be used to transfer data via the USB to the CP2102/9-based device without modifying the application. See “AN197: Serial Communications Guide for the CP210x” for Example Code for Interfacing to a CP2102/9 using the Virtual COM drivers.

9.2. USBXpress Drivers

The Silicon Laboratories USBXpress drivers provide an alternate solution for interfacing with CP2102/9 devices. No Serial Port protocol expertise is required. Instead, a simple, high-level application program interface (API) is used to provide simpler CP210x connectivity and functionality. The USBXpress for CP210x Development Kit includes Windows device drivers, Windows device driver installer and uninstallers, and a host interface function library (host API) provided in the form of a Windows Dynamic Link Library (DLL). The USBXpress driver set is recommended for new products that also include new PC software. The USBXpress interface is described in “AN169: USBXpress® Programmer's Guide.”

9.3. Driver Customization

In addition to customizing the device as described in "8. Internal Programmable ROM" on page 17, the drivers and the drivers installation package can be also be customized. See “AN220: USB Driver Customization” for more information on generating customized VCP and USBXpress drivers.

9.4. Driver Certification

The default drivers that are shipped with the CP2102/9 are Microsoft WHQL (Windows Hardware Quality Labs) certified. The certification means that the drivers have been tested by Microsoft and their latest operating systems (2000, Server 2003, XP, Vista, 7, and 8) will allow the drivers to be installed without any warnings or errors. Some installations of Windows will prevent unsigned drivers from being installed at all.

The customized drivers that are generated using the AN220 software are not automatically certified. They must first go through the Microsoft Driver Reseller Submission process. Contact Silicon Laboratories support for assistance with this process.

9. CP2102 / 9设备驱动程序CP2102 / 9设备有两组可用的设备驱动程序：虚拟COM端口（VCP）驱动程序和USBXpress Direct Access驱动程序与设备接口仅需要一组驱动程序。可从http://www.silabs.com/support/Pages/software-downloads.aspx获得最新的驱动程序。

9.1。 虚拟COM端口驱动程序CP2102 / 9虚拟COM端口（VCP）设备驱动程序允许基于CP2102 / 9的设备在COM应用程序软件中显示为COM端口。 PC上运行的应用程序软件可以访问基于CP2102 / 9的设备，因为它可以访问标准的硬件COM端口。 但是，PC和CP2102 / 9设备之间的实际数据传输是通过USB接口执行的。 因此，现有的COM端口应用程序可用于通过USB将数据传输到基于CP2102 / 9的设备，而无需修改该应用程序。 有关使用虚拟COM驱动程序与CP2102 / 9接口的示例代码，请参见“ AN197：CP210x的串行通信指南 ”。

9.2。 USBXpress驱动程序Silicon Laboratories USBXpress驱动程序提供了与CP2102 / 9设备接口的替代解决方案。 不需要串行端口协议专业知识。 取而代之的是，使用简单的高级应用程序接口（API）提供更简单的CP210x连接和功能。 用于CP210x的USBXpress开发套件包括Windows设备驱动程序，Windows设备驱动程序安装程序和卸载程序，以及以Windows动态链接库（DLL）形式提供的主机接口功能库（主机API）。 建议将USBXpress驱动程序集用于还包括新PC软件的新产品。 USBXpress接口在“ AN169：USBXpress®程序员指南 ”中进行了描述。

9.3。 驱动程序自定义除了按第17页的“ 8.内部可编程ROM ”中所述自定义设备外，还可以自定义驱动程序和驱动程序安装包。 有关生成定制的VCP和USBXpress驱动程序的更多信息，请参见“ AN220：USB驱动程序定制 ”。

9.4。 驱动程序认证CP2102 / 9随附的默认驱动程序已通过Microsoft WHQL（Windows硬件质量实验室）认证。 该证书表示该驱动程序已经过Microsoft测试，其最新操作系统（2000，Server 2003，XP，Vista，7和8）将允许安装该驱动程序而不会出现任何警告或错误。 Windows的某些安装将完全阻止未签名的驱动程序的安装。 使用AN220软件生成的自定义驱动程序不会自动获得认证。 他们必须首先通过Microsoft驱动程序经销商提交过程。 请联系Silicon Laboratories支持以获取有关此过程的帮助。

10. Voltage Regulator

The CP2102/9 includes an on-chip 5 to 3 V voltage regulator. This allows the CP2102/9 to be configured as either a USB bus-powered device or a USB self-powered device. These configurations are shown in Figure 6, Figure 7, Figure 8, Figure 9, and Figure 10. When enabled, the 3 V voltage regulator output appears on the V_{DD} pin and can be used to power external 3 V devices. See Table 6 for the voltage regulator electrical characteristics.

Alternatively, if 3 V power is supplied to the V_{DD} pin, the CP2102/9 can function as a USB self-powered device with the voltage regulator disabled. For this configuration, it is recommended that the REGIN input be tied to the 3 V net to disable the voltage regulator. In addition, if VDD or REGIN may be unpowered while VBUS is 5 V, a resistor divider (or functionally-equivalent circuit) shown in Note 1 of Figure 8 and Figure 10 is required to meet the absolute maximum voltage on VBUS specification in Table 2.

The USB max power and power attributes descriptor must match the device power usage and configuration. See "AN721: CP210x/CP211x Device Customization Guide" for information on how to customize USB descriptors for the CP2102/9.

Note: It is recommended to connect additional decoupling capacitance (e.g., 0.1 µF in parallel with 1.0 µF) to the REGIN input.



Figure 6. Configuration 1: USB Bus-Powered

CP2102 / 9包含一个片上5至3 V稳压器。 这允许CP2102 / 9被配置为USB总线供电的设备或USB自供电的设备。 这些配置如图6，图7，图8，图9和图10所示。启用后，3 V稳压器输出出现在VDD引脚上，可用于为外部3 V器件供电。 有关稳压器的电气特性，请参见表6。

或者，如果将3 V电源提供给VDD引脚，则CP2102 / 9可以用作USB自供电设备，并且禁用稳压器。 对于此配置，建议将REGIN输入连接到3 V网络，以禁用稳压器。 另外，如果在VBUS为5 V时VDD或REGIN可能不通电，则需要图8和图10所示的电阻分压器（或功能等效电路）满足表2中VBUS规范上的绝对最大电压 。

USB最大功率和功率属性描述符必须匹配设备的功率使用和配置。 有关如何自定义CP2102 / 9的USB描述符的信息，请参见“ AN721：CP210x / CP211x设备自定义指南 ”。
注意：建议将额外的去耦电容（例如，0.1 µF与1.0 µF并联）连接到REGIN输入。



Figure 7. CP2102 Configuration 2: USB Self-Powered



Note 1 : For self-powered systems where VDD or REGIN may be unpowered when VBUS is connected to 5 V, a resistor divider (or functionally-equivalent circuit) on VBUS is required to meet the absolute maximum voltage on VBUS specification in the Electrical Characteristics section.

Figure 8. CP2109 Configuration 2: USB Self-Powered



Figure 9. CP2102 Configuration 3: USB Self-Powered, Regulator Bypassed



Note 1 : For self-powered systems where VDD or REGIN may be unpowered when VBUS is connected to 5 V, a resistor divider (or functionally-equivalent circuit) on VBUS is required to meet the absolute maximum voltage on VBUS specification in the Electrical Characteristics section. 注1：对于VBUS连接到5 V时VDD或REGIN可能不供电的自供电系统，要求VBUS上的电阻分压器（或功能等效电路）满足VBUS规格中的绝对最大电压 部分。

Figure 10. CP2109 Configuration 3: USB Self-Powered, Regulator Bypassed

图10. CP2109配置3：USB自供电，旁路稳压器

11. Porting Considerations from CP2102 to CP2109

This section highlights the differences between the CP2102 and CP2109. These devices are designed to be pin-compatible, and thus require very minor changes when porting hardware between devices. The CP2109 is an updated, cost-reduced version of the CP2102 with a one-time programmable ROM.

11.1. Pin-Compatibility

The CP2109 is pin-compatible with the CP2102 with a single exception; the CP2109 requires an additional capacitor between V_{PP} and GND for in-application programming. This capacitor is not required after the CP2109 EPROM has been successfully programmed or if the CP2109 does not need to be customized in system.

11.2. Distinguishing Factors

The CP2102 has 1024 bytes of EEPROM for vendor ID (VID), product ID (PID), serial number, power descriptor, release number, and product description strings. This configuration EEPROM can be written and re-written multiple times. The CP2109 has 1024 bytes of one-time programmable EPROM for configuration. This configuration EPROM can only be written one time.

The CP2109 may require an additional capacitor on V_{PP} if in-application programming is desired.

The CP2102 default serial number is always “0001”. Every CP2109 is programmed from the factory with a unique serial number.

11.3. Differences in Electrical Specifications

Table 14 and Table 15 list differences in absolute maximum and electrical specifications between the CP2102 and CP2109. Refer to "3. Electrical Specifications" on page 6 for the comprehensive electrical specifications.

Table 14. Differences in Absolute Maximum Specifications between CP2102 and CP2109

Parameter	Symbol	Test Condition	CP2102	CP2109	Unit
Voltage on any I/O Pin, VBUS, or RST with respect to GND, Maximum		V_{DD} > 3.0 V V_{DD} not powered	5.8 5.8	5.8 V_{DD} + 3.6	V

Table 15. Differences in Electrical Specifications between CP2102 and CP2109

Parameter	Symbol	Test Condition	CP2102	CP2109	Unit
Supply Current—Normal, Typical	I_{REGIN}	Normal Operation; V_{REG} Enabled	20	17	mA
Supply Current—Normal, Maximum	I_{REGIN}	Normal Operation; V_{REG} Enabled	26	23	mA
Supply Current—Suspended, Typical	I_{REGIN}	Bus Powered; V_{REG} Enabled	80	90	µA
Supply Current—Suspended, Maximum	I_{REGIN}	Bus Powered; V_{REG} Enabled	100	230	µA
Output High Voltage, Minimum	V_{OH}	I_{OH} = –3 mA	V_{DD} – 0.7	V_{DD} – 0.2	V
Output High Voltage, Typical	V_{OH}	I_{OH} = –10 mA	V_{DD} – 0.8	V_{DD} – 0.4	V
Output Low Voltage, Maximum	V_{OL}	I_{OL} = 8.5 mA	0.6	0.4	V
Output Low Voltage, Typical	V_{OL}	I_{OL} = 25 mA	1.0	0.6	V
Input High Voltage, Minimum	V_{IH}		2.0	0.7 x V_{DD}	V
Input Low Voltage, Maximum	V_{IL}		0.8	0.6	V

Table 15. Differences in Electrical Specifications between CP2102 and CP2109 (Continued)

Parameter	Symbol	Test Condition	CP2102	CP2109	Unit
$\overline{RST}$ Input High Voltage, Minimum	$V_{IHRESET}$		0.7 x V_{DD}	0.75 x V_{DD}	V
$\overline{RST}$ Input Low Voltage, Maximum	$V_{ILRESET}$		0.25 x V_{DD}	0.6	V
Regulator Input Voltage Range, Minimum	V_{REGIN}		4.0	3.0	V
Regulator Output Voltage, Minimum	V_{DDOUT}	Output Current = 1 to 100 mA*	3.0	3.3	V
Regulator Output Voltage, Typical	V_{DDOUT}	Output Current = 1 to 100 mA*	3.3	3.45	V
VBUS Detection Input Threshold, Minimum	V_{VBUSTH}		1.0	2.5	V
VBUS Detection Input Threshold, Typical	V_{VBUSTH}		1.8	—	V
VBUS Detection Input Threshold, Maximum	V_{VBUSTH}		2.9	—	V
Regulator Bias Current, Typical			90	83	µA
Regulator Bias Current, Maximum			—	99	µA
USB Transceiver Output Impedance, Typical	Z_{DRV}	Driving High Driving Low	38 38	36 36	Ω
Voltage on V_{PP} with respect to GND during a ROM programming operation, Minimum		V_{DD} > 3.3 V	—	5.75	V
Voltage on V_{PP} with respect to GND during a ROM programming operation, Maximum		V_{DD} > 3.3 V	—	V_{DD} + 3.6	V
Capacitor on V_{PP} for In-application Programming, Typical			—	4.7	µF

12. Relevant Application Notes

The following application notes are applicable to the CP2102/9. The latest versions of these application notes and their accompanying software are available at:
http://www.silabs.com/products/mcu/Pages/ApplicationNotes.aspx.

- **AN169: USBXpress® Programmer's Guide**—This application note describes the USBXpress API interface and includes example code.
- **AN197: Serial Communications Guide for the CP210x**—This application note describes how to use the standard Windows COM port function to communicate with the CP2102/9 and includes example code.
- **AN220: USB Driver Customization—**This application note describes how to use the AN220 software to customize the VCP or USBXpress drivers with OEM information.
- **AN721: CP210x/CP211x Device Customization Guide**—This application note describes how to use the AN721 software to configure the USB parameters on the CP2102/9 devices.

Document Change List

Revision 1.0 to Revision 1.1

- Updated “Linux 2.40” bullet on page 1.
- Changed MLP to QFN throughout.

Revision 1.1 to Revision 1.2

- Added additional supported operating systems on page 1.
- Changed VDD conditions of Tables 3 and 4 from a minimum of 2.7 to 3.0 V.
- Updated typical and max Supply Current number in Table 3.
- Removed tantalum requirement in Figure 5.
- Consolidated Sections 8 and 9.
- Added Section "12. Relevant Application Notes" on page 24.

Revision 1.2 to Revision 1.3

- Updated Figure 1 on page 1.
- Updated Figure 5 on page 15.
- Updated Maximum VBUS Detection Input Threshold in Table 6 on page 9.

Revision 1.3 to Revision 1.4

- Updated Table 4 RST Input Low Voltage
- Updated Table 10, Note 4.
- Updated Table 11, Note 10.

Revision 1.4 to Revision 1.5

- Added CP2109.
- Updated Single-Chip USB to UART Data Transfer bullet on page 1.
- Added CP2109 to Ordering Part Numbers on page 1.
- Updated Section "1. System Overview" on page 4.
- Updated Figure 1.
- Added Section "2. Ordering Information" on page 5.
- Added Symbol columns to Tables in Section "3. Electrical Specifications" on page 6.
- Updated Table 3.
  - Added CP2109, Note 1, Note 2.
  - Updated thermal resistance spec.
  - Updated normal supply current spec.
- Updated Table 4, added CP2109, added Baud Rate.
- Updated Table 5, added CP2109, added V_{DD} Ramp Time.
- Moved Table 6.
- Updated Table 6, added CP2109.
- Added Table 7.
- Added Table 8.
- Updated Table 9.
  - Updated pin 18 spec, Note 1, Note 2.
- Updated Figure 2, added CP2109, pin 18.
- Updated Section "6. USB Function Controller and Transceiver" on page 15, added CP2109.
- Updated Figure 5, added CP2109, Option 5.
- Updated Section "8. Internal Programmable ROM" on page 17, added CP2109.
- Updated Table 12.
  - Updated Note 2 app note reference.
- Updated Table 13.
  - Added CP2109.
- Updated Table 15.
  - Updated normal maximum and suspended maximum supply current specs.
- Updated Section "10. Voltage Regulator" on page 19, changed AN144 to AN721.
- Added Section "11. Porting Considerations from CP2102 to CP2109" on page 22.
- Updated "11.2. Distinguishing Factors" on page 22.
  - Updated CP2102 default serial number to “0001”.
- Updated Section "12. Relevant Application Notes" on page 24.
  - Replaced AN144/AN205 with AN721.

Revision 1.5 to Revision 1.6

- Added mention of VBUS in Table 2, “Absolute Maximum Ratings,” on page 6 and split out port I/O maximums for CP2102 and CP2109.
- Added V_{PP} voltage specifications to Table 8, “EPROM Electrical Characteristics,” on page 10.
- Updated "10. Voltage Regulator" on page 19 to add CP2109 absolute maximum voltage on VBUS requirements in self-powered systems.
- Updated "11.3. Differences in Electrical Specifications" on page 22 to include the new or modified specifications.

Revision 1.6 to Revision 1.7

- Added Note to front page.

Revision 1.7 to Revision 1.8

January 20, 2017

- Revised front page note.



Simplicity Studio

One-click access to MCU and wireless tools, documentation, software, source code libraries & more. Available for Windows, Mac and Linux!

IoT Portfolio
www.silabs.com/IoT

SW/HW
www.silabs.com/simplicity

Quality
www.silabs.com/quality

Support and Community
community.silabs.com

SILICON LABS®

Silicon Laboratories Inc.
400 West Cesar Chavez
Austin, TX 78701
USA

http://www.silabs.com