







Practical Anomaly Detection in Internet Services: An ISP centric approach

Alex HUANG FENG - INSA Lyon

Pierre FRANCOIS - INSA Lyon

Kensuke FUKUDA - NII Tokyo

Wanting DU - Swisscom

Thomas GRAF - Swisscom

Paolo LUCENTE - pmacct.net

Stéphane FRENOT - INSA Lyon

Index

- 1. Introduction: Anomaly Detection in Real World ISPs
 - a. Use case: Anomaly Detection in BGP/MPLS VPN environments
 - b. Current work: Anomaly Detection in Internet Services
- 2. Architecture Components
 - a. General view
 - b. Rule-based checks
- 3. Internet anomalies (2 use cases)
 - a. Losing a Top talker
 - b. Settlement-free peer traffic shifted to a transit provider
- 4. Project Status
- 5. Conclusion









Introduction

- Monitor networks holistically for an ISP is important to minimize service impact
 - Issues happen to all networks
 - Connectivity service interruptions
 - Cost you money
 - Make you look bad

- → How can we detect anomalies in real world Internet Service Providers?
- → Which data can we use to detect these anomalies? Standards?
- → Can a rule-based approach be effective in detecting such anomalies?

Media & Telecom

2 minute read · July 14, 2021 7:57 AM GMT+2 · Last Updated 2 years ago

Swisscom boss apologises for massive network outage - newspaper

Reuters



[1/2] Chief Executive Urs Schaeppi of Swiss internet, mobile phone and digital television provider Swisscom addresses the company's annual news conference in Zurich, Switzerland February 7, 2019... Read more

Source:

https://www.euronews.com/next/2021/07/14/us-swisscom-ceo









Use case: Anomaly Detection in BGP/MPLS VPN environments

- Daisy: Practical Anomaly Detection in large BGP/MPLS and BGP/SRv6 VPN Networks *
- Work presented at IRTF 117/ANRW'23 San Francisco
- Anomaly Detection based on Customer profiles
 - Set of Strategies assigned to each profile
 - Set of Rule-based Checks assigned to each Strategy
 - Execution of these Checks in Real-time in polling mode
 - Comparing traffic to last week
 - Spikes in control-plane (BGP Updates & BGP Withdraws)
 - Interface status gone DOWN
 - ..



VANG-push

Collector

Rule-based
Anomaly Detection










^{*} Alex Huang Feng, Pierre Francois, Stéphane Frenot, Thomas Graf, Wanting Du, and Paolo Lucente. 2023. Daisy: Practical Anomaly Detection in large BGP/MPLS and BGP/SRv6 VPN Networks. In Proceedings of the Applied Networking Research Workshop (ANRW '23). Association for Computing Machinery, New York, NY, USA, 8–14. https://doi.org/10.1145/3606464.3606470 (Open access: https://hal.science/hal-04307611)

Daisy: Anomaly Detection (AD)











Current work: Anomaly Detection in Internet Connectivity Services

- Plan: use same Framework to detect anomalies in services providing Internet Connectivity
- Customer Profiles: BGP Communities vs AS Number
- Implement specific Strategies for monitoring ASN traversing an ISP

- Disruptions Detection

- Losing a Top talker
- Neighbour AS has been disconnected from the Internet
- Trending analysis: Saturating a neighbour peer link

Anomaly Detection

- Traffic from a Settlement-free peer has moved to a Transit provider
- Monitor traffic ratios on Settlement-free peers
- The traffic from an AS is traversing my whole network instead of rapidly being forwarded to the shortest path
- Prefix for which RPKI was valid is not anymore
- **Security related anomalies** (low priority)
 - Prefix hijacks
 - DDoS










Architecture - High level view



Network Planes

Forwarding-plane: **IPFIX**

Control-plane: BGP & BMP

Management-plane: YANG-Push









pmacct collector: http://www.pmacct.net

^{**} Apache Kafka: https://kafka.apache.org

^{***} Apache Druid https://druid.apache.org

Rule-based checks

- IPFIX
 - Comparing total bytes to one week before
 - Comparing the slope to one week before
 - Spike in flow count
 - Spike drop counters
- BGP/BMP
 - Spike in BGP withdraw messages
 - Spike in BGP update messages
 - Spike in peer down messages
- YANG-Push
 - Interfaces changed status to DOWN

Based on what operators do when looking at the data

More to come based on post-mortem analysis!









Use case: Losing a top talker (Disruption)

Top talkers = ASN sending the most traffic to you

Flow_1:

src:198.51.100.1; dst:192.0.2.1; Bytes: 10 bytes; AS_path: <AS3303,AS64496>; AS_path_src: <AS3303,AS65536>

Flow_2:

src:192.0.2.1; dst:198.51.100.1; Bytes: 10 bytes; AS_path: <AS3303,AS65536>; AS_path_src: <AS3303,AS64496>

Top talkers: **Aggregation of flows based on last value of AS_path_src** pmacct IPFIX + BGP AS3303 Swisscom AS65536 AS64496 198.51.100.0/24 192.0.2.0/24









Use case: Losing a top talker (Disruption)

Monitor ASN on a ASN basis:

- Compare ingress* traffic to last week
- Compare ingress* slope to last week
- Spike in egress** flow count
- BGP Withdraws spike from the Origin ASN
- BGP Update spike from the Origin ASN









 $^{^{\}ast}~$ ingress traffic: Traffic going from the Origin ASN to the local ASN

 $^{^{\}ast\ast}$ egress traffic: Traffic going from the local ASN to the Destination ASN

Use case: Losing a top talker (Disruption)












Use case: Settlement-free peer traffic shifted to transit provider (Anomaly)

Flow_1 (aggregated from 2 nodes):

- src:198.51.100.1; dst:192.0.2.1; Bytes: 10 bytes; AS_path: <AS3303,AS65536>; AS_path_src: <AS3303,AS65537,AS65539>; comms: [3303:1000] (customer); comms_src: [3303:XXXX] (Upstream)

Flow_2 (aggregated from 2 nodes):

- src:198.51.100.2; dst:192.0.2.2; Bytes: 10 bytes; AS_path: <AS3303,AS65536>; AS_path_src: <AS3303,AS65537,AS65538>; comms: [3303:1000] (customer); comms_src: [3303:YYYY] (Peer)












Use case: Settlement-free peer traffic shifted to transit provider (Anomaly)

- Track for selected ASN:
 - sum of traffic coming from settlement-free peers
 - sum of traffic coming from transit providers
- 2. Track ratio over time and alert

How?

- Leveraging **BGP** communities identifying where the prefixes were learned from



Project Status

- Current Network Telemetry data:
 - IPFIX (Internet flows)
 - BGP (Internet BGP messages)
 - YANG-Push (Lab only)
- AD Strategies implemented in Python (pulling based mode)
- Checks implemented
 - VPN environments (currently deployed in prod)
 - Internet Services (WIP)
- Conducting tests in Swisscom lab
- Analysis of Swisscom Production
- Goal: deployment on a subset of ASNs based on the different use cases









Conclusion

- Network Operators want to be alerted when there are issues in their network but also want to understand why these alerts were generated
- We provide a solution based on IETF Standards to collect the data and Open-source solutions
- What's next?
 - Complete use cases on Internet Services
 - Analysis using production use cases
 - Detect missing Standard gaps to support the anomaly detection
 - For some use cases, external views (outside of the ISP) would be needed (RouteViews*)
 - Root cause analysis?









^{*} RouteViews: https://www.routeviews.org/routeviews/

Reference Papers

- Alex Huang Feng, Pierre Francois, Kensuke Fukuda, Wanting Du, Thomas Graf, et al.. **Practical Anomaly Detection in Internet Services: An ISP centric** approach. *NOMS 2024-2024 IEEE Network Operations and Management Symposium*, May 2024, Seoul, South Korea. pp.1-4, (10.1109/NOMS59830.2024.10575071). (hal-04655324)
- Alex Huang Feng, Pierre Francois, Stéphane Frenot, Thomas Graf, Wanting Du, et al.. **Daisy: Practical Anomaly Detection in large BGP/MPLS and BGP/SRv6 VPN Networks**. *ANRW 2023 : Applied Networking Research Workshop*, Jul 2023, San Francisco, United States. pp.8-14, (10.1145/3606464.3606470). (hal-04307611)









Thanks for listening

Contacts

- Alex Huang Feng (INSA Lyon): <u>alex.huang-feng@insa-lyon.fr</u>
- Pierre Francois (INSA Lyon): pierre.francois@insa-lyon.fr
- Kensuke Fukuda (NII Tokyo): <u>kensuke@nii.ac.jp</u>
- Wanting Du (Swisscom): <u>wanting.du@swisscom.com</u>
- Thomas Graf (Swisscom): thomas.graf@swisscom.com
- Paolo Lucente (NTT, pmacct.net): paolo@pmacct.net
- Stéphane Frénot (INSA Lyon): stephane.frenot@insa-lyon.fr







