
draft-ietf-netconf-yp-transport-capabilities-00

Augments "ietf-system-capabilities" to enable a client to discover the transport protocol, encoding and security capabilities of a YANG-Push publisher

thomas.graf@swisscom.com alex.huang-feng@insa-lyon.fr bill.wu@huawei.com maqiufang1@huawei.com

Integrates in the YANG-Push to Message Broker Integration Architecture



- Section 4.1 of draft-ietf-nmop-yang-message-broker-integration describes the YANG-Push subscription workflow where before the subscription configuration the transport, notification and subscription capabilities are being discovered first.
- <u>draft-ietf-netconf-yp-transport-capabilities</u> extends "ietf-system-capabilities" for discovering transport.
- This allows a client to discover all YANG-Push pulisher capabilities to enable the automation of the YANG-Push subscription configuration workflow depending on the YANG-Push server capabilities.

Extending System Capabilities for YANG-Push Configured Subscription Transport

```
module: ietf-notification-transport-capabilities
 augment /sysc:system-capabilities/notc:subscription-capabilities:
   +--ro transport-capabilities
       +--ro transport-capability* [transport-protocol]
         +--ro transport-protocol
                                     identityref
         +--ro security-protocol?
                                    identityref
         +--ro encoding-format*
                                      identityref
augment "/sysc:system-capabilities/notc:subscription-capabilities" {
   description "Add system level capability.";
   container transport-capabilities {
     description "Capabilities related to YANG-Push transports.";
     list transport-capability {
        key "transport-protocol";
       description "Capability list related to notification transport capabilities.";
       leaf transport-protocol {
          type identityref {
            base sn:transport;
          description "Supported transport protocol for YANG-Push.";
        leaf security-protocol {
          type identityref {
            base security-protocol;
          description "Type of secure transport.";
        leaf-list encoding-format {
          type identityref {
            base sn:encoding;
          description "Supported encoding formats.";
```

- <u>draft-ietf-netconf-yp-transport-capabilities</u>
 augments System Capabilities model and provides
 additional transport related attributes associated
 with system capabilities:
 - Specification of which transport protocols are supported by the router (<u>draft-ietf-netconf-udp-notif</u>, <u>draft-ietf-netconf-https-notif</u>)
 - Specification of which YANG notification encodings are supported by the transport protocol (JSON <u>RFC 8040</u>, XML <u>RFC 8040</u>, CBOR RFC 9254)
 - Specification of which secure protocols are supported for the transport protocol (DTLS RFC 9147, TLS RFC 8446, SSH RFC 4254)

draft-netana-netconf-yp-transport-capabilities-00 - Status and Next Steps

Current Status

- Document is working group adopted.
- Many thanks to Reshad, Med, Rob, Giuseppe, Nils and Benoit for the review and support.

Changes after IETF 121

- We received a review from Med, thanks a lot!
- Review was addressed in -01 as following:
 - Some editorial updates
 - TLS has now also two identities, same as DTLS for version 1.2 and 1.3, matching with what is defined in RFC 9645 (ietf-tls-server.yang)

Next Steps

- 1. Validate with implementations.
- 2. Working group last call.

thomas.graf@swisscom.com alex.huang-feng@insa-lyon.fr bill.wu@huawei.com maqiufang1@huawei.com

16. March 2025

draft-ietf-netconf-yp-transport-capabilities-00 - IETF 122 Hackathon

```
<?xml version="1.0"?>
<rpc-reply message-id="101" xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
 <data>
   <system-capabilities xmlns="urn:ietf:params:xml:ns:yanq:ietf-system-capabilities">
     <subscription-capabilities xmlns="urn:ietf:params:xml:ns:yang:ietf-notification-capabilities">
        <max-nodes-per-update>4294967295/max-nodes-per-update>
        <periodic-notifications-supported>state-changes</periodic-notifications-supported>
        <minimum-update-period>3000</minimum-update-period>
        <on-change-supported>state-changes
        <notification-metadata xmlns="urn:ietf:params:xml:ns:yang:ietf-yp-notification">
         <notification-envelope>true</notification-envelope>
         <metadata>
           <hostname-sequence-number>true</hostname-sequence-number</pre>
         </metadata>
        </notification-metadata>
         <transport-capabilities xmlns="urn:ietf:params:xml:ns:yang:ietf-notification-transport-capabilities">
           <transport-capability>
           <transport-protocol xmlns:idx="urn:ietf:params:xml:ns:yang:ietf-udp-notif-transport">idx:udp-notif </transport-protocol>
           <encoding-format xmlns:idx="urn:ietf:params:xml:ns:yang:ietf-subscribed-notifications">idx:encode-json/encoding-format>
         </transport-capability>
       </transport-capabilities>
       <yang-push-observation-supported xmlns="urn:ietf:params:xml:ns:yang:ietf-yp-observation">true</yang-push-observation-supported>
       <yang-push-module-revision-supported xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-push-revision">true</yang-push-module-revision-supported>
     </subscription-capabilities>
   </system-capabilities>
 </data>
</rpc-reply>
```