

Network UPS Tools Change Log

NUT project community contributors

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME
2.8.4.888 2.8.4.992-992+ge439012cd	2025-12-18	Current release snapshot of Network UPS Tools (NUT).	
2.8.4	2025-08-07	Fixed a few regressions introduced by release v2.8.3. Some changes to docs and recipes, especially for parallel builds. Updated NUT SEMVER definition some more. Some rounds of code-hardening project. Numerous driver updates, some new ones introduced.	JK
2.8.3	2025-04-07	Some changes to docs and recipes, libupsclient API and functionality. Updated NUT SEMVER definition and added scripting around it. Groundwork for vendor-defined status and INSTCMD buzzwords like "ECO". Fixed some regressions and added improvements for certain new device series.	JK
2.8.2	2024-04-01	Some changes to docs and recipes, libnutscan API and functionality. Added nutconf (library and tool). Fixed some regressions and added improvements for certain new device series.	JK
2.8.1	2023-10-31	Some changes to API, docs and recipes, in particular to simplify local builds and tests (e.g. to help end-users check if current NUT codebase trunk has already fixed an issue they see with a packaged installation). Revived NUT for Windows effort, further improved other OS integrations. NUT became reference for "UPS management protocol", Informational RFC 9271. Documentation files refactored to ease maintenance. More drivers and new driver categories introduced.	JK

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME
2.8.0	2022-04-26	Change of maintainer. Many changes to API, docs (both style and content), and recipes, with a stress on non-regression test-ability, run-time debug-ability, general codebase maintainability, as well as OS integrations (notably nut-driver-enumerator for systemd and SMF service instance maintenance). Added a lot in area of CI support and documented pre-requisite package lists for numerous platforms, and CI agent set-up. Added libusb-1.x support and many new driver categories (and drivers), and daisychain device connection support. Instant commands enhanced with TRACKING to enable protocol-based waiting for completion of a particular INSTCMD or SET operation.	JK
2.7.4	2016-03-09	NUT variables namespace updated, in particular for outlet groups, alarms and thresholds, ATS devices, and battery.charger.status to supersede CHRG and DISCHRG flags published in ups.status readings. NUT network protocol extended with NUMBER type; some API changes.	AQ
2.7.3	2015-04-22	Documentation revised, including some API changes. Added NUT DDL links. NUT variables namespace updated.	AQ
2.7.2	2014-04-17	The nut-website project was offloaded into a separate repository. FreeDesktop HAL support was removed (obsoleted in GNOME consumer). Introduced nutdrv_atcl_usb driver.	AQ
2.7.1	2013-11-19	NUT source codebase migrated from SVN to Git (and from Debian infrastructure to GitHub source code hosting). jNut binding split into a separate project. Introduced libnutclient (C++ binding), al175, apcupsd-ups and nutdrv_qx drivers, Mozilla NSS support for simpler licensing than OpenSSL, and a newer apcsmart implementation. Documentation support enhanced with a spell checker, contents massively updated to reflect project changes.	CL

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME
2.6.5	2012-08-08	New macosx-ups driver, new implementation of mge-shut driver. NUT variables namespace updated. Docs cleaned up and revised.	AQ
2.6.4	2012-05-31	New NUT network protocol commands (LIST CLIENTS, LIST RANGE and NETVER), and socket protocol commands (ADDRANGE, DELRANGE). NUT variables namespace updated. Introduced nut-recorder tool.	AQ
2.6.3	2012-01-04	No substantial changes to documentation.	AQ
2.6.2	2011-09-15	Introduced nut-scanner tool and nut-ipmipsu driver, systemd support, and a new apcsmart implementation.	AQ
2.6.1	2011-06-01	Introduced default.* and override.* optional settings in ups.conf, an ups.efficiency report, and outlet.0 special handling.	AQ
2.6.0	2011-01-14	First release of AsciiDoc documentation for Network UPS Tools (NUT).	AQ

Contents

1	Introduction	1
2	Very detailed Change Log	1
2.1	2025-12-17 Jim Klimov <jimklimov+nut@gmail.com>	1
2.2	2025-12-16 Jim Klimov <jimklimov+nut@gmail.com>	2
2.3	2025-12-15 Jim Klimov <jimklimov+nut@gmail.com>	2
2.4	2025-12-11 Jim Klimov <jimklimov+nut@gmail.com>	3
2.5	2025-12-09 Tormod Volden <debian.tormod@gmail.com>	3
2.6	2025-12-09 Jim Klimov <jimklimov+nut@gmail.com>	4
2.7	2025-12-07 Jim Klimov <jimklimov+nut@gmail.com>	4
2.8	2025-12-02 Jim Klimov <jimklimov+nut@gmail.com>	4
2.9	2025-11-30 jhite1234 <jhite@bebuggin.com>	4
2.10	2025-11-30 Jim Klimov <jimklimov+nut@gmail.com>	4
2.11	2025-11-29 jhite1234 <jhite@bebuggin.com>	5
2.12	2025-11-29 Jim Klimov <jimklimov+nut@gmail.com>	5
2.13	2025-11-24 Jim Klimov <jimklimov+nut@gmail.com>	5
2.14	2025-11-23 Jim Klimov <jimklimov+nut@gmail.com>	6
2.15	2025-11-23 Atanas Vladimirov <vladimirov.atanas@gmail.com>	6
2.16	2025-11-22 Jim Klimov <jimklimov+nut@gmail.com>	6
2.17	2025-11-21 Jim Klimov <jimklimov+nut@gmail.com>	6
2.18	2025-11-20 rewsssiestedbo <48805403+rewsssiestedbo@users.noreply.github.com>	7
2.19	2025-11-20 Jim Klimov <jimklimov+nut@gmail.com>	7
2.20	2025-11-19 Jim Klimov <jimklimov+nut@gmail.com>	7
2.21	2025-11-17 Jim Klimov <jimklimov+nut@gmail.com>	7
2.22	2025-11-12 atanas-vladimirov <34871743+atanas-vladimirov@users.noreply.github.com>	7
2.23	2025-11-12 Jim Klimov <jimklimov+nut@gmail.com>	7
2.24	2025-11-12 Atanas Vladimirov <vladimirov.atanas@gmail.com>	8
2.25	2025-11-11 Jim Klimov <jimklimov+nut@gmail.com>	8
2.26	2025-11-11 Atanas Vladimirov <vladimirov.atanas@gmail.com>	8
2.27	2025-11-11 Andrew J. Kroll <xxxajk@gmail.com>	8
2.28	2025-11-10 Jim Klimov <jimklimov+nut@gmail.com>	8
2.29	2025-11-10 Atanas Vladimirov <vladimirov.atanas@gmail.com>	9
2.30	2025-11-09 Jim Klimov <jimklimov+nut@gmail.com>	9
2.31	2025-11-09 Atanas Vladimirov <vladimirov.atanas@gmail.com>	9
2.32	2025-11-08 Jim Klimov <jimklimov+nut@gmail.com>	9
2.33	2025-11-08 Atanas Vladimirov <vladimirov.atanas@gmail.com>	10
2.34	2025-11-07 Jim Klimov <jimklimov+nut@gmail.com>	10

2.35	2025-11-06 Jim Klimov <jimklimov+nut@gmail.com>	11
2.36	2025-11-05 Jim Klimov <jimklimov+nut@gmail.com>	12
2.37	2025-11-03 Jim Klimov <jimklimov+nut@gmail.com>	12
2.38	2025-10-31 Jim Klimov <jimklimov+nut@gmail.com>	12
2.39	2025-10-30 NOV <149171388+NohanV@users.noreply.github.com>	12
2.40	2025-10-30 Jim Klimov <jimklimov+nut@gmail.com>	13
2.41	2025-10-29 Atanas Vladimirov <vladimirov.atanas@gmail.com>	13
2.42	2025-10-27 Jim Klimov <jimklimov+nut@gmail.com>	13
2.43	2025-10-26 Jim Klimov <jimklimov+nut@gmail.com>	13
2.44	2025-10-25 Jim Klimov <jimklimov+nut@gmail.com>	13
2.45	2025-10-24 Jim Klimov <jimklimov+nut@gmail.com>	13
2.46	2025-10-23 Jim Klimov <jimklimov+nut@gmail.com>	14
2.47	2025-10-22 Jim Klimov <jimklimov+nut@gmail.com>	14
2.48	2025-10-22 Atanas Vladimirov <vladimirov.atanas@gmail.com>	15
2.49	2025-10-21 Viktor Drobot <linux776@gmail.com>	15
2.50	2025-10-21 Jim Klimov <jimklimov+nut@gmail.com>	15
2.51	2025-10-21 Atanas Vladimirov <vladimirov.atanas@gmail.com>	16
2.52	2025-10-20 Viktor Drobot <linux776@gmail.com>	16
2.53	2025-10-20 Jim Klimov <jimklimov+nut@gmail.com>	16
2.54	2025-10-19 Jim Klimov <jimklimov+nut@gmail.com>	17
2.55	2025-10-18 Atanas Vladimirov <vladimirov.atanas@gmail.com>	17
2.56	2025-10-17 Jim Klimov <jimklimov+nut@gmail.com>	17
2.57	2025-10-16 Jim Klimov <jimklimov+nut@gmail.com>	18
2.58	2025-10-15 Jim Klimov <jimklimov+nut@gmail.com>	18
2.59	2025-10-14 Jim Klimov <jimklimov+nut@gmail.com>	19
2.60	2025-10-13 Jim Klimov <jimklimov+nut@gmail.com>	19
2.61	2025-10-12 Jim Klimov <jimklimov+nut@gmail.com>	20
2.62	2025-10-11 Jim Klimov <jimklimov+nut@gmail.com>	20
2.63	2025-10-10 Jim Klimov <jimklimov+nut@gmail.com>	21
2.64	2025-10-09 Jim Klimov <jimklimov+nut@gmail.com>	21
2.65	2025-10-08 Jim Klimov <jimklimov+nut@gmail.com>	23
2.66	2025-10-07 Jim Klimov <jimklimov+nut@gmail.com>	24
2.67	2025-10-06 Jim Klimov <jimklimov+nut@gmail.com>	25
2.68	2025-10-04 Jim Klimov <jimklimov+nut@gmail.com>	26
2.69	2025-10-02 Jim Klimov <jimklimov+nut@gmail.com>	26
2.70	2025-10-01 Jim Klimov <jimklimov+nut@gmail.com>	26
2.71	2025-09-30 Jim Klimov <jimklimov+nut@gmail.com>	28
2.72	2025-09-29 Jim Klimov <jimklimov+nut@gmail.com>	28
2.73	2025-09-28 Nick Briggs <nicholas.h.briggs@gmail.com>	29

2.74	2025-09-25	Jim Klimov <jimklimov+nut@gmail.com>	29
2.75	2025-09-24	Jim Klimov <jimklimov+nut@gmail.com>	30
2.76	2025-09-23	Jim Klimov <jimklimov+nut@gmail.com>	30
2.77	2025-09-22	Jim Klimov <jimklimov+nut@gmail.com>	30
2.78	2025-09-21	Jim Klimov <jimklimov+nut@gmail.com>	31
2.79	2025-09-19	Jim Klimov <jimklimov+nut@gmail.com>	31
2.80	2025-09-18	Jim Klimov <jimklimov+nut@gmail.com>	31
2.81	2025-09-12	Jim Klimov <jimklimov+nut@gmail.com>	31
2.82	2025-09-11	Jim Klimov <jimklimov+nut@gmail.com>	32
2.83	2025-09-10	Jim Klimov <jimklimov+nut@gmail.com>	32
2.84	2025-09-08	Jim Klimov <jimklimov+nut@gmail.com>	32
2.85	2025-09-07	Jim Klimov <jimklimov+nut@gmail.com>	33
2.86	2025-09-06	desertwitch <24509509+desertwitch@users.noreply.github.com>	33
2.87	2025-09-05	Jim Klimov <jimklimov+nut@gmail.com>	33
2.88	2025-09-04	Jim Klimov <jimklimov+nut@gmail.com>	33
2.89	2025-09-03	Laurent Bigonville <bigon@bigon.be>	34
2.90	2025-09-03	Jim Klimov <jimklimov+nut@gmail.com>	34
2.91	2025-09-02	Jim Klimov <jimklimov+nut@gmail.com>	34
2.92	2025-09-02	Hector Martin <marcan@marcan.st>	34
2.93	2025-08-31	Jim Klimov <jimklimov+nut@gmail.com>	34
2.94	2025-08-21	me <me@LIONINE>	34
2.95	2025-08-09	Colin Dean <colindean@users.noreply.github.com>	35
2.96	2025-08-08	Jim Klimov <jimklimov+nut@gmail.com>	35
2.97	2025-07-30	Jim Klimov <jimklimov+nut@gmail.com>	35
2.98	2025-07-08	Jim Klimov <jimklimov+nut@gmail.com>	35
2.99	2024-01-31	Charles Lepple <clepple+nut@gmail.com>	36
2.100	2024-01-25	Charles Lepple <clepple+nut@gmail.com>	36
2.101	2023-02-28	Jim Klimov <jimklimov+nut@gmail.com>	36
2.102	2022-02-10	Jim Klimov <jim@jimklimov.com>	36
2.103	2022-02-09	Jim Klimov <jim@jimklimov.com>	36
2.104	2021-08-13	Clément <perrettecl@users.noreply.github.com>	36
2.105	2021-08-12	Clément <perrettecl@users.noreply.github.com>	36
2.106	2021-05-18	Clappier, Eric <EricClappier@Eaton.com>	36
2.107	2021-05-17	Clément <clementperrette@eaton.com>	36
2.108	2021-05-04	Jim Klimov <jim@jimklimov.com>	36
2.109	2021-02-10	Jim Klimov <jim@jimklimov.com>	37
2.110	2021-01-21	Jim Klimov <jim@jimklimov.com>	37
2.111	2021-01-20	Jim Klimov <jim@jimklimov.com>	37
2.112	2020-03-14	Jim Klimov <jim@jimklimov.com>	37

2.1132019-12-06 Jim Klimov <jim@jimklimov.com>	37
2.1142019-04-12 Jim Klimov <jim@jimklimov.com>	37
2.1152019-04-03 Jim Klimov <jim@jimklimov.com>	37
2.1162019-02-20 Jim Klimov <jim@jimklimov.com>	37
2.1172018-12-06 Jim Klimov <jim@jimklimov.com>	38
2.1182018-10-05 Jim Klimov <jim@jimklimov.com>	38
2.1192018-09-28 Jim Klimov <jim@jimklimov.com>	38
2.1202018-09-27 Jim Klimov <jim@jimklimov.com>	38
2.1212018-09-26 Jim Klimov <jim@jimklimov.com>	38
2.1222018-09-06 Jim Klimov <jim@jimklimov.com>	39
2.1232018-09-05 Jim Klimov <jim@jimklimov.com>	39
2.1242018-09-03 Jim Klimov <jim@jimklimov.com>	39
2.1252018-01-15 Jim Klimov <jim@jimklimov.com>	39
2.1262018-01-03 Jim Klimov <jim@jimklimov.com>	39
2.1272018-01-02 Jim Klimov <jim@jimklimov.com>	39
2.1282017-12-31 Jim Klimov <jim@jimklimov.com>	39
2.1292017-10-19 Jim Klimov <jim@jimklimov.com>	39
2.1302017-10-13 Jim Klimov <jim@jimklimov.com>	39
2.1312017-04-12 Jim Klimov <jim@jimklimov.com>	40
2.1322016-10-06 Arnaud Quette <arnaud.quette@free.fr>	40
2.1332016-09-22 Jim Klimov <jim@jimklimov.com>	40
2.1342016-09-14 Jim Klimov <jim@jimklimov.com>	40
2.1352016-08-19 Jim Klimov <jim@jimklimov.com>	40
2.1362016-08-18 Jim Klimov <jim@jimklimov.com>	41

1 Introduction

The primary goal of the Network UPS Tools (NUT) project is to provide support for Power Devices, such as Uninterruptible Power Supplies, Power Distribution Units and Solar Controllers.

2 Very detailed Change Log

This document intends to detail the change log for relatively recent work (roughly since the source code was tracked in Git).

Note

This change log section represents git commits in range `v2.8.4..HEAD` (commits `434cb36a3..e439012cd`).

2.1 2025-12-17 Jim Klimov <jimklimov+nut@gmail.com>

- `common/common.c`, `include/common.h`, `scripts/Windows/wininit.c`, `server/upsd.c`, `drivers/upsdrvctl.c`: refactor with a `getfullpath2()` to mix configure script options and hard-coded fallbacks [#3207]
 - `NEWS.adoc`: document fixes for WIN32 path resolution [#3207, #3063, #3065, #3219]
 - `common/common.c`: `confpath()`: first try `getfullpath(CONFPATH)`, only then fall back to `getfullpath(PATH_ETC)` [#3207]
 - `common/common.c`: `WIN32 getfullpath()`: fix some off-by-one errors and add debug tracing [#3207]
 - `drivers/upsdrvquery.c`: fix logging of failed `WaitNamedPipe`
 - `tests/NIT/nit.sh`: report if GID/UID was not found to offset "if test..." not-a-number errors [#1209]
 - `scripts/Windows/build-mingw-nut.sh`: fix back the location for NUT config files in reference WIN32 builds [broken by #3049]
 - `scripts/Windows/wininit.c`: also use `PATH_SBIN` to `upsdrvctl stop` [#3207, #3065]
 - `drivers/upsdrvctl.c`: look for drivers in `DRVPATH` in WIN32 too [#3207, #3065]
 - `common/common.c`: `getfullpath()`: allow passing "relative_path" with absolute-ish values from NUT build and convert them to be relative to the installed binary [#3207]
 - `common/common.c`: `getfullpath()`: avoid "DIRNAME../etc" kind of bugs
 - should be "DIRNAME../etc" [#3219]
 - `common/common.c`: refactor `getfullpath()` style and comments [#3207]
 - `Makefile.am`: `all-fanout-maybe`: report when optimized build is finished and we hand off to "make all" default implementation (may regenerate headers again) [#3039]
 - `Makefile.am`: do not default `NUT_VERSION_H_GENERATED=true` (at the cost that we would retry it once in "make all" default implementation) [#3039]
 - `common/Makefile.am`, `include/Makefile.am`, `tools/nut-scanner/Makefile.am`: do not skip rebuilding of `nut_version.h` if it is currently missing [#3039] May have been removed since, e.g. in `make check-parallel-builds`.
 - `tools/nut-scanner/Makefile.am`, `include/Makefile.am`, `common/Makefile.am`: streamline debugging of `MAINTAINER_GENERATE_H` [#3039]
 - `common/Makefile.am`, `tools/nut-scanner/Makefile.am`: consider `NUT_VERSION_H_GENERATED` in transitive dependency definition [#3039]
 - `docs/nut-versioning.adoc`: do not group non-C usages under "Use in C code" title
-

- tools/semver-compare.sh: for "test" action, quietly ignore trailing "]" or "]" and warn if any other trailing args exists and would be ignored [#3055]
- tools/semver-compare.sh: wrap help text so it fits in 80 cols (mostly) [#3055]
- docs/nut-versioning.adoc, docs/nut.dict: document semver-compare.sh [#3055]
- scripts/Solaris/reset-usb-solaris.sh.sample: use configure-script or otherwise detected functional GREP/EGREP if possible [#3099]
- scripts/Windows/dllldd.sh, scripts/Windows/build-mingw-prereqs.sh, Makefile.am: use configure-detected GREP and EGREP if possible [#3099]
- scripts/installer/common/ipp-status, scripts/installer/common/shutdown, scripts/installer/install.sh: scripts/installer/*: recognize primary/secondary upsmon roles [#2288, #840]
- scripts/installer/common/ipp-os-shutdown, scripts/installer/common/ipp-status, scripts/installer/install.sh, scripts/installer/make_package.sh: scripts/installer/*: use configure-script or otherwise detected functional GREP/EGREP if possible [#3099]
- scripts/installer/aix/aix_init, scripts/installer/common/aix_init, scripts/installer/common/init, scripts/installer/common/ipp-event.sh, scripts/installer/common/ipp-host-shutdown.sample, scripts/installer/common/ipp-notifier.sh, scripts/installer/common/ipp-os-shutdown, scripts/installer/common/ipp-shutdown-daemon.sh, scripts/installer/common/ipp-status, scripts/installer/common/ipp-wrapper, scripts/installer/common/shutdown, scripts/installer/common/solaris_init, scripts/installer/install.sh, scripts/installer/make_package.sh, scripts/installer/solcmn/solaris_init, scripts/installer/uninstall-ipp: scripts/installer/*: bump copyrights for NUT community maintained version [#2288, #2621]

2.2 2025-12-16 Jim Klimov <jimklimov+nut@gmail.com>

- tools/semver-compare.sh: with fixed-width strings instead of numbers, we can forgo the "sort -n", it is confusing on some systems [#3055] NetBSD, looking at you: (echo 0001 0030 ; echo 0001 0003) \ sort inverses order with sort -n
- tools/semver-compare.sh: rectify printf vs octal numbers (if there are leading zeroes) [#3055]
- tools/gitlog2version.sh, tools/semver-compare.sh: fix numeric envvar/CLI arg evaluation for ksh [#3055] ... where [" -ge 0] ; echo \$? does not report a non-numeric error, but succeeds instead.
- tools/gitlog2version.sh: make SCRIPT_DIR always known (so we can find semver-compare.sh helper) [#3055]
- tests/nut-driver-enumerator-test.sh: add testcase_semver_compare() [#3055]
- tools/semver-compare.sh: add "[[" alias to test action, and non-equality checks [#3055]
- tools/semver-compare.sh: add dashless aliases to expand and strip actions [#3055]
- tests/nut-driver-enumerator-test.sh: update comments for testcase_gitlog2version() [#3055]
- tests/nut-driver-enumerator-test.sh: update head comment [#3055]
- tools/semver-compare.sh: add an option to reverse-sort the versions [#3055]
- NEWS.adoc, tools/Makefile.am, tools/gitlog2version.sh, tools/semver-compare.sh: tools/semver-compare.sh, tools/gitlog2version.sh: refactor expand/strip logic out of gitlog2version.sh; add more abilities to it [#3055]

2.3 2025-12-15 Jim Klimov <jimklimov+nut@gmail.com>

- docs/FAQ.txt, docs/nut.dict: write down ideas from discussions about power race avoidance and killing UPS power when handling an outage [#1950, #2836] Mentored-by: Joshua M. Clulow <josh@sysmgr.org> Mentored-by: Lennart Poettering <lennart@poettering.net>
- NEWS.adoc, docs/nut-versioning.adoc, tests/nut-driver-enumerator-test.sh, tools/gitlog2version.sh: tools/gitlog2version.sh, tests/nut-driver-enumerator-test.sh, docs/nut-versioning.adoc: introduce NUT_VERSION_STRIP_LEADING_ZEROES [#3055]

- docs/nut-versioning.adoc: document more about the NUT_VERSION_QUERY=VER5X etc modes [#3055]
- tools/gitlog2version.sh: move filter_extra_width() up and rename to filter_add_extra_width() [#3055]
- docs/nut-versioning.adoc: rebalance examples for VER5X and DESC5X to consume about the same column width [#3055]

2.4 2025-12-11 Jim Klimov <jimklimov+nut@gmail.com>

- tools/gitlog2version.sh: simplify use of printf (variable width support is not ubiquitous) [#3055]
- docs/nut-versioning.adoc: more fix to asciidoc markup
- tools/gitlog2version.sh: filter_extra_width(): fix formatting string for printf() [#3055] busybox sh printf is strict enough to care about the dot
- tests/nut-driver-enumerator-test.sh: fix running the test suite itself by ksh [#3055] By default, VAR=VAL cmd sets VAR=VAL in the current shell and does not inherit it into cmd (nor reset it after the call).
- tools/gitlog2version.sh: avoid substituting backslash-N via SED [#3055, #3099]
- tools/gitlog2version.sh: avoid using alternation in SED [#3055, #3099]
- scripts/upsdrvsvccctl/nut-driver-enumerator.sh.in: substitute @SED@ to hopefully have the version with alternation support [#3099]
- docs/nut-versioning.adoc: list example values in tables always as bullet-points so monospace is honoured by asciidoc
- docs/nut-versioning.adoc: revise asciidoc markup (broken in the table context)
- docs/nut-versioning.adoc: note that we MAY sometime return to the more idiomatic adherence to SEMVER standard and/or even/odd numbering to maintain release and development branches
- NEWS.adoc: document changes of gitlog2version.sh and tests for it [#3055]
- tools/gitlog2version.sh, tests/nut-driver-enumerator-test.sh: add a fallback mode for NUT_VERSION_DEFAULT=X.Y.Z(.W)\+gHAS (missing the commit count) [#3055]
- tools/gitlog2version.sh: fix escaping of doublequote missed earlier [#3196]
- docs/nut-versioning.adoc, docs/nut.dict, tools/gitlog2version.sh: tools/gitlog2version.sh: getver_default(): parse non-RC NUT_VERSION values in legacy mode [#3055]
- tests/nut-driver-enumerator-test.sh: extend with some tests for tools/gitlog2version.sh [#3055] Overall, we want to make sure the script works across different shell interpreters and toolkits, and that a NUT_VERSION_FORCED saved for a dist tarball would be consistently treated by the non-git mode as well.
- tests/nut-driver-enumerator-test.sh: add a FAILFAST=true mode support [#3055]
- tools/gitlog2version.sh: fix RC version comparison in legacy mode
- tools/gitlog2version.sh, docs/nut-versioning.adoc: introduce NUT_VERSION_QUERY=VER5x etc. to simplify alphanumeric comparisons of different NUT releases [#3055]
- tools/gitlog2version.sh: only read VERSION_FORCED(_SEMVER) file(s) if respective envvars were not passed in env [#3055]
- tools/gitlog2version.sh: update comments

2.5 2025-12-09 Tormod Volden <debian.tormod@gmail.com>

- drivers/usb-common.c: usb-common.c: Fix truncation in nut_usb_get_string() References #3201

2.6 2025-12-09 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/usb-common.c: nut_usb_get_string(): combine the fix for "buflen vs ret/2" with log warning from issue discussion [#3201, #3211] Proposed-by: Tormod Volden <debian.tormod@gmail.com>
- NEWS.adoc: document the fix for nut_usb_get_string() [#3211]

2.7 2025-12-07 Jim Klimov <jimklimov+nut@gmail.com>

- Makefile.am, include/Makefile.am: introduce NUT_VERSION_H_GENERATED to pass run-time skip of active include/nut_version.h regeneration [#3039]
- NEWS.adoc, drivers/libhid.c, drivers/usb-common.c: NEWS.adoc, drivers/libhid.c::HIDGetIndexString(), drivers/usb-common.c::nut_trace the bytes going around [#3201, #2604]
- drivers/libhid.c: improve debugability of HIDDumpTree() Make it easier to see in debug log where processing of an entry starts

2.8 2025-12-02 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/01-make-dist.yml: fix dist/doc tarballs of PRs being made for target branch in fact
- docs/man/meanwell_ntu.txt: minor style and phrasing changes [#3206]
- drivers/meanwell_ntu.c: adjust indentations etc. with NUT style guide [#3206]
- docs/man/meanwell_ntu.txt: link to vendor doc file, it is very good [#3206]
- docs/man/meanwell_ntu.txt, drivers/meanwell_ntu.c: suggest and disregard similarity with Megatec Qx protocol [#3206]
- docs/man/meanwell_ntu.txt: fix dangling white-space chars [#3206]
- docs/man/meanwell_ntu.txt: fix UTF char in ASCII text [#3206]

2.9 2025-11-30 jhite1234 <jhite@bebuggin.com>

- docs/man/meanwell_ntu.txt: spelling
- docs/man/meanwell_ntu.txt: NUT style formatting and linkman useage
- drivers/meanwell_ntu.c: more CI fixes for OmniOS and OpenIndiana
- drivers/meanwell_ntu.c: small updates for CI fixes

2.10 2025-11-30 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/meanwell_ntu.c: make DRIVER_VERSION double-digit [#3206]
 - NEWS.adoc: introduced meanwell_ntu driver [#3206]
-

2.11 2025-11-29 jhite1234 <jhite@bebuggin.com>

- docs/nut.dict: dictionary update
- drivers/meanwell_ntu.c: fixes for CI build checks
- drivers/meanwell_ntu.c: meanwell_ntu: drop termios.h include
- data/driver.list.in: Add Mean Well NTU Series entry to driver.list.in
- drivers/meanwell_ntu.c: meanwell_ntu: use experimental.* vars and standard ups.mode
- docs/man/Makefile.am, drivers/Makefile.am: Add Mean Well NTU inverter/UPS driver
- docs/man/meanwell_ntu.txt, drivers/meanwell_ntu.c: Add Mean Well NTU inverter/UPS driver

2.12 2025-11-29 Jim Klimov <jimklimov+nut@gmail.com>

- docs/config-prereqs.txt: refer also to "Building NUT for in-place upgrades or non-disruptive tests" from "Prerequisites for building NUT on different OSes" as the two chapters are closely coupled
- docs/config-prereqs.txt: revise instructions for (now older) Debian 12

2.13 2025-11-24 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc: update about fixed back/double quoted shell scripting nuances [#3196]
 - Makefile.am, docs/Makefile.am, docs/man/Makefile.am, scripts/python/Makefile.am, scripts/python/module/Makefile.am, test-s/Makefile.am, tools/Makefile.am: */Makefile.am: revise shell script syntax with backticks and double-quotes; single-quote Make variable expansions into shell [#3196]
 - docs/docinfo.xml.sh.in: revise shell script syntax with backticks and double-quotes [#3196]
 - docs/ci-farm-lxc-setup.txt: revise shell script syntax with backticks and double-quotes [#3196]
 - tools/nut-ddl-dump.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - tools/nut-dumpdiff.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - tools/gitlog2version.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - tools/driver-list-format.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/valgrind/valgrind.sh.in: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/upsdrvsvccctl/upsdrvsvccctl.in: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/upsdrvsvccctl/nut-driver-enumerator.sh.in: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/subdriver/gen-usbhid-subdriver.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/subdriver/gen-snmp-subdriver.sh: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/python/app/NUT-Monitor: revise shell script syntax with backticks and double-quotes [#3196]
 - scripts/obs/nut.spec: revise packaging and init shell script syntax with backticks and double-quotes [#3196]
 - scripts/installer/aix/aix_init, scripts/installer/common/init, scripts/installer/common/ipp-event.sh, scripts/installer/common/ipp-host-shutdown.sample, scripts/installer/common/ipp-os-shutdown, scripts/installer/common/ipp-shutdown-daemon.sh, scripts/installer/status, scripts/installer/common/ipp-wrapper, scripts/installer/common/shutdown, scripts/installer/install.sh, scripts/installer/uninstall-ipp: scripts/installer/*: revise packaging and init shell script syntax with backticks and double-quotes [#3196]
-

- scripts/Aix/nut.init.in, scripts/Solaris/postinstall.in, scripts/Solaris/preinstall.in, scripts/Solaris/preremove.in, scripts/Solaris/reset-ups-usb-solaris.sh.sample: scripts/{Aix,Solaris}: revise packaging and init shell script syntax with backticks and double-quotes [#3196]
- scripts/fuse/execfuse-nut/getattr, scripts/fuse/execfuse-nut/read_file, scripts/fuse/execfuse-nut/readdir: scripts/fuse/*: revise shell script syntax with backticks and double-quotes [#3196]
- scripts/Windows/build-mingw-nut.sh, scripts/Windows/build-mingw-prereqs.sh, scripts/Windows/dllltd.sh: scripts/Windows/*.sh: revise shell script syntax with backticks and double-quotes [#3196]
- configure.ac, m4/ax_realpath.m4, m4/ax_realpath_lib.m4, m4/nut_check_aspell.m4, m4/nut_check_libavahi.m4, m4/nut_check_libfreexl.m4, m4/nut_check_libgd.m4, m4/nut_check_libltdl.m4, m4/nut_check_libmodbus.m4, m4/nut_check_libneon.m4, m4/nut_check_libnetsnmp.m4, m4/nut_check_libnss.m4, m4/nut_check_libopenssl.m4, m4/nut_check_libregex.m4, m4/nut_check_libusb.m4, m4/nut_check_libwpa.m4, m4/nut_check_python.m4, m4/nut_compiler_family.m4: configure.ac, m4/*.m4: revise shell script syntax with backticks and double-quotes [#3196]
- ci_build.sh: revise shell script syntax with backticks and double-quotes [#3196]
- autogen.sh: revise shell script syntax with backticks and double-quotes [#3196]
- tests/NIT/nit.sh: revise shell script syntax with backticks and double-quotes [#3196]
- tests/nut-driver-enumerator-test.sh: revise shell script syntax with backticks and double-quotes [#3196]
- tests/nut-driver-enumerator-test.sh: double-quote \$0 name inspection, safely for shell script syntax with backticks and double-quotes [#3196]
- tests/nut-driver-enumerator-test.sh: support passing-or-failing tests (for syntax not supported by all of ksh implementations) [#3196]
- tests/nut-driver-enumerator-test.sh: report if the failure could be due to unsupported or not-found shell interpreter [#3196]

2.14 2025-11-23 Jim Klimov <jimklimov+nut@gmail.com>

- tests/nut-driver-enumerator-test.sh: see now backticks and doublequotes play together in different shells [#3196]

2.15 2025-11-23 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- NEWS.adoc: Update the PR number.
- NEWS.adoc, drivers/nutdrv_qx.c: nutdrv_qx: Hides QX_FLAG_NONUT variables from syslog. One can see them by raising the debug level. Tested on A1000

2.16 2025-11-22 Jim Klimov <jimklimov+nut@gmail.com>

- Makefile.am: shellcheck-nde: be sure to test freshly generated script text
- scripts/upsdrvsvcctl/nut-driver-enumerator.sh.in, NEWS.adoc: revise message logging in the script [#3194]

2.17 2025-11-21 Jim Klimov <jimklimov+nut@gmail.com>

- docs/man/nut.txt: update sentence markup; expand on built-in vs configurable use of user/group accounts at run-time
 - docs/common.xsl, docs/man/asciidoc.conf.in: inherit style of anchorjs permalinks from the (heading) element they are in [#3185]
 - drivers/tripplite_usb.c, NEWS.adoc: bump the version and add news entry for PR #3192
-

2.18 2025-11-20 rewsssiestedbo <48805403+rewsssiestedbo@users.noreply.github.com>

- drivers/tripplite_usb.c: Update tripplite_usb.c to fix issue 3191 Use correct value (DEFAULT_UPSID) for the actual unit_id default value instead of a 32-bit -1 value. DEFAULT_UPSID is 65535, or a 16-bit -1 value.

2.19 2025-11-20 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/nutdrv_qx_masterguard.c: driver/nutdrv_qx_masterguard.c: bump version [#3181]

2.20 2025-11-19 Jim Klimov <jimklimov+nut@gmail.com>

- docs/Makefile.am, Makefile.am, NEWS.adoc: introduce SPELLCHECK_QUICK=true toggle for interactive mode to not re-check documents that passed with older nut.dict Follow-up to [#2871]
- docs/common.xsl, docs/man/asciidoc.conf.in, COPYING, NEWS.adoc, docs/nut.dict: stash a copy of "AnchorJS - v5.0.0 - 2023-01-18" to add permalinks to HTML sections [#3185] One for docbook ⇒ large HTML (single and chunked docs, technically also PDF but it will likely ignore the JavaScript or not see the tags where it goes), another for manpages via xhtml. Closes: [#3185]

2.21 2025-11-17 Jim Klimov <jimklimov+nut@gmail.com>

- docs/nut.dict: add British "ageing" for the keyword on the progress in getting old [#3181]
- docs/new-drivers.txt, docs/nut.dict: docs/new-drivers.txt: document addvar, getval and testvar, and nut_usb_addvars (and planned ser/modbus siblings) [#2419, #2748] Documentation addition triggered by discussion in [#3181]

2.22 2025-11-12 atanas-vladimirov <34871743+atanas-vladimirov@users.noreply.github.com>

- NEWS.adoc: Update the PR number.

2.23 2025-11-12 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc: formatting and typo fixes for masterguard QX updates [#3181]
- UPGRADING.adoc: new *.html.sample templates to consider [#3180]
- clients/upsclient.c: upscli_splitaddr(): highlight that currently a "port" must be numeric
- clients/upsc.c: return valid JSON documents also in case of error [#3178]
- clients/Makefile.am, common/Makefile.am, include/Makefile.am, {common ⇒ include}/strjson.h: includes/strjson.h: keep common headers in one place [#3178]
- clients/Makefile.am: limit use of libcommonstrjson.la to upsc and upsstats.cgi [#3178]
- .github/workflows/01-make-dist.yml: shorten workflow name, move details into job name [#1400] The workflow name is a shared prefix now for the job itself and for final "URL" entry that poses as a GHA check result. A prefix too long hides valuable data, especially in the latter case.

2.24 2025-11-12 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- NEWS.adoc, data/cmdvartab, docs/man/nutdrv_qx.txt, docs/nut-names.txt, docs/nut.dict, drivers/nutdrv_qx_masterguard.c: nutdrv_qx_masterguard: Adds a clear.fault.record instant command Also adds two experimental variables: - battery.ageing.factor ("Battery ageing factor in promille) and - battery.calibration.factor (Battery calibration factor in percent). Tested on A1000 and A2000 units
- NEWS.adoc: Update the PR number.
- NEWS.adoc, conf/upsstats-single.html.sample, conf/upsstats.html.sample: upsstats*.html.sample: Enhance model detection in upsstats HTML templates. Some devices lack ups.model, causing the CGI to incorrectly report "Not supported".
- clients/Makefile.am: Make sure libcommonstrjson.la dependencies exist

2.25 2025-11-11 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/01-make-dist.yml: Create new GH Check report via shell/cURL [#1400]
- .github/workflows/01-make-dist.yml, NEWS.adoc, docs/download.txt: drop experiments with updates of GH Check reports, and noise with PR/commit comments - leave just a new GH Check entry with text of the URL (and link to details page with clickable URL) [#1400]
- clients/upsmon.c, scripts/systemd/nutshutdown.in: comments to clarify that POWERDOWNFLAG can happen on both NUT servers and pure client machines
- configure.ac, NEWS.adoc: align British vs Americanish English spelling [#1400]
- clients/upsstats.c: json_escape(): reduce the char value range-check [#3171] Avoid comparison is always true due to limited range of data type warning.

2.26 2025-11-11 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- common/strjson.c, common/strjson.h: strjson.c, strjson.h: Add newline at end of files
- NEWS.adoc: Update the PR number.
- Makefile.am, NEWS.adoc, clients/Makefile.am, clients/upsc.c, clients/upsstats.c, common/Makefile.am, common/strjson.c, common/strjson.h, docs/man/upsc.txt: upsc: Add -j option for JSON output This commit introduces a new -j command-line flag to upsc to provide machine-readable JSON output for all operating modes. To support this and share logic with upsstats, the JSON string escaping logic has been refactored into a new, reusable module: - A new helper function json_print_esc() now lives in common/strjson.c - common/Makefile.am builds this as a new libcommonstrjson library. - clients/Makefile.am links both upsc and upsstats against this new library and adds the common/ include path. - upsstats.c is updated to use the shared json_print_esc() function.

2.27 2025-11-11 Andrew J. Kroll <xxxajk@gmail.com>

- scripts/python/app/NUT-Monitor-py2gtk2.in, scripts/python/app/NUT-Monitor-py3qt5.in: fix notification spamming

2.28 2025-11-10 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/01-make-dist.yml: PoC with LouisBrunner/checks-action to change the action/check entry itself (as alternative to PR/commit comments) [#1400]
 - clients/upsstats.c: printf("%x") requires an UNSIGNED int argument [#3171]
 - UPGRADING.adoc: configure script would now probe the OS for more user and group account names [#3173]
 - configure.ac, NEWS.adoc: warn if nobody or nogroup end up being used for a build [#3173]
-

- configure.ac, NEWS.adoc, docs/configure.txt: support more default user/group account names that may be defined in the OS [#3173]
- NEWS.adoc: rephrase the upsstats\+JSON entry [#3171]

2.29 2025-11-10 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- docs/man/upsstats.cgi.txt: Use `devices` instead of `upses`.

2.30 2025-11-09 Jim Klimov <jimklimov+nut@gmail.com>

- server/sstate.c, NEWS.adoc: wait a second before declaring UPS data stale [#661]
- docs/download.txt: align British vs Americanish English spelling [#1400]
- .github/workflows/01-make-dist.yml: drop MAKE_DIST_TOKEN [#1400]
- .github/workflows/01-make-dist.yml: drop commented-away permissions [#1400]
- docs/download.txt: revise notes on snapshots (not only GitHub now) and build types (git/dist) [#1400]

2.31 2025-11-09 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- NEWS.adoc, clients/upsstats.c, docs/man/upsstats.cgi.txt: upsstats: Add JSON output mode via `?json` parameter When the `?json` (or `&json`) parameter is added to the URL, upsstats.cgi will now bypass all HTML template processing. Instead, it returns a "Content-Type: application/json" response containing the full data for the requested UPS(es), including all variables, raw status, and parsed status. This provides a modern API for external monitoring tools without affecting the existing HTML template functionality.

2.32 2025-11-08 Jim Klimov <jimklimov+nut@gmail.com>

- docs/download.txt: move notes about building from source upwards [#1400]
 - docs/download.txt: add intro for development sources chapter [#1400]
 - NEWS.adoc: update about links to automatic dist tarballs [#1400]
 - .github/workflows/01-make-dist.yml: drop superfluous comment-posting action [#1400]
 - .github/workflows/01-make-dist.yml: update comments [#1400]
 - .github/workflows/01-make-dist.yml: extend to contents:write permission for commit comments [#1400]
 - .github/workflows/01-make-dist.yml: add links for running a custom container inside GHA worker [#1400]
 - .github/workflows/01-make-dist.yml: expand criteria for comment posting [#1400]
 - .github/workflows/01-make-dist.yml: debug-print inputs for substitution [#1400]
 - .github/workflows/01-make-dist.yml: try to blend in the github.event.pull_request.number to subst-github-ref-name [#1400]
 - .github/workflows/01-make-dist.yml: do not fail if we can not post the commit comment [#1400]
 - .github/workflows/01-make-dist.yml: rephrase initial sticky note for the PR [#1400]
 - .github/workflows/01-make-dist.yml: attempt to post a comment for commit itself [#1400]
 - .github/workflows/01-make-dist.yml: uncomment attempts to post comments with PR context only [#1400]
 - .github/workflows/01-make-dist.yml: drop the list of wider permissions we experimented with [#1400]
-

- .github/workflows/01-make-dist.yml: comment away one of the ways to post a sticky comment; both seem to work well [#1400]
- .github/workflows/01-make-dist.yml: try to report the more correct Git SHA with the tarball link [#1400]
- NEWS.adoc: fix asciidoc markup for upsset improvement [#3164]
- .github/workflows/01-make-dist.yml: subst-github-ref-name prefer github.head_ref (if set) since github.ref_name for pull_request_target reports the target branch [#1400]
- drivers/nhs_ser.c, NEWS.adoc: limit the use of baud rates by what the OS does declare [#3163]

2.33 2025-11-08 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- NEWS.adoc, clients/upsset.c: upsset.c: Recognize RANGE NUMBER and NUMBER types. Tested on Masterguard A1000 and A2000 units.

2.34 2025-11-07 Jim Klimov <jimklimov+nut@gmail.com>

- docs/qa-guide.adoc: expand chapter on OBS [#1209]
- .github/workflows/01-make-dist.yml: fix message [#1400]
- .github/workflows/01-make-dist.yml: introduce "make distcheck-completeness" to verify that our dist archives exactly reproduce themselves [#2829]
- Makefile.am, NEWS.adoc: introduce "make distcheck-completeness" to verify that our dist archives exactly reproduce themselves [#2829]
- .github/workflows/01-make-dist.yml: refer to links from GH checks entry title [#1400] We have hit some snags about changing the artifact history or adding PR comments, at least before initially merging the first PR that adds this workflow (so pull_request_target has something to run from the master branch at all). Even if this turns out to be the end of the road, at least this way we can let people know where to find those generated tarballs :)
- .github/workflows/01-make-dist.yml: try pull_request_target again, to use context of the main repo for actions [#1400]
- .github/workflows/01-make-dist.yml: Revert ".github/workflows/01-make-dist.yml: add permissions for delete artifact [#1400]" This reverts commit 621e0e71aed71da21521ecf7784ece4b892720d0.
- .github/workflows/01-make-dist.yml: try using a custom MAKE_DIST_TOKEN [#1400]
- .github/workflows/01-make-dist.yml: add permissions for delete artifact [#1400]
- scripts/obs/debian.control: Revert "scripts/obs/debian.control: dumb down the libmodbus requirement [#1209]" This reverts commit 21e5d7a79d8e3432c6382252c667eae3fb9e6223. Dropped NUT CI OBS support for platforms it still refuses to build instead.
- scripts/obs/debian.control: Revert "scripts/obs/debian.control: dumb down the libi2c requirement [#1209]" This reverts commit 313e13e8fcae4f59d74ed20da7709d286dee14b7. Dropped NUT CI OBS support for platforms it still refuses to build instead.
- scripts/obs/nut.spec: Revert "scripts/obs/nut.spec: try to constrain udev to non-RHEL [#1209]" This reverts commit 2b1a596f364ab172. Dropped NUT CI OBS support for platforms it still refuses to build instead.
- scripts/obs/nut.spec: try to constrain udev to non-RHEL [#1209]
- scripts/obs/debian.control: dumb down the libi2c requirement [#1209]
- scripts/obs/debian.control: dumb down the libmodbus requirement [#1209] Do not constrain the versions so it can build on Debian 9 and 10; Note that for USB support we would need our fork anyway (until it gets merged to upstream, which may take years at their pace).

- scripts/obs/nut.spec: more constraints about what is available in what distro versions [#1209]
- scripts/obs/nut.spec: libltdl-devel (nut-scanner and consumers) and libgd-devel (cgi) are not ubiquitous [#1209]
- scripts/obs/nut.spec: fix "distro_version" numbers (some have extra digits for sub-releases) [#1209]
- scripts/obs/_config: no ccache in RHEL_7 it seems [#1209]
- scripts/obs/_config: CentOS 10 depends on "either of" util-linux(-core), so we must pick one [#1209]
- scripts/obs/nut.spec: define NUTPKG_WITH_<DEPNAME> when we require the deps or not, based on distro/release [#1209]
- scripts/obs/nut.spec: turn package availability/requirement for NUTPKG_WITH_* upside down [#1209]
- .github/workflows/01-make-dist.yml: comment about substitute-string-action [#1400]
- .github/workflows/01-make-dist.yml: try "issues: write" into permissions [#1400]
- .github/workflows/01-make-dist.yml: try more ways to post a PR comment [#1400]

2.35 2025-11-06 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/01-make-dist.yml: try to use GITHUB_TOKEN when posting a PR comment - v2 [#1400]
- .github/workflows/01-make-dist.yml: define permissions for auto-generated GITHUB_TOKEN differently [#1400]
- .github/workflows/01-make-dist.yml: no fatal problem if we can not delete an older tarball [#1400]
- .github/workflows/01-make-dist.yml: try to use GITHUB_TOKEN when posting a PR comment [#1400]
- .github/workflows/01-make-dist.yml: do not immediately fail the CI job if we can not post actions-comment-pull-request (e.g. in a NUT fork build) [#1400]
- .github/workflows/01-make-dist.yml: after all use pull_request not pull_request_target so there is an attached PR to comment into [#1400]
- .github/workflows/01-make-dist.yml: allow to fire on more branches [#1400]
- .github/workflows/01-make-dist.yml: try to fix permissions for PR commenter [#1400]
- .github/workflows/01-make-dist.yml: fix step IDs [#1400]
- .github/workflows/01-make-dist.yml: "Try to get more Git metadata" only if "git describe" is initially useless [#1400]
- .github/workflows/01-make-dist.yml: tell actions/checkout to fetch more git history right away [#1400]
- .github/workflows/01-make-dist.yml: "Try to get more Git metadata" earlier so we can debug it better [#1400]
- .github/workflows/01-make-dist.yml: typo fix (renamed subst-github-ref-name step) [#1400]
- .github/workflows/01-make-dist.yml: flip TEST_REF for branches and commits (prNNNN/merge) alike [#1400]
- .github/workflows/01-make-dist.yml: different var for built SHA [#1400]
- .github/workflows/01-make-dist.yml: more trickery to make git-describe work [#1400]
- .github/workflows/01-make-dist.yml: debug subst-github-ref-name [#1400]
- .github/workflows/01-make-dist.yml: try to post a link to tarballs on build page - v2 (message/comment in PRs) [#1400]
- .github/workflows/01-make-dist.yml: there is no env.GITHUB_HEAD_REF [#1400]
- .github/workflows/01-make-dist.yml: act on tags too [#1400]
- .github/workflows/01-make-dist.yml: pull whole repo if git describe fails [#1400]
- .github/workflows/01-make-dist.yml: try to post a link to tarballs on build page [#1400]

- `.github/workflows/01-make-dist.yml`: fix GHA scripting syntax; update comments [#1400]
- `.github/workflows/01-make-dist.yml`: more debugging of git workspace [#1400]
- `.github/workflows/01-make-dist.yml`: do not make `dist-sig` (via `dist-files`) in the CI job [#1400]
- `.github/workflows/01-make-dist.yml`, `NEWS.adoc`: introduce a CI job to maintain `dist` tarballs of recent iterations [#1400, #2829]
- `.github/workflows/{codeql.yml ⇒ 05-codeql.yml}`, `.github/workflows/{PyNUTClient.yml ⇒ 08-PyNUTClient.yml}`: `.github/workflows`: re-number the jobs to hopefully impact processing order on GHA farm [#1400]
- `Makefile.am`, `NEWS.adoc`, `docs/maintainer-guide.txt`: introduce `make dist-docs` [#1400]
- `Makefile.am`: `dist-hook`: report if DISTing `VERSION_FORCED*` files
- `.github/workflows/codeql.yml`: fix typo for `ccache` key name

2.36 2025-11-05 Jim Klimov <jimklimov+nut@gmail.com>

- `common/common.c`: do not track `upsnotify_reported_extend_timeout_systemd`, we do not limit by it anyway [#3003] ... and in the few cases this `systemd` notification is used, we do want to see it all
- `common/common.c`, `NEWS.adoc`: do not comment on "watchdog situation logged once" if we do not actually log it before (visibly) [#3157]

2.37 2025-11-03 Jim Klimov <jimklimov+nut@gmail.com>

- `NEWS.adoc`, `drivers/dstate.c`, `drivers/dstate.h`, `drivers/main.c`, `drivers/main.h`: `drivers/main.{c,h}`, `drivers/dstate.{c,h}`, `NEWS.adoc`: track `CHRG/DISCHRG` reality in all drivers, verify against what the device/protocol says [#3146]
- `drivers/usbhid-ups.c`: only consider `current_charge > 0` to rule out a conversion error [#3156]
- `drivers/usbhid-ups.c`: fix indentations
- `NEWS.adoc`, `common/state.c`, `docs/nut.dict`, `include/state.h`: `common/state.c`, `include/state.h`, `NEWS.adoc`: refactor with `diff_time_st_tree_timespec()` [#3156]
- `NEWS.adoc`, `drivers/dstate.c`, `drivers/dstate.h`, `drivers/main.c`, `drivers/main.h`: `drivers/main.{c,h}`, `drivers/dstate.{c,h}`, `NEWS.adoc`: track `previous_battery_charge_value` and `previous_battery_charge_timestamp` [#3146]
- `clients/upsmon.c`, `include/common.h`: tone down definition of "infinity" by a notch [#3003]

2.38 2025-10-31 Jim Klimov <jimklimov+nut@gmail.com>

- `NEWS.adoc`, `drivers/usbhid-ups.c`, `drivers/usbhid-ups.h`: `drivers/usbhid-ups.{c,h}`, `NEWS.adoc`: consider `FULLYCHARGED` and `NOTFULLYCHARGED` separately, because many subdrivers report neither; fall back to checking `battery.charge=?100` to set `CHRG` flag [#3146]

2.39 2025-10-30 NOV <149171388+NohanV@users.noreply.github.com>

- `drivers/cyberpower-mib.c`: Add `SNMP` info for `ups.realpower`
-

2.40 2025-10-30 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/libusb0.c, drivers/libusb1.c: drivers/libusb{0,1}.c: nut_libusb_open(): drop commented-away "goto next_device" now that we have a loop and "continue" to try another rdlen [#3136]
- drivers/cyberpower-mib.c: bump CYBERPOWER_MIB_VERSION for added ups.realpower [#3154]
- configure.ac, scripts/systemd/nut-monitor.service.in: introduce SYSTEMD_DAEMON_TIMEOUT_STOP_UPSMON substitution [#3003]
- clients/upsmon.c: use upsnotify(NOTIFY_STATE_EXTEND_TIMEOUT, ...) to protect from systemd or similar framework killing us by timeout [#3033]
- common/common.c, include/common.h, NEWS.adoc: Introduced NOTIFY_STATE_EXTEND_TIMEOUT option and relevant variables [#3003]
- common/common.c: upsnotify(): comment since which systemd versions different features are supported

2.41 2025-10-29 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- docs/man/nutdrv_qx.txt: Fix the formatting of VOLTRONIC-AXPERT UNITS

2.42 2025-10-27 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upsmon.c, NEWS.adoc: doshutdown() etc: tickle (systemd) watchdog instead of long quietness when shutting down [#3003]
- NEWS.adoc, drivers/libusb0.c, drivers/libusb1.c: drivers/libusb{0,1}.c, NEWS.adoc: if the tried "rdlen" did not succeed, fall back to the other value we had in mind [#3136] In libusb1.c also fix printout of rdlen variables from %d to %PRIi32

2.43 2025-10-26 Jim Klimov <jimklimov+nut@gmail.com>

- .obs/workflows.yml: retarget to "home:networkupstools:*" OBS project for now, and expand workflows for PRs, master iterations and tag releases [#1209]
- .obs/workflows.yml: extend workflow definition [#1209] Revised docs at https://openbuildservice.org/help/manuals/obs-user-guide/cha-obs-scm-ci-workflow-integration#sec.obs.obs_scm_ci_workflow_integration.setup.token_authentication.how_to_authentication
- .obs/workflows.yml: Introduce an OBS workflow [#1209] Follow <https://openbuildservice.org/2021/05/31/scm-integration/instructions>

2.44 2025-10-25 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/obs/Makefile.am: fix EXTRA_DIST list

2.45 2025-10-24 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc, docs/nut.dict: NEWS.adoc: announce upstreamed OBS packaging recipes [#1209, #3136, #3144]
- tests/NIT/nit.sh: detect PYTHON from caller-provided PYTHON_DEFAULT as fallback interpreter [#3130]
- configure.ac: on MacOS, also pass PYTHON_DEFAULT via /usr/bin/env [#3130]
- tests/NIT/nit.sh: detect PYTHON from PY_SHEBANG (or use a caller-provided one) as explicit interpreter [#3130] CircleCI does see the correct shebang and the script as executable, but apparently tries to call it as a shell script and fails. Maybe /Users/distiller/.pyenv/shims/python3.13 is broken though?.. Or we hit <https://github.com/NixOS/nixpkgs/issues/65351> ?

- .circleci/config.yml: set DEBUG_NIT=true to troubleshoot python test client runs [#3130]
- tests/NIT/nit.sh: shouldDebug(): extend with a variable that can be set specifically for this script
- .circleci/config.yml: opt out of blobless checkouts
- .circleci/config.yml: update from XCode-13.4.1 to XCode-16.4 Older releases are deprecated and to be removed in November:
* <https://circleci.com/changelog/deprecation-of-eol-xcode-versions/> * <https://circleci.com/changelog/images/#filtered>
- tests/NIT/nit.sh: revise isTestablePython() possible outcomes [#3130]
- .github/workflows/PyNUTClient.yml: update to use PYTHON_DEFAULT varname now expected by scripts/python/module/-
Makefile.am [#3130]
- NEWS.adoc, UPGRADING.adoc: warn about renamed data/html{,cgi} source dir [#3049]
- lib/.gitignore, lib/libupsclient-config.in: lib/libupsclient-config.in, lib/.gitignore: README⇒README.adoc renamed a while ago
- NEWS.adoc, UPGRADING.adoc: warn about renamed data/html{,cgi} source dir [#3049]
- scripts/obs/debian.nut-cgi.docs: align with renaming of data/html ⇒ data/htmlcgi

2.46 2025-10-23 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc, drivers/apc-hid.c, drivers/apc_modbus.c, drivers/arduino-hid.c, drivers/bcmxcp_usb.c, drivers/blazer_usb.c, drivers/cps-hid.c, drivers/delta_ups-hid.c, drivers/legrand-hid.c, drivers/liebert-hid.c, drivers/mge-hid.c, drivers/nutdrv_atcl_usb.c, driver-s/richcomm_usb.c: drivers/*.c, NEWS.adoc: revised use of NUT macros for USB Vendor IDs [#3139]
- drivers/usb-common.h: update comment about USB_DEVICE() macro
- drivers/nutdrv_qx.c: use symbolic names for USB Vendor IDs [#3139]
- data/driver.list.in: add Ippon Innova TAE 1000 [#3137, #3139]
- NEWS.adoc, UPGRADING.adoc, drivers/nutdrv_qx.c: drivers/nutdrv_qx.c: add USB ID based detection for innovatae protocol [#3137, #3139]
- NEWS.adoc, UPGRADING.adoc, docs/nut.dict: list new nutdrv_qx_innovatae protocol support [#issue 3137, PR #3139]

2.47 2025-10-22 Jim Klimov <jimklimov+nut@gmail.com>

- docs/nut.dict: update for NEWS of PR #3141
 - m4/nut_check_libregex.m4, NEWS.adoc: Added configure script options for libregex tuning [#3140, #3049]
 - NEWS.adoc, docs/nut.dict: update about logging the source of CFLAGS/LIBS/LDFLAGS values [#3049, #3140]
 - m4/nut_check_libsystemd.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libpowerman.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libopenssl.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libnss.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libgpiod.m4: fix the var names we "unset" in the end [#3049]
 - m4/nut_check_libneon.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libmodbus.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
 - m4/nut_check_libnetnmp.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
-

- m4/nut_check_libltdl.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libgpiod.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libavahi.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libusb.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libgd.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libfreeipmi.m4: track and report depCFLAGS_SOURCE/depLIBS_SOURCE consistently [#3049]
- m4/nut_check_libfreeipmi.m4: comment a reminder about numerous libs that we can resolve here (with one being correct) [#3049]
- m4/nut_arg_with.m4: revise brackets to pass arguments with commas in the value correctly [#3049]
- m4/nut_arg_with.m4: Revert "m4/nut_arg_with.m4: simplify with use of m4_default() [#3049]" This reverts commit 9eba1eb885e9d2 seems autoconf (or myself) gets lost in the maze of m4_default with or without brackets, especially when arguments with commas are involved.

2.48 2025-10-22 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- NEWS.adoc, drivers/nutdrv_qx_masterguard.c: nutdrv_qx_masterguard: Bump MASTERGUARD_VERSION to 0.04 And updates the NEWS.adoc in regards of PR [#3141] Tested on Masterguard A1000 and A2000 units.
- drivers/nutdrv_qx_masterguard.c: nutdrv_qx_masterguard: Makes the deep battery test command works The test.battery.start.deep (TUD) command requires the slave address as a parameter to function. Following the fix to masterguard_add_slaveaddr in the previous commit, this command can now be properly enabled. Tested on Masterguard A1000 and A2000 units.

2.49 2025-10-21 Viktor Drobot <linux776@gmail.com>

- drivers/nutdrv_qx_innovatae.c: More info about firmware version in bogus reply

2.50 2025-10-21 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc: update notes for #3049 and #3140
- ci_build.sh: check more ARCH and BITS sources for illumos/Solaris pkgconfig path guessing
- m4/nut_check_libnetsnmp.m4: fix new --with-net-snmp-config=auto mode [#3049]
- NEWS.adoc: update entry with PR number
- m4/nut_arg_with.m4: NUT_ARG_WITH_LIBOPTS_CONFIGSCRIPT_IMPLEM: drop extra brackets [#3049]
- m4/nut_check_libusb.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_libnetsnmp.m4, m4/nut_check_libsystemd.m4: m4/nut_check_libnetsnmp.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_libpowerman.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_libopenssl.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_pkgconfig.m4: refactor NUT_ARG_* help and determination of --with-pkg-config [#3049]
- m4/nut_check_libnss.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_libneon.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_check_libmodbus.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]

- m4/nut_check_libltdl.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- configure.ac, NEWS.adoc: there was never a scripts/devd/nut-usbups.rules.in (probably a copy-paste typo in NUT v2.8.0)
- configure.ac, scripts/devd/README.adoc: revise help and doc regarding FreeBSD devd snippet file installation
- m4/nut_arg_with.m4: simplify with use of m4_default() [#3049]
- m4/nut_check_libgpiod.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_arg_with.m4: extend NUT_ARG_WITH_LIBOPTS* with optional alternate spelling of project name for help text [#3049]
- configure.ac: rephrase help for (alt)pidpath [#3049]
- m4/nut_check_libgd.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
- m4/nut_arg_with.m4: add NUT_ARG_WITH_LIBOPTS_LIBS_AS_LDFLAGS and NUT_ARG_WITH_LIBOPTS_LDFLAGS for cosmetic completeness [#3049]
- m4/nut_arg_with.m4: rearrange NUT_ARG_WITH_LIBOPTS_INCLUDES and NUT_ARG_WITH_LIBOPTS_LIBS using renamed NUT_ARG_WITH_LIBOPTS_INVALID_YESNO; use simpler NUT_ARG_WITH_LIBOPTS for new NUT_ARG_WITH methods [#3049]
- m4/nut_check_libfreeipmi.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]

2.51 2025-10-21 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- drivers/nutdrv_qx_masterguard.c: nutdrv_qx_masterguard: Fix masterguard_add_slaveaddr return value The masterguard_add_slaveaddr function, defined as a preprocess_command handler, must return the length of the command string it has processed. It was incorrectly returning 0. This caused the main qx_process function to see a 0-byte command length, resulting in a send: timeout (0) debug log and a failure to send the command to the UPS. This commit fixes the function to return the correct command length (which was already stored in the local variable l), resolving the bug for all commands that use the ,XX slave address placeholder. Tested on Masterguard A1000 and A2000 units.

2.52 2025-10-20 Viktor Drobot <linux776@gmail.com>

- docs/nut.dict: Forgot to add to dict
- docs/man/nutdrv_qx.txt, docs/nutdrv_qx-subdrivers.txt, drivers/Makefile.am, drivers/nutdrv_qx.c, drivers/nutdrv_qx_blazer-common.c, drivers/nutdrv_qx_blazer-common.h, drivers/nutdrv_qx_innovatae.c, drivers/nutdrv_qx_innovatae.h: Basic Ippon Innova TAE support

2.53 2025-10-20 Jim Klimov <jimklimov+nut@gmail.com>

- m4/nut_check_libavahi.m4: refactor to word the help and determine options via NUT_ARG_WITH_LIBOPTS* [#3049]
 - m4/nut_arg_with.m4: introduce NUT_ARG_WITH_LIBOPTS* [#3049]
 - configure.ac: refactor NUT_ARG_* help and determination of --with-CCACHE_NAMESPACE [#3049]
 - configure.ac: refactor NUT_ARG_* help and determination of --enable-extapi-enphase [#3049]
 - configure.ac: refactor NUT_ARG_* help and determination of --with-user and --with-group (reword the latter) [#3049, #3120]
 - configure.ac: refactor NUT_ARG_* help and determination of --with-valgrind [#3049]
 - configure.ac: move SYSTEM_AIX and CPU_TYPE determination way up, to where we detect other aspects of the build target
 - configure.ac: refactor NUT_ARG_* help and determination of udev, hotplug, devd, freebsdquirksdir paths [#3049]
-

- configure.ac: refactor NUT_ARG_* help and determination of --with-augeas-lenses-dir [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --enable-cppunit [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of systemd paths [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of Solaris/illumos packaging options, fix a few logical mismatches [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of PKGCONFIGDIR [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --enable-strip (and actually fix a missed compiler family dependency) [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --enable-force-nut-version-header (and actually fix default report vs. setting) [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --with-logfacility [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --with-port [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --enable-check-NIT [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of --with-doc(s) and --with-docs-changelog* tunables [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of DEFAULT_MAN_* tunables [#3049]
- configure.ac: refactor NUT_ARG_* help and determination of CGIDATAPATH [#3049]

2.54 2025-10-19 Jim Klimov <jimklimov+nut@gmail.com>

- Makefile.am, configure.ac, data/Makefile.am, data/{html ⇒ htmlcgi}/.gitignore, data/{html ⇒ htmlcgi}/Makefile.am, data/{html ⇒ htmlcgi}/README.adoc, data/{html ⇒ htmlcgi}/bottom.html, data/{html ⇒ htmlcgi}/header.html.in, data/{html ⇒ htmlcgi}/index.html, data/{html ⇒ htmlcgi}/nut-banner.png, docs/configure.txt, docs/nut.dict: configure.ac, *.am: rename "htmldir" to "htmlcgidir", "data/html" to "data/htmlcgi", CGIPATH to CGIEXECPTH, and tentatively HTMLPATH to CGIDATAPATH (and actually expose the latter two from configure script) [#3049]
- data/html/Makefile.am: ensure that HTML files for CGI are in dist tarball
- configure.ac: add separators between unrelated subjects, revise comments
- configure.ac: refactor NUT_ARG_* help and determination of CGIPATH [#3049]
- NEWS.adoc, docs/man/nutdrv_qx.txt: update regarding test.battery.start.low [#3135]

2.55 2025-10-18 Atanas Vladimirov <vladimirov.atanas@gmail.com>

- data/cmdvartab, docs/nut-names.txt, drivers/nutdrv_qx_masterguard.c: nutdrv_qx_masterguard: Adds battery test until battery low. The difference between the battery test until battery low and deep battery test is that the latter is actually a battery calibration test and needs some preconditions to be met, i.e. the load must be between 30% and 100% and the battery capacity is greater than 99%. Battery test until battery low can be started anytime. Tested on Masterguard A1000 and A2000 units.

2.56 2025-10-17 Jim Klimov <jimklimov+nut@gmail.com>

- configure.ac: refactor NUT_ARG_* help and determination of DRVPATH [#3049]
 - configure.ac: refactor NUT_ARG_* help and determination of POWERDOWNFLAG [#3049]
 - configure.ac: refactor NUT_ARG_* help and determination of STATEPATH, PIDPATH and ALTPIDPATH [#3049]
-

- configure.ac: define "confdir-suffix" via 4-arg syntax of NUT_ARG_WITH; rephrase other confdir options to say =PATH ⇒ =DIRPATH [#3049]
- m4/nut_arg_with.m4: clarify that parentheses mean "default:" and *_SINGLEQUOTE values are "resolved from" [#3049]
- m4/nut_arg_with.m4: extend NUT_ARG_ENABLE and NUT_ARG_WITH to optionally accept one more (second) argument for "...=VALUES" [#3049]
- m4/nut_arg_with.m4: extend NUT_ARG_ENABLE_CUSTOM_DEFAULT_HELP and NUT_ARG_WITH_CUSTOM_DEFAULT_HELP to short-circuit \$5==\$4 if \$5 is not specified [#3049]
- m4/nut_arg_with.m4: more uniquely name the conftemp variables [#3049]
- m4/nut_arg_with.m4: update comments [#3049]

2.57 2025-10-16 Jim Klimov <jimklimov+nut@gmail.com>

- configure.ac, m4/nut_arg_with.m4: extend newer NUT_ARG_WITH_CUSTOM_DEFAULT_HELP, NUT_ARG_WITH_EXPAND_HELP, etc. methods to optionally print "--with-VARNAME=VALUES" formatted messages [#3049]
- m4/nut_arg_with.m4: fix passing of conftemp (non-verbatim per se) [#3049]
- configure.ac, m4/nut_arg_with.m4: m4/nut_arg_with.m4, configure.ac, NEWS.adoc: refactor with ability to provide custom representation for default value in AS_HELP_STRING message [#3049]
- configure.ac: fix typo in help message for --with-CCACHE_NAMESPACE
- Makefile.am: install-as-root: fix typo after replacement of @VAR@ to \$(VAR) [#3131]
- Makefile.am, NEWS.adoc, UPGRADING.adoc, ci_build.sh, conf/Makefile.am, configure.ac, docs/configure.txt, docs/man/apc_modbus, docs/nut.dict, docs/packager-guide.txt, lib/libnutclient.pc.in, lib/libnutclientstub.pc.in, lib/libnutconf.pc.in, lib/libnutscan.pc.in, lib/libupsclient-config.in, lib/libupsclient.pc.in, scripts/Aix/nut-aix.spec.in, scripts/upsdrvsvectl/nut-driver-enumerator.sh.in: configure.ac, docs/configure.txt, lib/.pc.in, *.am et al: introduce --with-confdir= options, separate delivery of sample configs [#3131]
- Makefile.am: install-as-root: use make variables for paths and package version [#3131]
- m4/nut_check_python.m4, scripts/Solaris/Makefile.am, scripts/Solaris/precheck.py.in, scripts/augeas/Makefile.am, scripts/augeas/gen_nutupsconf-aug.py.in, scripts/python/module/Makefile.am, scripts/python/module/PyNUT.py.in, scripts/python/module/test_nutclient.py.in, tools/Makefile.am, tools/gitlog2changelog.py.in, tools/nut-snmppinfo.py.in: m4/nut_check_python.m4, *.am, *.py.in: introduce PYTHON_DEFAULT to track the implementation to substitute into shebangs or use as tool calls [#1792]

2.58 2025-10-15 Jim Klimov <jimklimov+nut@gmail.com>

- m4/nut_check_python.m4: separate NUT_CHECK_PYTHON_DEFAULT_BEST and NUT_CHECK_PYTHON_INTERIM_RESULTS and implement discarding of "auto-prio" hits if another hit exists (yes, explicit, auto) [#1792] It seems AC_REQUIRE () calls have priority over other code lines in a method, and get executed first - so using extra methods (also for clearer code base).
- docs/configure.txt: clarify --with-python*=yes; fix markup [#1792]
- m4/nut_check_python.m4: separate NUT_CHECK_PYTHON*_SITE_PACKAGES into dedicated methods, to honour forgetting of interpreters due to auto-prio [#1792]
- m4/nut_check_python.m4, NEWS.adoc, UPGRADING.adoc, INSTALL.nut.adoc, docs/configure.txt, docs/nut.dict: change default to auto-prioritize some one available python interpreter [#1792]

2.59 2025-10-14 Jim Klimov <jimklimov+nut@gmail.com>

- ci_build.sh: pkg-rpm\pkg-spec: fix rpmbuild callout
- ci_build.sh, scripts/obs/_service, scripts/obs/{debian.nut.changes ⇒ nut.changes}: scripts/obs/nut.changes: isn't it a placeholder for RPM changelog?
- INSTALL.nut.adoc: mention some surprising configure options, like the many --with-python* settings, and a --sysconfdir override [#1792]
- docs/configure.txt, docs/nut.dict: revise the section on --with-python* settings [#1792]
- NEWS.adoc, configure.ac: configure.ac: warn if several python versions were AUTO-detected and configured [#1792]

2.60 2025-10-13 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/obs/debian.rules: make list-missing optional (absent in new cdb)
- scripts/obs/debian.rules: do not mislead about lack of dh_python2 due to our own tests
- scripts/obs/debian.rules: update for bleeding-edge CDBS that lacks many scripts
- docs/configure.txt: clarify that --with-group is barely used directly by daemons [#3120]
- Makefile.am: spellcheck-interactive: follow-up with a spellcheck-quick to soak up timestamp changes of the dictionary file
- drivers/snmp-ups.c: comment about us not parsing the port from device_path
- configure.ac: when we suggest to "make" after "configure" is done, have a fallback if MAKE was not defined/exported
- NEWS.adoc: Revert "NEWS.adoc: Fallout of the refactoring of drivers to use shutdown.* commands consistently [#1962]" This reverts commit 15bc72b0ae7952fe30b013b48eebfd7a6c9bf0a7 prepared problem log was not a problem after all.
- drivers/victronups.c: fix whitespace markup; translate comments
- drivers/victronups.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/usbhid-ups.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/powervar_cx_ser.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/powercom.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/pijuice.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/phoenixcontact_modbus.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/oneac.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/mge-utalk.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/metasys.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]
- drivers/masterguard.c, NEWS.adoc: reshuffle code — upsdvr_initups() is for preparing comms; upsdvr_initinfo() is for first using them [#1962]

- drivers/gamatronic.c: upsdv_initups(): update comments [#1962]
- drivers/everups.c, NEWS.adoc: reshuffle code — upsdv_initups() is for preparing comms; upsdv_initinfo() is for first using them [#1962]
- drivers/bicker_ser.c, NEWS.adoc: reshuffle code — upsdv_initups() is for preparing comms; upsdv_initinfo() is for first using them [#1962]
- drivers/bestuferrups.c, NEWS.adoc: reshuffle code — upsdv_initups() is for preparing comms; upsdv_initinfo() is for first using them [#1962]
- drivers/bestfortress.c, NEWS.adoc: reshuffle code — upsdv_initups() is for preparing comms; upsdv_initinfo() is for first using them [#1962]

2.61 2025-10-12 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/asem.c, NEWS.adoc: reshuffle code — upsdv_initups() is for preparing comms; upsdv_initinfo() is for first using them [#1962]
- drivers/upscode2.c: fix indentation
- drivers/powervar_cx.c, drivers/powervar_cx.h: drivers/powervar_cx.{c,h}: fix setcmd()→setvar() for consistency [#1962]
- NEWS.adoc, docs/nut.dict, drivers/powerp-bin.c, drivers/powerp-txt.c: drivers/powerp-{txt,bin}.c: install instcmd and setvar handlers [#1962]
- drivers/optiups.c: fix indentation broken in white-space refactoring of early NUT v2.8.x evolution [#1962]
- drivers/oneac.c: fix setcmd()→setvar() for consistency [#1962]
- drivers/metasys.c: avoid spurious void return at end of upsdv_initinfo() [#1962]
- drivers/main.c: better log the progress for killpower via running driver instance
- drivers/riello_ser.c: relocate methods to match structure of riello_usb.c to ease the comparisons
- NEWS.adoc, drivers/riello_ser.c, drivers/riello_usb.c: drivers/riello_{ser,usb}.c: refactor parse_ups_status() and do not constrain "shutdown.return" and "load.*" INSTCMD with whether the UPS is known to be on battery or not [#1962]
- scripts/Solaris/Makefile.am: "target_cpu=sparc" is inconclusive about binary bitness [#3099]
- NEWS.adoc: Fallout of the refactoring of drivers to use shutdown.* commands consistently [#1962]
- configure.ac: refactor echo of NUT_SOURCE_VERSION_REPORT, and suggest to "make" after "configure" is done Many projects do this latter convenience for beginner users. Seems nice.

2.62 2025-10-11 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc, docs/man/apcupsd-ups.txt, docs/nut.dict, drivers/apcupsd-ups.c: drivers/apcupsd-ups.c, docs: migrate from gethostbyname() to getaddrinfo(); become IPv6 capable [#1209]
- drivers/apcupsd-ups.c: revise comments and markup
- drivers/apcupsd-ups.c: use strrchr(device_path,:) to look for LAST colon, since bare IPv6 addresses contain colons too [#1209]
- drivers/apcupsd-ups.c: update comments about default port 3551
- scripts/upsdrvsvctnl/nut-driver-enumerator.sh.in: avoid logging bogus-looking "OK" confirming undeclared activities [#3099]
- docs/config-notes.txt, docs/configure.txt, docs/man/nut.txt, docs/man/upsmon.conf.txt: clarify /run vs. /var/run [#3099]
- configure.ac, NEWS.adoc, UPGRADING.adoc: PIDPATH is now more strictly /var/run, unless /run is more preferable for good reason [#3099]

2.63 2025-10-10 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/obs/nut.spec: update comment about python locations
- scripts/obs/nut.spec: hide %dir /var/log (we do not own it), suffice to mkdir it in build area to match our logrotate configuration
- scripts/obs/nut.spec: nut-monitor requires python-base
- scripts/obs/_config: track a copy of prjconf data
- scripts/obs/README.adoc: update notes on OBS prjconf
- scripts/upsdrvsvctnl/nut-driver-enumerator.sh.in: fix svcfg setprop for multiple DEPSVC FMRIs [#3099] Co-authored-by: Nick Briggs <nicholas.h.briggs@gmail.com>
- NEWS.adoc, UPGRADING.adoc, docs/nut.dict, m4/nut_check_python.m4: m4/nut_check_python.m4: try harder to report the "purelib" location as PYTHON*_SITE_PACKAGES [#1209]
- NEWS.adoc, docs/nut.dict, tests/NIT/Makefile.am, tests/NIT/nit.sh: tests/NIT/nit.sh, tests/NIT/Makefile.am, NEWS.adoc: let test runs started as root in under-provisioned environments tweak user/group to what is available [#1209]
- NEWS.adoc: one more Eaton USB ID supported [#2380]

2.64 2025-10-09 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/obs/nut.spec: register other service units (enablement is via presets after all)
 - scripts/obs/nut.spec, scripts/obs/debian.rules: enable storing build configuration and checking the build with NUT Integration Tests suite, and strip binaries of debug symbols
 - scripts/obs/nut.spec: deduplicate man page files with symlinks
 - scripts/obs/nut.spec: reduce layering of HTMLPATH under apache_serverroot_data
 - scripts/obs/nut.spec: reduce layering of CGIPATH under apache_serverroot_cgi
 - scripts/obs/nut.spec: anticipate something like /usr/lib64/python2.7/site-packages/ too
 - scripts/obs/nut.spec: keep excluding from main package stuff that should be in others
 - scripts/obs/nut.spec: revise delivery of CGI artifacts as %dir
 - scripts/obs/nut.spec: address SUSE rpmlint issues with "make check" section
 - scripts/obs/nut.spec: address SUSE rpmlint issues with scripted-only NUT-Monitor package
 - scripts/obs/nut.spec: address SUSE rpmlint issues with logrotate
 - scripts/obs/nut.spec: deliver libs each in its ABI-version-named package
 - scripts/obs/nut.spec: comment away "%dir" and "%exclude" hacks that felt superfluous and probably are
 - scripts/obs/nut.spec: revise pre/port-in/un snippets
 - scripts/obs/nut.spec: do not relocate upssched-cmd to hard-coded /bin
 - scripts/obs/nut.spec: fence delivery of systemd files (check if we could resolve the the paths involved)
 - scripts/obs/nut.spec: fix systemdtmpfilesdir determination
 - scripts/obs/nut.spec: BuildRequires: libxml2-devel
 - scripts/obs/nut.spec: dep on accounts for pkg self-test does not work like this
 - scripts/obs/nut.spec: dep on chroot does not work like this
-

- scripts/obs/nut.spec: do not package directly-named "/bin" objects
- scripts/obs/nut.spec: require more tools for SUSE platform tests on OBS
- scripts/obs/nut.spec: require user/group for post-install script context
- scripts/obs/nut.spec: refactor how we get HTMLPATH and CGIPATH, they may be different in APXS output
- scripts/obs/nut.spec: let the SPEC version reflect in NUT self-identification
- ci_build.sh: add failsafes into pkg* build types
- docs/nut.dict, scripts/obs/README.adoc: scripts/obs/README.adoc: update with Practical setup and Other notes
- scripts/obs/Makefile.am, scripts/obs/_service: scripts/obs/_service: add a copy of working OBS recipe
- Makefile.am, ci_build.sh, configure.ac, scripts/Makefile.am, {obs ⇒ scripts/obs}/Makefile.am, {obs ⇒ scripts/obs}/README.adoc, {obs ⇒ scripts/obs}/debian.Makefile.am, {obs ⇒ scripts/obs}/debian.NEWS, {obs ⇒ scripts/obs}/debian.changelog, {obs ⇒ scripts/obs}/debian.compat, {obs ⇒ scripts/obs}/debian.control, {obs ⇒ scripts/obs}/debian.copyright, {obs ⇒ scripts/obs}/debian.description.subst, {obs ⇒ scripts/obs}/debian.gbp.conf, {obs ⇒ scripts/obs}/debian.hotplug, {obs ⇒ scripts/obs}/debian.dev.install, {obs ⇒ scripts/obs}/debian.libnutclient-dev.manpages, {obs ⇒ scripts/obs}/debian.libnutclient1.install, {obs ⇒ scripts/obs}/debian.libnutclient1.lintian-overrides, {obs ⇒ scripts/obs}/debian.libnutclientstub-dev.install, {obs ⇒ scripts/obs}/debian.libnutclientstub1.lintian-overrides, {obs ⇒ scripts/obs}/debian.libnutscan-dev.install, {obs ⇒ scripts/obs}/debian.libnutscan1.install, {obs ⇒ scripts/obs}/debian.libups-nut-perl.install, {obs ⇒ scripts/obs}/debian.libupsclient-dev.install, {obs ⇒ scripts/obs}/debian.libupsclient-dev.manpages, {obs ⇒ scripts/obs}/debian.libupsclient4.install, {obs ⇒ scripts/obs}/debian.nut-cgi.README.Debian, {obs ⇒ scripts/obs}/debian.nut-cgi.docs, {obs ⇒ scripts/obs}/debian.nut-cgi.install, {obs ⇒ scripts/obs}/debian.nut-cgi.manpages, {obs ⇒ scripts/obs}/debian.nut-cgi.postinst, {obs ⇒ scripts/obs}/debian.nut-cgi.postrm, {obs ⇒ scripts/obs}/debian.nut-client.init.in, {obs ⇒ scripts/obs}/debian.nut-client.install, {obs ⇒ scripts/obs}/debian.nut-client.links, {obs ⇒ scripts/obs}/debian.nut-client.lintian-overrides, {obs ⇒ scripts/obs}/debian.nut-client.maintscript, {obs ⇒ scripts/obs}/debian.nut-client.manpages, {obs ⇒ scripts/obs}/debian.nut-client.postinst, {obs ⇒ scripts/obs}/debian.nut-client.preinst, {obs ⇒ scripts/obs}/debian.nut-client.prem, {obs ⇒ scripts/obs}/debian.nut-common.install, {obs ⇒ scripts/obs}/debian.nut-common.postinst.in, {obs ⇒ scripts/obs}/debian.nut-common.prem.in, {obs ⇒ scripts/obs}/debian.nut-common.tmpfiles.in, {obs ⇒ scripts/obs}/debian.nut-doc.doc-base.nut-developer-guide, {obs ⇒ scripts/obs}/debian.nut-doc.doc-base.nut-faq, {obs ⇒ scripts/obs}/debian.nut-doc.doc-base.nut-packager-guide, {obs ⇒ scripts/obs}/debian.nut-doc.doc-base.nut-user-manual, {obs ⇒ scripts/obs}/debian.nut-doc.install, {obs ⇒ scripts/obs}/debian.nut-ipmi.install, {obs ⇒ scripts/obs}/debian.nut-ipmi.manpages, {obs ⇒ scripts/obs}/debian.nut-linux-i2c.install, {obs ⇒ scripts/obs}/debian.nut-linux-i2c.manpages, {obs ⇒ scripts/obs}/debian.nut-modbus.install, {obs ⇒ scripts/obs}/debian.nut-modbus.manpages, {obs ⇒ scripts/obs}/debian.nut-monitor.install, {obs ⇒ scripts/obs}/debian.nut-monitor.menu, {obs ⇒ scripts/obs}/debian.nut-monitor.xpm, {obs ⇒ scripts/obs}/debian.nut-powerman-pdu.install, {obs ⇒ scripts/obs}/debian.nut-powerman-pdu.manpages, {obs ⇒ scripts/obs}/debian.nut-server.dirs, {obs ⇒ scripts/obs}/debian.nut-server.init.in, {obs ⇒ scripts/obs}/debian.nut-server.install, {obs ⇒ scripts/obs}/debian.nut-server.manpages, {obs ⇒ scripts/obs}/debian.nut-server.postinst, {obs ⇒ scripts/obs}/debian.nut-server.postrm, {obs ⇒ scripts/obs}/debian.nut-server.preinst, {obs ⇒ scripts/obs}/debian.nut-server.prem.in, {obs ⇒ scripts/obs}/debian.nut-snmp.docs, {obs ⇒ scripts/obs}/debian.nut-snmp.install, {obs ⇒ scripts/obs}/debian.nut-snmp.manpages, {obs ⇒ scripts/obs}/debian.nut-xml.install, {obs ⇒ scripts/obs}/debian.nut-xml.manpages, {obs ⇒ scripts/obs}/debian.nut.README.Debian, {obs ⇒ scripts/obs}/debian.nut.TODO.Debian, {obs ⇒ scripts/obs}/debian.nut.changes, {obs ⇒ scripts/obs}/debian.nut.docs, {obs ⇒ scripts/obs}/debian.python-nut.install, {obs ⇒ scripts/obs}/debian.rules, {obs ⇒ scripts/obs}/debian.series, {obs ⇒ scripts/obs}/debian.watch, {obs ⇒ scripts/obs}/nut.dsc, {obs ⇒ scripts/obs}/nut.spec, {obs ⇒ scripts/obs}/pkgsrc.obs: Move obs/ to scripts/obs/ for consistency with other helper code
- obs/nut.spec: shebangs: fix shell and sed syntax
- obs/nut.spec: abstract the DOCPATH as a spec-var
- obs/nut.spec: do not mention man1
- obs/nut.spec: abstract the LIBEXECPATH as a spec-var
- obs/nut.spec: reject found apache_serverroot that is under /usr/share
- obs/nut.spec: announce where and how we rewrite shebangs
- obs/nut.spec: seems there is no "%if X != Y" syntax

- obs/nut.spec: comment about alias man pages seen as duplicate files in package
- obs/nut.spec: specify system locations we use via %dir
- obs/nut.spec: do not dump sockdebug and NDE script into /usr/libexec directly
- obs/nut.spec: avoid what looks like spec-var expansion in comments
- obs/debian.rules: try harder to detect python2/3 helper
- ci_build.sh: pkg*: pre-cleanup more
- ci_build.sh: pkg-deb: clean away cdb's temp leftovers
- ci_build.sh: pkg-deb: install prereqs (TBD;: optional?)
- ci_build.sh: pkg-deb: force debuild differently
- ci_build.sh: pkg-deb: fix shell and sed syntax
- obs/Makefile.am, obs/control: obs/*: drop "control" symlink
- ci_build.sh, obs/Makefile.am, obs/{nut-linux-i2c.install ⇒ debian.nut-linux-i2c.install}, obs/{nut-linux-i2c.manpages ⇒ debian.nut-linux-i2c.manpages}, obs/{nut-modbus.install ⇒ debian.nut-modbus.install}, obs/{nut-modbus.manpages ⇒ debian.nut-modbus.manpages}, obs/{nut.changes ⇒ debian.nut.changes}: obs/*, ci_build.sh: rename debian recipe files to standard pattern
- ci_build.sh: wrap pkg-rpm and pkg-deb (PoC)
- obs/debian.rules: convince cdb's about dh_python3 when it is the only viable option
- obs/nut.dsc, obs/debian.control: do not require "python-is-..." which confuses cdb's
- NEWS.adoc, UPGRADING.adoc: Drop git-tracked compile script
- Makefile.am: EXTRA_DIST the autotools compile script
- .gitignore, compile: Drop git-tracked compile script

2.65 2025-10-08 Jim Klimov <jimklimov+nut@gmail.com>

- obs/nut.spec: reshuffle NUT_SYSTEMD_UNITS_SERVICE_TARGET definition
 - obs/debian.rules: fix pkg-config search for systemd vars
 - obs/debian.rules: fix iteration for debian *.install fixup (DMF)
 - obs/debian.rules: fix check for NUTPKG_WITH_DMF
 - obs/debian.rules: search for systemd configs also in libsystemd
 - obs/nut.spec: udev rules no longer under /etc - not a %config (hopefully)
 - obs/nut.spec: fix rpm-var expansion for conditionals
 - obs/debian.rules: fix sed with parentheses
 - obs/nut.spec: only package docs/cables/*.txt, not the whole builddir
 - obs/nut.spec: address some concerns from rpmlint
 - obs/nut.spec: %pre: try to groupadd to be sure
 - obs/debian.rules: make NUTPKG_WITH_DMF optional (based on the branch we build)
 - obs/debian.nut-cgi.docs: README renamed to *.adoc
 - obs/README.adoc, docs/nut.dict: update info about OBS recipes [[#1209](#)]
-

- obs/nut.spec: require basic tooling used in rpmlint checks
- obs/nut.spec: try another way of checking that apache_serverroot is defined and not empty
- obs/debian.rules: bump SO_MAJOR_LIB* vars and add libnutconf installation
- obs/nut.spec: comment about %(cmd) definitions
- obs/debian.rules: binary-install/nut-monitor: use dh_python* more clearly
- obs/debian.rules: fix a shell/make typo
- obs/nut.spec: try another way of checking that apache_serverroot is defined and not empty
- obs/nut.spec: exclude in root package whatever we put into sub-packages (rpmbuild seems to duplicate this)
- obs/nut.spec: post: neuter faults of chown/chgrp/chmod (some rpmbuilds fail self-check due to lack of accounts)
- obs/nut.spec: update comments
- obs/nut.spec: actually detect ability to build NUTPKG_WITH_DMFC (sources available or not in this branch)
- obs/nut.spec: only use apache_serverroot if we can detect it; otherwise dump NUT CGI artifacts under our _libexecdir and _datadir
- NEWS.adoc, UPGRADING.adoc, docs/man/Makefile.am, .../{nutdrv_siemens_sitop.txt ⇒ nutdrv_siemens-sitop.txt}: docs/man/nutdrv_siemens-sitop.txt, docs/man/Makefile.am, UPGRADING.adoc: Fixed man page naming for nutdrv_siemens-sitop(.8) (dash vs. underscore) to match the driver program name [#1209, #545]
- configure.ac, scripts/python/Makefile.am: Avoid "make install" writing PyNUT.py and test_nutclient.py to same location twice
- drivers/mge-hid.c: add Eaton Ellipse PRO 5S1600 [#2380]

2.66 2025-10-07 Jim Klimov <jimklimov+nut@gmail.com>

- obs/nut.spec: fix sub-package name for NUT-Monitor (GUI)
 - obs/debian.nut-monitor.install: GUI glade files have moved
 - obs/nut.spec: avoid "chown USER:GROUP" syntax
 - obs/debian.nut.docs: update file name lists
 - obs/nut.spec: only run udevadm where available
 - obs/nut.spec: rename "GROUP" which tends to pull in package type string
 - obs/nut.spec: deliver files that are built and installed but were not listed
 - obs/debian.control: support several libusb implementations
 - obs/debian.rules: do not run python directly anymore
 - obs/debian.changelog, obs/nut.dsc: bump formal versioning
 - obs/nut.spec: many docs files were renamed to *.adoc
 - obs/nut.spec: exclude DMFC artifacts from main pkg only if NUTPKG_WITH_DMFC in the first place
 - obs/nut.spec: reword comment
 - obs/nut.spec: hide dblatex
 - obs/nut.spec: explicitly "Prefer" something when OBS sees we "have choice for (X or Y)"
 - obs/nut.spec: do not call "python" directly
-

- obs/nut.spec: revise neon dependency
- obs/nut.spec: LUA only needed for DMF builds
- obs/nut.spec: fix typos; make cppunit-devel optional (not in RHEL7)
- obs/nut.spec: make TCP_WRAPPERS builds optional (if package seems available to be installed - was obsoleted in many distros)
- obs/nut.spec: refactor BuildRequires to avoid catering to distro-specific macro names
- obs/nut.spec: make IPMI, AVAHI and POWERMAN builds optional (if package seems available to be installed)
- obs/nut.spec: make DMF builds and deliveries optional (currently off by default)
- obs/nut.spec: accept either httpd-devel or apache2-devel
- obs/nut.spec: accept either libusb-0.1 or 1.0
- obs/nut.spec: update heading metadata
- obs/nut.spec: expand python requirements
- clients/upssched.c: start_timer(): drop unneeded NULLness checks [#3105]
- conf/upsmon.conf.sample.in: align NOTIFYFLAG samples with NOTIFYMSG definitions [#3084] Also helps NIT generate an upsmon.conf to report those events in tests.
- tests/NIT/upssched.conf.in: add handling for SHUTDOWN_HOSTSYNC [#3084]
- docs/man/upsmon.txt, docs/nut.dict: introduce SHUTDOWN ACTIVITY WORKFLOW section [#3003, #3110]
- docs/man/upsmon.txt: in SIMULATING POWER FAILURES section, refer to NIT scripts as a source of inspiration
- docs/man/upsmon.txt: from UPS CONNECTION TYPES AND UPSMON ROLES section, refer to TIMED SHUTDOWNS section
- docs/man/upsmon.txt: reword intro (and name) of UPS CONNECTION TYPES AND UPSMON ROLES section

2.67 2025-10-06 Jim Klimov <jimklimov+nut@gmail.com>

- docs/man/upssched.txt: suggest using FSD notification for early shutdown activity on the upsmon primary system [#3003]
 - docs/man/upssched.conf.txt, docs/man/upssched.txt: note that command execution is not async in upssched
 - NEWS.adoc, clients/upsmon.c, clients/upsmon.h: clients/upsmon.{c,h}, NEWS.adoc: Make sure FSD notifications are always issued at latest when shutdown handling just starts (or earlier) [#3003, #3110]
 - ci_build.sh: consider_cleanup_shortcut(): better react to changes of sources for configure script ... even if there is no Makefile yet
 - scripts/misc/nut.bash_completion.in: fix indentations
 - configure.ac, scripts/Makefile.am, scripts/misc/.gitignore, scripts/misc/{nut.bash_completion ⇒ nut.bash_completion.in}: scripts/misc/nut.bash_completion: convert to .in template to use TAIL_ARGS_FROM_NTH_LINE [#3099]
 - scripts/upsdrvsvccctl/nut-driver-enumerator.sh.in: use TAIL_ARGS_FROM_NTH_LINE [#3099]
 - configure.ac: detect TAIL_ARGS_FROM_NTH_LINE [#3099]
 - configure.ac: fix indent
-

2.68 2025-10-04 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/Solaris/postinstall.in: Update comments/messages for legacy init script usage on Solaris older than 10 [#3099]
- scripts/Solaris/preremove.in, scripts/Solaris/postinstall.in: quiesce upsdrvctl activity; add tweak-ability for debugging NUT programs in the install script context (possibly with custom package builds) [#3099]
- scripts/misc/nut.bash_completion, scripts/Solaris/reset-ups-usb-solaris.sh.sample, scripts/upsdrvsvctl/nut-driver-enumerator.sh.in: avoid "tail -n \+/-NUM" syntax as unportable [#3099]
- .github/workflows/codeql.yml: disable ccache use for actual compilation, for CodeQL analysis to hook into compiler correctly

2.69 2025-10-02 Jim Klimov <jimklimov+nut@gmail.com>

- ci_build.sh: fix typo in message
- ci_build.sh: USE_CONFIG_SHELL at least from explicit caller envvar [#3099]
- ci_build.sh: revise indentation
- clients/upssched.c: simplify loop processing [#3097]
- tests/NIT/upssched.conf.in: rename parameters passed to "EXECUTE" methods, for less confusing dev-testing logs [#3105]
- clients/upsmon.c: add debug logging to NOTIFYCMD (WIN32) [#3097]
- docs/man/upssched.txt: list common and unique options
- NEWS.adoc, clients/upssched-cmd, clients/upssched.c, conf/upssched.conf.sample.in, docs/man/upssched.conf.txt, docs/man/upssched.txt, scripts/misc/notifyme-debug: upssched: introduce passing of NOTIFYMSG to CMDSCRIPT [#3105]

2.70 2025-10-01 Jim Klimov <jimklimov+nut@gmail.com>

- Makefile.am: work around lack of "id -u" [#3099]
 - ci_build.sh: detect_platform_PKG_CONFIG_PATH_and_FLAGS(): fix use of PKG_CONFIG variable [#3099]
 - ci_build.sh: work around NCPUS prefixed with white-space [#3099]
 - ci_build.sh: work around lack of "find -maxdepth" [#3099]
 - scripts/python/Makefile.am: add a fallback TOUPPER/TOLOWER implementation [#3099]
 - ci_build.sh, scripts/subdriver/gen-snm-subdriver.sh, scripts/subdriver/gen-usbhid-subdriver.sh: add a fallback TOUPPER/TOLOWER implementation [#3099]
 - configure.ac, m4/ax_realpath.m4: introduce a fallback "mktemp" [#3099]
 - scripts/subdriver/gen-usbhid-subdriver.sh: quote calls to mktemp [#3099]
 - scripts/subdriver/gen-snm-subdriver.sh, scripts/subdriver/gen-usbhid-subdriver.sh: add a fallback mktemp implementation [#3099]
 - scripts/subdriver/gen-snm-subdriver.sh: avoid grep for char classes, it is also not ubiquitous [#3099]
 - scripts/subdriver/gen-snm-subdriver.sh: avoid "GREP -e", it is also not ubiquitous [#3099]
 - ci_build.sh: avoid "GREP -e", it is also not ubiquitous [#3099]
 - ci_build.sh: fix GGREP detection [#3099]
 - tools/driver-list-format.sh: revise reaction to "diff" problems or successes [#3099]
 - tools/driver-list-format.sh: sed class [:blank:] is not portable [#3099]
-

- tools/driver-list-format.sh, docs/docinfo.xml.sh.in: fallback for absent "diff -u" feature in pretty reporting [#3099]
 - Makefile.am, tests/nut-driver-enumerator-test.sh: fallback for absent "diff -u" feature; use detected or passed EGREP [#3099]
 - NEWS.adoc: update about portability fixes [#3099]
 - tests/NIT/nit.sh: "id -u" is not ubiquitous, find fallback ways to check that I_AM_ROOT [#3099]
 - ci_build.sh, configure.ac, docs/Makefile.am, docs/man/Makefile.am, m4/ax_realpath_lib.m4, m4/nut_check_libnetsnmp.m4, scripts/upsdrvsvctnl/nut-driver-enumerator.sh.in: Portability: in some shells, "if" only accepts the list of commands to run (there is no "if ! condition" support) - some better hidden cases [#3099]
 - scripts/installer/common/aix_init, scripts/installer/common/ipp-host-shutdown.sample, scripts/installer/common/ipp-os-shutdown: scripts/installer/*: fix syntax to pass on old Solaris 8 /bin/sh [#3099]
 - Makefile.am, ci_build.sh, configure.ac, docs/Makefile.am, docs/man/Makefile.am, scripts/Windows/build-mingw-prereqs.sh, scripts/python/app/NUT-Monitor, scripts/python/module/Makefile.am, scripts/upsdrvsvctnl/nut-driver-enumerator.sh.in, tests/NIT/nit.sh, tools/Makefile.am, tools/gitlog2version.sh: Portability: in some shells, "if" only accepts the list of commands to run (there is no "if ! condition" support) [#3099]
 - autogen.sh: do fail if configure script did not get generated [#3099]
 - configure.ac, m4/ax_check_compile_flag.m4, m4/ax_realpath_lib.m4, m4/nut_check_asciidoc.m4, m4/nut_check_aspell.m4, m4/nut_check_libmodbus.m4, m4/nut_check_libsystemd.m4, m4/nut_check_os.m4, m4/nut_check_pkgconfig.m4, m4/nut_check_python.m4, m4/nut_compiler_family.m4: configure.ac, m4/*.m4: try to use the detected GREP and EGREP tools [#3099]
 - NEWS.adoc: add historic reference from #3099 to #1660
 - ci_build.sh: handle a couple more "test -e" cases [#3099]
 - docs/Makefile.am, docs/man/Makefile.am: handle a couple more "test -e" cases [#3099]
 - scripts/upsdrvsvctnl/nut-driver-enumerator.sh.in: substitute plain GREP too [#3099]
 - docs/man/Makefile.am: substitute plain GREP too [#3099]
 - docs/Makefile.am: substitute plain GREP too [#3099]
 - data/Makefile.am: export GREP or EGREP detected by configure, so further called scripts do not have to re-detect [#3099]
 - tools/gitlog2version.sh: use or discover GREP to avoid literal "grep" [#3099]
 - tools/driver-list-format.sh: use or discover EGREP to avoid literal "grep -E" [#3099]
 - configure.ac: detect and export (E)GREP as early as possible [#3099]
 - configure.ac: avoid "[-e" or "test -e" which some older shells lack [#3099]
 - tests/NIT/Makefile.am: nut_version.h: export GREP or EGREP detected by configure, so further called scripts do not have to re-detect [#3099]
 - include/Makefile.am: nut_version.h: export GREP or EGREP detected by configure, so further called scripts do not have to re-detect [#3099]
 - autogen.sh, ci_build.sh: export GREP or EGREP if we detect them, so further called scripts do not have to re-detect [#3099]
 - NEWS.adoc: summarize fixes for "grep" and "test" callouts [issue #3099]
 - scripts/Solaris/postinstall.in: avoid "[-e" or "test -e" which some older shells lack [#3099]
 - m4/ax_realpath.m4: protect against lack of "test -e" even better (some shells do crash trying) [#3099]
 - docs/man/Makefile.am: avoid "[-e" or "test -e" which some older shells lack [#3099]
 - tests/NIT/nit.sh: use or discover EGREP to avoid literal "grep -E"; also GREP [#3099]
 - tools/nut-dumppdiff.sh: use or discover EGREP to avoid literal "grep -E" [#3099]
-

- scripts/subdriver/gen-usbhid-subdriver.sh: use or discover EGREP to avoid literal "grep -E"; also GREP; avoid "grep -q" [#3099]
- scripts/subdriver/gen-snmplib-subdriver.sh: use or discover EGREP to avoid literal "grep -E"; also GREP; avoid "grep -q" [#3099]
- scripts/Solaris/reset-ups-usb-solaris.sh.sample: roll back "grep -E" requirement [#3099, #1660]
- ci_build.sh: use or discover EGREP to avoid literal "grep -E" [#3099]
- drivers/nutdrv_hashx.c: do not directly require "stdint.h" [#3099]
- drivers/Makefile.am: fix library search order for upsdvctl build [#3099]
- autogen.sh: avoid "find -not ..." [#3099]
- autogen.sh: use or discover EGREP to avoid literal "grep -E" [#3099]
- autogen.sh: report about testing generated script syntax [#3099]
- tools/gitlog2version.sh: avoid shell substitution missing in older shells [#3099]
- tools/gitlog2version.sh: use or discover EGREP to avoid literal "grep -E" [#3099]
- tools/gitlog2version.sh: avoid "[-e" or "test -e" which some older shells lack and do crash trying [#3099]
- docs/Makefile.am: avoid "[-e" or "test -e" which some older shells lack [#3099]
- Makefile.am: avoid "[-e" or "test -e" which some older shells lack [#3099]
- tests/NIT/README.adoc, tests/NIT/nit.sh: tests/NIT/nit.sh: avoid "[-e" or "test -e" which some older shells lack [#3099]
- ci_build.sh: avoid "[-e" or "test -e" which some older shells lack [#3099]
- Makefile.am: EXTRA_DIST some more useful files

2.71 2025-09-30 Jim Klimov <jimklimov+nut@gmail.com>

- docs/net-protocol.txt: log the TODO idea for "Logout pending" of some sort [#3086]
- docs/net-protocol.txt: cross-link LIST CLIENT and GET NUMLOGINS
- docs/net-protocol.txt: clarify intro about client libraries and other bindings, in-tree or third-party

2.72 2025-09-29 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/snmplib-ups.c: allow to actually abort stuck init [#3101]
- drivers/snmplib-ups.c: implement a non-trivial upsdv_tweak_prognames() to allow aliasing with "snmp-ups-old" [#3101]
- NEWS.adoc, UPGRADING.adoc, docs/new-drivers.txt, docs/nut.dict, drivers/adelsystem_cbi.c, drivers/al175.c, drivers/apc_modbus.c, drivers/apcsmart-old.c, drivers/apcsmart.c, drivers/apcupsd-ups.c, drivers/asem.c, drivers/bcmxcp.c, drivers/belkin.c, drivers/belkinunv.c, drivers/bestfcom.c, drivers/bestfortress.c, drivers/bestuferrups.c, drivers/bestups.c, drivers/bicker_ser.c, drivers/blazer_ser.c, drivers/blazer_usb.c, drivers/clone-outlet.c, drivers/clone.c, drivers/dummy-ups.c, drivers/etapro.c, drivers/everups.c, drivers/failover.c, drivers/gamatronic.c, drivers/generic_gpio_common.c, drivers/generic_gpio_libgpod.c, drivers/generic_modbus.c, drivers/genericups.c, drivers/huawei-ups2000.c, drivers/hwmon_ina219.c, drivers/isbmex.c, drivers/ivtsd.c, drivers/liebert-esp2.c, drivers/liebert-gxe.c, drivers/liebert.c, drivers/macosx-ups.c, drivers/masterguard.c, drivers/metasys.c, drivers/mge-utalk.c, drivers/microdowell.c, drivers/microsol-apc.c, drivers/microsol-common.c, drivers/netxml-ups.c, drivers/nhs_ser.c, drivers/nut-ipmipsu.c, drivers/nutdrv_atcl_usb.c, drivers/nutdrv_hashx.c, drivers/nutdrv_qx.c, drivers/nutdrv_siemens_sitop.c, drivers/oneac.c, drivers/optiups.c, drivers/phoenixcontact_modbus.c, drivers/pijuice.c, drivers/powercom.c, drivers/powerman-pdu.c, drivers/powerpanel.c, drivers/powervar_cx_ser.c, drivers/powervar_cx_usb.c, drivers/rhino.c, drivers/richcomm_usb.c, drivers/riello_ser.c, drivers/riello_usb.c, drivers/safenet.c, drivers/skel.c, drivers/sms_ser.c, drivers/snmplib-ups.c, drivers/socomec_jbus.c, drivers/solis.c, drivers/triplite.c, drivers/triplite_usb.c, drivers/triplitesu.c, drivers/upscod2.c, drivers/usbhid-ups.c, drivers/ve-direct.c, drivers/victronups.c: drivers/*, docs/new-drivers.txt, UPGRADING.adoc, NEWS.adoc: implement (no-op) upsdv_tweak_prognames() and bump DRIVER_VERSION numbers [#3101]

- drivers/main.c, drivers/main.h: drivers/*: introduce upsdrv_tweak_prognames() hook [#3101]
- common/common.c, drivers/main.c: drivers/main.c: main(): use new sendsignalfnaliases() and sendsignalpidaliases() with prognames[] [#3101]
- NEWS.adoc, common/common.c, docs/nut.dict, include/common.h: common/common.c, include/common.h, NEWS.adoc: extend with plural sendsignalpidaliases() and sendsignalfnaliases() [#3101]
- drivers/main.c, drivers/main.h: drivers/main.{c,h}: allow to track several prognames[] for acceptable driver program aliases [#3101]
- drivers/upsdrvctl.c: help(): fix global vs local arg name
- NEWS.adoc, common/common.c, docs/nut.dict, include/common.h: common/common.c, include/common.h, NEWS.adoc: extend with plural checkprocnames() and compareprocnames() [#3101]
- clients/upsmon.c: add comments to methods involved in shutdown to clarify who normally runs as root or not [#3084]

2.73 2025-09-28 Nick Briggs <nicholas.h.briggs@gmail.com>

- Makefile.am, clients/Makefile.am, docs/Makefile.am, docs/docinfo.xml.sh.in, docs/man/Makefile.am, scripts/python/Makefile.am, scripts/systemd/nut-server.service.in, scripts/upsdrvsvctl/nut-driver-enumerator.sh.in: Modifies Makefile.am files and some script ".in" files to use \$EGREP The standard Solaris 10/11 "/usr/bin/grep" does not accept the "-E" option. The autotools will set EGREP to the best available tool. Makefile.am that need EGREP functionality should use \$(EGREP) rather than directly calling "grep -E". Additionally, scripts that are generated to be installed as part of the package that need EGREP functionality should use the same tool that was located during configuration (assuming no cross-compilation with different EGREP tool availability). Closes #3099

2.74 2025-09-25 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upsmon.c: main loop: avoid sleep if FSD signal was raised during the long work cycle [#3084]
- clients/upsmon.c: user_fsd(), main loop: try to ensure immediate reaction to FSD signals (interrupt a sleep() if needed) [#3084]
- docs/config-notes.txt: clarify that upsmon exit is now subject to SHUTDOWNEXIT setting [#3084, #2133]
- NEWS.adoc, clients/upsmon.c, clients/upsmon.h, common/nutconf.cpp, common/nutwriter.cpp, conf/upsmon.conf.sample.in, docs/config-notes.txt, docs/man/upsmon.conf.txt, include/nutconf.hpp: clients/upsmon.h, conf/upsmon.conf.sample.in, etc: Introduced a SHUTDOWN_HOSTSYNC notification message [#3084]
- conf/upsmon.conf.sample.in, docs/man/upsmon.conf.txt: revise documentation of FINALDELAY [#3084] Notably, both primary and secondary upsmon doshutdown() to handle FSD.
- clients/upsmon.c: doshutdown(), runparent(): debug-log just before executing shutdowncmd [#3084]
- clients/upsmon.c: runparent(): when waiting for a child to exit, and we know its PID, react to the end of specifically that process [#3084]
- clients/upsmon.c: doshutdown(), runparent(): Take note of start timestamp before calling SHUTDOWNCMD [#3084]
- clients/upsmon.c: doshutdown(): debug-log about waiting for FINALDELAY [#3084]
- clients/upsmon.c: set_pflag(): log if POWERDOWNFLAG is not configured or is being written now [#3084]
- clients/upsmon.c: doshutdown(), runparent(): initialize "time(&start)" always [#3084] Avoid (semi-bogus) warnings from clang that variable 'start' may be uninitialized when used here in difftime() later on.
- clients/upsmon.c: truly deal with SHUTDOWNEXIT timeout as such, not a countdown [#3084]
- clients/upsmon.c: revise tracking pid_pipechild when parent exits [#3084]
- clients/upsmon.c: fix whitespace markup in decls

2.75 2025-09-24 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upsmon.c: add interaction between upsmon parent and child if SHUTDOWNEXIT is non-trivial [#3084]
- clients/upsmon.c: revise comments and log messages in forceshutdown(), doshutdown(), start_pipe() [#3084]
- clients/upsmon.c: start_pipe(), notify(): revise parent/child logging around the fork() [#3084]
- clients/upsmon.c, clients/upssched.c, drivers/upsdrvctl.c: call first setproctag() after setting up nut_debug_level [#3084]
- common/common.c, include/common.h: refactor and optimize getpidname(getpid()) calls with caching getmyprocname() and getmyprocbasename() [#3084]
- common/common.c, include/common.h, clients/upsmon.c, clients/upssched.c, drivers/upsdrvctl.c: move proctag_cleanup() into common code and auto-register during first use of setproctag() [#3084]
- drivers/upsdrvctl.c, NEWS.adoc: introduce logging of self-assigned forked process tags [#3084]
- clients/upssched.c, NEWS.adoc: introduce logging of self-assigned forked process tags [#3084]
- clients/upsmon.c: improve debugging messages of forceshutdown() [#3084]
- clients/upsmon.c, NEWS.adoc: introduce logging of self-assigned forked process tags [#3084]
- common/common.c, include/common.h, NEWS.adoc, docs/nut.dict: introduce logging of self-assigned forked process tags [#3084]

2.76 2025-09-23 Jim Klimov <jimklimov+nut@gmail.com>

- ci_build.sh: honour CI_CCACHE_USE=no more diligently
- NEWS.adoc, clients/upssched.c, conf/upssched.conf.sample.in, docs/man/upssched.conf.txt: clients/upssched.c: revise CANCEL-TIMER, introduce CANCEL-TIMER-MATCHED [#3097]
- scripts/misc/notifyme-debug: fix shell typo
- clients/upssched.c: fix START-TIMER-SHARED [#3097]
- clients/upssched.c: revise logging of timer events [#3097]

2.77 2025-09-22 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upssched.c: start_timer(): revise START-TIMER-SHARED behavior [#3097]
 - clients/upssched.c: fix CI suggestions [#3097]
 - clients/upssched.c: log-trace through, and fix, removetimers() and connection loss due to a recent bug there [#3097]
 - clients/upssched.c: send_to_one(): improve debugging [#3097]
 - clients/upssched.c: collect_string(): fix the iteration logic [#3097]
 - clients/upssched.c, docs/man/upssched.txt, NEWS.adoc: introduce upssched -l mode [#3097]
 - docs/man/upssched.conf.txt: PIPEFN: chain the paragraphs of one description (indent them correctly) [#3097]
 - NEWS.adoc, clients/upssched.c, conf/upssched.conf.sample.in, docs/man/upssched.conf.txt, tests/NIT/upssched.conf.in: clients/upssched.c, conf/upssched.conf.sample.in, docs/man/upssched.conf.txt, NEWS.adoc: introduce support for DEBUG_MIN in upssched.conf [#3097]
 - clients/upssched.c: update © header with major contributors
 - clients/upssched.c: in messages that refer to upsmon, append its man page section
 - clients/upssched.c, NEWS.adoc, conf/upssched.conf.sample.in, docs/man/upssched.conf.txt: let timers pass forward the UPSNAME and NOTIFYTYPE again - now with relevant values; introduce START-TIMER-SHARED [#3092, #3097]
-

2.78 2025-09-21 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upssched.c: update comments [#3092]
- clients/upssched.c: rename global upsname ⇒ ups_name to be on par with global notify_type [#3092]
- docs/man/nut.txt, docs/nut.dict: describe NUT layer 3.5 - role of the drivers during shutdown
- docs/man/nut.txt: suggest more packaged user-names for NUT daemons
- NEWS.adoc, drivers/nutdrv_qx.c, drivers/nutdrv_qx.h: drivers/nutdrv_qx.{c,h}, NEWS.adoc: define an internal QX_FLAG_MAPPING introduce analyze_mapping_usage() method [#3095]
- drivers/nutdrv_qx.c: fix whitespace
- drivers/usbhid-ups.c: analyze_mapping_usage(): rephrase last suggestion with also checking and building recent NUT code [#3082, #3095]

2.79 2025-09-19 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/snmp-ups.c, drivers/usbhid-ups.c: drivers/snmp-ups.c: account SU_FLAG_MAPPING_HANDLED and do analyze_mapping_usage() method [#3095]
- NEWS.adoc, drivers/snmp-ups.h: drivers/snmp-ups.{c,h}, NEWS.adoc: define an internal SU_FLAG_MAPPING_HANDLED [#3095]
- drivers/snmp-ups.c: fix markup
- drivers/snmp-ups.h: modernize a few comments
- drivers/snmp-ups.c: suggest in log how to improve a driver where only IETF auto-matched [#3095]
- drivers/hidtypes.h: update a comment [#3082]
- drivers/usbhid-ups.c: fix whitespace
- drivers/usbhid-ups.c: offload analyze_mapping_usage() to a method [#3082, #3095] Note the activity is now still limited to when debug logging is enabled.

2.80 2025-09-18 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/usbhid-ups.c, NEWS.adoc: suggest in log how to improve a driver with too few mappings defined/used [#3082]
- NEWS.adoc, docs/ci-farm-do-setup.adoc, docs/ci-farm-lxc-setup.txt, docs/config-notes.txt, docs/config-prereqs.txt, docs/configure.txt, docs/daisychain.txt, docs/design.txt, docs/documentation.txt, docs/download.txt, docs/features.txt, docs/hid-subdrivers.txt, docs/net-protocol.txt, docs/new-clients.txt, docs/new-drivers.txt, docs/nut-names.txt, docs/nut-versioning.adoc, docs/nutdrv_qx-subdrivers.txt, docs/outlets.txt, docs/scheduling.txt, docs/security.txt, docs/snmp-subdrivers.txt, docs/sock-protocol.txt, docs/support.txt: docs/*.txt: add asciidoc comments with links to nut-website rendered contents of most interesting pages
- docs/maintainer-guide.txt: avoid pushing final release tags to upstream more than once, really!
- scripts/Makefile.am: do not EXTRA_DIST the generated scripts/Windows/Makefile — the .in template suffices Thanks to @gdt for the heads-up.

2.81 2025-09-12 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upsmon.c: doshutdown(): log more loudly that exit_flag is raised, so shutdownexitdelay does not apply currently [#3084]
-

2.82 2025-09-11 Jim Klimov <jimklimov+nut@gmail.com>

- clients/upsmon.c, NEWS.adoc: doshutdown(): collapse non-zero shutdownnextdelay handling into one clause, and ping the data server(s) while in the loop [#3084]
- clients/upsmon.c: more logging about ways to exit() the program, and why/when it happened [#3084]

2.83 2025-09-10 Jim Klimov <jimklimov+nut@gmail.com>

- scripts/python/module/Makefile.am: emit log note that .pypi-dist-pip-wheel goal does not produce sdist archives [#3056]
- scripts/python/module/Makefile.am: fix typo in comment
- NEWS.adoc: fixed PyPI publication to include sdist tarball [#3056]
- .github/workflows/PyNUTClient.yml: fix shell markup [#3056]
- .github/workflows/PyNUTClient.yml: actually install "setuptools" module with "pip" [#3056]
- .github/workflows/PyNUTClient.yml: allow manually running the GHA task

2.84 2025-09-08 Jim Klimov <jimklimov+nut@gmail.com>

- docs/hid-subdrivers.txt, docs/nut.dict: docs/hid-subdrivers.txt: updating existing drivers: suggest newly logged discrepancies of "seen vs. used" data [#3082]
- drivers/nutdrv_atcl_usb.c: when suggesting other drivers and configs, refer to build-aware man page sections
- docs/hid-subdrivers.txt: fix a bit of markup
- clients/upslog.c, NEWS.adoc: update help() and failure messages to suggest -m *, -
- drivers/usbhid-ups.c: process_boolean_info(): handle OB=!OL and OL=!OB here (when the bit is being set) [#3080]
- drivers/usbhid-ups.c: upsdv_initups(): upsdebugx() at verbosity 0 (always) if there are too few mappings known or used via USB HID [#3082]
- drivers/apc-hid.c, NEWS.adoc, scripts/upower/95-upower-hid.hwdb: declare support for APC 0x051d:0x0005 as a USB HID device [#3047]
- drivers/nutdrv_atcl_usb.c: upsdv_initups() failure mode: suggest using nutdrv_qx(8) or blazer_usb(8) driver instead [#1021, #2152 follow-up]
- data/driver.list.in: add Voltronic Power USB ID 0665:5161 as nutdrv_qx supported (per driver source comments)
- data/driver.list.in: add "Various" USB interface chip names or IDs 0665:5161 and 0001:0000 as nutdrv_qx or rarely nutdrv_atcl_usb supported
- data/driver.list.in: add Salicru SPS 500 ONE USB ID 0665:5161 as nutdrv_qx supported [#3079]
- data/driver.list.in: add Belkin USB ID 0665:5161 as nutdrv_qx supported (per driver source comments)
- drivers/usbhid-ups.c: upsdv_initups(): fix variable name for the snprintf() return value [#3083]
- drivers/usbhid-ups.c: upsdv_initups(): also report how many hid2nut mappings are known vs. how many were used using USB HID [#3082]
- drivers/usbhid-ups.c: upsdv_initups(): generalize the report of unused report descriptor entries to "completely unused" vs. "partially unused" (e.g. Feature vs Input) [#3082]
- drivers/usbhid-ups.c, drivers/hidtypes.h, NEWS.adoc: check if the subdriver code (mappings) and the device report sit together well [#3082]

- drivers/usbhid-ups.c: callback(): update logged message that not only Manufacturer, but possibly an explicit Model, may be not-supported
- NEWS.adoc: update about usbhid-ups suggestion to iterate "subdriver" values
- drivers/usbhid-ups.c: upsdv_initups(): check that if no ups_status bit was set, suggest that wrong "subdriver" is used then [#3080, #3061, #2058]
- drivers/usbhid-ups.c: callback(): add log messages to stress that the dump of Report Descriptor actually seen, and its later hid_ups_walk() with a particular subdriver, may not match up well [#3061]
- drivers/usbhid-ups.c: upsdv_initups(): add log messages to help trace logical progress through the code [#3061]
- drivers/usbhid-ups.c: possibly_supported(): suggest iterating "subdriver" values [#2058]
- NEWS.adoc, drivers/usbhid-ups.c, drivers/usbhid-ups.h: drivers/usbhid-ups.c: do not assume that "!online"=="offline" [#3080]
- drivers/usbhid-ups.c: fix indentation (cosmetic)
- drivers/usbhid-ups.c: ups_status_set(): revise code markup/style

2.85 2025-09-07 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/mge-hid.c, NEWS.adoc: Improved support for Eaton 5S1500LCD (US version). [#2380]
- NEWS.adoc, docs/config-prereqs.txt, docs/configure.txt, docs/developers.txt, docs/download.txt, docs/maintainer-guide.txt, docs/man/apcsmart.txt, docs/man/belkin.txt, docs/man/genericups.txt, docs/man/mge-shut.txt, docs/man/upsdrvsvctl.txt, docs/man/upsmon.conf.txt, docs/man/upssched.conf.txt, docs/man/upsset.cgi.txt, docs/man/usbhid-ups.txt, docs/new-drivers.txt, docs/outlets.txt, docs/packager-guide.txt, docs/scheduling.txt, scripts/Windows/README.adoc, scripts/external_apis/enphase/README Reword multiple docs to avoid admonition blocks with invalid sentences
- docs/Makefile.am: spellcheck: help avoid admonition blocks with invalid sentences (after rendering as a box)
- docs/download.txt: revise markup for Windows downloads
- docs/download.txt: revise info about/from Repology
- docs/download.txt: revise note about official releases
- docs/download.txt: revise part about source archives from github

2.86 2025-09-06 desertwitch <24509509+desertwitch@users.noreply.github.com>

- drivers/nutdrv_qx_megatec.c: trim battery.runtime variable

2.87 2025-09-05 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/codeql.yml: fix syntax for codeql queries

2.88 2025-09-04 Jim Klimov <jimklimov+nut@gmail.com>

- .github/workflows/codeql.yml: Revert ".github/workflows/codeql.yml: use modern "language" ID "c-cpp"" This reverts commit 972358ec7663007419f0b1926d30f9f5a494d910.
 - .github/workflows/codeql.yml: enable ccache per scenario, follow experience from wmnut#24
 - .github/workflows/codeql.yml: enable more codeql queries
 - .github/workflows/codeql.yml: relocate comments, drop dead code
-

- .github/workflows/codeql.yml: avoid man-db update in APT actions
- .github/workflows/codeql.yml: report the location and version of compiler used
- .github/workflows/codeql.yml: add a way to vary matrix.build-mode for codeql
- .github/workflows/codeql.yml: only init CodeQL just before the actual build, not before other filesystem changes
- .github/workflows/codeql.yml: use modern "language" ID "c-cpp" "c" and "cpp" are older names, now aliases to this one
- .github/workflows/codeql.yml: revise markup and comments of the matrix definition
- .github/workflows/codeql.yml: Allow manually running the action, e.g. if disabled after some quietness in the source

2.89 2025-09-03 Laurent Bigonville <bigon@bigon.be>

- docs/Makefile.am: Fix installation of the pdf files

2.90 2025-09-03 Jim Klimov <jimklimov+nut@gmail.com>

- docs/developers.txt: clarify use of "void" argument lists

2.91 2025-09-02 Jim Klimov <jimklimov+nut@gmail.com>

- tools/nut-usbinfopl: update comment
- tools/nut-usbinfopl: use binmode for written files to have same markup regardless of builder OS
- ci_build.sh: when reporting host envvars, use backslashes to facilitate copy-paste reproduction of CI builds
- ci_build.sh: when reporting CONFIGURING NUT, use backslashes to facilitate copy-paste reproduction of CI builds
- configure.ac, docs/configure.txt, m4/nut_check_python.m4, NEWS.adoc: allow to configure Python module install location more generally [#3062]
- scripts/python/app/NUT-Monitor-py2gtk2.in, scripts/python/app/NUT-Monitor-py3qt5.in, scripts/python/app/NUT-Monitor-py3qt6.in, scripts/python/app/NUT-Monitor-py*.in: try to honour a customized PyNUT(Client) module path [#3062]

2.92 2025-09-02 Hector Martin <marcan@marcan.st>

- drivers/apc_modbus.c: apc_modbus: Fix invalid memory access for USB vendor/product/serial

2.93 2025-08-31 Jim Klimov <jimklimov+nut@gmail.com>

- configure.ac, docs/configure.txt, m4/nut_check_python.m4, NEWS.adoc: allow to configure PyNUT(Client) install location [#3062]

2.94 2025-08-21 me <me@LIONINE>

- drivers/upsdrvctl.c: In case of WIN32 build, most drivers are located in "bin". but referred Relative running path, it is "sbin". So changing to "NULL(running path)" to "bin"
 - scripts/Windows/wininit.c: nut.exe are call upsdrvctl.exe in bin. but upsdrvctl.exe located in sbin. So, change bin to sbin.
-

2.95 2025-08-09 Colin Dean <colindean@users.noreply.github.com>

- docs/download.txt, docs/nut.dict: Include macOS with Mac OS X Apple shortened the name to "OS X" in 2011 and then changed it to "macOS" in 2016 to align with the branding of Apple's other operating systems. <https://en.wikipedia.org/w/index.php?title=MacOS&oldid=1304698699>
- docs/download.txt: Update download.txt with link to Homebrew formula for macOS nut has been in Homebrew since 2014.

2.96 2025-08-08 Jim Klimov <jimklimov+nut@gmail.com>

- NEWS.adoc, UPGRADING.adoc: prepare for v2.8.5.x iterations
- NEWS.adoc, UPGRADING.adoc, docs/docinfo.xml.in: Revert "NEWS.adoc, UPGRADING.adoc, docs/docinfo.xml.in: finalize text before NUT v2.8.4 release" This reverts commit 8f14140bbc395baa108bd06a9f664bd0a6f00bc8.
- tools/gitlog2version.sh: for development, set fallback NUT_VERSION_DEFAULT=2.8.4.1
- configure.ac: for now do not require (pre-)release tagged commits to build changelog by default - keep doing it on systems where we can though
- configure.ac: rephrase the message about --enable-docs-changelog [#3019, #3053]
- ci_build.sh: limit default "configure --enable-docs-changelog=no" for CI builds on systems where CANBUILD_DOCS_ALL!=yes
- ci_build.sh: add support for WITH_CHANGELOG envvar to pass down as configure --enable-docs-changelog=...
- .github/workflows/codeql.yml: configure --disable-docs-changelog in CI builds
- configure.ac: for (pre-)release builds we default nut_enable_docs_changelog auto⇒yes - do so loudly, and default --with-docman⇒auto as well for all builds to have a chance to try this
- docs/maintainer-guide.txt: update the guide
- docs/maintainer-guide.txt: commit that in tools/gitlog2version.sh: for development, set fallback NUT_VERSION_DEFAULT=X.Y.Z.
- docs/maintainer-guide.txt: remind to double-check that release NUT_VERSION_DEFAULT in tools/gitlog2version.sh must be a triplet

2.97 2025-07-30 Jim Klimov <jimklimov+nut@gmail.com>

- docs/qa-guide.adoc: mention OBS [#1209]
- obs/README.adoc, obs/Makefile.am, Makefile.am, configure.ac: document the "obs" directory and cover it with scripting [#1209]
- docs/qa-guide.adoc: move CodeQL up (alphabetically, and before semi-defunct Travis)
- docs/nut-versioning.adoc, docs/developers.txt: rename to "NUT Semantic Versioning" consistently

2.98 2025-07-08 Jim Klimov <jimklimov+nut@gmail.com>

- drivers/usbhid-ups.c, drivers/powercom-hid.c, docs/man/usbhid-ups.txt, NEWS.adoc: introduce powercom_sdcmd_discrete_delay flag for Powercom Raptor and Smart KING Pro series [#3000]
 - drivers/powercom-hid.c: WIP fixes for discrete shutdown timings (per RAPTOR RPT-1500AP LCD practice) - fix messages [#3000]
 - NEWS.adoc, drivers/powercom-hid.c: fix shutdown delays for Powercom HID [#3000]
 - drivers/powercom-hid.c: WIP fixes for discrete shutdown timings (per RAPTOR RPT-1500AP LCD practice) [#3000] Authored-by: <https://github.com/aleka204>
-

2.99 2024-01-31 Charles Lepple <clepple+nut@gmail.com>

- drivers/tripplite_usb.c: add battery.charge for Protocol 3017 Reference: [#2258](#)

2.100 2024-01-25 Charles Lepple <clepple+nut@gmail.com>

- drivers/tripplite_usb.c: Protocol 3017 adjustments Reference: [#2258](#) SMX1200XLHG is 230V / 50 Hz

2.101 2023-02-28 Jim Klimov <jimklimov+nut@gmail.com>

- common/str.c: str_ends_with(): update origin attribution

2.102 2022-02-10 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: packaging/debian/rules: define a systemdtmpfilesdir
- obs/debian.rules: packaging/debian/rules: report PKG_CONFIG_PATH default
- obs/debian.control: packaging/debian/control: update "libmodbus5" dependency name for Debian 11

2.103 2022-02-09 Jim Klimov <jim@jimklimov.com>

- obs/debian.changelog, obs/debian.control, obs/debian.nut-server.install, obs/debian.nut-server.manpages, obs/nut-linux-i2c.install, obs/nut-linux-i2c.manpages, obs/nut-modbus.install, obs/nut-modbus.manpages, obs/nut.dsc: packaging/debian: update for nut-modbus and nut-linux-i2c driver packages

2.104 2021-08-13 Clément <perrettecl@users.noreply.github.com>

- obs/nut.dsc: Update nut.dsc

2.105 2021-08-12 Clément <perrettecl@users.noreply.github.com>

- obs/debian.control: Update debian.control

2.106 2021-05-18 Clappier, Eric <EricClappier@Eaton.com>

- obs/debian.libnutclientstub-dev.install: Remove lib static for libnutclientstub dev install
- obs/debian.rules: Fix issue in debian rules for libnutclientstub

2.107 2021-05-17 Clément <clementperrette@eaton.com>

- obs/debian.control, obs/debian.libnutclientstub-dev.install, obs/debian.libnutclientstub1.install, obs/debian.libnutclientstub1.lintian-overrides: Add new package for nut client stub

2.108 2021-05-04 Jim Klimov <jim@jimklimov.com>

- obs/pkgsrc.obs: pkgsrc.obs: tell OBS pusher to append gitdate to version (first line must be from a specific range of values)
 - obs/pkgsrc.obs: pkgsrc.obs: tell OBS pusher to append gitdate to version
-

2.109 2021-02-10 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-client.links, obs/debian.rules: obs packaging: avoid warnings from systemd-sysv about legacy init scripts without a service unit

2.110 2021-01-21 Jim Klimov <jim@jimklimov.com>

- obs/debian.control, obs/nut.dsc: debian.rules, nut.dsc: rather ask for dh-python | dh-python2 | dh-python3 \ dh-pypy
- obs/debian.control, obs/nut.dsc: debian.rules, nut.dsc: ask for dh_python2 | dh_python3 \ dh_pypy
- obs/debian.rules: debian.rules: clarify that any python 2/3 is okay, but we need an interpreter called "python" to be generic
- obs/debian.control: debian.control: clarify that any python 2/3 is okay, but we need an interpreter called "python" to be generic
- obs/nut.dsc: nut.dsc: clarify that any python 2/3 is okay, but we need an interpreter called "python" to be generic

2.111 2021-01-20 Jim Klimov <jim@jimklimov.com>

- obs/debian.control, obs/nut.dsc: FTY OBS packaging: require libsystemd-dev in the build root (to use pkgconfig systemd queries)

2.112 2020-03-14 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-monitor.install: Fix formal 42ity packaging for nut-monitor.png icon (recent master branch added different resolutions)

2.113 2019-12-06 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : fix away debian. prefix for *.in templates
- obs/debian.Makefile.in, ... n.nut-client.init ⇒ debian.nut-client.init.in}, ... mmon.postinst ⇒ debian.nut-common.postinst.in}, ... nut-common.prerm ⇒ debian.nut-common.prerm.in}, obs/debian.nut-common.tmpfiles, obs/debian.nut-common.tmpfiles.in, ... n.nut-server.init ⇒ debian.nut-server.init.in}, ... nut-server.prerm ⇒ debian.nut-server.prerm.in}, obs/debian.rules: Introduce "runbasedir" in debian packaging on OBS to use /run or /var/run as appropriate

2.114 2019-04-12 Jim Klimov <jim@jimklimov.com>

- obs/debian.control, obs/nut.dsc: Debian packaging: explicitly request libssl*-dev so OBS is not confused for Debian 9 options
- obs/nut.spec: nut.spec : do not fail making build dir trees
- obs/debian.control, obs/nut.dsc: Debian packaging: explicitly request libjpeg-dev so OBS is not confused for Debian 9 options

2.115 2019-04-03 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : update SO_MAJOR_LIBUPSCLIENT for 42ity packaging

2.116 2019-02-20 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : make sure wanted SONAMES exist (numbers remained unchanged)
 - obs/debian.control, obs/debian.libnutclient0.lintian-overrides, ... bnutclient0.install ⇒ debian.libnutclient1.install}, obs/debian.libnutclient0.lintian-overrides, obs/debian.rules, obs/nut.dsc: Problem: libnutclient not found in consumer packaged builds Solution: update the hardcoded pathnames in recipes, leave some comments for improvement
-

2.117 2018-12-06 Jim Klimov <jim@jimklimov.com>

- obs/debian.control: debian.control : nut-ipmi should have run-time deps on IPMI libs
- obs/debian.control: debian.control : rephrase nut-server description

2.118 2018-10-05 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-server.postinst: debian.nut-server.postinst : REPORT_RESTART_42=no when reconfiguring
- obs/debian.nut-server.postinst: nut-driver-enumerator : use --reconfigure to remake units from scratch in Debian postinstall

2.119 2018-09-28 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-client.postinst, obs/debian.nut-common.postinst, obs/debian.nut-server.postinst: nut-(client|server|common).postinst : skip DEBHELPER in our case

2.120 2018-09-27 Jim Klimov <jim@jimklimov.com>

- obs/debian.control: debian.control : "nut-server" should have no business requiring "nut-client"
- obs/debian.control: debian.control : have "nut" metapackage explicitly depend on nut-common to pre-create things
- obs/debian.control: debian.control : new nut-common has no opinion about old nut-hal-drivers
- obs/debian.nut-client.postinst, obs/debian.nut-common.postinst, obs/debian.nut-server.postinst: debian.nut-*.post/pre-inst/rm : do not fail package installation if could not start services
- obs/debian.nut-client.postinst, obs/debian.nut-client.preinst, obs/debian.nut-common.postinst, obs/debian.nut-common.preinst, obs/debian.nut-server.postinst, obs/debian.nut-server.preinst: debian.nut-*.post/pre-inst/rm : call /bin/systemctl only on systems where it is available, and do not block on attempts to start the services

2.121 2018-09-26 Jim Klimov <jim@jimklimov.com>

- obs/debian.control: debian.control : reference nut-common
- obs/debian.rules: debian.rules : deliver one nut-common.conf tmpfiles config instead of two same files for client and server
- obs/debian.control: debian.control : update sub-driver packages to rely on just the nut-server package, not nut metapackage
- obs/debian.control: debian.control : clarify where packages provide clients for "a local or remote NUT server"
- obs/debian.nut-client.preinst, obs/debian.nut-common.preinst, obs/debian.nut-server.preinst: Add systemd shutdown of installed units during uninstallation of the packages
- obs/debian.nut-client.postinst, obs/debian.nut-common.postinst, obs/debian.nut-server.postinst: Add systemd startup of installed units
- obs/debian.nut-client.postinst, obs/debian.nut-common.postinst, obs/debian.nut-server.postinst: Add systemd registration of installed units
- obs/debian.control, obs/debian.nut-cgi.postinst, obs/debian.nut-client.postinst, obs/debian.nut-common.install, obs/debian.nut-common.postinst, obs/debian.nut-common.preinst, ... -client.tmpfiles ⇒ debian.nut-common.tmpfiles}, obs/debian.nut-server.postinst, obs/debian.nut-server.tmpfiles, obs/debian.rules: Introduce (debian) nut-common package for user account and shared FS objects

2.122 2018-09-06 Jim Klimov <jim@jimklimov.com>

- obs/nut.spec: nut.spec : do not use the configure macro
- obs/nut.spec: nut.spec : do not use the configure macro

2.123 2018-09-05 Jim Klimov <jim@jimklimov.com>

- obs/nut.spec: nut.spec : do not redefine (differently) paths set by %configure macro, try to set them directly
- obs/nut.spec: nut.spec : whitespace
- obs/nut.spec: nut.spec : remove commented-away references to private OBS patches that are not used anymore

2.124 2018-09-03 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-server.install, obs/nut.spec: nut.spec : fix RPM packaging for OBS

2.125 2018-01-15 Jim Klimov <jim@jimklimov.com>

- obs/nut.spec: nut.spec : avoid "nut" vs "nut-drivers-net" conflict over gen-snmplib-subdriver.sh

2.126 2018-01-03 Jim Klimov <jim@jimklimov.com>

- obs/nut.spec: nut.spec : publish augeas files

2.127 2018-01-02 Jim Klimov <jim@jimklimov.com>

- obs/debian.control, obs/debian.rules, obs/nut.dsc: Debian packaging : require pkg-config, and provide some fallbacks if systemd dirs are unknown
- obs/nut.spec: nut.spec : suse wants a package
- obs/nut.spec: nut.spec : dist augeas files
- obs/debian.rules, obs/nut.spec: Packaging : pass the systemd*dir arguments to configure script
- obs/nut.spec: nut.spec : use proper systemdshutdowndir relevant for current distro/arch
- obs/nut.spec: nut.spec : fix "bindir" macro to "_bindir"

2.128 2017-12-31 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : avoid re-configuring before "make install" again
- obs/debian.rules, obs/nut.spec: packaging : use --with-docs=man=dist-auto

2.129 2017-10-19 Jim Klimov <jim@jimklimov.com>

- obs/debian.compat, obs/debian.rules: Use DH_COMPAT=10 to enable parallel build support by default

2.130 2017-10-13 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : enable parallelized packaging
-

2.131 2017-04-12 Jim Klimov <jim@jimklimov.com>

- obs/debian.nut-server.install: Drop remaining references to oldmge-shut

2.132 2016-10-06 Arnaud Quette <arnaud.quette@free.fr>

- obs/nut.spec: Distribute gen-snmp-subdriver.sh with nut-snmp for RPM
- obs/debian.nut-snmp.install, obs/debian.rules: Distribute gen-snmp-subdriver.sh with nut-snmp

2.133 2016-09-22 Jim Klimov <jim@jimklimov.com>

- obs/debian.rules: debian.rules : skip even the manpages if the host cannot build them
- obs/debian.rules: debian.rules : whitespace fixes
- obs/debian.rules, obs/nut.dsc, obs/nut.spec: nut.dsc / nut.spec : do not request rebuild and revalidation of DMF files - they were tested in Jenkins NUT-master job (remove build dependency on pycparser and speed up the build)
- obs/nut.spec: nut.spec : try to fix inability to detect LUA on some RPM buildhosts

2.134 2016-09-14 Jim Klimov <jim@jimklimov.com>

- obs/debian.libnutscan1.install, obs/debian.nut-snmp.install: debian.nut-snmp.install debian.libnutscan1.install : fix conflict for dmfnutscan resource dirs delivered by both packages
- obs/nut.spec: nut.spec : fix mixed spaces vs tabs
- obs/debian.nut-snmp.install, obs/nut.spec: RPM/DEB : deliver the sorted symlinks in packages

2.135 2016-08-19 Jim Klimov <jim@jimklimov.com>

- obs/debian.control, obs/nut.dsc, obs/nut.spec: OBS: Try to rectify package numbering and dependencies of sub-packages for Debian
 - obs/nut.dsc, obs/nut.spec: Build Requires python-pycparser
 - obs/nut.spec: OBS nut.spec : make manpages optional
 - obs/nut.spec: OBS nut.spec : fix LUA requirement at == 5.1 (not >= 5.1)
 - obs/nut.spec: nut.spec : make asciidoc a common dependency
 - obs/debian.rules, obs/nut.spec: OBS : try to call autogen.sh before configuring sources
 - obs/nut.spec: OBS nut.spec : use common tarball filename pattern
 - obs/nut.dsc: OBS nut.dsc : comment away DEBTRANSFORM of teh tarball
 - obs/debian.nut-snmp.install, obs/nut.spec: Update OBS packaging to deliver bin/nut-scanner-reindex-dmfsnmp
 - obs/debian.nut-snmp.install, obs/debian.rules, obs/nut.spec: Update packaging files to install DMF data files
 - obs/control: Seems OBS mkpac.sh wants a file named "control" in any debian-pkg directory type (obs/ too)
-

2.136 2016-08-18 Jim Klimov <jim@jimklimov.com>

- obs/debian.Makefile.am, obs/debian.Makefile.in, obs/debian.NEWS, obs/debian.changelog, obs/debian.compat, obs/debian.control, obs/debian.copyright, obs/debian.description.subst, obs/debian.gbp.conf, obs/debian.hotplug, obs/debian.libnutclient-dev.install, obs/debian.libnutclient-dev.manpages, obs/debian.libnutclient0.install, obs/debian.libnutclient0.lintian-overrides, obs/debian.libnutscan1-dev.install, obs/debian.libnutscan1.install, obs/debian.libups-nut-perl.install, obs/debian.libupsclient-dev.install, obs/debian.libupsclient-dev.manpages, obs/debian.libupsclient4.install, obs/debian.nut-cgi.README.Debian, obs/debian.nut-cgi.docs, obs/debian.nut-cgi.install, obs/debian.nut-cgi.manpages, obs/debian.nut-cgi.postinst, obs/debian.nut-cgi.postrm, obs/debian.nut-client.init, obs/debian.nut-client.install, obs/debian.nut-client.links, obs/debian.nut-client.lintian-overrides, obs/debian.nut-client.maintscript, obs/debian.nut-client.manpages, obs/debian.nut-client.postinst, obs/debian.nut-client.preinst, obs/debian.nut-client.tmpfiles, obs/debian.nut-doc.doc-base.nut-developer-guide, obs/debian.nut-doc.doc-base.nut-faq, obs/debian.nut-doc.doc-base.nut-packager-guide, obs/debian.nut-doc.doc-base.nut-user-manual, obs/debian.nut-doc.install, obs/debian.nut-ipmi.install, obs/debian.nut-ipmi.manpages, obs/debian.nut-monitor.install, obs/debian.nut-monitor.menu, obs/debian.nut-monitor.xpm, obs/debian.nut-powerman-pdu.install, obs/debian.nut-powerman-pdu.manpages, obs/debian.nut-server.dirs, obs/debian.nut-server.init, obs/debian.nut-server.install, obs/debian.nut-server.manpages, obs/debian.nut-server.postinst, obs/debian.nut-server.postrm, obs/debian.nut-server.preinst, obs/debian.nut-server.prem, obs/debian.nut-server.tmpfiles, obs/debian.nut-snmp.docs, obs/debian.nut-snmp.install, obs/debian.nut-snmp.manpages, obs/debian.nut-xml.install, obs/debian.nut-xml.manpages, obs/debian.nut.README.Debian, obs/debian.nut.TODO.Debian, obs/debian.nut.docs, obs/debian.python-nut.install, obs/debian.rules, obs/debian.series, obs/debian.watch, obs/nut.changes, obs/nut.dsc, obs/nut.spec: Added packaging metadata used by OBS as of 2016-08-18 (except debian.series)
-