

CS 4530: Fundamentals of Software Engineering

Module 06: React Hook Patterns

Adeel Bhutta, Rob Simmons and Mitch Wand
Khoury College of Computer Sciences

Learning Objectives for this Module

- By the end of this module, you should be able to:
 - Explain the basic use cases for useEffect
 - Explain when a useEffect is executed, and when its return value is executed
 - Construct simple custom hooks and explain why they are useful.
 - Be able to explain the three core steps of a test (assemble, act, assess) can map to UI component testing

Lesson 6.1 useEffect

useEffect is a mechanism for synchronizing a component with an external system

```
export default function ClockDisplay(props: ClockDisplayProps) {  
  const clock = props.clock;  
  const [localTime, setLocalTime] = useState(0);
```

```
  useEffect(() => {  
    const listener1 = () => setLocalTime(time => time +1)  
    clock.addListener(listener1);
```

```
  return () => {clock.removeListener(listener1);  
  };  
}, []);
```

Empty array says: do this on first render only

Action to take on first render

Action to take when component dismounts

src/Shared/Components/SimpleClockDisplay.tsx

<https://react.dev/reference/react/useEffect>

An external system means any piece of code that's not inside your React component

- An event in the lifecycle of a component, like `render`.
- A timer managed with `setInterval` and `clearInterval`
- An event subscription like a chat server (sockets?)
- A call to fetch data from an external API or web site
- An external animation library
- A piece of business logic in an app that is external to your component

Let's build a clock display

- Start by defining the props

```
export interface ClockDisplayProps
{
  name: string;
  key: number;
  clock: ITicker;
  handleDelete?: () => void;
  handleAdd?: () => void;
  noisyDelete?: boolean;
}
```

<ClockDisplay> (1): set up the useEffect

```
import { useState, useEffect } from "react";
import { Box, Button, HStack, VStack } from "@chakra-ui/react";
import type { ClockDisplayProps } from "../types";

// this version simply imports a clock from its parent
export default function ClockDisplay(props: ClockDisplayProps) {
  const clock = props.clock;
  const [localTime, setLocalTime] = useState(0);

  useEffect(() => {
    const listener1 = () => {setLocalTime((localTime) => localTime + 1)};
    clock.addListener(listener1);
    return () => {
      clock.removeListener(listener1);
    };
  }, []);
```

<ClockDisplay> (2): the handlers

```
function handleStart() { clock.start(); }
```

```
function handleStop() { clock.stop(); }
```

```
function handleReset() { setLocalTime(0); }
```

<ClockDisplay> (3): the display logic

```
return (  
  <VStack border="2px" borderColor="green" padding="1" width="fit-content" mx="auto">  
    <HStack>  
      <Box>Clock: {props.name}</Box>  
      <Box>Time = {localTime}</Box>  
      <Box>nlisteners = {clock.nListeners}</Box>  
    </HStack>  
    <HStack>  
      <Button onClick={handleStart}>Start</Button>  
      <Button onClick={handleStop}>Stop</Button>  
      <Button onClick={handleReset}>Reset</Button>  
    </HStack>  
    {props.handleAdd && (  
      <HStack>  
        <Button onClick={props.handleDelete}>Delete {props.name}</Button>  
        <Button onClick={props.handleAdd}>Add a clock</Button>  
      </HStack>  
    )}  
  </VStack>  

```


Running a single clock

```
import { useState, useEffect } from "react";
import { type ITicker } from "../../Shared/types";
import Ticker from "../../Shared/Classes/Ticker";
import ClockDisplay from "../../Shared/Components/SimpleClockDisplay";

export default function App() {
  const [clock, _] = useState<ITicker>(new Ticker(1000));

  return (
    <ClockDisplay name="demo1" key={1} clock={clock} />
  )
}
```

Demo!



We can use ClockDisplay with a different parent!

src/Examples/ThreeClocks/App.tsx

- Components are modular, so we can use ClockDisplay with a different parent.
- But this required careful design!

```
export default function App() {  
  const [clock, _] = useState<ITicker>(new Ticker(1000));  
  
  return (  
    <VStack>  
      <Heading>Three Clocks</Heading>  
      <ClockDisplay key={1} name="Clock A" clock={clock} />  
      <ClockDisplay key={2} name="Clock B" clock={clock} />  
      <ClockDisplay key={3} name="Clock C" clock={clock} />  
    </VStack>  
  );  
}
```

running ThreeClocks

e Drive Trello New Trello NY Times Boston Globe

Three Clocks

Clock: Clock A	Time = 119	nlisteners = 3
Start	Stop	Reset

Clock: Clock B	Time = 119	nlisteners = 3
Start	Stop	Reset

Clock: Clock C	Time = 119	nlisteners = 3
Start	Stop	Reset

- Next: back to useEffect in detail....

useEffect's Dependencies Control Its Execution

- `useEffect` takes an optional array of dependencies
- The effect is only executed if one or more of the values in the dependency change (e.g. by a setter)
- Special Cases:
 - `[]` means run only on first render
 - No argument means run on every render

Example (Part 1)

src/Examples/useEffect-demo.tsx

```
export default function App() {
  const [i, setI] = useState(0);
  const [j, setJ] = useState(0);

  // runs only on first render.
  useEffect(() => {
    console.log('useEffect #1 is run only on first render');
  }, []);

  useEffect(() => {
    console.log('useEffect #2I is run when i changes');
  }, [i]);

  useEffect(() => {
    console.log('useEffect #2J is run when j changes');
  }, [j]);

  useEffect(() => {
    console.log('useEffect #2IJ is run when either i or j
changes');
  }, [i, j]);

  // runs on every render
  useEffect(() => {
    console.log('useEffect #3 is called on every render');
  });
}
```

```
function onClickI() {
  console.log('Clicked i!');
  setI(lastI => lastI+1);
  // bound variable name doesn't matter, of course
  // setI(i+1) is a bug, because value of i may not
  // be current.
}

function onClickJ() {
  console.log('Clicked j!');
  setJ(j => j+1);
}

return (
  <VStack>
    <Heading>useEffect demo #1IJ</Heading>
    <Text> i is {i} </Text>
    <Button onClick={onClickI}>Increment i</Button>
    <Text> j is {j} </Text>
    <Button onClick={onClickJ}>Increment j</Button>
  </VStack>
);
```

Demo


useEffect demo #1

i is 1

Increment i

j is 1

Increment j



Elements Console Sources Network >> 1

top Filter Default levels 1 issue:

2 hidden

useEffect #1 is run only on first render	useEffect-demo.tsx:11
useEffect #2I is run when i changes	useEffect-demo.tsx:20
useEffect #2J is run when j changes	useEffect-demo.tsx:24
useEffect #2IJ is run when either i or j changes	useEffect-demo.tsx:28
useEffect #3 is called on every render	useEffect-demo.tsx:33
useEffect #1 is run only on first render	useEffect-demo.tsx:11
useEffect #2I is run when i changes	useEffect-demo.tsx:20
useEffect #2J is run when j changes	useEffect-demo.tsx:24
useEffect #2IJ is run when either i or j changes	useEffect-demo.tsx:28
useEffect #3 is called on every render	useEffect-demo.tsx:33
Clicked i!	useEffect-demo.tsx:49
useEffect #2I is run when i changes	useEffect-demo.tsx:20
useEffect #2IJ is run when either i or j changes	useEffect-demo.tsx:28
useEffect #3 is called on every render	useEffect-demo.tsx:33
Clicked j!	useEffect-demo.tsx:54
useEffect #2J is run when j changes	useEffect-demo.tsx:24
useEffect #2IJ is run when either i or j changes	useEffect-demo.tsx:28
useEffect #3 is called on every render	useEffect-demo.tsx:33

> `ctrl` `i` to turn on code suggestions. *Don't show again* NEW

When is the cleanup function executed?

- In general, the cleanup function is executed sometime before the next time the hook is run.
- For the first-time-only case, this means when the component is dismantled.
- Let's look at useEffect demo again, this time with noisy cleanups.

Demo

```
function cleanup(message: string) {
  return () => {
    console.log('cleanup: ' + message);
  };
}

export default function App() {
  const [i, setI] = useState(0);
  const [j, setJ] = useState(0);

  // runs only on first render.
  useEffect(() => {
    console.log('useEffect #1 is run only on first render');
    return cleanup('useEffect #1');
  }, []);

  useEffect(() => {
    console.log('useEffect #2I is run when i changes');
    return cleanup('useEffect #2I');
  }, [i]);

  // etc.
```

useEffect demo with CleanUps

n is 1

Increment n

m is 0

Increment m

The screenshot shows a web browser's developer console with the 'Console' tab selected. The console displays a series of log messages from a React application, demonstrating the behavior of `useEffect` with `CleanUps`. The messages are as follows:

- `useEffect #1 is run only on first render` (linked to `...Effect-demoWithCleanUps.tsx:20:16`)
- `useEffect #2N is run only when n changes` (linked to `...Effect-demoWithCleanUps.tsx:25:16`)
- `useEffect #2M is run when m changes` (linked to `...Effect-demoWithCleanUps.tsx:30:16`)
- `useEffect #2MN is called when m or n changes` (linked to `...Effect-demoWithCleanUps.tsx:36:16`)
- `useEffect #3 is called on every render` (linked to `...Effect-demoWithCleanUps.tsx:42:16`)
- `Clicked n!` (linked to `...Effect-demoWithCleanUps.tsx:54:16`)
- `cleanup: useEffect #2N` (linked to `...Effect-demoWithCleanUps.tsx:10:57`)
- `cleanup: useEffect #2MN` (linked to `...Effect-demoWithCleanUps.tsx:10:57`)
- `cleanup: useEffect #3` (linked to `...Effect-demoWithCleanUps.tsx:10:57`)
- `useEffect #2N is run only when n changes` (linked to `...Effect-demoWithCleanUps.tsx:25:16`)
- `useEffect #2MN is called when m or n changes` (linked to `...Effect-demoWithCleanUps.tsx:36:16`)
- `useEffect #3 is called on every render` (linked to `...Effect-demoWithCleanUps.tsx:42:16`)

The console interface includes a toolbar at the top with icons for Inspector, Console, Debugger, Network, and a search icon. Below the toolbar is a 'Filter Output' section. The log messages are categorized into 'Errors', 'Warnings', 'Logs', 'Info (1)', 'Debug', 'CSS', 'XHR', and 'Requests'. The 'Logs' tab is currently selected, showing the messages listed above. At the bottom of the console, there is a double arrow icon and a small icon representing a document with a blue dot.

Communication with an (Actual) External System

- In the previous example, everything was present in the one codebase, including the clock.
- More common situation is that the user interface components need to communicate with a remote system, not necessarily in the same codebase.

Example: Interacting With a REST-based Server

```
export default function RandomNASA() {
  const [image, setImage] = useState<null | string>(null);
  const [error, setError] = useState<unknown>(null);

  useEffect(() => {
    fetch("https://api.nasa.gov/planetary/apod?api_key=DEMO_KEY")
      .then((response) => response.json())
      .then((json) => {
        const data = z.object({ url: z.string() }).parse(json);
        setImage(data.url);
      })
      .catch((err) => setError(err));
  }, []);

  return error !== null ? (
    `Could not retrieve image: ${error}`
  ) : image !== null ? (
    <img src={image} />
  ) : (
    `Loading...`
  );
}
```

Doing this in the real world is somewhat more complicated than this (see Resources for details)

This function runs *after* the fetch returns

And this function runs *after that*

This function runs if there's an error in the previous

Lesson 6.2 Custom Hooks

Custom Hooks

- REACT lets us combine `useState` and `useEffect` to build custom hooks.
- Custom Hooks let us separate business logic from display logic

Example: ToDoList

```
export default function ToDoApp () {  
  const [todoList, setTodolist] = useState<ToDoItem[]>([])  
  const [itemKey, setItemKey] = useState<number>(0) // first unused key  
  
  function handleAdd (title:string, priority:string) {  
    if (title === '') {return} // ignore blank button presses  
    setTodolist(todoList.concat({title: title, priority: priority, key: itemKey}))  
    setItemKey(itemKey + 1)  
  }  
  
  function handleDelete(targetKey:number) {  
    const newList = todoList.filter(item => item.key !== targetKey)  
    setTodolist(newList)  
  }  
  
  return (  
    <VStack>  
      <Heading>TODO List</Heading>  
      <ToDoItemEntryForm onAdd={handleAdd}/>  
      <ToDoListDisplay items={todoList} onDelete={handleDelete}/>  
    </VStack>  
  )  
}
```




business logic



display logic

Refactoring ToDoList

```
export default function ToDoApp () {  
  
  const {todoList, handleAdd, handleDelete} = useToDoItemList()  
  
  return (  
    <VStack>  
      <Heading>TODO List</Heading>  
      <ToDoItemEntryForm onAdd={handleAdd}/>  
      <ToDoListDisplay items={todoList} onDelete={handleDelete}/>  
    </VStack>  
  )  
}
```



business logic
is encapsulated

The hook encapsulates the business logic

```
export default function useToDoItemList () {  
  const [todoList,setTodolist] = useState<ToDoItem[]>([])  
  const [itemKey,setItemKey] = useState<number>(0)    // first unused key  
  
  function handleAdd (title:string, priority:string) {  
    if (title === '') {return}    // ignore blank button presses  
    setTodolist(todoList.concat({title: title, priority: priority, key: itemKey}))  
    setItemKey(itemKey + 1)  
  }  
  
  function handleDelete(targetKey:number) {  
    const newList = todoList.filter(item => item.key !== targetKey)  
    setTodolist(newList)  
  }  
  
  return {todoList: todoList, handleAdd: handleAdd, handleDelete: handleDelete}  
}
```

The hook is like a class managing a piece of state

```
export default function useToDoItemList () {  
  const [todoList, setTodolist] = useState<ToDoItem[]>([])  
  const [itemKey, setItemKey] = useState<number>(0) // first unused key  
  
  function handleAdd (title:string, priority:string) {  
    if (title === '') {return} // ignore blank button presses  
    setTodolist(todoList.concat({title: title, priority: priority, key: itemKey}))  
    setItemKey(itemKey + 1)  
  }  
  
  function handleDelete(targetKey:number) {  
    const newList = todoList.filter(item => item.key !== targetKey)  
    setTodolist(newList)  
  }  
  
  return {todoList: todoList, handleAdd: handleAdd, handleDelete: handleDelete}  
}
```

handleAdd and handleDelete
are the only methods for
manipulating the state

The hook's state becomes part of its user's state.

```
export default function useToDoItemList () {  
  const [todoList, setTodolist] = useState<ToDoItem[]>([])  
  const [itemKey, setItemKey] = useState<number>(0) // first unused key  
  
  function handleAdd (title:string, priority:string) {  
    if (title === '') {return} // ignore blank button presses  
    setTodolist(todoList.concat({title: title, priority: priority, key: itemKey}))  
    setItemKey(itemKey + 1)  
  }  
  
  function handleDelete(targetKey:number) {  
    const newList = todoList.filter(item => item.key !== targetKey)  
    setTodolist(newList)  
  }  
  
  return {todoList: todoList, handleAdd: handleAdd, handleDelete: handleDelete}  
}
```

calling these setters redisplay
the whole component

The Rules of Hooks

1. Only call hooks at the top level

- Not within loops, inside conditions, or nested functions
- Rationale: The order of hooks called must always be the same each time a component renders

2. Only call hooks from React Components or Custom Hooks

- Not from any other helper methods or classes
- Rationale: React must know the component that the call to the hook is associated with

```
export function LikeButton() {  
  const [isLiked, setIsLiked] = useState(false);  
  const [count, setCount] = useState(0);  
  ...  
}
```

React knows which `useState` is which by tracking calls to them from components in the render tree

We Use Two ESLint Rules for React Hooks

- You should not violate the rules of hooks. These linter plugins help detect violations
- React-hooks/rules-of-hooks
 - Enforces that hooks are only called from React functional components or custom hooks
- React-hooks/exhaustive-deps
 - Enforces that all variables used in useEffects are included as dependencies

Putting it All Together

- In the previous examples, we learned
 - how to introduce side effects
 - how to create our own hooks
- We can use these concepts to make React components interact with a remote system (e.g., REST services).

Example: Setting Up and Cleaning Up a Chat Subscription; Showing Unread Messages

```
useEffect(() => {  
  const socket = new WebSocket('wss://api.randomsite.com/chat');
```

```
  socket.onmessage = (event) => {  
    const message = JSON.parse(event.data);  
    setMessages((prev) => [...prev, message]);  
  };  
  return () => {  
    socket.close();  
  };  
}, []);
```

This allows you to subscribe to live chat messages

This function runs at cleanup to avoid memory leaks

```
useEffect(() => {  
  document.title = `You have ${unreadMsgs} unread messages`;  
}, [unreadMsgs]);
```

This updates the browser tab title to show the number of unread messages or notifications

Lesson 6.3 Testing your React components

Testing React components

- The AAA pattern ("Assemble/Act/Assess") still applies
- Need a test double for the React system
 - render components into a "virtual dom" or into a captive web browser
- We'll be using a package called "Playwright" to do this.

Recall: Most tests are in AAA form: Assemble/Act/Assess

```
test('addStudent should add a student to the database', () => {  
  // const db = new DataBase ()  
  expect(db.nameToIDs('blair')).toEqual([])  
  
  const id1 = db.addStudent('blair');  
  
  expect(db.nameToIDs('blair')).toEqual([id1])  
});
```

The diagram illustrates the AAA (Assemble/Act/Assess) test pattern using a code example. Three green callout boxes with red borders and arrows point to specific parts of the code:

- Assemble (and check that you've assembled it)**: Points to the first `expect` statement: `expect(db.nameToIDs('blair')).toEqual([])`.
- Act (do the action that you are trying to test)**: Points to the `const id1 = db.addStudent('blair');` line.
- Assess: check to see that the response is correct**: Points to the second `expect` statement: `expect(db.nameToIDs('blair')).toEqual([id1])`.

Playwright commands work on a “page object”

<code>.goto()</code>	Navigate to a URL. Many tests begin with this command.
<code>.getByLabel()</code>	Find form elements by their associated label text.
<code>.getByRole()</code>	Find elements by their ARIA role(button, textbox, etc) .
<code>.getByText()</code>	Find elements by their text content.
<code>.waitForURL()</code>	Wait for navigation to complete to a specific URL.
<code>.fill()</code>	Type text into an input field.

These will fail if the specified element does not exist

A typical playwright test

```
test('should allow an existing user to log in', async ({ page }) => {  
  await page.goto('/login');  
  
  await page.getByLabel('Username')  
    .fill("Frau Drei");  
  
  await page.getByLabel('Password',  
    { exact: true }).fill(password);  
  
  await page.getByRole('button',  
    { name: 'Log In' }).click();  
  
  await page.waitForURL('/');  
  await expect(page.getByText('signed in as Frau Drei')).toBeVisible();  
});
```



Assemble (navigate to the page)



Act (fill form and click login)



Assess: check to see that the response is correct

Learning Objectives for this Lesson

- By the end of this lesson, you should be able to:
 - Explain the basic use cases for `useEffect`
 - Explain when a `useEffect` is executed, and when its return value is executed
 - Construct simple custom hooks and explain why they are useful.
 - Be able to explain the three core steps of a test (assemble, act, assess) can map to UI component testing