

CS 4530 Software Engineering

Lesson 8.2: Deployment Infrastructure

Jonathan Bell, Adeel Bhutta, Ferdinand Vesely, Mitch Wand

Khoury College of Computer Sciences
© 2022, released under [CC BY-SA](#)


Learning Objectives for this Lesson

By the end of this lesson, you should be able to...


- Describe the difference between key deployment container abstractions and their role in modern software
- Compare the performance and cost of different deployment infrastructures, including platform-as-a-service

Deploying a Web App

Circa 2008: Manual deployments to private or shared machines





- A simple approach that works, but does not scale in:
 - Number of machines
 - Number of programs
 - Size of programs
 - Frequency of deployments



Deploying a Web App

Making it better: automation


- Automatically sFTP code to all 50+ machines
- Monitor for anomalies
- Write a scheduler for machine assignment...



Deploying a Web App

Making it better: Multitenancy


- What if the mapping of programs/users to machines is not 1:1?
- Example: 5 applications, each get 200MB of RAM, server has 1GB
- Problem: What happens if someone's program goes awry?



Multi-Tenancy


Virtualization to the rescue

- Solution: Each app gets its own Virtual Machine (VM)
- OS provides resource limits and quality guarantees per-VM
- Each VM runs its own OS - not an efficient use of resources (5x200MB RAM for each app PLUS 5x500MB RAM to run 5 OS's)
- Lightweight containers (e.g. Docker) provide isolation, but run in same OS, less resource utilization




Automating Deployment of Complex Infrastructure

Automation + Multi-tenancy: Kubernetes



“Give me at least 1 of each of these app services in their own docker containers, and if the load gets above a threshold, spin up more of them”



Managed by Kubernetes

Large-scale cluster management at Google with Borg

Abhishek Verma[†] Luis Pedrosa[‡] Madhukar Korupolu
David Oppenheimer Eric Tune John Wilkes
Google Inc.

Abstract

Google's Borg system is a cluster manager that runs hundreds of thousands of jobs, from many thousands of different applications, across a number of clusters each with up to tens of thousands of machines.

It achieves high utilization by combining admission control, efficient task-packing, over-commitment, and machine sharing with process-level performance isolation. It supports high-availability applications with runtime features that minimize fault-recovery time, and scheduling policies that reduce the probability of correlated failures. Borg simplifies life for its users by offering a declarative job specification language, name service integration, real-time job monitoring, and tools to analyze and simulate system behavior.

We present a summary of the Borg system architecture and features, important design decisions, a quantitative analysis of some of its policy decisions, and a qualitative examination of lessons learned from a decade of operational experience with it.




Figure 1: The high-level architecture of Borg. Only a tiny fraction of the thousands of worker nodes are shown.

1. Introduction

The cluster management system we internally call Borg admits, schedules, starts, restarts, and monitors the full range of applications that Google runs. This paper explains how.

Borg provides three main benefits: (1) hides the details of resource management and failure handling so its users can focus on application development instead; (2) operates with very high reliability and availability, and supports applications that do the same; and (3) lets us run workloads across tens of thousands of machines effectively. Borg is not the first system to address these issues, but it's one of the few operating at this scale, with this degree of resiliency and completeness. This paper is organized around these topics, con-

2. The user perspective

Borg's users are Google developers and system administrators (site reliability engineers or SREs) that run Google's applications and services. Users submit their work to Borg in the form of *jobs*, each of which consists of one or more *tasks* that all run the same program (binary). Each job runs in one Borg *cell*, a set of machines that are managed as a unit. The remainder of this section describes the main features exposed in the user view of Borg.

2.1 The workload

Borg cells run a heterogenous workload with two main parts. The first is long-running services that should “never” go down, and handle short-lived latency-sensitive requests (a few μ s to a few hundred ms). Such services are used for end-user-facing products such as Gmail, Google Docs, and web search, and for internal infrastructure services (e.g., BigTable). The second is batch jobs that take from a few seconds to a few days to complete; these are much less sensitive to short-term performance fluctuations. The workload mix varies across cells, which run different mixes of applications depending on their major tenants (e.g., some cells are quite batch-intensive), and also varies over time: batch jobs


[†] Work done while author was at Google.
[‡] Currently at University of Southern California.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

EuroSys '15, April 21–24, 2015, Bordeaux, France.
Copyright is held by the owner/author(s).
ACM 978-1-4503-3238-5/15/04.
<http://dx.doi.org/10.1145/2741948.2741964>

Multi-Tenancy

Platform-as-a-service: What if we *don't care* about the infrastructure?



Platform-as-a-Service: Covey.Town Deployment

Heroku

neu-se / **covey.town** Public

<> Code

Issues

Pull requests

Actions

Projects

Wiki

Security

Insights

Settings

master 6 branches 1 tag

Go to file Add file Code

jon-bell Fix tests after reorg 58d9e79 18 hours ago 83 commits

.github/workflows

docs

frontend

services/townService

.editorconfig

.gitignore

Procfile

README.md

captain-definition-fro

captain-definition-roomservice

package-lock.json

package.json

Disable deployment

Update architecture

Fix tests after reorg

First draft of Handout

Update deployment scripts based on townService refactoring

Prepare for Spring 2022:

Prepare for Spring 2022:

20 hours ago

14 months ago

14 months ago

last month

last month

2 months ago

last month

2 months ago




last month

1 lines (1 sloc) 47 Bytes

1 web: node services/townService/build/server.js


My project runs with NodeJS

After running npm install, run this to make a server



Platform-as-a-Service: Covey.Town Deployment

Netlify




Settings for epic-leakey-0cbc99

[app.covey.town](#)

Deploys from [GitHub](#). Owned by [Jonathan Bell's team](#).


Last update on Mar 12 (6 days ago)




General
Build & deploy
Continuous Deployment
Environment
Post processing
Deploy notifications
Domain management
Analytics
Functions
Identity
Forms

Continuous Deployment

Settings for Continuous Deployment from a Git repository

Build settings	
Repository:	 github.com/epic-se/covey.town-private
Base directory:	frontend
Build command:	CI= npm run-script build
Publish directory:	frontend/build
Builds:	Active
Learn more about common configuration directives in the docs ↗	

Run this command
to build my site



Computing Infrastructure

Choosing an abstraction for your application

- Centralization vs customization: “machines as cattle vs machines as pets”
- How do we manage state?
- What is our expected scale?
- How much management overhead do we want to take on?

Computing Infrastructure

Summary of the options

- Deploy VMs: Greatest degree of control, greatest cost, greatest latency
- Deploy containers: Better resource utilization
- Platform-as-a-service: Minimal degree of control, YMMV with cost