

MOBILE DEVELOPMENT FILES & PERSISTENCE: PART 1

Rudd Taylor
Founder, SALT

FILES AND PERSISTENCE

LEARNING OBJECTIVES

- › Recognize the different types of persistence and their pros/cons
- › Implement user defaults, but recognize that storage here should be limited
- › Create property lists and save/read data from property lists
- › Discover the iOS folder structure and where we should store certain types of files
- › Use folder search within our applications to read and write files
- › Create, read, and write to flat files

FILES AND PERSISTENCE

INTRO TO PERSISTENCE

FILES AND PERSISTENCE

WHY PERSIST?

FILES AND PERSISTENCE

WHY PERSIST?

- Saving data across sessions
 - App high scores
 - App settings
 - User credentials
 - And lots, lots more
- Sharing data between screens

FILES AND PERSISTENCE

HOW TO PERSIST?

- There are many, many ways to persist data
- There is no 'right' way
- Choosing how to persist depends on several things
 - What kind of data am I writing?
 - What kind of data am I reading?
 - Am I storing relations between things?
 - How persistent does my data need to be?

FILES AND PERSISTENCE

HOW TO PERSIST?

- There are several built-in options for persisting data in iOS
 - This session:
 - Flat files
 - Property lists
 - User defaults
 - Next session (high level):
 - Core data
 - SQL

FILES AND PERSISTENCE

USER DEFAULTS

FILES AND PERSISTENCE

USER DEFAULTS

- A key/value store for storing app settings and other small, independent bits of data

FILES AND PERSISTENCE

USER DEFAULTS

- What kind of data am I writing?
 - Small bits of data and an associated key, stored one at a time
 - e.g. A string, a number, a boolean, a dictionary, an array, ~~a dictionary~~
- What kind of data am I reading?
 - Same as above, retrieved one at a time
- Am I storing relations between things?
 - No
- How persistent does my data need to be?
 - Persistent across app sessions, deleted when the app is deleted

NSData is a type

FILES AND PERSISTENCE

USER DEFAULTS

- Good for:
 - App settings
 - App state
- Not good for:
 - Large data sets
 - Complex relations
 - Sensitive data
 - Caches

FILES AND PERSISTENCE

NSUSERDEFAULTS

- Storing data:
 - `NSUserDefaults.standardUserDefaults().setBool(true, forKey: "mySetting")`
- Retrieving data:
 - `NSUserDefaults.standardUserDefaults().boolForKey("mySetting") // true`
- Very easy interaction with Apple settings menu settings

PERSISTENCE

NSUSERDEFAULTS CODE

ALONG

FILES AND PERSISTENCE

GROUP ASSIGNMENT

- › Create an array of athlete names **when your application starts**, store this array in user defaults
- › In the view controller, retrieve this list of names and print them out
- › Bonus 1: Print these names in a table view
- › Bonus 2: Add ability to add a persisted name to the list

FILES AND PERSISTENCE

PROPERTY LISTS

FILES AND PERSISTENCE

PROPERTY LISTS

- A bundle of text data (XML, specifically) stored in a text file.

FILES AND PERSISTENCE

PROPERTY LISTS

- What kind of data am I writing? **Plist**
 - Small-ish sets of data (a few hundred Kb) retrieved file-at-a-time
 - e.g. A string, a number, a boolean, a dictionary, an array, a dictionary
- What kind of data am I reading?
 - Same as above, retrieved file-at-time
- Am I storing relations between things?
 - Not complicated ones
- How persistent does my data need to be?
 - Persistent across app sessions, deleted when the app is deleted

FILES AND PERSISTENCE

PROPERTY LISTS

- Good for:
 - Persisting lists,
 - Persisting collections of properties
- Not good for:
 - Very data sets
 - Complex relations
 - Sensitive data

FILES AND PERSISTENCE

PROPERTY LISTS

NSUserDefaults loads up when app loads

Larger amounts of data (few 00s KB) should go into plists

▸ Storing data:

- `let cocoaArray: NSArray = someSwiftArray`
- `cocoaArray.writeToFile(fileUrlString, atomically: true)` // If you have a URL String
- `cocoaArray.writeToURL(fileUrl, atomically: true)` // If you have a URL

▸ Retrieving data:

- `let myArray = NSArray(contentsOfFile: fileUrlString)` // If you have a URL String
- `let myArray = NSArray(contentsOfURL: fileUrl)` // If you have a URL

Objective-C version of Array

different from Swift's Array, but can be transformed

FILES AND PERSISTENCE

PROPERTY LISTS

- UserDefaults is a fancy wrapper around an app-specific plist file
- plists can store:
 - Strings
 - Numbers
 - Date
 - Data
 - Dictionary
 - Array
- Or any combination of the above

PERSISTENCE AND FILES

PLIST CODE-ALONG

PERSISTENCE AND FILES

GROUP ASSIGNMENT

- › Extend your app to add a plist for coaches with at least 2 coaches. Coaches should have name, years of experience, coach title.
- › Print the name of each coach and their title.
- › Bonus: Allow user to add coaches through user interface.
- › Bonus 2: Display all players and coaches in their own respective table view.

FILES AND PERSISTENCE

FLAT FILES AND DIRECTORY STRUCTURES

PERSISTENCE AND FILES

DIRECTORY

- Your app bundle contains a lot of useful information
 - Your app binary, and all of its supporting files
 - Your app's documents
 - Settings
 - Temporary files
 - These are stored in various directories

PERSISTENCE AND FILES

DIRECTORY

- › **App/Documents:** User created content. Backed up.
- › **App/Documents/Inbox:** for accessing outside entities such as opening email attachments. Backed up.
- › **App/YourApp.app:** The app itself and its branding supporting documents. Ie: app icons, app binary, different branding images, fonts, sounds. Not backed up.
- › **App/Library:** Most other files that are not user files. This folder itself usually does not contain files, but contains sub folders where content is stored. Backed up.
- › **App/Library/Caches:** Temporary data that our app needs to re-create later. Don't place any important application files in this folder, as system puts least priority on these files and clears out the folder if out of space. Not backed up.
- › **App/Library/Preferences:** Preferences that app remembers between launches. Backed up.
- › **App/tmp:** Temporary files that app creates and downloads. Used for storing downloaded files to increase app performance. The system may purge these files when app is not in use. Not backed up.

PERSISTENCE AND FILES

DIRECTORY

- › We can get at these directories with `NSFileManager`
- › `if let documentPath = NSFileManager.defaultManager().URLsForDirectory(.DocumentDirectory, inDomains: .UserDomainMask).first as? NSURL { /* my code*/ }` // This gets the documents directory
- › `let filePath = documentPath.URLByAppendingPathComponent("file.plist", isDirectory: false)` // This is for appending a file path onto the directory

FILES AND PERSISTENCE

FLAT FILES CODE ALONG

PERSISTENCE AND FILES

GROUP ASSIGNMENT

- › Create a new file in the documents folder to store player notes
- › The signatures will be in the form of an array of strings
- › Append a new note to the end of the list (through user input from single text box) and save it to the signatures file
- › Notes are global, not associated with a specific player
- › Bonus: List all players, when one is clicked, give the ability to add notes to that player specifically. Those notes should be persisted and printed out when the 'notes' screen is navigated to
- › Bonus 2: Display and remove player notes through a table view.