

Secure Digital Signature Validated by Ambient

User's Wi-Fi-enabled devices
North Carolina AT State University
AlQahtani.aasa@gmail.com

Ali Abdullah S. AlQahtani
Computer science
hosam.amleh@gmail.com

Computer Systems Technology
University of North Carolina
Wilmington
Znelawadi@gmail.com

Greensboro
Cyberspace Engineering

North Carolina
Louisiana Tech University

USA
Hosam Alamleh
Wilmington
NC
Zakaria El-Awadi
Ruston
Louisiana
USA

Abstract

In cyberspace, a digital signature is a mathematical technique that plays a significant role, especially in validating the authenticity of digital messages, emails, or documents. Furthermore, the digital signature mechanism allows the recipient to trust the authenticity of the received message that is coming from the said sender and that the message was not altered in transit. Moreover, a digital signature provides a solution to the problems of tampering and impersonation in digital communications. In a real-life example, it is equivalent to a handwritten signature or stamp seal, but it offers more security. This paper proposes a scheme to enable users to digitally sign their communications by validating their identity through users' mobile devices. This is done by utilizing the user's ambient Wi-Fi-enabled devices. Moreover, the proposed scheme depends on something that a user possesses (i.e., Wi-Fi-enabled devices), and something that is in the user's environment (i.e., ambient Wi-Fi access points) where the validation process is implemented, in a way that requires no effort from users and removes the "weak link" from the validation process. The proposed scheme was experimentally examined.

Keywords

digital signature, validation, email spoofing, public-key, private-key, Wi-Fi, RSSI.

ACM Reference Format:

User's Wi-Fi-enabled devices, Ali Abdullah S. AlQahtani, Computer Systems Technology, Greensboro, North Carolina, USA, Hosam Alamleh, Wilmington, NC, Zakaria El-Awadi, Ruston, Louisiana, and USA. 2026. Secure Digital Signature Validated by Ambient. In . ACM, New York, NY, USA, 5 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
Conference'17, Washington, DC, USA

© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 978-x-xxxx-xxxx-x/YYYY/MM
<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 Introduction D

DIGITAL signatures are based on public-key cryptography, also known as Asymmetric Cryptographic Algorithms which utilizes two keys: one for encryption (i.e., a method that converts data into an unreadable form); the other for decryption (i.e., a method that converts data back into a readable form) [11]. It is not possible to use the same key to both encrypt and decrypt the same message [4]. These two keys are related to each other mathematically and are known as public-key and private-key. The public-key is available and known to everyone on the internet, while the private-key is only known to its owner and must be kept secret and never shared. When a user wants to send a secure message to another user, the first user must use the second user's public key to encrypt the message. Then, the second user must use their private key to decrypt it. Spam and phishing attacks utilize email spoofing methods to deceive users to believe that a message came from a legit source. In spoofing attacks, the email headers are forged by the attacker so that at the receiver, the client software displays a spoofed sender address. Today, email systems allow email spoofing because of the way they were designed. The client application assigns outgoing messages to a sender address. The outgoing Simple mail transmission protocol (SMTP) servers have difficulties determining whether the sender address is legitimate or spoofed [6]. On the other hand, the recipient email servers can filter the spoofed message with the help of antimalware software. Today, email spoofing is one of the most common cyber-attacks. 3.1 billion domain-spoofed emails are transmitted every day [12]. Moreover, exceeding 90 percent of cyber-attacks start with an email message. Email spoofing and phishing have universal damage with losses estimated \$26 billion since 2016 [7]. This proposed system in this paper aims to combat email spoofing by digitally signing messages. In the proposed system, emails are signed automatically when the user's Wi-Fi capable device (e.g., smartphone, smartwatch, etc.) is within a small range of the message sending device (e.g., personal computer, laptop, etc.). This helps validate the sender's identity as the email sender when the sender's Wi-Fi-enabled device is proximate to the sending device.

2 Guide To Paper

This paper is organized as follows; Section III introduces the motivation of this study. The contribution of this study is presented in Section IV. Section V reviews the previous research on validating a user's digital signature. Section VI describes the proposed scheme system for validating a user's digital signature using ambient the user's Wi-Fi-enabled devices. The experiment to test proposed system along with the test's results are presented in Section VII, which indicates the ability to use a user's Wi-Fi-enabled devices to enable digital signing. Lastly, 159 Section VIII illustrates the summary and conclusion for the proposed scheme.

3 Motivation

A digital signature is a scheme for verifying the authenticity of digital messages, emails, or documents. A digital signature provides the recipient of the message to trust the authenticity of the received message that is coming from the said sender and that the message was not altered in transit. Digital signatures, like handwritten signatures, are unique to each signer. A digital signature uses Public Key Infrastructure (PKI); PKI requires the sender to generate two keys. One key is public, and one key is private. When a signer electronically signs of the received messages. In this paper, we propose a system that allows users to automatically digitally sign their email when their smart Wi-Fi-enabled device is proximate to their sending device (e.g., personal computer, laptop, etc.). The proposed system aims to combat email spoofing by developing an environment to securely digitally sign emails automatically without requiring any additional steps from users.

4 Contribution

This paper proposes a scheme to enable users to automatically digitally sign messages by utilizing the users' scheme depends on something that a user possesses (i.e., Wi-Fi-enabled devices), and something that is in the user's environment (i.e., ambient Wi-Fi access points) where the validation process is implemented in a way that requires no effort from the client-side arguably the most significant contribution of this paper. Primarily due to the proposed scheme removing the "weak link" from the validation process.

5 Related Works

Electronic signature and digital signature are often used interchangeably, but they are different. Digital signatures are mainly used to secure documents and are authorized by certification authorities, while electronic signatures are often associated with a contract to verify a document [3]. Digital signatures can be the underlying technology for e-signature [14]. A paper titled "Cryptographic key generation from multiple biometric modalities: Fusing minutiae with iris feature" was published in 2010 [1]. The published paper proposes an approach that depends on multimodal biometrics (i.e., Iris and fingerprint) to generate a cryptographic key securely to be used in digital signatures. In a paper titled "Using Voice to Generate Cryptographic Keys" a user's voice was utilized to generate a cryptographic key and utilize it to prove an identity to resource [8]. There have been several research works that propose using biometrics to digitally sign files and emails, including fingerprints [5], iris scans [10], and face [2]. However, such systems require specialized

hardware to enable such functionalities. Moreover, such techniques might face sensitivity problems [9] and user acceptance [9]. Other works propose using RFID to digitally sign transactions [13], which also requires RFID readers and tags. The proposed system is unique, as it does not require any new hardware. Alternatively, it uses the user's smartphone to sign messages and emails. Moreover, it is zero effort, which means it does not require any effort from users. All are required to have the user's smartphone in proximity to the user's workstation, where emails and messages are signed automatically.

6 The Proposed Scheme

6.1 Scheme's architecture The proposed system consists

of the following entities: 1) User devices: Wi-Fi-enabled devices (e.g., a smartphone, smartwatch, Laptop, etc.) with a relevant application. One of them (e.g., Laptop) will act as a message sending device while the other one will act as a validation device (e.g., smartphone). 2) Wi-Fi access points: Three access points in the user's environment are utilized to determine the positions of the participating devices. The primary function of the participating devices is to record and send the RSSI values, which to a remote validation entity. 3) A validation entity to collect the RSSI values sent by the Wi-Fi-enabled devices. Then, the validation entity will determine if the user's sending device is in proximity to the validation device; if yes, a private key will be provide to sign to sign the message; if not, the signing request will be denied.

6.2 Scheme's operation procedure In this

section, the proposed scheme's operating is presented step-by-step as showing in values then send them back to the 160 validation entity. Then the scanned RSSI values are collocated and sent to the validation entity. 2) The validation entity will run the calculated RSSI values equation (1) to compute the distance between the client's devices and all access points in the location. $PL_{log} = PL_0 + 10 \log_{10} d/d_0$ (1) Where PL_{log} is Ptx Prx. PL_0 is the path loss in dB. d is the path loss exponent. d_0 is the reference distance (1m). 3) The previous step outcome will be run through equation (2) to estimate the user's device's position (i.e., a user's x and y coordinates). $(x - x_1)^2 + (y - y_1)^2 = d_1^2$ $(x - x_2)^2 + (y - y_2)^2 = d_2^2$ $(x - x_3)^2 + (y - y_3)^2 = d_3^2$ (2) 4) After finding the user's Wi-Fi enabled devices x and y coordinates, the distance between the the client's two devices will be estimated using equation (3). Distance = $p \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}$ (3) 5) The validation entity now determines if the user's is authorized to sign the email based on distance between the two devices if they are within predefined acceptable range private key is granted; otherwise validation is denied. 6) When the user's private key is provided. it is used to sign the message. The signing can be done through an extension to the web browser or to the email client software.




Figure 1: Overview

7 Experiment

A smartphone application and a google chrome extension were designed to perform the proposed scheme. The applications reply to a request from the validation entity and scan all three access points. In the experimental setup, three access points were utilized at different positions in the user's environment. The three access points' exact standings were measured and located manually on the experiment site as a preliminary step. Moreover, x and y coordinates of seven different actual points were manually located within a room. A Wi-Fi-enabled device was placed at each point, then collected 20 RSSI values from each access point.

7.1 Position accuracy In this

experiment, the collected RSSI values were plugged into equation (2) to find the estimated x and y coordinates of each the seven different points. Find the different between each actual point and its estimated x and y coordinate were estimated using (3). shows the estimated positions and the different between the actual and estimated points after utilizing the first RSSI value that the Wi-Fi-enabled device collected. shows the estimated x and y coordinate and the difference between the actual and estimated points after utilizing the average of 60 RSSI values. shows the estimated x and y coordinate and the difference between the actual and estimated points after utilizing the maximum of 60 RSSI values. FIRST RSSI VALUE RESULTS Actual points Estimated points Difference (2, 17) (4.2, 14.3) 3.6 ft (3, 2) (1.3, 7.7) 5.9 ft (4.5, 9) (4.3, 9.3) 0.3 ft (5, 14) (4.1, 12.3) 1.96 ft (6, 2) (10.7, -1) 5.6 ft (7, 2) (-0.1, 7.4) 8.9 ft (8, 17) (6.4, 9) 7.2 ft AVERAGE OF 60 RSSI VALUES RESULTS Actual points Estimated points Difference (2, 17) (5.2, 15.4) 3.6 ft (3, 2) (1.4, 7.5) 5.6 ft (4.5, 9) (3.9, 9.9) 0.98 ft (5, 14) (4, 12.6) 1.6 ft (6, 2) (7, 2.4) 0.98 ft (7, 2) (3.2, 4.5) 4.6 ft (8, 17) (10.5, 15) 2.6 ft MAXIMUM OF 60 RSSI VALUES RESULTS Actual points Estimated points Difference (2, 17) (4.2, 14.3) 3.6 ft (3, 2) (1.5, 7.3) 5.6 ft (4.5, 9) (3.3, 10) 1.6 ft (5, 14) (3.8, 12.5) 1.97 ft (6, 2) (5.3, 4) 1.97 ft (7, 2) (1.3, 6.6) 7.5 ft (8, 17) (4.6, 9.9) 6.88 ft

7.2 Performance Measurement The validation performance

rate of the proposed scheme was examined by utilizing every RSSI value to estimate the distance between two Wi-Fi-enabled devices;

if the distance between the two device is 2 m or less validation is granted; otherwise, validation is denied. Then the results were run through a machine learning algorithm to generate a confusion matrix. After that, the proposed scheme's validation success rate was computed using equation (4). As a result, the proposed scheme provided a 95.63% validation success rate. TP + TN × 100 (4) PERFORMANCE MEASUREMENT Actual N=1260 Positive Negative True 660 32 False 23 545

Table 1: $(x - x_1)^2 + (y - y_1)^2 = d_1^2$

$$\begin{aligned} (x - x_1)^2 + (y - y_1)^2 &= d_1^2 \\ (x - x_2)^2 + (y - y_2)^2 &= d_2^2 \\ (x - x_3)^2 + (y - y_3)^2 &= d_3^2 \end{aligned} \quad (2)$$

- 4) After finding the user's Wi-Fi enabled devices x and y coordinates, the distance between the the client's two devices will be estimated using equation (3).

$$Distance = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2} \quad (3)$$

Table 2: AVERAGE OF 60 RSSI VALUES RESULTS

$$Distance = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2} \quad (3)$$

- 5) The validation entity now determines if the user's is authorized to sign the email based on distance between the two devices if they are within predefined acceptable range private key is granted; otherwise validation is denied.
- 6) When the user's private key is provided, it is used to sign the message. The signing can be done through an extension to the web browser or to the email client software.

Table 3: MAXIMUM OF 60 RSSI VALUES RESULTS

Actual points	Estimated points	Difference
(2, 17)	(4.2, 14.3)	3.6 ft
(3, 2)	(1.5, 7.3)	5.6 ft
(4.5, 9)	(3.3, 10)	1.6 ft
(5, 14)	(3.8, 12.5)	1.97 ft
(6, 2)	(5.3, 4)	1.97 ft
(7, 2)	(1.3, 6.6)	7.5 ft
(8, 17)	(4.6, 9.9)	6.88 ft

formance Measurement

Table 4: Systems for Video Technology, 18(4):549–553, 2008.

N=1260	Actual	
	Positive	Negative
True	660	32
False	23	545

VIII CONCLUSION

to validate a user's digital signature by utilizing the user's ambient Wi-Fi-enabled devices. Moreover, the proposed scheme depends on something that a user possesses (i.e., Wi-Fi-enabled devices), and something in the user's environment (i.e., ambient Wi-Fi access points) where the validation process is implemented in a way that requires no effort from the client-side arguably the most significant contribution of this paper. Primarily due to the proposed scheme removing the "weak link" from the validation process. The proposed scheme's experiments show that the proposed scheme results in a practical approach to validating a user's identity using his/her wi-fi enabled devices and enabling digitally signing the message. This

- [1] G. C. Kesler, "An overview of cryptography, 2003.
- [2] J. Koetzier, "Scammers send 3.1 billion domain spoofing emails a day, here's how to protect yourself (and your company). May
- [3] P. Grother and E. Tabassi, "Performance of biometric quality measures," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(4):531–543, 2007.
- [4] A. Jagadeesan, T. Thillaikarasi, and K. Duraiswamy, "Cryptographic key generation from multiple biometric modalities: Fusing minutiae with iris feature," *International Journal of Computer Applications*, 26(6):16–26.
- [5] Espellman, "More than 90% of successful cyber attacks worldwide begin with a phishing email, Oct 2017.
- [6] G. C. Kesler, "An overview of cryptography, 2003.
- [7] J. Koetzier, "Scammers send 3.1 billion domain spoofing emails a day, here's how to protect yourself (and your company). May

$$PL_{log} = PL_0 + 10\gamma \log_{10} \frac{d}{d_0} \quad (1)$$

$$(x - x_1)^2 + (y - y_1)^2 = d_1^2$$

$$(x - x_2)^2 + (y - y_2)^2 = d_2^2$$

$$(x - x_3)^2 + (y - y_3)^2 = d_3^2$$

$$Distance = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2} \quad (3)$$

8 Conclusion

A digital signature is a scheme for verifying the authenticity of digital messages, emails, or documents. A digital signature provides the recipient of the message to trust the authenticity of the received message that is coming from the said sender and that the message was not altered in transit. Digital signatures, like handwritten signatures, are unique to each signer. A digital signature uses Public Key Infrastructure (PKI). PKI requires the sender to generate two keys. One key is public, and the other key is private. For example, when a signer electronically signs of the received messages. This paper proposes a scheme to validate a user's digital signature by utilizing the user's scheme depends on something that a user possesses (i.e., Wi-Fi-enabled devices), and something in the user's environment (i.e., ambient Wi-Fi access points) where the validation process is implemented in a way that requires no effort from the client-side arguably the most significant contribution of this paper. Primarily due to the proposed scheme removing the "weak link" from the validation process. The proposed scheme's experiments show that the proposed scheme results in a practical approach to validating a user's identity using his/her wi-fienabled device and enabling digitally signing the message. This is done by utilizing the user's ambient Wi-Fi-enabled devices based on the distance between the two devices if they are within a predefined acceptable range the private key is provided and the message is signed automatically; otherwise, validation is denied. The proposed scheme is an efficient method with a validation accuracy of 95.63%.




Figure 2: Extracted figure 1

N=1260
True

References

- [1] T. Thillaikkarasi A. Jagadeesan and K. Duraiswamy. [n. d.]. Cryptographic key generation from multiple biometric modalities: Fusing minutiae with iris feature. *International Journal of Computer Applications*, 2(6):16- ([n. d.]). A. Jagadeesan, T. Thillaikkarasi, and K. Duraiswamy. Cryptographic key generation from multiple biometric modalities: Fusing minutiae with iris feature. *International Journal of Computer Applications*, 2(6):16-.
- [2] N. Nikolaidis C. Cotsaces and I. Pitas. 2008. Face-based digital signatures for video retrieval. *IEEE Transactions on Circuits and Systems for Video Technology*, 18(4):549-553 (2008). C. Cotsaces, N. Nikolaidis, and I. Pitas. Face-based digital signatures for video retrieval. *IEEE Transactions on Circuits and Systems for Video Technology*, 18(4):549-553.
- [3] M. Ciampa. 2015. Security+ guide to network security fundamentals. M. Ciampa. Security+ guide to network security fundamentals. Work, 100:10.
- [4] M. Ciampa. 2021. CompTIA security+ guide to network security fundamentals. M. Ciampa. CompTIA security+ guide to network security fundamentals. Cengage Learning.
- [5] A. S. Aziz S. Sukaridhoto F. A. Damastuti M. M. Bachtiar E. Rahmawati, M. Listyasari and A. Sudarsono. 2017. Digital signature on file using biometric fingerprint with fingerprint sensor on smartphone. In *In. E. Rahmawati, M. Listyasari, A. S. Aziz, S. Sukaridhoto, F. A. Damastuti, M. M. Bachtiar, and A. Sudarsono. Digital signature on file using biometric fingerprint with fingerprint sensor on smartphone. In 2017 International Electronics Symposium on Engineering Technology and Applications (IES-ETA)*, pages 234- 238.
- [6] Jun Email spoofing what it is, how it works more: Proofpoint us. 2021. Email spoofing - what it is, how it works more: Proofpoint us, Jun. Email spoofing - what it is, how it works more: Proofpoint us, Jun.
- [7] Oct Espellman. More than 90cyber attacks worldwide begin with a phishing email. 2017. Espellman. More than 90worldwide begin with a phishing email, Oct. Espellman. More than 90with a phishing email, Oct.
- [8] Q. Li F. Monrose, M. K. Reiter and S. Wetzel. 2001. Using voice to generate cryptographic keys. In *In. F. Monrose, M. K. Reiter, Q. Li, and S. Wetzel. Using voice to generate cryptographic keys. In 2001: A Speaker Odyssey-The Speaker Recognition Workshop*.
- [9] P. Grother and E. Tabassi. 2007. Performance of biometric quality measures. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(4):531-543 (2007). P. Grother and E. Tabassi. Performance of biometric quality measures. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(4):531-543.
- [10] E. A. Mohammed H. M. Therar and A. J. Ali. 2020. Biometric signature based public key security system. In *In. H. M. Therar, E. A. Mohammed, and A. J. Ali. Biometric signature based public key security system. In 2020 International Conference on Advanced Science and Engineering (ICOASE)*, pages 1-6.

- [11] G. C. Kessler. 2003. An overview of cryptography. G. C. Kessler. An overview of cryptography.
- [12] J. Koetsier. 2020. Scammers send 3.1 billion domain spoofing emails a day. J. Koetsier. Scammers send 3.1 billion domain spoofing emails a day. here's how to protect yourself (and your company), May.
- [13] M. Mcloone and M. Robshaw. 2010. Low-cost digital signature architecture suitable for radio frequency identification tags. M. Mcloone and M. Robshaw. Low-cost digital signature architecture suitable for radio frequency identification tags. Computers Digital Techniques, IET, 4:14 - 26, 02.
- [14] L. Zhu and L. Zhu. 2012. Electronic signature based on digital signature and digital watermarking. In *In*. L. Zhu and L. Zhu. Electronic signature based on digital signature and digital watermarking. In 2012 5th International Congress on Image and Signal Processing, pages 1644-1647, 2012.