Statistical equivalence of jmbayes2py and JMbayes2

Joint model for longitudinal and time-to-event data, ported from the R package JMbayes2 (v0.6-5) to Python/PyTorch. Same model, same priors and same MCMC algorithm; it runs on CPU or GPU. This report tests whether the two programs give the same answers on the same data. All numbers were measured on one machine (24-core CPU, 64 GB RAM, NVIDIA RTX 3090).

• **R vs Python differs no more than R vs R.** Each program was run twice with different random seeds. Two R runs differ from each other by a median of 0.02 posterior SDs (largest 0.14); two Python runs by 0.05 (largest 0.20); R and Python by 0.02 (largest 0.16). The choice of implementation has no effect beyond the ordinary run-to-run noise of either program.

• **Same conclusions.** For all 15 of 15 regression coefficients (survival and longitudinal), R and Python agree on the direction of the effect, on significance at 5% and on whether the 95% credible interval excludes zero. Hazard ratios, intervals and p-values are shown side by side in Section 1.

• **Formal equivalence.** In an equivalence test (TOST, $\alpha = 0.05$) 45 of 50 parameters are proven equivalent within ±0.2 posterior SD (37 within ±0.1 SD). For the remaining 5 the runs are not precise enough to decide; no parameters are shown to differ. With realistic error bars, 98% of differences lie within 2 standard errors (expected ~95%) and 100% within 3.

• **Faster as cohorts grow.** At 3,120 patients the MCMC took 202 s in R and 46 s in Python on the GPU (4.4x). Python's time grows slowly with patients; R's grows roughly in proportion (Section 2).

• **Small data.** On the original 312 patients R and Python are comparable; most of R's time there is fixed start-up cost of its parallel workers, not sampling.


Model and data

PBC data (pbc2, 312 patients, 1,945 visits, 169 deaths or transplants). The model is the one in the JMbayes2 README: a Cox-type survival model with sex, linked through the current value of three longitudinal markers - log serum bilirubin and prothrombin time (linear mixed models, random intercept and slope) and ascites (logistic mixed model, random intercept and slope). MCMC: 12 chains, 30,000 iterations per chain, 5,000 burn-in, no thinning (300,000 retained draws per program), identical in both programs. The R model was fitted with `jm()`; the Python model with `jmbayes2py`, using its own versions of the separate starting fits (lme, mixed_model, coxph).

1. Do the two implementations agree?

Survival sub-model: hazard ratios. Posterior mean hazard ratio with 95% credible interval (exp of the log-scale estimates) and the Bayesian tail probability P (2 x min(P(β>0), P(β<0)), as reported by JMbayes2).

Effect on the hazard of death or transplant	R: HR (95% CI)	R: P	Python: HR (95% CI)	Python: P
Female sex	0.52 (0.26 - 1.03)	0.061	0.52 (0.26 - 1.03)	0.060
log serum bilirubin (per unit)	1.68 (1.18 - 2.33)	0.006	1.69 (1.19 - 2.31)	0.006
Prothrombin time (per second)	1.01 (0.79 - 1.25)	0.919	1.00 (0.79 - 1.25)	0.933
Ascites (per unit log-odds)	1.77 (1.40 - 2.39)	<0.001	1.75 (1.40 - 2.35)	<0.001



log(serum bilirubin) - linear mixed model

Coefficient	R: estimate (95% CI)	R: P	Python: estimate (95% CI)	Python : P
(Intercept)	0.699 (0.374, 1.024)	<0.001	0.696 (0.372, 1.022)	<0.001
year	0.277 (0.210, 0.347)	<0.001	0.278 (0.210, 0.346)	<0.001
sexfemale	-0.241 (-0.586, 0.103)	0.168	-0.237 (-0.581, 0.106)	0.176
year:sexfemale	-0.084 (-0.155, -0.013)	0.019	-0.083 (-0.154, -0.013)	0.021

Prothrombin time - linear mixed model

Coefficient	R: estimate (95% CI)	R: P	Python: estimate (95% CI)	Python : P
(Intercept)	10.942 (10.607, 11.275)	<0.001	10.939 (10.605, 11.272)	<0.001
year	0.251 (0.106, 0.397)	<0.001	0.251 (0.106, 0.396)	<0.001
sexfemale	-0.403 (-0.757, -0.049)	0.026	-0.401 (-0.754, -0.046)	0.027
year:sexfemale	0.052 (-0.099, 0.204)	0.496	0.053 (-0.098, 0.205)	0.487

Ascites - logistic mixed model

Coefficient	R: estimate (95% CI)	R: P	Python: estimate (95% CI)	Python : P
(Intercept)	-4.613 (-6.135, -3.255)	<0.001	-4.646 (-6.178, -3.271)	<0.001
year	0.652 (0.508, 0.811)	<0.001	0.663 (0.515, 0.830)	<0.001
sexfemale	-0.493 (-1.861, 0.895)	0.476	-0.484 (-1.867, 0.911)	0.486

Residual standard deviation	R: mean (SD)	Python: mean (SD)
log(serum bilirubin)	0.3468 (0.0067)	0.3467 (0.0066)
Prothrombin time	1.0547 (0.0203)	1.0546 (0.0202)

Same conclusions. 15 of 15 regression coefficients lead to the same conclusion in both programs.

Coefficient	Same direction	Same significance (P < 0.05)	Same 'CI excludes 0'
Survival: sexfemale	yes	yes	yes
Survival: value(log(serBilir))	yes	yes	yes
Survival: value(prothrombin)	yes	yes	yes
Survival: value(ascites)	yes	yes	yes
log(serum bilirubin): (Intercept)	yes	yes	yes
log(serum bilirubin): year	yes	yes	yes
log(serum bilirubin): sexfemale	yes	yes	yes
log(serum bilirubin): year:sexfemale	yes	yes	yes
Prothrombin time: (Intercept)	yes	yes	yes
Prothrombin time: year	yes	yes	yes
Prothrombin time: sexfemale	yes	yes	yes
Prothrombin time: year:sexfemale	yes	yes	yes
Ascites: (Intercept)	yes	yes	yes
Ascites: year	yes	yes	yes
Ascites: sexfemale	yes	yes	yes

Formal equivalence test (all 50 parameters)

Step 1: realistic error bars. Any comparison of two MCMC runs needs the Monte Carlo standard error (MCSE) of each estimate. JMbayes2 reports MCSE = SD / sqrt(effective sample size), with the effective sample size from an autoregressive fit to all chains stacked together. To check this formula we compared two runs of the same program that differ only in their random seed: their differences should be within ±2 MCSE about 95% of the time. For Python only 62% were, for R only 80%, so the formula understates the real run-to-run error by a factor k = 1.67 (k = sqrt(mean z^2) over all parameters and both same-program pairs). All error bars below are multiplied by k; the correction applies equally to R and Python.


Step 2: equivalence test. A non-significant difference test only says a difference could not be detected. An **equivalence test (TOST)** asks whether the difference is small enough to be irrelevant. For each parameter, d = Python mean - R mean (each pooled over its seeds), with SE = k · sqrt($MCSE_R^2$ + $MCSE_{Py}^2$). The programs are declared equivalent for that parameter if the 90% confidence interval d ± 1.645·SE lies inside ±δ (two one-sided tests at $\alpha = 0.05$). The margin is relative to the parameter's own posterior uncertainty: $\delta = 0.1$ posterior SD (strict) or 0.2 SD. A shift of 0.2 SD moves a 95% credible interval by about 5% of its width.

Benchmark: how different are two runs of the same program?

Comparison	Median |difference|	Largest |difference|
R vs Python (pooled seeds)	0.018 SD	0.155 SD
Python seed 123 vs Python seed 456	0.047 SD	0.199 SD
R seed 123 vs R seed 456	0.023 SD	0.141 SD

Parameter group	Parameters	Equivalent at ±0.1 SD	Equivalent at ±0.2 SD	Largest |d| (SD)
Survival covariate	1	1	1	0.01
Association (marker -> hazard)	3	2	3	0.02
Fixed effects: log(bilirubin)	4	4	4	0.01
Fixed effects: prothrombin	4	4	4	0.02
Fixed effects: ascites	3	2	3	0.05
Residual SDs	2	2	2	0.01
Random-effects covariance	21	12	16	0.16
Baseline hazard spline	11	9	11	0.04
Spline smoothing	1	1	1	0.00
All	**50**	**37**	**45**	**0.16**

Figure: each parameter's difference (Python - R) in posterior SDs with its 90% CI (calibrated error bars). Orange: equivalent at ±0.1 SD; grey: equivalent at ±0.2 SD only; red: not shown equivalent at ±0.2 SD. Wide intervals belong to parameters that mix slowly in both programs (the random-effects covariances, mainly the ascites random slope, and the baseline-hazard spline); their estimates still sit close to zero difference, and longer runs would narrow the intervals.



Noise check. If both programs sample the same posterior, z = d / SE behaves like a standard normal. Observed: 98% of |z| below 2 (expected ~95%) and 100% below 3 (expected ~99.7%).

Model fit statistics. DIC, WAIC and LPML are themselves Monte Carlo estimates. The table puts the R-vs-Python gap next to the gap between two Python seeds; the gaps are of comparable size, so the fit statistics agree within run-to-run variation (relative differences are below 0.3%).

Fit statistic (conditional)	R	Python (seed 123)	Python (seed 456)	|R - Python mean|	|Python - Python|
DIC	12606.6	12631.9	12598.7	8.7	33.1
pD	1716.5	1719.9	1717.1	2.0	2.7
WAIC	12354.8	12375.9	12348.6	7.4	27.3
LPML	-6823.5	-6842.6	-6831.9	13.8	10.7

Isolating the sampler: Python started from R's own starting fits


JMbayes2 does not start from scratch: it takes fitted lme / mixed_model / coxph objects, uses them as starting values and centres some priors on them (for example the prior for each random-effect standard deviation). The Python runs above used Python's own versions of those fits, which match R's to 4-5 digits for the linear mixed models but differ by about 1% for the ascites logistic mixed model. To remove that difference entirely, the R fits were exported (benchmark/export_initfits.R) and Python was run again from exactly those values, with the same MCMC settings and two seeds. Any remaining difference can then only come from the sampler itself.

	Python, own starting fits	Python, R's starting fits
Median |difference| from R	0.018 SD	0.012 SD
Largest |difference| from R	0.155 SD	0.151 SD
Mean difference, ascites random-slope covariances D[6,·]	+0.108 SD	+0.103 SD
Equivalent at ±0.1 SD (TOST)	37 / 50	39 / 50
Equivalent at ±0.2 SD (TOST)	45 / 50	45 / 50
|z| below 2 (expected ~95%)	98%	98%
|z| below 3 (expected ~99.7%)	100%	100%
Parameters shown to differ (90% CI outside ±0.2 SD)	0	0

The parameters that differed most (posterior means; every column averages two seeds)

Parameter	R	Python (own fits)	Python (R's fits)
ascites: year	0.6530	0.6571	0.6611
D[6, 1]	0.2075	0.2151	0.2144
D[6, 2]	0.0634	0.0658	0.0657
D[6, 3]	0.0892	0.0924	0.0918
D[6, 4]	0.0804	0.0830	0.0835
D[6, 5]	-0.0321	-0.0060	-0.0203
D[6, 6]	0.2448	0.2513	0.2546

Figure: as before, R vs Python started from R's fits (calibration factor k = 1.60, estimated from the same-program pairs).



inner band: ±0.1 SD outer band: ±0.2 SD
sexfemale [Survival covariate]
value(log(serBilir)) [Association (marker -> hazard)]
value(prothrombin)
value(ascites)
(Intercept) [log(bilirubin)]
year
sexfemale
year:sexfemale
(Intercept) [prothrombin]
year
sexfemale
year:sexfemale
(Intercept) [ascites]
year
sexfemale
sigma_1 [Residual SDs]
sigma_2
D[1, 1] [Random-effects covariance]
D[2, 1]
D[3, 1]
D[4, 1]
D[5, 1]
D[6, 1]
D[2, 2]
D[3, 2]
D[4, 2]
D[5, 2]
D[6, 2]
D[3, 3]
D[4, 3]
D[5, 3]
D[6, 3]
D[4, 4]
D[5, 4]
D[6, 4]
D[5, 5]
D[6, 5]
D[6, 6]
bs_gammas_1 [Baseline hazard spline]
bs_gammas_2
bs_gammas_3
bs_gammas_4
bs_gammas_5
bs_gammas_6
bs_gammas_7
bs_gammas_8
bs_gammas_9
bs_gammas_10
bs_gammas_11
tau_bs_gammas [Spline smoothing]
−0.4
−0.3
−0.2
−0.1
0.0
0.1
0.2
0.3
0.4
Python - R, in posterior SDs (point and 90% CI)


2. Speed and memory (preliminary)


Preliminary: the sweep was paused to run the equivalence test. The Python run at 28,000 iterations and the colleague-scale runs (30,000-90,000 iterations) will be added in a later version. The R run at 28,000 iterations overlapped with another R run on this 24-core machine, so its time may be slightly inflated.

Each run is a separate process, run one at a time. Peak RAM is the resident memory of the whole process tree, sampled every 0.2 s (R starts one worker process per chain; all are counted). Larger cohorts are pbc2 copied 2, 5 and 10 times with new patient ids. 3 chains, burn-in 500, thinning 5. **MCMC time** is the sampling step; for R it includes starting its parallel worker processes. **Total time** also includes the separate starting fits (lme, mixed_model, coxph) that both programs need.


Scaling with the number of patients (3,500 iterations, JMbayes2's default)








Scaling with the number of iterations (1,560 patients)





All measurements

Implementation	Patients	Iterations	MCMC (s)	Total (s)	Peak RAM (GB)	GPU memory (GB)
Python, GPU	312	3,500	22.0	53.1	1.22	0.04
JMbayes2 (R)	312	3,500	54.6	94.1	1.28	-
Python, GPU	624	3,500	24.4	89.7	1.22	0.05
JMbayes2 (R)	624	3,500	87.0	158.9	1.45	-
Python, GPU	1,560	3,500	32.5	95.0	1.22	0.07
JMbayes2 (R)	1,560	3,500	157.4	301.2	1.95	-
Python, GPU	3,120	3,500	46.4	175.6	1.24	0.11
JMbayes2 (R)	3,120	3,500	202.2	415.4	2.41	-
Python, GPU	1,560	7,000	66.0	220.3	1.23	0.08
JMbayes2 (R)	1,560	7,000	236.8	335.0	2.34	-
Python, GPU	1,560	14,000	132.8	288.0	1.24	0.10
JMbayes2 (R)	1,560	14,000	716.4	919.4	3.36	-
JMbayes2 (R)	1,560	28,000	1045.8	1333.4	6.25	-

3. What was ported, and caveats

• **Same algorithm.** Python follows JMbayes2's C++ sampler step for step: the same parameter blocks in the same order, the same proposal types, the same Gibbs steps, the same adaptive step sizes and burn-in rules. Only the random-number stream differs, so individual draws differ while the results agree within Monte Carlo error.

• **How it is faster.** All chains and all patients are updated together as tensor operations, and on the GPU each iteration is recorded once and replayed (CUDA graph). The per-patient log-likelihood is not stored for every iteration; DIC, WAIC and LPML are accumulated during sampling, which gives identical values (checked to 1e-16).

• **Starting fits.** JMbayes2 takes fitted lme / mixed_model / coxph objects, which also set some prior centres. Python re-implements these estimators (REML, ML with adaptive Gauss-Hermite quadrature, Cox with Efron ties); they match to optimiser tolerance.

• **Two possible issues in JMbayes2's C++** were found and deliberately reproduced so results match: the random-effects log-density is not refreshed after the fixed-effects step, and the survival denominator is not refreshed after the smoothing-parameter update. Both are worth raising with the package authors.

• **Timing caveats.** A first R run on pbc2 took 143 s of MCMC and a repeat 58.5 s, so single timings vary. On large copies, R's own nlme starting fit failed to converge with its default optimiser; the optim() fallback was used only in that case.

• **Scope.** The Python version currently covers what this model needs: Gaussian and binomial outcomes, current-value association, right censoring. Other JMbayes2 features (more families, slope/area associations, competing risks, recurrent events) are not ported yet, and marginal fit statistics are not computed.