NEURULUS

COMPUTE + SILICON OS

PRODUCT TECHNICAL DATASHEET

D3HW-5212H5-ICCCVMS

Intel Core i7 Tower Server

Application-oriented compute for IP video management, recording, monitoring and on-premise control systems.



4 CORES / 8 THREADS
3.4–4.0 GHz CPU

32 GB DDR4
Installed memory

10 TB HDD
SATA mass storage

DUAL GIGABIT LAN
2 x RJ45 total

SYSTEM CONFIGURATION

Processor	Intel Core i7 (64-bit)
CPU configuration	4 cores / 8 threads
CPU frequency	3.4 GHz base / up to 4.0 GHz turbo
Cache / power	8 MB cache / 65 W CPU TDP
Memory	32 GB DDR4 (2133 MT/s)
Primary storage	1 x 10 TB SATA HDD
Graphics	Integrated Intel HD graphics
Network	2 x 10/100/1000 Mbps RJ45
LAN implementation	Onboard LAN + PCIe LAN adapter
Power supply	450 W ATX SMPS

CONNECTIVITY & DEPLOYMENT

Display outputs	1 x HDMI; 1 x VGA*
USB ports	2 x USB 3.0; 2 x USB 2.0*
Audio	3 x analog audio jacks*
Legacy I/O	PS/2 keyboard / mouse*
Drive interface	SATA 6 Gb/s
Expansion	PCIe expansion capability
Form factor	Tower chassis
Dimensions	420 x 190 x 400 mm (H x W x D, estimated)
Operating system	OS selected per deployment
Primary use	VMS / NVR / control room

APPLICATION & DESIGN NOTES

Designed for video surveillance management, IP camera recording, monitoring stations and secure local operations. Actual camera/channel capacity and retention depend on codec, bitrate, recording profile, installed software and usable storage capacity.

REGULATORY INFORMATION

BIS CRS Registration	**R-63006084**
Registered product	SERVER (ADPM)
Applicable standard	IS 13252 (Part 1):2010 / IEC 60950-1:2005
Model	**D3HW-5212H5-ICCCVMS**

* Rear I/O shown is the intended typical configuration, subject to final port verification.
Dimensions estimated; verify chassis measurements and PSU label before ordering.