

Remodex

One-page repo summary

What it is

Remodex is a local-first open-source system that lets you control Codex from an iPhone while the Codex runtime, git operations, and workspace actions stay on your Mac. This repo includes the iOS app, a Node bridge/CLI, a relay, and local developer tooling.

Who it's for

Primary persona: developers who already use Codex on a Mac and want to monitor, steer, and continue coding sessions from an iPhone.

What it does

- Pair an iPhone to a Mac once with a QR bootstrap and reconnect through a saved relay session.
- Stream live Codex chats and active runs to the phone while execution stays local on the Mac.
- Queue follow-up prompts and steer an in-flight run without starting over.
- Expose plan mode, fast mode, reasoning controls, access controls, and photo attachments.
- Run local git actions from the phone through bridge JSON-RPC handlers.
- Hand off a thread to Codex.app on the Mac and share thread history through stored session files.
- Show in-app notifications when runs finish or need attention.

How it works

- iOS app: SwiftUI views plus a central CodexService state container for connection, messaging, sync, history, and turn handling.
- Secure local state: SecureStore keeps relay/session identity data in Keychain; CodexMessagePersistence saves encrypted per-thread history on disk.
- Bridge CLI: phodex-bridge/src/bridge.js manages QR pairing, relay sockets, secure transport, notifications, git/workspace handlers, and desktop handoff/refresh hooks.
- Codex runtime transport: codex-transport.js either spawns codex app-server locally or connects to an existing WebSocket endpoint.
- Data flow: iPhone app -> relay WebSocket -> bridge -> Codex JSON-RPC, with rollout/session files under ~/.codex/sessions used for shared history/live mirroring.

How to run

- From the repo root, run ./run-local-remodex.sh to start the local relay and bridge and print the pairing QR.
- Build/install the iOS app from CodexMobile in Xcode on a device, then open the app.
- Scan the QR in the app to pair the Mac; after that, the saved pairing is used for reconnects.