


BGP Part 2

~~Empire~~ BGP Strikes Back!

by Anatoliy Vedyakin (modemfux@gmail.com)

BGP – Базовая конфигурация – Cisco IOS

```
router bgp 100
  bgp router-id 1.1.1.1
  neighbor 10.1.2.2 remote-as 200
  neighbor 10.1.2.2 update-source Ethernet0/0
  neighbor 10.1.3.3 remote-as 300
  neighbor 10.1.3.3 update-source Ethernet0/1
  !
  address-family ipv4
    network 1.1.1.1 mask 255.255.255.255
    neighbor 10.1.2.2 activate
    neighbor 10.1.3.3 activate
  exit-address-family
  !
  !
```



BGP – Базовая конфигурация – IOS/IOS-XE

```
R1#show bgp ipv4 unicast summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 4, main routing table version 4
3 network entries using 432 bytes of memory
5 path entries using 420 bytes of memory
5/3 BGP path/bestpath attribute entries using 800 bytes of memory
4 BGP AS-PATH entries using 96 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 1748 total bytes of memory
BGP activity 3/0 prefixes, 7/2 paths, scan interval 60 secs
```

Neighbor	V		AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down
State/PfxRcd									
10.1.2.2	4	200	45	41	4	0	0	00:31:58	2
10.1.3.3	4	300	34	36	4	0	0	00:26:37	2

BGP – Базовая конфигурация – IOS/IOS-XE

```
R1#show bgp ipv4 unicast
```

```
BGP table version is 4, local router ID is 1.1.1.1
```

```
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,  
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,  
               x best-external, a additional-path, c RIB-compressed,  
               t secondary path,
```

```
Origin codes: i - IGP, e - EGP, ? - incomplete
```

```
RPKI validation codes: V valid, I invalid, N Not found
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	1.1.1.1/32	0.0.0.0	0		32768	i
*	2.2.2.2/32	10.1.3.3			0 300 200	i
*>		10.1.2.2	0		0 200	i
*	3.3.3.3/32	10.1.2.2			0 200 300	i
*>		10.1.3.3	0		0 300	i

BGP – Базовая конфигурация – Huawei VRP

```
bgp 200
  router-id 2.2.2.2
  peer 10.1.2.1 as-number 100
  peer 10.1.2.1 connect-interface Ethernet1/0/0
  peer 10.2.3.3 as-number 300
  peer 10.2.3.3 connect-interface Ethernet1/0/1
#
  ipv4-family unicast
    network 2.2.2.2 255.255.255.255
    peer 10.1.2.1 enable
    peer 10.2.3.3 enable
#
#
```

BGP – Базовая конфигурация – Huawei VRP

```
<R2>display bgp peer
```

```
BGP local router ID : 2.2.2.2
```

```
Local AS number : 200
```

```
Total number of peers : 2
```

```
Peers in established state : 2
```

Peer	V	AS	MsgRcvd	MsgSent	OutQ	Up/Down	State	PrefRcv
10.1.2.1	4	100	19	19	0	00:11:57	Established	2
10.2.3.3	4	300	12	14	0	00:06:51	Established	2

BGP – Базовая конфигурация – Huawei VRP

```
<R2>display bgp routing-table
```

```
BGP Local router ID is 2.2.2.2
```

```
Status codes: * - valid, > - best, d - damped, x - best external, a - add path,  
               h - history, i - internal, s - suppressed, S - Stale
```

```
Origin : i - IGP, e - EGP, ? - incomplete
```

```
RPKI validation codes: V - valid, I - invalid, N - not-found
```

```
Total Number of Routes: 5
```

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	1.1.1.1/32	10.1.2.1	0		0	100i
*		10.2.3.3			0	300 100i
*>	2.2.2.2/32	0.0.0.0	0		0	i
*>	3.3.3.3/32	10.2.3.3	0		0	300i
*		10.1.2.1			0	100 300i

BGP – Базовая конфигурация – IOS-XR

```
route-policy RP_PERMIT_ANY
  pass
end-policy

router bgp 300
  bgp router-id 3.3.3.3
  !
  address-family ipv4 unicast
    network 3.3.3.3/32
  !
```

```
<..router bgp 300..>
neighbor 10.1.3.1
  remote-as 100
  update-source GigabitEthernet0/0/0/1
  address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_PERMIT_ANY out
  !
!
neighbor 10.2.3.2
  remote-as 200
  update-source GigabitEthernet0/0/0/2
  address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_PERMIT_ANY out
  !
```


BGP – Базовая конфигурация – IOS-XR

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast summary
Tue Apr 12 15:54:25.639 UTC
BGP router identifier 3.3.3.3, local AS number 300
BGP generic scan interval 60 secs
Non-stop routing is enabled
BGP table state: Active
Table ID: 0xe0000000 RD version: 5
BGP main routing table version 5
BGP NSR Initial initsync version 5 (Reached)
BGP NSR/ISSU Sync-Group versions 0/0
BGP scan interval 60 secs
```

BGP is operating in STANDALONE mode.

Process	RcvTblVer	bRIB/RIB	LabelVer	ImportVer	SendTblVer	StandbyVer
Speaker	5	5	5	5	5	0

Neighbor	Spk	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	St/PfxRcd
10.1.3.1	0	100	15	14	5	0	0	00:08:07	2
10.2.3.2	0	200	15	14	5	0	0	00:08:22	2

BGP – Базовая конфигурация – IOS-XR

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast
Tue Apr 12 16:14:30.127 UTC
BGP router identifier 3.3.3.3, local AS number 300
BGP generic scan interval 60 secs
Non-stop routing is enabled
BGP table state: Active
Table ID: 0xe0000000 RD version: 9
BGP main routing table version 9
BGP NSR Initial initsync version 5 (Reached)
BGP NSR/ISSU Sync-Group versions 0/0
BGP scan interval 60 secs
```

```
Status codes: s suppressed, d damped, h history, * valid, > best
               i - internal, r RIB-failure, S stale, N Nexthop-discard
```

```
Origin codes: i - IGP, e - EGP, ? - incomplete
```

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 1.1.1.1/32	10.1.3.1	0		0 100	i
*	10.2.3.2			0 200 100	i
* 2.2.2.2/32	10.1.3.1			0 100 200	i
*>	10.2.3.2	0		0 200	i
*> 3.3.3.3/32	0.0.0.0	0		32768	i

```
Processed 3 prefixes, 5 paths
```

BGP – Базовая конфигурация – IOS-XR

```
RP/0/0/CPU0:R3(config)#router bgp 300
RP/0/0/CPU0:R3(config-bgp)#neighbor 10.2.3.2 address-family ipv4 unicast
RP/0/0/CPU0:R3(config-bgp-nbr-af)#no route-policy RP_PERMIT_ANY in
RP/0/0/CPU0:R3(config-bgp-nbr-af)#no route-policy RP_PERMIT_ANY out
RP/0/0/CPU0:R3(config-bgp-nbr-af)#commit
RP/0/0/CPU0:R3#show bgp ipv4 unicast summary | b Process
Tue Apr 12 16:04:46.597 UTC
Process          RcvTblVer    bRIB/RIB    LabelVer    ImportVer    SendTblVer    StandbyVer
Speaker          7            7           7           7            7            0
```

Some configured eBGP neighbors (under default or non-default vrfs) do not have both inbound and outbound policies configured for IPv4 Unicast address family. These neighbors will default to sending and/or receiving no routes and are marked with '!' in the output below. Use the 'show bgp neighbor <nbr_address>' command for details.

Neighbor	Spk	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	St/PfxRcd
10.1.3.1	0	100	27	25	7	0	0	00:18:28	2
10.2.3.2	0	200	32	25	7	0	0	00:18:43	0!

```
<R2>display bgp peer
```

BGP local router ID : 2.2.2.2

Local AS number : 200

Total number of peers : 2

Peers in established state : 2

Peer	V	AS	MsgRcvd	MsgSent	OutQ	Up/Down	State	PrefRcv
10.1.2.1	4	100	34	36	0	00:25:24	Established	2
10.2.3.3	4	300	27	34	0	00:20:18	Established	0

BGP – Базовая конфигурация – IOS-XR

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast
Tue Apr 12 16:15:32.243 UTC
BGP router identifier 3.3.3.3, local AS number 300
BGP generic scan interval 60 secs
Non-stop routing is enabled
BGP table state: Active
Table ID: 0xe0000000 RD version: 11
BGP main routing table version 11
BGP NSR Initial initsync version 5 (Reached)
BGP NSR/ISSU Sync-Group versions 0/0
BGP scan interval 60 secs
```

```
Status codes: s suppressed, d damped, h history, * valid, > best
               i - internal, r RIB-failure, S stale, N Nexthop-discard
```

```
Origin codes: i - IGP, e - EGP, ? - incomplete
```

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 1.1.1.1/32	10.1.3.1	0		0 100	i
*> 2.2.2.2/32	10.1.3.1			0 100 200	i
*> 3.3.3.3/32	0.0.0.0	0		32768	i

```
Processed 3 prefixes, 3 paths
```

BGP – Обработка маршрутов

- Манипуляции с маршрутами могут производиться на основании:
 1. Содержимое NLRI (за счет применения ACL или prefix-list)
 2. Содержимое AS_PATH
 3. Атрибута Community
 4. Атрибута Next-hop
 5. Прочие атрибуты
- Что можно сделать:
 1. Запретить получение/анонс маршрута
 2. Изменить за счет prepend длину AS_PATH
 3. Добавить/изменить/убрать коммьюнити
 4. Изменить next-hop
 5. Прочие манипуляции с атрибутами

BGP – NLRI Prefix Filtering

- NLRI представляет собой набор из префикса и его длины
- Для поиска совпадений в содержимом NLRI используются:
 - ACL
 - Prefix-list
- В подавляющем большинстве случаев, для поиска соответствия будет использоваться именно префикс-лист, т.к. он имеет более короткую и очевидную форму записи
- ACL может использоваться в том случае, если необходимо задать какой-то очень специфичный шаблон или для простых вариантов фильтрации анонсов вроде distribute-list

```
Internet Protocol Version 4, Src: 195.2.3.2, Dst: 195.2.3.3
Transmission Control Protocol, Src Port: 179, Dst Port: 50544,
Border Gateway Protocol - UPDATE Message
  Marker: ffffffffffffffffffffffffffffffffffffffff
  Length: 55
  Type: UPDATE Message (2)
  Withdrawn Routes Length: 0
  Total Path Attribute Length: 27
  Path attributes
    > Path Attribute - ORIGIN: IGP
    > Path Attribute - AS_PATH: 200
    > Path Attribute - NEXT_HOP: 195.2.3.2
    > Path Attribute - MULTI_EXIT_DISC: 0
  Network Layer Reachability Information (NLRI)
    2.2.2.2/32
      NLRI prefix length: 32
      NLRI prefix: 2.2.2.2
```

BGP – NLRI Prefix Filtering - ACL

ACL – Access Control List, изначально использовался для фильтрации пакетов на основе какого-то шаблона, однако, также используется для классификации трафика и для сравнения префиксов в протоколах маршрутизации.

За счет использования wildcard позволяет создавать очень гибкие фильтры, которые получить невозможно, используя prefix-list

Cisco IOS/IOS-XE:

Стандартные:

```
ip access-list standard ACL_ST_01
 10 permit 10.0.0.0 0.255.255.255
```

Расширенные:

```
ip access-list extended ACL_EXT_02
 10 permit ip 10.0.0.0 0.255.255.255 255.0.0.0
0.255.255.255
```

Huawei VRP:

Стандартные:

```
acl name ACL_BASIC_01 basic number 2000
 rule 10 permit source 10.0.0.0 0.0.0.255
```

BGP – NLRI Prefix Filtering - ACL

Before:

```
R1#show bgp ipv4 unicast neighbors 10.1.2.2 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  2.2.2.2/32      10.1.2.2          0             0 200 i
*>  3.3.3.3/32      10.1.3.3          0             0 300 i
*>  11.11.11.0/27    0.0.0.0          0         32768 i
*>  11.11.11.0/24    0.0.0.0          0         32768 i
*>  11.11.11.11/32   0.0.0.0          0         32768 i
```

Total number of prefixes 6

--

```
ip access-list extended ACL_ODD_PREF_AND_NARROW_MASK
 permit ip 1.0.0.0 254.255.255.255 255.255.255.128 0.0.0.127
!
router bgp 100
 address-family ipv4 unicast
  neighbor 10.1.2.2 distribute-list ACL_ODD_PREF_AND_NARROW_MASK out
```

--

After:

```
R1#show bgp ipv4 unicast neighbors 10.1.2.2 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  3.3.3.3/32      10.1.3.3          0             0 300 i
*>  11.11.11.0/27    0.0.0.0          0         32768 i
*>  11.11.11.11/32   0.0.0.0          0         32768 i
```

Total number of prefixes 4

BGP – NLRI Prefix Filtering - ACL

Before:

```
<R2>display bgp routing-table peer 10.2.3.3 received-routes
```

```
Total Number of Routes: 3
  Network                NextHop                MED          LocPrf        PrefVal Path/Ogn
*      1.1.1.1/32         10.2.3.3
*>     3.3.3.3/32         10.2.3.3                0
*      11.11.11.11/32    10.2.3.3                0          300 100i
--
```

```
acl number 2000
  description Match only 1 or 3 in first octet
  rule 10 permit source 1.0.0.0 2.255.255.255
#
route-policy RP_MATCH_1_OR_3 permit node 10
  if-match acl 2000
#
bgp 200
  ipv4-family unicast
    peer 10.2.3.3 route-policy RP_MATCH_1_OR_3 import
--
```

After:

```
<R2>display bgp routing-table peer 10.2.3.3 received-routes
```

```
Total Number of Routes: 2
  Network                NextHop                MED          LocPrf        PrefVal Path/Ogn
*      1.1.1.1/32         10.2.3.3
*>     3.3.3.3/32         10.2.3.3                0          300 100i
--
```

BGP – NLRI Prefix Filtering – Prefix-list

Prefix-list – инструмент сравнения с эталоном каких-либо префиксов
Имеет логичный и гораздо более человекочитабельный вид.

Как и в ACL, проверка идет «сверху-вниз» до первого совпадения

В большинстве систем имеет следующий вид:

```
{prefix-list operator} {network address} {prefix length} {additional operators}
```

где:

- Operator – действие (permit/deny, есть не везде)
- Network address – IP-адрес сети
- Prefix length – длина префикса (фактически, маска в битовом виде, указывается через разделитель “/” (в большинстве систем) или “ ” (в Huawei)).
- Additional operators – операторы, расширяющие возможности префикс-листов:
 - Greater or equal
 - Lesser or equal

BGP – NLRI Prefix Filtering – Prefix-list

Запись в префикс-листе без использования доп. операторов проверяет на полное соответствие.

Например, есть такой префикс-лист:

```
ip prefix-list PL_TEST01 permit 192.168.0.0/24
```

и если сравнить префикс 192.168.0.0/25 с этим листом, то совпадения не будет.

Операторы же позволяют искать какие-то более специфичные префиксы внутри «основного» префикса.

Lesser or equal N – проверяет префиксы на вхождение в «основной» и на соответствие заданной длины префикса: он не должен быть «уже», чем N

Greater or equal N - проверяет префиксы на вхождение в «основной» и на соответствие заданной длины префикса: он не должен быть «шире», чем N

Операторы могут использоваться вместе, чтобы задать диапазон длины префикса:

- `ip prefix-list PL_TEST01 permit 0.0.0.0/0 ge 16 le 24` – под данное условие подойдут любые маршруты с длиной префикса от 16 до 24 (т.е. от 255.255.0.0 до 255.255.255.0)
- `ip prefix-list PL_TEST02 permit 10.0.0.0/8 ge 24 le 24` – под данное условие подойдут любые маршруты, входящие в сеть 10.0.0.0/8 и имеющие длину префикса 24 бита (т.е. 255.255.255.0)

Operator	IOS/IOS-XE	IOS-XR	Huawei VRP
Lesser or equal	le	le	less-equal
Greater or equal	ge	ge	greater-equal
Equal	-	eq	-

BGP – NLRI Prefix Filtering – Prefix-list

Lesser or equal:	Greater or equal:	Mixed:
<pre>ip prefix-list PL_TEST01 permit 10.0.0.0/16 le 24</pre>	<pre>ip ip-prefix PL_TEST02 permit 10.0.0.0 16 greater-equal 24</pre>	<pre>prefix-set PS_TEST03 10.0.0.0/16 ge 22 le 26 end-set</pre>
<ul style="list-style-type: none">• 10.0.0.0/16 – YES• 10.64.0.0/18 – YES• 10.127.255.0/24 – YES• 10.250.15.0/24 – NO• 10.0.0.0/15 – NO• 10.0.0.0/25 – NO• 10.1.1.1/32 – NO	<ul style="list-style-type: none">• 10.0.0.0/16 – NO• 10.64.0.0/18 – NO• 10.127.255.0/24 – YES• 10.250.15.0/24 – NO• 10.0.0.0/15 – NO• 10.0.0.0/25 – YES• 10.1.1.1/32 – YES	<ul style="list-style-type: none">• 10.0.0.0/16 – NO• 10.64.0.0/18 – NO• 10.127.255.0/24 – YES• 10.250.15.0/24 – NO• 10.0.0.0/15 – NO• 10.0.0.0/25 – YES• 10.1.1.1/32 – NO

BGP – NLRI Prefix Filtering – Prefix-list

Cisco IOS/IOS-XE:

```
ip prefix-list PL_R1_to_R2 seq 10 permit 3.3.3.3/32
ip prefix-list PL_R1_to_R2 seq 20 permit 11.11.11.0/24
le 27
ip prefix-list PL_R1_to_R2 seq 30 permit 1.1.1.1/32
ip prefix-list PL_R1_to_R3 seq 10 permit 0.0.0.0/0 ge
32
!
route-map RM_R1_to_R2 permit 10
  match ip address prefix-list PL_R1_to_R2
!
router bgp 100
  address-family ipv4
    neighbor 10.1.2.2 route-map RM_R1_to_R2 out
    neighbor 10.1.3.3 prefix-list PL_R1_to_R3 out
!
```

Before:

```
R1#show bgp ipv4 unicast neighbors 10.1.2.2 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  2.2.2.2/32      10.1.2.2         0          0 200 i
*>  3.3.3.3/32      10.1.3.3         0          0 300 i
*>  11.11.11.0/27   0.0.0.0          0         32768 i
*>  11.11.11.0/24   0.0.0.0          0         32768 i
*>  11.11.11.11/32  0.0.0.0          0         32768 i
```

```
R1#show bgp ipv4 unicast neighbors 10.1.3.3 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  2.2.2.2/32      10.1.2.2         0          0 200 i
*>  3.3.3.3/32      10.1.3.3         0          0 300 i
*>  11.11.11.0/27   0.0.0.0          0         32768 i
*>  11.11.11.0/24   0.0.0.0          0         32768 i
*>  11.11.11.11/32  0.0.0.0          0         32768 i
--
```

After:

```
R1#show bgp ipv4 unicast neighbors 10.1.2.2 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  3.3.3.3/32      10.1.3.3         0          0 300 i
*>  11.11.11.0/27   0.0.0.0          0         32768 i
*>  11.11.11.0/24   0.0.0.0          0         32768 i
```

```
R1#show bgp ipv4 unicast neighbors 10.1.3.3 advertised-routes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*>  1.1.1.1/32      0.0.0.0          0         32768 i
*>  2.2.2.2/32      10.1.2.2         0          0 200 i
*>  11.11.11.11/32  0.0.0.0          0         32768 i
```

BGP – NLRI Prefix Filtering – Prefix-list

Huawei VRP:

```
ip ip-prefix PL_FROM_R3 index 10 deny 11.11.11.11 32
ip ip-prefix PL_FROM_R3 index 20 permit 0.0.0.0 0 less-
equal 32
#
bgp 200
  ipv4-family unicast
    peer 10.2.3.3 ip-prefix PL_FROM_R3 import
#
```

Before:

```
<R2>display bgp routing-table peer 10.2.3.3 received-routes
```

Total Number of Routes: 3

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*	1.1.1.1/32	10.2.3.3			0	300 100i
*>	3.3.3.3/32	10.2.3.3	0		0	300i
*>	11.11.11.11/32	10.2.3.3			0	300 100i

After:

```
<R2>display bgp routing-table peer 10.2.3.3 received-routes
```

Total Number of Routes: 2

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*	1.1.1.1/32	10.2.3.3			0	300 100i
*>	3.3.3.3/32	10.2.3.3	0		0	300i

BGP – NLRI Prefix Filtering – Prefix-list

Cisco IOS-XR:

```
prefix-set PS_FROM_R3_TO_R2
  33.33.0.0/16 ge 24 le 32
end-set
!
route-policy RP_FROM_R3_TO_R2
  if destination in PS_FROM_R3_TO_R2 then
    pass
  else
    drop
  endif
end-policy
!
router bgp 300
  neighbor 10.2.3.2
  address-family ipv4 unicast
    route-policy RP_FROM_R3_TO_R2 out
  !
```

Before:

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast neighbors 10.2.3.2 advertised-routes
Sun Apr 17 15:13:57.351 UTC
```

Network	Next Hop	From	AS Path
1.1.1.1/32	10.2.3.3	10.1.3.1	300 100i
2.2.2.2/32	10.2.3.3	10.2.3.2	300 200i
3.3.3.3/32	10.2.3.3	Local	300i
11.11.11.0/24	10.2.3.3	10.2.3.2	300 200 100i
11.11.11.0/27	10.2.3.3	10.2.3.2	300 200 100i
11.11.11.11/32	10.2.3.3	10.1.3.1	300 100i
33.33.0.0/16	10.2.3.3	Local	300i
33.33.33.0/24	10.2.3.3	Local	300i
33.33.33.33/32	10.2.3.3	Local	300i

Processed 9 prefixes, 9 paths

After:

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast neighbors 10.2.3.2 advertised-routes
Sun Apr 17 15:14:53.277 UTC
```

Network	Next Hop	From	AS Path
33.33.33.0/24	10.2.3.3	Local	300i
33.33.33.33/32	10.2.3.3	Local	300i

Processed 2 prefixes, 2 paths

BGP – AS_PATH Filtering and Manipulation

- Атрибут AS_PATH представляет собой строку, в которой перечислены номера автономных систем, через которые проходит маршрут
- Т.к. указанный атрибут является строкой, его можно обрабатывать регулярными выражениями:
 - . - любой символ, включая пробел
 - * - ноль или больше совпадений с выражением
 - + - одно или больше совпадений с выражением
 - ? - ноль или одно совпадение с выражением
 - ^ - начало строки
 - \$ - конец строки
 - _ - любой разделитель (включая, начало, конец, пробел)
 - \ - не воспринимать следующий символ как специальный
 - [] - совпадение с одним из символов в диапазоне
 - | - логическое или

BGP – AS_PATH Filtering and Manipulation

```
<HUAWEI_with_FV>display bgp routing-table regular-expression _43038$
```

Total Number of Routes: 14

BGP Local router ID is 2.2.2.2

Status codes: * - valid, > - best, d - damped,
h - history, i - internal, s - suppressed, S - Stale
Origin : i - IGP, e - EGP, ? - incomplete

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	178.17.176.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	178.17.178.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	178.17.180.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	178.17.182.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	193.33.230.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	213.176.232.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i
*>	213.176.234.0/23	198.51.100.2		101	10	8359 43038i
* i		198.51.100.6		101	0	8359 43038i

BGP – AS_PATH Filtering and Manipulation

```
RP/0/RSP0/CPU0:XR_with_FV#show bgp ipv4 unicast regexp _2497_  
Wed Apr 13 07:18:05.705 MSK  
BGP router identifier 3.3.3.3, local AS number 64500  
BGP generic scan interval 60 secs  
Non-stop routing is enabled  
BGP table state: Active  
Table ID: 0xe0000000 RD version: 3410686769  
BGP main routing table version 3410686769  
BGP NSR Initial initsync version 718523 (Reached)  
BGP NSR/ISSU Sync-Group versions 3410686769/0  
BGP scan interval 60 secs
```

Status codes: s suppressed, d damped, h history, * valid, > best
i - internal, r RIB-failure, S stale, N Nexthop-discard

Origin codes: i - IGP, e - EGP, ? - incomplete

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 1.1.64.0/19	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.96.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.97.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.98.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.99.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.100.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.101.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.102.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.103.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.104.0/24	198.51.100.106	250	0	8359	2497 2519 i
*> 1.1.105.0/24	198.51.100.106	250	0	8359	2497 2519 i

BGP – AS_PATH Filtering and Manipulation

```
ios_with_fv#show bgp ipv4 unicast regexp ^8359_  
BGP table version is 8159492, local router ID is 1.1.1.1  
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,  
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,  
               x best-external, a additional-path, c RIB-compressed,  
Origin codes: i - IGP, e - EGP, ? - incomplete  
RPKI validation codes: V valid, I invalid, N Not found
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	0.0.0.0	198.51.100.201	0		0	8359 i
*>	1.0.64.0/18	198.51.100.201	0		0	8359 7670 18144 i
*>	1.0.128.0/19	198.51.100.201	0		0	8359 38040 23969 i
*>	1.0.128.0/18	198.51.100.201	0		0	8359 38040 23969 i
*>	1.0.128.0/17	198.51.100.201	0		0	8359 38040 23969 i
*>	1.0.144.0/20	198.51.100.201	0		0	8359 38040 23969 ?
*>	1.0.160.0/19	198.51.100.201	0		0	8359 38040 23969 i
*>	1.0.192.0/19	198.51.100.201	0		0	8359 38040 23969 i

BGP – AS_PATH Filtering and Manipulation

- **Фильтрация на основе AS_PATH:**
 - Отбор маршрутов, с заданной длиной AS_PATH: `^[0-9]+_[0-9]+$`
 - Отбор маршрутов из локальной AS: `^$`
 - Отбор маршрутов, проходящих через конкретную AS: `_2497_`
 - Отбор маршрутов, зародившихся в конкретной AS: `43038$`
 - Отбор маршрутов, начинающихся в конкретной AS: `^8359_`
- **Инструменты:**
 - **IOS/IOS-XE: AS-Path access list:**

```
ip as-path access-list 1 permit _56437$
```
 - **IOS-XR: AS-Path set:**

```
as-path-set AS_PATH_TEST01
  originates-from '56437'
end-set
```
 - **Huawei VRP: AS-Path-Filter**

```
ip as-path-filter ASF_TEST permit _56437$
```

BGP – AS_PATH Filtering and Manipulation

- Модификация AS-PATH теоретически возможна несколькими способами, однако, фактически, именно в целях модификации используется только один
- Изменение AS_PATH происходит при агрегации маршрутов – в AS_PATH агрегата по умолчанию не копируются значения из составляющих
- Prepending – добавление в AS_PATH дополнительных элементов. Де-юре никто не ограничивает значения, которые можно добавить в AS_PATH, де-факто добавлять необходимо только номер своей AS.
- Prepending в первую очередь нужен для управления входящим трафиком: увеличивая длину AS_PATH, мы «ухудшаем» маршрут, делая его менее выгодным для соседей

BGP – AS_PATH Filtering and Manipulation

R1 (IOS) prepends to R3:

```
route-map RM_PREPEND_3 permit 10
  set as-path prepend 100 100 100
!
router bgp 100
  address-family ipv4
    neighbor 10.1.3.3 route-map RM_PREPEND_3 out
  exit-address-family
!
```

Before prepend:

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast | b Network
```

```
Wed Apr 13 16:49:03.423 UTC
```

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 1.1.1.1/32	10.1.3.1	0		0	100 i
* 10.2.3.2	10.2.3.2			0	200 100 i
* 2.2.2.2/32	10.1.3.1			0	100 200 i
*> 10.2.3.2	10.2.3.2	0		0	200 i
*> 3.3.3.3/32	0.0.0.0	0		32768	i

```
<R2>dis bgp routing-table
```

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	1.1.1.1/32	10.1.2.1	0		0	100i
*	10.2.3.3	10.2.3.3			0	300 100i
*>	2.2.2.2/32	0.0.0.0	0		0	i
*>	3.3.3.3/32	10.2.3.3	0		0	300i
*	10.1.2.1	10.1.2.1			0	100 300i

After prepend:

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast | b Network
```

```
Wed Apr 13 16:53:26.015 UTC
```

Network	Next Hop	Metric	LocPrf	Weight	Path
* 1.1.1.1/32	10.1.3.1	0		0	100 100 100 100 i
*>	10.2.3.2			0	200 100 i
* 2.2.2.2/32	10.1.3.1			0	100 100 100 100 200 i
*>	10.2.3.2	0		0	200 i
*> 3.3.3.3/32	0.0.0.0	0		32768	i

```
<R2>display bgp routing-table
```

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	1.1.1.1/32	10.1.2.1	0		0	100i
*>	2.2.2.2/32	0.0.0.0	0		0	i
*>	3.3.3.3/32	10.2.3.3	0		0	300i
*	10.1.2.1	10.1.2.1			0	100 300i

BGP – AS_PATH Filtering and Manipulation

R3 (IOS-XR) prepends to R3:

```
route-policy RP_PREPEND_3
  prepend as-path own-as 3
end-policy
!
router bgp 300
  neighbor 10.2.3.2
  address-family ipv4 unicast
    route-policy RP_PREPEND_3 out
  !
```

Before:

```
<R2>display bgp routing-table
```

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	1.1.1.1/32	10.1.2.1	0		0	100i
*>	2.2.2.2/32	0.0.0.0	0		0	i
*>	3.3.3.3/32	10.2.3.3	0		0	300i
*		10.1.2.1			0	100 300i

```
R1#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	1.1.1.1/32	0.0.0.0	0		32768	i
*	2.2.2.2/32	10.1.3.3				0 300 200 i
*>		10.1.2.2	0			0 200 i
*	3.3.3.3/32	10.1.2.2				0 200 300 i
*>		10.1.3.3	0			0 300 i

After:

```
<R2>dis bgp routing-table
```

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	1.1.1.1/32	10.1.2.1	0		0	100i
*>	2.2.2.2/32	0.0.0.0	0		0	i
*>	3.3.3.3/32	10.1.2.1			0	100 300i
*		10.2.3.3	0		0	300 300 300 300i

```
R1#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	1.1.1.1/32	0.0.0.0	0		32768	i
*	2.2.2.2/32	10.1.3.3				0 300 200 i
*>		10.1.2.2	0			0 200 i
*>	3.3.3.3/32	10.1.3.3	0			0 300 i

BGP – AS_PATH Filtering and Manipulation

R2 (Huawei VRP) prepends to R1:

```
route-policy RP_PREPEND_3 permit node 10
  apply as-path 200 200 200 additive
bgp 200
  ipv4-family unicast
    peer 10.1.2.1 route-policy RP_PREPEND_3 export
```

Before:

```
R1#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	1.1.1.1/32	0.0.0.0	0		32768	i
*	2.2.2.2/32	10.1.3.3				0 300 200 i
*>		10.1.2.2	0			0 200 i
*>	3.3.3.3/32	10.1.3.3	0			0 300 i

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast | b Network
```

```
Wed Apr 13 17:46:51.355 UTC
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*	1.1.1.1/32	10.1.3.1	0			0 100 100 100 100 i
*>		10.2.3.2				0 200 100 i
*	2.2.2.2/32	10.1.3.1				0 100 100 100 100 200 i
*>		10.2.3.2	0			0 200 i
*>	3.3.3.3/32	0.0.0.0	0		32768	i

After:

```
R1#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	1.1.1.1/32	0.0.0.0	0		32768	i
*>	2.2.2.2/32	10.1.3.3				0 300 200 i
*		10.1.2.2	0			0 200 200 200 200 i
*>	3.3.3.3/32	10.1.3.3	0			0 300 i


```
RP/0/0/CPU0:R3#show bgp ipv4 unicast | b Network
```

```
Wed Apr 13 17:45:37.630 UTC
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*	1.1.1.1/32	10.1.3.1	0			0 100 100 100 100 i
*>		10.2.3.2				0 200 100 i
*>	2.2.2.2/32	10.2.3.2	0			0 200 i
*>	3.3.3.3/32	0.0.0.0	0		32768	i

BGP – Community

- Community – для управления трафиком чаще всего используются standard community
- За исключением well-known community, действия, применяемые к маршруту, определяются инженером самостоятельно, исходя из общей политики управления сетью и целей, которых необходимо достигнуть
- Well-known community позволяют добиться конкретных результатов меньшим количеством конфига и вне зависимости от вендора получать предсказуемый результат



BGP – Community – Huawei VRP

```
ip ip-prefix PL_DEFAULT_ONLY index 10 permit 0.0.0.0 0
ip ip-prefix PL_OUT index 10 permit 192.0.2.0 23 greater-equal 23
less-equal 24
#
ip community-filter basic CF_BLACKHOLE index 10 permit 64501:666
ip community-filter basic CF_R3 index 10 permit 64500:65003
ip community-filter basic CF_R4 index 10 permit 64500:65004
#
route-policy RP_OUT permit node 10
  if-match community-filter CF_BLACKHOLE
#
route-policy RP_OUT permit node 20
  if-match ip-prefix PL_OUT
#
route-policy RP_R4_IN permit node 10
  apply community 64500:65004 additive
#
route-policy RP_R4_OUT permit node 10
  if-match ip-prefix PL_DEFAULT_ONLY
#
route-policy RP_R4_OUT permit node 20
  if-match community-filter CF_R3
#
```

```
bgp 64500
  router-id 10.255.255.2
  peer 10.2.4.4 as-number 65004
  peer 10.2.4.4 connect-interface Ethernet1/0/1
  peer 10.255.255.1 as-number 64500
  peer 10.255.255.1 connect-interface LoopBack0
  peer 198.51.10.2 as-number 64501
  peer 198.51.10.2 connect-interface Ethernet1/0/2
#
ipv4-family unicast
  undo synchronization
  aggregate 192.0.2.0 255.255.254.0
  aggregate 192.0.2.0 255.255.255.0
  aggregate 192.0.3.0 255.255.255.0
  peer 10.2.4.4 enable
  peer 10.2.4.4 route-policy RP_R4_IN import
  peer 10.2.4.4 route-policy RP_R4_OUT export
  peer 10.2.4.4 advertise-community
  peer 10.255.255.1 enable
  peer 10.255.255.1 next-hop-local
  peer 10.255.255.1 advertise-community
  peer 198.51.10.2 enable
  peer 198.51.10.2 route-policy RP_OUT export
  peer 198.51.10.2 advertise-community
#
```

BGP – Community – Huawei VRP

```
<R2>dis bgp routing-table 192.0.2.3 32

BGP local router ID : 10.255.255.2
Local AS number : 64500
Paths: 1 available, 1 best, 1 select, 0 best-external, 0 add-path
BGP routing table entry information of 192.0.2.3/32:
From: 10.255.255.1 (10.255.255.1)
Route Duration: 0d00h01m08s
Relay IP Nexthop: 10.1.2.1
Relay IP Out-Interface: Ethernet1/0/0
Original nexthop: 10.255.255.1
Qos information : 0x0
Community: <64500:65003>, <64501:666>
AS-path 65003, origin igp, MED 0, localpref 100, pref-val 0, valid, internal, best, select, pre
255, IGP cost 2
Advertised to such 2 peers:
10.2.4.4
198.51.10.2
<R2>dis bgp routing-table 192.0.2.4 32

BGP local router ID : 10.255.255.2
Local AS number : 64500
Paths: 1 available, 1 best, 1 select, 0 best-external, 0 add-path
BGP routing table entry information of 192.0.2.4/32:
From: 10.2.4.4 (10.255.255.4)
Route Duration: 0d00h03m11s
Direct Out-interface: Ethernet1/0/1
Original nexthop: 10.2.4.4
Qos information : 0x0
Community: <64500:65004>
AS-path 65004, origin incomplete, MED 0, pref-val 0, valid, external, best, select, pre 255
Advertised to such 2 peers:
10.255.255.1
198.51.10.2
```

Before:

```
<R2>display bgp routing-table peer 198.51.10.2 advertised-routes
```

Total Number of Routes: 3						
	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	192.0.2.0/23	0.0.0.0			0	64500?
*>	192.0.2.0/24	0.0.0.0			0	64500?
*>	192.0.3.0/24	0.0.0.0			0	64500i

After:

```
<R2>display bgp routing-table peer 10.2.4.4 advertised-routes
```

Total Number of Routes: 5						
	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	0.0.0.0/0	0.0.0.0			0	64500 64501i
*>i	192.0.2.3/32	0.0.0.0			0	64500 65003?
*>i	192.0.2.13/32	0.0.0.0			0	64500 65003?
*>i	192.0.2.23/32	0.0.0.0			0	64500 65003?
*>i	192.0.3.0/25	0.0.0.0			0	64500 65003i

BGP – Community – IOS-XR

```
prefix-set PS_OUT
 192.0.2.0/23 le 24
end-set
!
prefix-set PS_DEFAULT_ONLY
 0.0.0.0/0
end-set
!
community-set CS_R3
 64500:65003
end-set
!
community-set CS_R4
 64500:65004
end-set
!
route-policy RP_OUT
 if community matches-any (64501:666) or destination
 in PS_OUT then
   pass
 else
   drop
 endif
end-policy
!
route-policy RP_R3_IN
 set community (64500:65003) additive
end-policy
!
route-policy RP_PERMIT_ANY
 pass
end-policy
!
```

```
route-policy RP_R3_OUT
 if destination in PS_DEFAULT_ONLY or community
 matches-any CS_R4 then
   pass
 else
   drop
 endif
end-policy
!
router bgp 64500
 bgp router-id 10.255.255.1
 address-family ipv4 unicast
  aggregate-address 192.0.2.0/23
  aggregate-address 192.0.2.0/24
  aggregate-address 192.0.3.0/24
!
neighbor 10.1.3.3
 remote-as 65003
 update-source GigabitEthernet0/0/0/1
 address-family ipv4 unicast
 send-community-ebgp
 route-policy RP_R3_IN in
 route-policy RP_R3_OUT out
 default-originate
!
!
```

```
!
neighbor 198.51.10.0
 remote-as 64501
 update-source GigabitEthernet0/0/0/2
 address-family ipv4 unicast
 send-community-ebgp
 route-policy RP_PERMIT_ANY in
 route-policy RP_OUT out
!
!
neighbor 10.255.255.2
 remote-as 64500
 update-source Loopback0
 address-family ipv4 unicast
 route-policy RP_PERMIT_ANY in
 route-policy RP_PERMIT_ANY out
 next-hop-self
!
!
!
```

BGP – Community – IOS-XR

```
RP/0/0/CPU0:R1#show bgp ipv4 unicast 192.0.2.13/32
Mon Apr 18 17:54:48.473 UTC
BGP routing table entry for 192.0.2.13/32
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          84        84
Last Modified: Apr 18 17:52:15.558 for 00:02:32
Paths: (1 available, best #1)
  Advertised IPv4 Unicast paths to peers (in unique update groups):
    10.255.255.2
  Path #1: Received by speaker 0
  Advertised IPv4 Unicast paths to peers (in unique update groups):
    10.255.255.2
    65003
    10.1.3.3 from 10.1.3.3 (10.255.255.3)
      Origin incomplete, metric 0, localpref 100, valid, external, best, group-best
      Received Path ID 0, Local Path ID 1, version 84
      Community: 64500:65003
      Origin-AS validity: (disabled)
RP/0/0/CPU0:R1#show bgp ipv4 unicast 192.0.2.14/32
Mon Apr 18 17:54:56.573 UTC
BGP routing table entry for 192.0.2.14/32
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          103       103
Last Modified: Apr 18 17:52:33.558 for 00:02:23
Paths: (1 available, best #1)
  Advertised IPv4 Unicast paths to peers (in unique update groups):
    10.1.3.3
  Path #1: Received by speaker 0
  Advertised IPv4 Unicast paths to peers (in unique update groups):
    10.1.3.3
    65004
    10.255.255.2 (metric 1) from 10.255.255.2 (10.255.255.2)
      Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best
      Received Path ID 0, Local Path ID 1, version 103
      Community: 64500:65004
```

Before:

```
RP/0/0/CPU0:R1#show bgp ipv4 unicast neighbors 198.51.10.0
advertised-routes
Mon Apr 18 17:56:38.636 UTC
Network          Next Hop          From              AS Path
192.0.2.0/23      198.51.10.1       Local Aggregate   64500i
192.0.2.0/24      198.51.10.1       Local Aggregate   64500i
192.0.3.0/24      198.51.10.1       Local Aggregate   64500i
```

Processed 3 prefixes, 3 paths

After:

```
RP/0/0/CPU0:R1#show bgp ipv4 unicast neighbors 10.1.3.3
advertised-routes
Mon Apr 18 17:59:51.092 UTC
Network          Next Hop          From              AS Path
0.0.0.0/0         0.0.0.0           Local             i
192.0.2.4/32      10.1.3.1          10.255.255.2      64500 65004?
192.0.2.14/32     10.1.3.1          10.255.255.2      64500 65004?
192.0.2.24/32     10.1.3.1          10.255.255.2      64500 65004?
192.0.3.128/25    10.1.3.1          10.255.255.2      64500 65004i
```

Processed 5 prefixes, 5 paths


BGP – Community – IOS/IOS-XE

```
ip bgp-community new-format
!
ip prefix-list PL_RDSTB_CONNECTED seq 10 permit 192.0.2.0/23 ge 32
!
route-map RM_BLACKHOLE permit 10
  set community 64501:666
!
route-map RM_BGP_RDSTB_CONNECTED permit 10
  match ip address prefix-list PL_RDSTB_CONNECTED
!
router bgp 65003
  bgp router-id 10.255.255.3
  neighbor 10.1.3.1 remote-as 64500
  neighbor 10.1.3.1 update-source Ethernet0/0
!
address-family ipv4
  network 192.0.2.3 mask 255.255.255.255 route-map RM_BLACKHOLE
  network 192.0.3.0 mask 255.255.255.128
  redistribute connected route-map RM_BGP_RDSTB_CONNECTED
  neighbor 10.1.3.1 activate
  neighbor 10.1.3.1 send-community
exit-address-family
!
```

```
R3#show bgp ipv4 unicast 192.0.2.3/32
BGP routing table entry for 192.0.2.3/32, version 67
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    3
  Refresh Epoch 1
  Local
    0.0.0.0 from 0.0.0.0 (10.255.255.3)
      Origin IGP, metric 0, localpref 100, weight 32768, valid, sourced,
local, best
      Community: 64501:666
      rx pathid: 0, tx pathid: 0x0
```

BGP – MED

- MED – Multi Exit Discriminator
- Применяется при необходимости разбалансировать трафик между несколькими стыками с **одной** AS
- За пределы соседней AS не передаются
- Достаточно слабый атрибут
- Чем меньше значение, тем лучше
- По умолчанию не проставляется (при сравнении считается равным нулю)



BGP – MED

R1:

```
route-policy RP_AGGREGATED
  set origin igp
  set med 0
end-policy
!
route-policy RP_BGP_UPLINK_OUT
  if destination in (192.0.2.0/24) or destination in (192.0.2.0/23) then
    pass
  elseif destination in (192.0.3.0/24) then
    prepend as-path own-as 3
  else
    drop
  endif
end-policy
!
router bgp 64500
  address-family ipv4 unicast
    aggregate-address 192.0.2.0/23 route-policy RP_AGGREGATED
    aggregate-address 192.0.2.0/24 route-policy RP_AGGREGATED
    aggregate-address 192.0.3.0/24 route-policy RP_AGGREGATED
  !
  neighbor 198.51.10.0
  address-family ipv4 unicast
    route-policy RP_BGP_UPLINK_OUT out
  !
```

R2:

```
ip ip-prefix PL_NO_PREPEND_OUT index 10 permit 192.0.3.0 24
ip ip-prefix PL_NO_PREPEND_OUT index 20 permit 192.0.2.0 23
ip ip-prefix PL_PREPEND_OUT index 10 permit 192.0.2.0 24
#
route-policy RP_AGGREGATED permit node 10
  apply cost 0
  apply origin igp
#
route-policy RP_BGP_UPLINK_OUT permit node 10
  if-match ip-prefix PL_NO_PREPEND_OUT
#
route-policy RP_BGP_UPLINK_OUT permit node 20
  if-match ip-prefix PL_PREPEND_OUT
  apply as-path 64500 64500 64500 additive
#
```

R5 & R6:

```
ip as-path access-list 1 permit ^64500$
!
ip prefix-list PL_WIDE_NETS seq 10 permit 0.0.0.0/0 le 24
!
route-map RM_BGP_64500_IN permit 10
  match ip address prefix-list PL_WIDE_NETS
  match as-path 1
!
router bgp 64501
  address-family ipv4
    neighbor 198.51.10.1 route-map RM_BGP_64500_IN in
  !
```


BGP – MED

```
R1:
RP/0/0/CPU0:R1#show  bgp  ipv4  unicast  neighbors  198.51.10.0  advertised-
routes
Fri Apr 22 17:43:44.841 UTC
Network                Next Hop                From                AS Path
192.0.2.0/23           198.51.10.1             Local Aggregate 64500i
192.0.2.0/24           198.51.10.1             Local Aggregate 64500i
192.0.3.0/24           198.51.10.1             Local Aggregate 64500 64500 64500 64500i

Processed 3 prefixes, 3 paths
```

```
R2:
<R2>dis bgp routing-table peer 198.51.10.2 advertised-routes

Total Number of Routes: 3
Network      NextHop  MED  LocPrf  PrefVal  Path/Ogn
*> 192.0.2.0/23 0.0.0.0  0           0        64500i
*> 192.0.2.0/24 0.0.0.0  0           0        64500 64500 64500 64500i
*> 192.0.3.0/24 0.0.0.0  0           0        64500i
```

```
R5:
R5#show bgp ipv4 uni neighbors 198.51.10.1 routes | b Network
Network                Next Hop                Metric LocPrf Weight Path
*> 192.0.2.0           198.51.10.1             0              0 64500 i
*> 192.0.2.0/23        198.51.10.1             0              0 64500 i

Total number of prefixes 2

R6:
R6#show bgp ipv4 unicast neighbors 198.51.10.3 routes | b Network
Network                Next Hop                Metric LocPrf Weight Path
*> 192.0.2.0/23        198.51.10.3             0              0 64500 i
*> 192.0.3.0           198.51.10.3             0              0 64500 i

Total number of prefixes 2
```

BGP – MED – IOS-XR and Huawei VRP

R1:

```
route-policy RP_BGP_UPLINK_MED_OUT
  if destination in (192.0.2.0/24) or destination in
(192.0.2.0/23) then
    pass
  elseif destination in (192.0.3.0/24) then
    set med 200
  else
    drop
  endif
end-policy
!
router bgp 64500
  neighbor 198.51.10.0
  address-family ipv4 unicast
    route-policy RP_BGP_UPLINK_MED_OUT out
  !
R2:
route-policy RP_BGP_UPLINK_MED_OUT permit node 10
  if-match ip-prefix PL_NO_PREPEND_OUT
#
route-policy RP_BGP_UPLINK_MED_OUT permit node 20
  if-match ip-prefix PL_PREPEND_OUT
  apply cost 200
#
```

R5:

```
R5#show bgp ipv4 unicast 192.0.2.0/23 longer-prefixes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
*> 192.0.2.0      198.51.10.1          0           0 64500 i
* i 192.0.2.0/23 198.51.10.6          0      100     0 64500 i
*>                198.51.10.1          0           0 64500 i
* 192.0.3.0      198.51.10.1        200           0 64500 i
*>i                198.51.10.6          0      100     0 64500 I
```

R6:

```
R6#show bgp ipv4 unicast 192.0.2.0/23 longer-prefixes | b Network
      Network      Next Hop      Metric LocPrf Weight Path
* 192.0.2.0      198.51.10.3        200           0 64500 i
*>i                198.51.10.5          0      100     0 64500 i
* i 192.0.2.0/23 198.51.10.5          0      100     0 64500 i
*>                198.51.10.3          0           0 64500 i
*> 192.0.3.0      198.51.10.3          0           0 64500 i
```

BGP – MED – IOS/IOS-XE

R5:

```
ip prefix-list PL_TO_OUTER_AS seq 10 permit 0.0.0.0/0 le 24
!
route-map RM_BGP_TO_OUTER_AS permit 10
  match ip address prefix-list PL_TO_OUTER_AS
!
router bgp 64501
  address-family ipv4 unicast
    neighbor 198.51.10.9 route-map RM_BGP_TO_OUTER_AS out
```

R6:

```
ip prefix-list PL_TO_OUTER_AS seq 10 permit 0.0.0.0/0 le 24
!
route-map RM_BGP_TO_OUTER_AS permit 10
  match ip address prefix-list PL_TO_OUTER_AS
!
router bgp 64501
  address-family ipv4 unicast
    neighbor 198.51.10.11 route-map RM_BGP_TO_OUTER_AS out
```

R2:

```
R7#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	7.7.7.7/32	0.0.0.0	0		32768	i
*	192.0.2.0	198.51.10.8			0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*	192.0.2.0/23	198.51.10.8			0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*	192.0.3.0	198.51.10.8			0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*	198.51.10.0	198.51.10.8	0		0	64501 i
*>		198.51.10.10	0		0	64501 i

BGP – MED – IOS/IOS-XE

R5:

```
ip prefix-list PL_TO_OUTER_AS_NO_MED seq 10 permit 198.51.10.0/24
!
ip prefix-list PL_TO_OUTER_AS_SET_MED seq 10 permit 0.0.0.0/0 le 24
!
route-map RM_BGP_TO_OUTER_AS_SET_MED permit 10
  match ip address prefix-list PL_TO_OUTER_AS_NO_MED
!
route-map RM_BGP_TO_OUTER_AS_SET_MED permit 20
  match ip address prefix-list PL_TO_OUTER_AS_SET_MED
  set metric 200
!
router bgp 64501
  address-family ipv4 unicast
    neighbor 198.51.10.9 route-map RM_BGP_TO_OUTER_AS_SET_MED out
```

R6:

```
ip prefix-list PL_TO_OUTER_AS_SET_MED seq 10 permit 198.51.10.0/24
!
ip prefix-list PL_TO_OUTER_AS_NO_MED seq 10 permit 0.0.0.0/0 le 24
!
route-map RM_BGP_TO_OUTER_AS_SET_MED permit 10
  match ip address prefix-list PL_TO_OUTER_AS_SET_MED
  set metric 200
!
route-map RM_BGP_TO_OUTER_AS_SET_MED permit 20
  match ip address prefix-list PL_TO_OUTER_AS_NO_MED
!
router bgp 64501
  address-family ipv4 unicast
    neighbor 198.51.10.11 route-map RM_BGP_TO_OUTER_AS_SET_MED out
```


R7#show bgp ipv4 unicast | b Network

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	7.7.7.7/32	0.0.0.0	0		32768	i
*	192.0.2.0	198.51.10.8	200		0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*	192.0.2.0/23	198.51.10.8	200		0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*	192.0.3.0	198.51.10.8	200		0	64501 64500 i
*>		198.51.10.10			0	64501 64500 i
*>	198.51.10.0	198.51.10.8	0		0	64501 i
*		198.51.10.10	200		0	64501 i

BGP – Next-hop

Как и большую часть других атрибутов, можно изменить, согласно каких-то своих политик: например, чтобы оптимизировать загрузку каналов.

Одним из вариантов использования является т.н. blackholing – умышленный сброс трафика, идущего на какой-то конкретный IP-адрес, который подвергается DoS-атаке.



BGP – Next-hop

R1:

```
router bgp 64501
  bgp router-id 192.0.2.1
  neighbor 10.1.3.3 remote-as 64503
  neighbor 10.1.3.3 update-source Ethernet0/0
  neighbor 10.1.4.4 remote-as 64504
  neighbor 10.1.4.4 update-source Ethernet0/1
  !
  address-family ipv4
    network 192.0.2.0
    neighbor 10.1.3.3 activate
    neighbor 10.1.3.3 filter-list 1 out
    neighbor 10.1.4.4 activate
    neighbor 10.1.4.4 filter-list 1 out
  exit-address-family
  !
  ip as-path access-list 1 permit ^$
```

R1#show bgp ipv4 unicast | b Network

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0	0		32768	i
*	198.51.100.0	10.1.4.4			0	64504 64502 i
*>		10.1.3.3			0	64503 64502 i
*	203.0.113.0	10.1.4.4			0	64504 64502 i
*>		10.1.3.3			0	64503 64502 i

R1#ping 198.51.100.2 source 192.0.2.1

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 198.51.100.2, timeout is 2 seconds:

Packet sent with a source address of 192.0.2.1

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 2/2/4 ms

R1#ping 198.51.100.22 source 192.0.2.1

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 198.51.100.22, timeout is 2 seconds:

Packet sent with a source address of 192.0.2.1

U.U.U

Success rate is 0 percent (0/5)

BGP – Next-hop

R2:

```
router bgp 64502
  bgp router-id 198.51.100.2
  neighbor 10.2.5.5 remote-as 64503
  neighbor 10.2.5.5 update-source Ethernet0/0
  neighbor 10.2.6.6 remote-as 64504
  neighbor 10.2.6.6 update-source Ethernet0/1
  !
  address-family ipv4
    network 198.51.100.2 mask 255.255.255.255
    network 198.51.100.22 mask 255.255.255.255 route-map RM_SET_LOCAL_BH_COMMUNITY
    network 203.0.113.2 mask 255.255.255.255
    network 203.0.113.22 mask 255.255.255.255 route-map RM_SET_LOCAL_BH_COMMUNITY
    aggregate-address 203.0.113.0 255.255.255.0 summary-only
    aggregate-address 198.51.100.0 255.255.255.0 summary-only
    neighbor 10.2.5.5 activate
    neighbor 10.2.5.5 send-community
    neighbor 10.2.5.5 route-map RM_EBGP_AS64503_OUT out
    neighbor 10.2.5.5 unsuppress-map RM_UNSUPPRESS
    neighbor 10.2.5.5 filter-list 1 out
    neighbor 10.2.6.6 activate
    neighbor 10.2.6.6 send-community
    neighbor 10.2.6.6 route-map RM_EBGP_AS64504_OUT out
    neighbor 10.2.6.6 unsuppress-map RM_UNSUPPRESS
    neighbor 10.2.6.6 filter-list 1 out
  exit-address-family
  !
  ip bgp-community new-format
  ip community-list standard CL_LOCAL_BLACKHOLE permit 64502:666
```

```
ip as-path access-list 1 permit ^$
ip prefix-list PL_AGGREGATE seq 10 permit 198.51.100.0/24
ip prefix-list PL_AGGREGATE seq 20 permit 203.0.113.0/24
!
route-map RM_EBGP_AS64503_OUT permit 10
  match community CL_LOCAL_BLACKHOLE
  set community 64503:666 additive
route-map RM_EBGP_AS64503_OUT permit 20
  match ip address prefix-list PL_AGGREGATE
!
route-map RM_EBGP_AS64504_OUT permit 10
  match community CL_LOCAL_BLACKHOLE
  set community 64504:666
route-map RM_EBGP_AS64504_OUT permit 20
  match ip address prefix-list PL_AGGREGATE
!
route-map RM_SET_LOCAL_BH_COMMUNITY permit 10
  set community 64502:666
!
route-map RM_UNSUPPRESS permit 10
  match community CL_LOCAL_BLACKHOLE
```

```
R2#show bgp ipv4 unicast neighbor 10.2.5.5 advertised-routes | b
Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	198.51.100.0	0.0.0.0			32768	i
s>	198.51.100.22/32	0.0.0.0	0		32768	i
*>	203.0.113.0	0.0.0.0			32768	i
s>	203.0.113.22/32	0.0.0.0	0		32768	i

BGP – Next-hop – IOS/IOS-XE

```
R3:
router bgp 64503
  bgp router-id 10.255.255.3
  neighbor 10.1.3.1 remote-as 64501
  neighbor 10.1.3.1 update-source Ethernet0/0
  neighbor 10.255.255.5 remote-as 64503
  neighbor 10.255.255.5 update-source Loopback0
  !
  address-family ipv4
    neighbor 10.1.3.1 activate
    neighbor 10.1.3.1 route-map RM_EBGP_IN in
    neighbor 10.255.255.5 activate
    neighbor 10.255.255.5 route-map RM_IBGP_OUT out
  exit-address-family
  !
  ip route 172.16.0.1 255.255.255.255 Null0
  !
  ip prefix-list PL_PERMIT_ANY seq 10 permit 0.0.0.0/0 le 32
  !
  route-map RM_EBGP_IN permit 10
    match community CL_BLACKHOLE
    set community no-export additive
    set ip next-hop 172.16.0.1
  !
  route-map RM_EBGP_IN permit 20
    match ip address prefix-list PL_PERMIT_ANY
  !
```

```
route-map RM_IBGP_OUT permit 10
  match community CL_BLACKHOLE
  set ip next-hop 172.16.0.1
!
route-map RM_IBGP_OUT permit 20
  match ip address prefix-list PL_PERMIT_ANY
  set ip next-hop peer-address
!
```

```
R3#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	10.1.3.1	0			0 64501 i
*>i	198.51.100.0	10.255.255.5	0	100		0 64502 i
*>i	198.51.100.22/32	172.16.0.1	0	100		0 64502 i
*>i	203.0.113.0	10.255.255.5	0	100		0 64502 i
*>i	203.0.113.22/32	172.16.0.1	0	100		0 64502 i

```
R3#show ip cef 198.51.100.2
198.51.100.0/24
  nexthop 10.3.5.5 Ethernet0/1
R3#show ip cef 198.51.100.22
198.51.100.22/32
  nexthop 172.16.0.1 Null0
```


BGP – Next-hop – Huawei VRP

R5:

```
bgp 64503
 router-id 10.255.255.2
 peer 10.2.5.2 as-number 64502
 peer 10.2.5.2 connect-interface GE1/0/1
 peer 10.5.6.6 as-number 64504
 peer 10.5.6.6 connect-interface GE1/0/2
 peer 10.255.255.3 as-number 64503
 peer 10.255.255.3 connect-interface LoopBack0
 #
 ipv4-family unicast
  peer 10.2.5.2 enable
  peer 10.2.5.2 route-policy RP_EBGP_IN import
  peer 10.2.5.2 default-route-advertise
  peer 10.5.6.6 enable
  peer 10.5.6.6 route-policy RP_EBGP_IN import
  peer 10.255.255.3 enable
  peer 10.255.255.3 route-policy RP_IBGP_OUT export
  peer 10.255.255.3 advertise-community
 #
 route-policy RP_EBGP_IN permit node 10
  if-match community-filter CF_BLACKHOLE
  apply ip-address next-hop 172.16.0.1
  apply community no-export additive
 #
 route-policy RP_EBGP_IN permit node 20
  if-match ip-prefix PL_PERMIT_ANY
```

```
route-policy RP_IBGP_OUT permit node 10
  if-match community-filter CF_BLACKHOLE
  apply ip-address next-hop 172.16.0.1
 #
route-policy RP_IBGP_OUT permit node 20
  if-match ip-prefix PL_PERMIT_ANY
  apply ip-address next-hop peer-address
 #
ip ip-prefix PL_PERMIT_ANY index 10 permit 0.0.0.0 0 less-equal 32
ip community-filter basic CF_BLACKHOLE index 10 permit 64503:666
ip community-filter basic CF_BLACKHOLE index 20 permit 64502:666
ip community-filter basic CF_BLACKHOLE index 30 permit 64501:666
ip community-filter basic CF_BLACKHOLE index 40 permit 64504:666
 #
ip route-static 172.16.0.1 255.255.255.255 NULL0 description BlackHole
```

<R5>dis bgp routing-table

Total Number of Routes: 5

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>i	192.0.2.0/24	10.255.255.3	0	100	0	64501i
*>	198.51.100.0/24	10.2.5.2	0		0	64502i
*>	198.51.100.22/32	172.16.0.1	0		0	64502i
*>	203.0.113.0/24	10.2.5.2	0		0	64502i
*>	203.0.113.22/32	172.16.0.1	0		0	64502i

<R5>dis ip routing-table 198.51.100.0 24 longer-match

Destination/Mask	Proto	Pre	Cost	Flags	NextHop	Interface
198.51.100.0/24	EBGP	255	0	RD	10.2.5.2	GE1/0/1
198.51.100.22/32	EBGP	255	0	RDB	172.16.0.1	NULL0

BGP – Next-hop – IOS-XR

R5:

```
community-set CS_BLACKHOLE
*:666
end-set
!
route-policy RP_EBGP_IN
  if community matches-any CS_BLACKHOLE then
    set next-hop 172.16.0.1
    set community (no-export) additive
  else
    pass
  endif
end-policy
!
route-policy RP_IBGP_OUT
  if community matches-any CS_BLACKHOLE then
    set next-hop 172.16.0.1
  else
    set next-hop self
  endif
end-policy
!
route-policy RP_PERMIT_ANY
  pass
end-policy
!
```

```
router bgp 64504
  bgp router-id 10.255.255.6
  address-family ipv4 unicast
  !
  neighbor 10.2.6.2
    remote-as 64502
    update-source GigabitEthernet0/0/0/1
    address-family ipv4 unicast
    route-policy RP_EBGP_IN in
    route-policy RP_PERMIT_ANY out
    default-originate
  !
  !
  neighbor 10.5.6.5
    remote-as 64503
    update-source GigabitEthernet0/0/0/2
    address-family ipv4 unicast
    route-policy RP_EBGP_IN in
    route-policy RP_PERMIT_ANY out
  !
  !
  neighbor 10.255.255.4
    remote-as 64504
    update-source Loopback0
    address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_IBGP_OUT out
```

```
router static
  address-family ipv4 unicast
    172.16.0.1/32
```

!

RP/0/0/CPU0:R6# show bgp ipv4 unicast | b Network

Sun Apr 24 17:01:47.188 UTC

Network	Next Hop	Metric	LocPrf	Weight	Path
*>i192.0.2.0/24	10.255.255.4	0	100	0	64501 i
*> 198.51.100.0/24	10.2.6.2	0		0	64502 i
*> 198.51.100.22/32	172.16.0.1	0		0	64502 i
*> 203.0.113.0/24	10.2.6.2	0		0	64502 i
*> 203.0.113.22/32	172.16.0.1	0		0	64502 i

Processed 5 prefixes, 5 paths

RP/0/0/CPU0:R6#show cef 198.51.100.2 detail | b Interface

Sun Apr 24 17:02:29.775 UTC

Hash	OK	Interface	Address
0	Y	GigabitEthernet0/0/0/1	10.2.6.2

RP/0/0/CPU0:R6#show cef 198.51.100.22 detail | b Interface

Sun Apr 24 17:02:33.584 UTC


Hash	OK	Interface	Address
0	Y	Unknown	null0

BGP – IBGP

Из-за работы split-horizon в IBGP, все BGP-устройства в одной AS должны иметь полносвязные соседства (т.е. full mesh). Количество связей в этом случае равно $(N * (N - 1)) / 2$.

Чтобы обойти это ограничение могут использоваться несколько способов:

- Конфедерации – RFC 5065
- Отражатель маршрутов – RFC 4456



BGP – IBGP - Confederation

- Идея проста: единая автономная система дробится на группу отдельных AS. Внутри этих отдельных sub-AS сохраняется логика работы IBGP, а между ними – используется стандартный EBGP.
- Конфедерация – это совокупность автономных систем, передающих наружу информацию как единая отдельная AS
- AS Confederation Identifier – номер AS, видимый снаружи и идентифицирующий конфедерацию как единое целое
- Member Autonomous System (Member-AS) – AS, входящая в конфедерацию
- Member-AS Number – номер AS, идентифицирующий AS как видимый только внутри конфедерации


BGP – IBGP - Confederation

RFC 5065 добавляет два дополнительных типа в атрибут AS_PATH:

AS_CONFED_SEQUENCE – упорядоченный набор Member-AS в локальной конфедерации, через которые прошел передаваемый маршрут

AS_CONFED_SET – неупорядоченный набор Member-AS в локальной конфедерации, через которые прошел передаваемый маршрут

При передаче маршрутов BGP-соседу не входящему в конфедерацию из AS_PATH убираются указанные выше составляющие AS_PATH, касающиеся конфедерации, и заменяются на номер AS, указанный в AS Confederation Identifier



BGP – Confederation

R1:

```
router bgp 64501
  bgp router-id 198.51.100.1
  bgp log-neighbor-changes
  neighbor 192.0.2.0 remote-as 64500
  neighbor 192.0.2.0 update-source Ethernet0/0
  !
  address-family ipv4
    network 198.51.100.0
    neighbor 192.0.2.0 activate
  exit-address-family
  !
```

R2:

```
router bgp 64502
  bgp router-id 203.0.113.2
  bgp log-neighbor-changes
  neighbor 192.0.2.2 remote-as 64500
  neighbor 192.0.2.2 update-source Ethernet0/0
  !
  address-family ipv4
    network 203.0.113.0
    neighbor 192.0.2.2 activate
  exit-address-family
```

R1:

```
AS64501-R1#show bgp ipv4 unicast summary | b Neighbor
Neighbor          V      AS  MsgRcvd  MsgSent   TblVer   InQ  OutQ  Up/Down
State/PfxRcd
192.0.2.0          4      64500    24      26        4     0     0 00:20:36      2
```

```
AS64501-R1#show bgp ipv4 unicast | b Network
      Network          Next Hop           Metric LocPrf Weight Path
*>   192.0.2.0          192.0.2.0                0 64500 i
*>   198.51.100.0        0.0.0.0                  0    32768 i
*>   203.0.113.0         192.0.2.0                0 64500 64502 i
```

R2:

```
AS64502-R2#show bgp ipv4 unicast summary | b Neighbor
Neighbor          V      AS  MsgRcvd  MsgSent   TblVer   InQ  OutQ  Up/Down
State/PfxRcd
192.0.2.2          4      64500    32      31        4     0     0 00:24:53      2
```

```
AS64502-R2#show bgp ipv4 unicast | b Network
      Network          Next Hop           Metric LocPrf Weight Path
*>   192.0.2.0          192.0.2.2                0 64500 i
*>   198.51.100.0         192.0.2.2                0 64500 64501 i
*>   203.0.113.0         0.0.0.0                  0    32768 i
```

BGP – Confederation

R3:

```
route-policy RP_PERMIT_ANY
  pass
end-policy
!
route-policy RP_BGP_OUTSIDE
  if destination in (0.0.0.0/0 le 24) then
    pass
  else
    drop
  endif
end-policy
!
router bgp 65001
  bgp confederation peers
    65002
  !
  bgp confederation identifier 64500
  address-family ipv4 unicast
    network 192.0.2.0/31
    network 192.0.2.103/32
    aggregate-address 192.0.2.0/24
```

```
!
neighbor-group 65001
  remote-as 65001
  update-source Loopback0
  address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_PERMIT_ANY out
  !
!
neighbor 192.0.2.1
  remote-as 64501
  update-source GigabitEthernet0/0/0/0
  address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_BGP_OUTSIDE out
  !
!
neighbor 10.255.255.4
  use neighbor-group 65001
!
neighbor 10.255.255.5
  use neighbor-group 65001
```

```
!
neighbor 10.255.255.6
  remote-as 65002
  ebgp-multihop 255
  update-source Loopback0
  address-family ipv4 unicast
    route-policy RP_PERMIT_ANY in
    route-policy RP_PERMIT_ANY out
  !
!
!
```

BGP – Confederation

R3:

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast summary | b Neighbor
```

Sat Apr 30 07:06:23.784 UTC

Neighbor	Spk	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	St/PfxRcd
10.255.255.4	0	65001	31	33	22	0	0	00:24:10	1
10.255.255.5	0	65001	31	33	22	0	0	00:24:07	1
10.255.255.6	0	65002	33	22	22	0	0	00:14:27	6
192.0.2.1	0	64501	30	28	22	0	0	00:24:22	1

```
RP/0/0/CPU0:R3#show bgp ipv4 unicast | b Network
```

Sat Apr 30 07:06:34.574 UTC

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 192.0.2.0/24	0.0.0.0			32768	i
*	10.255.255.6		100	0	(65002) i
*> 192.0.2.0/31	0.0.0.0	0		32768	i
*> 192.0.2.2/31	10.255.255.6	0	100	0	(65002) i
*> 192.0.2.103/32	0.0.0.0	0		32768	i
*>i192.0.2.104/32	10.255.255.4	0	100	0	i
*>i192.0.2.105/32	10.255.255.5	0	100	0	i
*> 192.0.2.106/32	10.255.255.6	0	100	0	(65002) i
*> 192.0.2.107/32	10.255.255.7	0	100	0	(65002) i
*> 192.0.2.108/32	10.255.255.8	0	100	0	(65002) i
*> 198.51.100.0/24	192.0.2.1	0		0	64501 i
*> 203.0.113.0/24	192.0.2.3	0	100	0	(65002) 64502 i

Processed 11 prefixes, 12 paths

```
> Internet Protocol Version 4, Src: 10.255.255.5, Dst: 10.255.255.8
> Transmission Control Protocol, Src Port: 22149, Dst Port: 179, Seq: 96, Ack: 77, Len: 630
> Border Gateway Protocol - UPDATE Message
> Border Gateway Protocol - UPDATE Message
> Border Gateway Protocol - UPDATE Message
> Border Gateway Protocol - UPDATE Message
> Border Gateway Protocol - UPDATE Message
  > Border Gateway Protocol - UPDATE Message
    Marker: ffffffffffffffffffffffffffffffffff
    Length: 67
    Type: UPDATE Message (2)
    Withdrawn Routes Length: 0
    Total Path Attribute Length: 40
  > Path attributes
    > Path Attribute - ORIGIN: IGP
    > Path Attribute - AS_PATH: (65001) 64501
      > Flags: 0x40, Transitive, Well-known, Complete
      Type Code: AS_PATH (2)
      Length: 12
      > AS Path segment: (65001)
        Segment type: AS_CONFED_SEQUENCE (3)
        Segment length (number of ASN): 1
        AS4: 65001
      > AS Path segment: 64501
        Segment type: AS_SEQUENCE (2)
        Segment length (number of ASN): 1
        AS4: 64501
    > Path Attribute - NEXT_HOP: 192.0.2.1
    > Path Attribute - MULTI_EXIT_DISC: 0
    > Path Attribute - LOCAL_PREF: 100
  > Network Layer Reachability Information (NLRI)
    > 198.51.100.0/24
> Border Gateway Protocol - UPDATE Message
```


BGP – Confederation

R4:

```
router bgp 65001
  bgp router-id 10.255.255.4
  bgp log-neighbor-changes
  bgp confederation identifier 64500
  bgp confederation peers 65002
  neighbor 65001 peer-group
  neighbor 65001 remote-as 65001
  neighbor 65001 update-source Loopback0
  neighbor 10.255.255.3 peer-group 65001
  neighbor 10.255.255.5 peer-group 65001
  !
  address-family ipv4
    network 192.0.2.104 mask 255.255.255.255
    neighbor 65001 send-community
    neighbor 65001 next-hop-self
    neighbor 10.255.255.3 activate
    neighbor 10.255.255.5 activate
  exit-address-family
  !
```

R1:

```
R4#show bgp ipv4 unicast summary | b Neighbor
Neighbor          V          AS  MsgRcvd  MsgSent      TblVer   InQ  OutQ  Up/Down
State/PfxRcd
10.255.255.3      4      65001     34      12        0    0  00:25:42      9
10.255.255.5      4      65001     36      12        0    0  00:29:35      1
```

```
R4#show bgp ipv4 unicast | b Network
```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0/31	10.255.255.3	0	100	0	i
*>i	192.0.2.0	10.255.255.3		100	0	i
*>i	192.0.2.2/31	10.255.255.6	0	100	0	(65002) i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>	192.0.2.104/32	0.0.0.0	0		32768	i
*>i	192.0.2.105/32	10.255.255.5	0	100	0	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	(65002) i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	(65002) i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	(65002) i
*>i	198.51.100.0	192.0.2.1	0	100	0	64501 i
*>i	203.0.113.0	192.0.2.3	0	100	0	(65002) 64502 i

BGP – Confederation

R5:

```
router bgp 65001
  bgp router-id 10.255.255.5
  bgp log-neighbor-changes
  bgp confederation identifier 64500
  bgp confederation peers 65002
  neighbor 65001 peer-group
  neighbor 65001 remote-as 65001
  neighbor 65001 update-source Loopback0
  neighbor 10.255.255.3 peer-group 65001
  neighbor 10.255.255.4 peer-group 65001
  neighbor 10.255.255.8 remote-as 65002
  neighbor 10.255.255.8 ebgp-multihop 255
  neighbor 10.255.255.8 update-source Loopback0
  !
  address-family ipv4
    network 192.0.2.105 mask 255.255.255.255
    neighbor 65001 send-community
    neighbor 65001 next-hop-self
    neighbor 10.255.255.3 activate
    neighbor 10.255.255.4 activate
    neighbor 10.255.255.8 activate
    neighbor 10.255.255.8 send-community
  exit-address-family
```

R5:

R5#show bgp ipv4 unicast summary | b Neighbor

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.255.255.3	4	65001	36	34	12	0	0	00:26:54	9
10.255.255.4	4	65001	37	38	12	0	0	00:30:50	1
10.255.255.8	4	65002	29	22	12	0	0	00:08:50	6

R5#show bgp ipv4 unicast | b Network

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0/31	10.255.255.3	0	100	0	i
*	192.0.2.0	10.255.255.6	0	100	0	(65002) i
*>i		10.255.255.3		100	0	i
*	192.0.2.2/31	10.255.255.6	0	100	0	(65002) i
*>i		10.255.255.6	0	100	0	(65002) i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i	192.0.2.104/32	10.255.255.4	0	100	0	i
*>	192.0.2.105/32	0.0.0.0	0		32768	i
*	192.0.2.106/32	10.255.255.6	0	100	0	(65002) i
*>i		10.255.255.6	0	100	0	(65002) i
*	192.0.2.107/32	10.255.255.7	0	100	0	(65002) i
*>i		10.255.255.7	0	100	0	(65002) i
*	192.0.2.108/32	10.255.255.8	0	100	0	(65002) i
*>i		10.255.255.8	0	100	0	(65002) i
*>i	198.51.100.0	192.0.2.1	0	100	0	64501 i
*	203.0.113.0	10.255.255.6	0	100	0	(65002) 64502 i
*>i		192.0.2.3	0	100	0	(65002) 64502 i

BGP – Confederation

R6:

```
bgp 65002
router-id 10.255.255.6
confederation id 64500
confederation peer-as 65001
peer 10.255.255.3 as-number 65001
peer 10.255.255.3 ebgp-max-hop 255
peer 10.255.255.3 connect-interface LoopBack0
peer 192.0.2.3 as-number 64502
peer 192.0.2.3 connect-interface Ethernet1/0/0
group 65002 internal
peer 65002 connect-interface LoopBack0
peer 10.255.255.7 as-number 65002
peer 10.255.255.7 group 65002
peer 10.255.255.8 as-number 65002
peer 10.255.255.8 group 65002
#
ipv4-family unicast
undo synchronization
aggregate 192.0.2.0 255.255.255.0
network 192.0.2.2 255.255.255.254
network 192.0.2.106 255.255.255.255
peer 10.255.255.3 enable
peer 10.255.255.3 advertise-community
peer 192.0.2.3 enable
peer 192.0.2.3 ip-prefix PL_WIDE_NETS export
peer 65002 enable
peer 65002 next-hop-local
peer 65002 advertise-community
peer 10.255.255.7 enable
peer 10.255.255.7 group 65002
peer 10.255.255.8 enable
peer 10.255.255.8 group 65002
```

R6:

<R6>dis bgp peer

Peer	V	AS	MsgRcvd	MsgSent	OutQ	Up/Down	State	PrefRcv
10.255.255.3	4	65001	26	38	0	00:18:47	Established	6
10.255.255.7	4	65002	39	47	0	00:31:32	Established	1
10.255.255.8	4	65002	41	47	0	00:31:28	Established	6
192.0.2.3	4	64502	39	40	0	00:31:39	Established	1

<R6>dis bgp routing-table

	Network	NextHop	MED	LocPrf	PrefVal	Path/Ogn
*>	192.0.2.0/24	127.0.0.1			0	i
* i		10.255.255.3		100	0	(65001) i
*>i	192.0.2.0/31	10.255.255.3	0	100	0	(65001) i
* i		10.255.255.8	0	100	0	(65001) i
*>	192.0.2.2/31	0.0.0.0	0		0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	(65001) i
* i		10.255.255.8	0	100	0	(65001) i
*>i	192.0.2.104/32	10.255.255.8	0	100	0	(65001) i
* i		10.255.255.4	0	100	0	(65001) i
*>i	192.0.2.105/32	10.255.255.8	0	100	0	(65001) i
* i		10.255.255.5	0	100	0	(65001) i
*>	192.0.2.106/32	0.0.0.0	0		0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
*>i	198.51.100.0/24	192.0.2.1	0	100	0	(65001) 64501i
* i		10.255.255.8	0	100	0	(65001) 64501i
*>	203.0.113.0/24	192.0.2.3	0		0	64502i

BGP – Confederation

R7:

```
router bgp 65002
  bgp router-id 10.255.255.7
  bgp log-neighbor-changes
  bgp confederation identifier 64500
  bgp confederation peers 65001
  neighbor 65002 peer-group
  neighbor 65002 remote-as 65002
  neighbor 65002 update-source Loopback0
  neighbor 10.255.255.6 peer-group 65002
  neighbor 10.255.255.8 peer-group 65002
  !
  address-family ipv4
    network 192.0.2.107 mask 255.255.255.255
    neighbor 65002 send-community
    neighbor 65002 next-hop-self
    neighbor 10.255.255.6 activate
    neighbor 10.255.255.8 activate
  exit-address-family
  !
```

R7:

```
R7#show bgp ipv4 unicast summary | b Neighbor
Neighbor          V      AS  MsgRcvd  MsgSent   TblVer   InQ  OutQ  Up/Down
State/PfxRcd
10.255.255.6      4      65002   49       18      0     0  00:33:28      7
10.255.255.8      4      65002   41       18      0     0  00:34:22      6

R7#show bgp ipv4 unicast | b Network
      Network          Next Hop      Metric LocPrf Weight Path
*>i  192.0.2.0/31      10.255.255.8          0   100      0 (65001) i
* i                                10.255.255.3          0   100      0 (65001) i
*>i  192.0.2.0          10.255.255.6          100      0 i
*>i  192.0.2.2/31      10.255.255.6          0   100      0 i
*>i  192.0.2.103/32    10.255.255.8          0   100      0 (65001) i
* i                                10.255.255.3          0   100      0 (65001) i
*>i  192.0.2.104/32    10.255.255.8          0   100      0 (65001) i
*>i  192.0.2.105/32    10.255.255.8          0   100      0 (65001) i
*>i  192.0.2.106/32    10.255.255.6          0   100      0 i
*>  192.0.2.107/32    0.0.0.0              0      32768 i
*>i  192.0.2.108/32    10.255.255.8          0   100      0 i
* i  198.51.100.0      10.255.255.8          0   100      0 (65001) 64501 i
*>i                                192.0.2.1          0   100      0 (65001) 64501 i
*>i  203.0.113.0       10.255.255.6          0   100      0 64502 i
```

BGP – Confederation

R8:

```
router bgp 65002
  bgp router-id 10.255.255.8
  bgp log-neighbor-changes
  bgp confederation identifier 64500
  bgp confederation peers 65001
  neighbor 65002 peer-group
  neighbor 65002 remote-as 65002
  neighbor 65002 update-source Loopback0
  neighbor 10.255.255.5 remote-as 65001
  neighbor 10.255.255.5 ebgp-multihop 255
  neighbor 10.255.255.5 update-source Loopback0
  neighbor 10.255.255.6 peer-group 65002
  neighbor 10.255.255.7 peer-group 65002
  !
address-family ipv4
  network 192.0.2.108 mask 255.255.255.255
  neighbor 65002 send-community
  neighbor 65002 next-hop-self
  neighbor 10.255.255.5 activate
  neighbor 10.255.255.5 send-community
  neighbor 10.255.255.6 activate
  neighbor 10.255.255.7 activate
exit-address-family
```


R8:

```
R8#show bgp ipv4 unicast summary | b Neighbor
Neighbor          V      AS  MsgRcvd  MsgSent   TblVer   InQ  OutQ  Up/Down
State/PfxRcd
10.255.255.5      4      65001    34      17       0     0    00:13:10      6
10.255.255.6      4      65002    44      17       0     0    00:34:14      7
10.255.255.7      4      65002    43      17       0     0    00:35:12      1

R8#show bgp ipv4 unicast | b Network
Network          Next Hop        Metric LocPrf Weight Path
*> 192.0.2.0/31   10.255.255.3      0    100      0 (65001) i
* i              10.255.255.3      0    100      0 (65001) i
* 192.0.2.0      10.255.255.3      0    100      0 (65001) i
*>i              10.255.255.6      100    0 i
*>i 192.0.2.2/31  10.255.255.6      0    100      0 i
*> 192.0.2.103/32 10.255.255.3      0    100      0 (65001) i
* i              10.255.255.3      0    100      0 (65001) i
*> 192.0.2.104/32 10.255.255.4      0    100      0 (65001) i
*> 192.0.2.105/32 10.255.255.5      0    100      0 (65001) i
*>i 192.0.2.106/32 10.255.255.6      0    100      0 i
*>i 192.0.2.107/32 10.255.255.7      0    100      0 i
*> 192.0.2.108/32 0.0.0.0          0          32768 i
*> 198.51.100.0   192.0.2.1        0    100      0 (65001) 64501 i
* i              192.0.2.1        0    100      0 (65001) 64501 i
*>i 203.0.113.0   10.255.255.6     0    100      0 64502 i
```

BGP – IBGP – Route Reflector

Идея рефлектора в следующем: выбирается один (или несколько) BGP-маршрутизаторов, который будет выступать как «сервер» для остальных пиров: получив какой-то анонс от своего «клиента», он распространит его своим остальным «клиентам». Т.о. логическая топология переходит из полносвязной в «Звезду».



К рефлектору могут быть подключены не только клиенты – в этом случае требования к полносвязности остаются.

Как распространяются маршруты можно увидеть на иллюстрации на этом слайде.


BGP – IBGP – Route Reflector

Совокупность из рефлектора(-ов) и клиентов составляет «кластер». Кластер характеризуется параметром “Cluster-ID” (по умолчанию берется из BGP Router-ID). При получении рефлектором маршрута, в него добавляются два дополнительных атрибута, которые служат для предотвращения появления петель маршрутизации:

- **ORIGINATOR_ID** – в него проставляется router-id маршрутизатора, от которого изначально пришел маршрут
- **CLUSTER_LIST** – это список, в который добавляются cluster-id рефлекторов, через который прошел маршрут

Маршруты между IBGP-соседями с одинаковым cluster-id не принимаются.

Маршрутизатор, получая анонс с
 ORIGINATOR_ID равным его Router-ID,
 отбрасывает такой анонс



BGP – Route Reflectors – Clients (Single Cluster-ID)

R3:

```
router bgp 64500
  bgp router-id 10.255.255.3
  bgp log-neighbor-changes
  neighbor RR_C1 peer-group
  neighbor RR_C1 remote-as 64500
  neighbor RR_C1 update-source Loopback0
  neighbor 10.255.255.4 peer-group RR_C1
  neighbor 10.255.255.5 peer-group RR_C1
  neighbor 192.0.2.1 remote-as 64501
  neighbor 192.0.2.1 update-source
Ethernet0/0
!
  address-family ipv4
    network 192.0.2.103 mask
255.255.255.255
    aggregate-address 192.0.2.0
255.255.255.0
  neighbor RR_C1 next-hop-self
  neighbor 10.255.255.4 activate
  neighbor 10.255.255.5 activate
  neighbor 192.0.2.1 activate
  neighbor 192.0.2.1 prefix-list
PL_WIDE_NETS out
  exit-address-family
```

R3#show bgp ipv4 unicast | b Network

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0				32768 i
*>	192.0.2.103/32	0.0.0.0	0			32768 i
*>i	192.0.2.104/32	10.255.255.4	0	100		0 i
* i		10.255.255.4	0	100		0 i
* i	192.0.2.105/32	10.255.255.5	0	100		0 i
*>i		10.255.255.5	0	100		0 i
* i	192.0.2.106/32	10.255.255.6	0	100		0 i
*>i		10.255.255.6	0	100		0 i
* i	192.0.2.107/32	10.255.255.7	0	100		0 i
*>i		10.255.255.7	0	100		0 i
*>i	192.0.2.108/32	10.255.255.8	0	100		0 i
*>i	192.0.2.109/32	10.255.255.9	0	100		0 i
* i	192.0.2.110/32	10.255.255.10	0	100		0 i
*>i		10.255.255.10	0	100		0 i
*>	198.51.100.0	192.0.2.1	0			0 64501 i
* i	203.0.113.0	10.255.255.7	0	100		0 64502 i
*>i		10.255.255.7	0	100		0 64502 i

R3#show bgp ipv4 unicast neighbors 10.255.255.4 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0				32768 i
*>	192.0.2.103/32	0.0.0.0	0			32768 i
*>	198.51.100.0	192.0.2.1	0			0 64501 i

R3#show bgp ipv4 unicast neighbors 10.255.255.5 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0				32768 i
*>	192.0.2.103/32	0.0.0.0	0			32768 i
*>	198.51.100.0	192.0.2.1	0			0 64501 i

R3#show bgp ipv4 unicast summary | b Neigh

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.255.255.4	4	64500	28	26	15	0	0	00:19:20	7
10.255.255.5	4	64500	18	15	15	0	0	00:06:17	7
192.0.2.1	4	64501	26	26	15	0	0	00:19:34	1

BGP – Route Reflectors – Clients (Dual Cluster-ID)

R7:

```
router bgp 64500
  bgp router-id 10.255.255.7
  bgp log-neighbor-changes
  neighbor RR_C2 peer-group
  neighbor RR_C2 remote-as 64500
  neighbor RR_C2 update-source Loopback0
  neighbor 10.255.255.8 peer-group RR_C2
  neighbor 10.255.255.9 peer-group RR_C2
  neighbor 192.0.2.3 remote-as 64502
  neighbor 192.0.2.3 update-source
Ethernet0/0
!
  address-family ipv4
    network 192.0.2.107 mask
255.255.255.255
    aggregate-address 192.0.2.0
255.255.255.0
    neighbor RR_C2 next-hop-self
    neighbor 10.255.255.8 activate
    neighbor 10.255.255.9 activate
    neighbor 192.0.2.3 activate
    neighbor 192.0.2.3 prefix-list
PL_WIDE_NETS out
  exit-address-family
```

R7#show bgp ipv4 unicast

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0				32768 i
* i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i		10.255.255.3	0	100	0	i
*>i	192.0.2.104/32	10.255.255.4	0	100	0	i
*>i	192.0.2.105/32	10.255.255.5	0	100	0	i
* i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i		10.255.255.6	0	100	0	i
*>	192.0.2.107/32	0.0.0.0	0			32768 i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
* i		10.255.255.8	0	100	0	i
* i	192.0.2.109/32	10.255.255.9	0	100	0	i
*>i		10.255.255.9	0	100	0	i
* i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i		10.255.255.10	0	100	0	i
* i	198.51.100.0	10.255.255.3	0	100	0	64501 i
*>i		10.255.255.3	0	100	0	64501 i
*>	203.0.113.0	192.0.2.3	0			0 64502 i

R7#show bgp ipv4 unicast neighbors 10.255.255.8 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	192.0.2.0	0.0.0.0				32768 i
*>	192.0.2.107/32	0.0.0.0	0			32768 i
*>	203.0.113.0	192.0.2.3	0			0 64502 i

R7#show bgp ipv4 unicast neighbors 10.255.255.8 routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i	192.0.2.104/32	10.255.255.4	0	100	0	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
* i	192.0.2.109/32	10.255.255.9	0	100	0	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i

R7#show bgp ipv4 unicast summary

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.255.255.8	4	64500	43	30	17	0	0	00:22:37	7
10.255.255.9	4	64500	25	19	17	0	0	00:10:27	7
192.0.2.3	4	64502	30	30	17	0	0	00:23:01	1

BGP – Route Reflectors – RR IOS-XR (Single Cluster-ID)

```
router bgp 64500
  bgp router-id 10.255.255.4
  bgp cluster-id 10.255.255.45
  address-family ipv4 unicast
    network 192.0.2.104/32
  !
  neighbor-group RRC_C1
    remote-as 64500
    update-source Loopback0
    address-family ipv4 unicast
      route-policy RP_PERMIT_ANY in
      route-reflector-client
      route-policy RP_PERMIT_ANY out
  !
  neighbor 10.255.255.3
    use neighbor-group RRC_C1
  !
  neighbor 10.255.255.5
    remote-as 64500
    update-source Loopback0
    address-family ipv4 unicast
      route-policy RP_PERMIT_ANY in
      route-policy RP_PERMIT_ANY out
  !
  neighbor 10.255.255.6
    use neighbor-group RRC_C1
  !
  neighbor 10.255.255.8
    remote-as 64500
    update-source Loopback0
    address-family ipv4 unicast
      route-policy RP_PERMIT_ANY in
      route-policy RP_PERMIT_ANY out
```

RP/0/0/CPU0:R4#show bgp ipv4 unicast summary

Neighbor	Spk	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	St/PfxRcd
10.255.255.3	0	64500	37	37	19	0	0	00:20:58	3
10.255.255.5	0	64500	16	16	19	0	0	00:07:52	1
10.255.255.6	0	64500	19	27	19	0	0	00:14:14	1
10.255.255.8	0	64500	41	37	19	0	0	00:26:41	5

RP/0/0/CPU0:R4#show bgp ipv4 unicast

Network	Next Hop	Metric	LocPrf	Weight	Path
*>i192.0.2.0/24	10.255.255.3	0	100	0	i
* i	10.255.255.7	0	100	0	i
*>i192.0.2.103/32	10.255.255.3	0	100	0	i
*> 192.0.2.104/32	0.0.0.0	0		32768	i
*>i192.0.2.105/32	10.255.255.5	0	100	0	i
*>i192.0.2.106/32	10.255.255.6	0	100	0	i
*>i192.0.2.107/32	10.255.255.7	0	100	0	i
*>i192.0.2.108/32	10.255.255.8	0	100	0	i
*>i192.0.2.110/32	10.255.255.10	0	100	0	i
*>i198.51.100.0/24	10.255.255.3	0	100	0	64501 i
*>i203.0.113.0/24	10.255.255.7	0	100	0	64502 i

RP/0/0/CPU0:R4#show bgp ipv4 unicast neighbors 10.255.255.3 advertised-routes

Network	Next Hop	From	AS Path
192.0.2.0/24	10.255.255.4	10.255.255.3	i
192.0.2.103/32	10.255.255.4	10.255.255.3	i
192.0.2.104/32	10.255.255.4	Local	i
192.0.2.105/32	10.255.255.5	10.255.255.5	i
192.0.2.106/32	10.255.255.6	10.255.255.6	i
192.0.2.107/32	10.255.255.7	10.255.255.8	i
192.0.2.108/32	10.255.255.8	10.255.255.8	i
192.0.2.110/32	10.255.255.10	10.255.255.8	i
198.51.100.0/24	10.255.255.4	10.255.255.3	64501i
203.0.113.0/24	10.255.255.7	10.255.255.8	64502i

RP/0/0/CPU0:R4#show bgp ipv4 unicast neighbors 10.255.255.5 advertised-

Network	Next Hop	From	AS Path
192.0.2.0/24	10.255.255.3	10.255.255.3	i
192.0.2.103/32	10.255.255.3	10.255.255.3	i
192.0.2.104/32	10.255.255.4	Local	i
192.0.2.106/32	10.255.255.6	10.255.255.6	i
198.51.100.0/24	10.255.255.3	10.255.255.3	64501i

RP/0/0/CPU0:R4#show bgp ipv4 unicast neighbors 10.255.255.5 routes

Network	Next Hop	Metric	LocPrf	Weight	Path
*>i192.0.2.105/32	10.255.255.5	0	100	0	i

RP/0/0/CPU0:R4#show bgp ipv4 unicast neighbors 10.255.255.8 advertised-routes

Network	Next Hop	From	AS Path
192.0.2.0/24	10.255.255.3	10.255.255.3	i
192.0.2.103/32	10.255.255.3	10.255.255.3	i
192.0.2.104/32	10.255.255.4	Local	i
192.0.2.106/32	10.255.255.6	10.255.255.6	i
198.51.100.0/24	10.255.255.3	10.255.255.3	64501i

RP/0/0/CPU0:R4#show bgp ipv4 unicast neighbors 10.255.255.8 routes

Network	Next Hop	Metric	LocPrf	Weight	Path
* i192.0.2.0/24	10.255.255.7	0	100	0	i
*>i192.0.2.107/32	10.255.255.7	0	100	0	i
*>i192.0.2.108/32	10.255.255.8	0	100	0	i
*>i192.0.2.110/32	10.255.255.10	0	100	0	i
*>i203.0.113.0/24	10.255.255.7	0	100	0	64502 i

BGP – Route Reflectors – RR IOS/IOS-XE (Single Cluster-ID)

R5:

```
router bgp 64500
  bgp router-id 10.255.255.5
  bgp cluster-id 10.255.255.45
  bgp log-neighbor-changes
  neighbor RRC_C1 peer-group
  neighbor RRC_C1 remote-as 64500
  neighbor RRC_C1 update-source Loopback0
  neighbor 10.255.255.3 peer-group RRC_C1
  neighbor 10.255.255.4 remote-as 64500
  neighbor 10.255.255.4 update-source
Loopback0
  neighbor 10.255.255.6 peer-group RRC_C1
  neighbor 10.255.255.9 remote-as 64500
  neighbor 10.255.255.9 update-source
Loopback0
!
address-family ipv4
  network 192.0.2.105 mask
255.255.255.255
  neighbor RRC_C1 route-reflector-client
  neighbor 10.255.255.3 activate
  neighbor 10.255.255.4 activate
  neighbor 10.255.255.6 activate
  neighbor 10.255.255.9 activate
exit-address-family
```

R5#show bgp ipv4 unicast

	Network	Next Hop	Metric	LocPrf	Weight	Path
* i	192.0.2.0	10.255.255.7	0	100	0	i
*>i		10.255.255.3	0	100	0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i	192.0.2.104/32	10.255.255.4	0	100	0	i
*>	192.0.2.105/32	0.0.0.0	0		32768	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	192.0.2.109/32	10.255.255.9	0	100	0	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i

R5#show bgp ipv4 unicast neighbors 10.255.255.4 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0	10.255.255.3	0	100	0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>	192.0.2.105/32	0.0.0.0	0		32768	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i

R5#show bgp ipv4 unicast neighbors 10.255.255.4 routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.104/32	10.255.255.4	0	100	0	i

R5#show bgp ipv4 unicast summary

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.255.255.3	4	64500	19	22	11	0	0	00:10:03	3
10.255.255.4	4	64500	18	18	11	0	0	00:10:00	1
10.255.255.6	4	64500	16	22	11	0	0	00:10:03	1
10.255.255.9	4	64500	18	18	11	0	0	00:09:03	5

R5#show bgp ipv4 unicast neighbors 10.255.255.9 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0	10.255.255.3	0	100	0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>	192.0.2.105/32	0.0.0.0	0		32768	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i

R5#show bgp ipv4 unicast neighbors 10.255.255.9 routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
* i	192.0.2.0	10.255.255.7	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	192.0.2.109/32	10.255.255.9	0	100	0	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i

BGP – Route Reflectors – RR IOS/IOS-XE (Dual Cluster-ID)

R9:

```
router bgp 64500
  bgp router-id 10.255.255.9
  bgp cluster-id 10.255.255.9
  bgp log-neighbor-changes
  neighbor RRC_C2 peer-group
  neighbor RRC_C2 remote-as 64500
  neighbor RRC_C2 update-source Loopback0
  neighbor 10.255.255.5 remote-as 64500
  neighbor 10.255.255.5 update-source
Loopback0
  neighbor 10.255.255.7 peer-group RRC_C2
  neighbor 10.255.255.8 remote-as 64500
  neighbor 10.255.255.8 update-source
Loopback0
  neighbor 10.255.255.10 peer-group
RRC_C2
!
address-family ipv4
  network 192.0.2.109 mask
255.255.255.255
  neighbor RRC_C2 route-reflector-client
  neighbor 10.255.255.5 activate
  neighbor 10.255.255.7 activate
  neighbor 10.255.255.8 activate
  neighbor 10.255.255.10 activate
exit-address-family
```

R9#show bgp ipv4 unicast

	Network	Next Hop	Metric	LocPrf	Weight	Path
* i	192.0.2.0	10.255.255.3	0	100	0	i
*>i		10.255.255.7	0	100	0	i
* i		10.255.255.7	0	100	0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i	192.0.2.105/32	10.255.255.5	0	100	0	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
* i		10.255.255.7	0	100	0	i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
*>	192.0.2.109/32	0.0.0.0	0		32768	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
* i		10.255.255.10	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i
* i		10.255.255.7	0	100	0	64502 i

R9#show bgp ipv4 unicast neighbors 10.255.255.8 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0	10.255.255.7	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>	192.0.2.109/32	0.0.0.0	0		32768	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i

R9#show bgp ipv4 unicast summary

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.255.255.5	4	64500	24	23	13	0	0	00:13:54	5
10.255.255.7	4	64500	23	28	13	0	0	00:13:51	3
10.255.255.8	4	64500	26	23	13	0	0	00:13:58	5
10.255.255.10	4	64500	21	28	13	0	0	00:13:51	1

R9#show bgp ipv4 unicast neighbors 10.255.255.8 routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
* i	192.0.2.0	10.255.255.7	0	100	0	i
* i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
* i	192.0.2.110/32	10.255.255.10	0	100	0	i
* i	203.0.113.0	10.255.255.7	0	100	0	64502 i

R9#show bgp ipv4 unicast neighbors 10.255.255.7 advertised-routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0	10.255.255.7	0	100	0	i
*>i	192.0.2.103/32	10.255.255.3	0	100	0	i
*>i	192.0.2.105/32	10.255.255.5	0	100	0	i
*>i	192.0.2.106/32	10.255.255.6	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	192.0.2.108/32	10.255.255.8	0	100	0	i
*>	192.0.2.109/32	0.0.0.0	0		32768	i
*>i	192.0.2.110/32	10.255.255.10	0	100	0	i
*>i	198.51.100.0	10.255.255.3	0	100	0	64501 i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i

R9#show bgp ipv4 unicast neighbors 10.255.255.7 routes

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>i	192.0.2.0	10.255.255.7	0	100	0	i
*>i	192.0.2.107/32	10.255.255.7	0	100	0	i
*>i	203.0.113.0	10.255.255.7	0	100	0	64502 i

BGP – Route Reflectors – RR Huawei VRP (Dual Cluster-ID)

```
R8:
bgp 64500
 router-id 10.255.255.8
 peer 10.255.255.4 as-number 64500
 peer 10.255.255.4 connect-interface LoopBack0
 peer 10.255.255.9 as-number 64500
 peer 10.255.255.9 connect-interface LoopBack0
 group RRC_C2 internal
 peer RRC_C2 connect-interface LoopBack0
 peer 10.255.255.7 as-number 64500
 peer 10.255.255.7 group RRC_C2
 peer 10.255.255.10 as-number 64500
 peer 10.255.255.10 group RRC_C2
#
ipv4-family unicast
 undo synchronization
 reflector cluster-id 10.255.255.8
 network 192.0.2.108 255.255.255.255
 peer 10.255.255.4 enable
 peer 10.255.255.9 enable
 peer RRC_C2 enable
 peer RRC_C2 reflect-client
 peer 10.255.255.7 enable
 peer 10.255.255.7 group RRC_C2
 peer 10.255.255.10 enable
 peer 10.255.255.10 group RRC_C2
#
```

```
[R8]dis bgp routing-table
      Network      NextHop      MED      LocPrf      PrefVal Path/Ogn
*>i  192.0.2.0/24    10.255.255.7      0        100         0        i
* i   10.255.255.7    10.255.255.7      0        100         0        i
* i   10.255.255.3    10.255.255.3      0        100         0        i
*>i  192.0.2.103/32  10.255.255.3      0        100         0        i
*>i  192.0.2.104/32  10.255.255.4      0        100         0        i
*>i  192.0.2.106/32  10.255.255.6      0        100         0        i
*>i  192.0.2.107/32  10.255.255.7      0        100         0        i
* i   10.255.255.7    10.255.255.7      0        100         0        i
*>   192.0.2.108/32  0.0.0.0           0         100         0        i
*>i  192.0.2.109/32  10.255.255.9      0        100         0        i
*>i  192.0.2.110/32  10.255.255.10     0        100         0        i
* i   10.255.255.10   10.255.255.10     0        100         0        i
*>i  198.51.100.0/24 10.255.255.3      0        100         0        64501i
*>i  203.0.113.0/24  10.255.255.7      0        100         0        64502i
* i   10.255.255.7    10.255.255.7      0        100         0        64502i
```

```
[R8]dis bgp routing-table peer 10.255.255.9 received-routes
      Network      NextHop      MED      LocPrf      PrefVal Path/Ogn
* i   192.0.2.0/24    10.255.255.7      0        100         0        i
* i   192.0.2.107/32  10.255.255.7      0        100         0        i
*>i  192.0.2.109/32  10.255.255.9      0        100         0        i
* i   192.0.2.110/32  10.255.255.10     0        100         0        i
* i   203.0.113.0/24  10.255.255.7      0        100         0        64502i
```

```
[R8]dis bgp routing-table peer 10.255.255.7 advertised-routes
      Network      NextHop      MED      LocPrf      PrefVal Path/Ogn
*>i  192.0.2.0/24    10.255.255.7      0        100         0        i
*>i  192.0.2.103/32  10.255.255.3      0        100         0        i
*>i  192.0.2.104/32  10.255.255.4      0        100         0        i
*>i  192.0.2.106/32  10.255.255.6      0        100         0        i
*>i  192.0.2.107/32  10.255.255.7      0        100         0        i
*>   192.0.2.108/32  0.0.0.0           0        100         0        i
*>i  192.0.2.109/32  10.255.255.9      0        100         0        i
*>i  192.0.2.110/32  10.255.255.10     0        100         0        i
*>i  198.51.100.0/24 10.255.255.3      0        100         0        64501i
*>i  203.0.113.0/24  10.255.255.7      0        100         0        64502i
```

```
[R8]dis bgp routing-table peer 10.255.255.9 advertised-routes
      Network      NextHop      MED      LocPrf      PrefVal Path/Ogn
*>i  192.0.2.0/24    10.255.255.7      0        100         0        i
*>i  192.0.2.107/32  10.255.255.7      0        100         0        i
*>   192.0.2.108/32  0.0.0.0           0        100         0        i
*>i  192.0.2.110/32  10.255.255.10     0        100         0        i
*>i  203.0.113.0/24  10.255.255.7      0        100         0        64502i
```

```
[R8]dis bgp routing-table peer 10.255.255.7 received-routes
      Network      NextHop      MED      LocPrf      PrefVal Path/Ogn
*>i  192.0.2.0/24    10.255.255.7      0        100         0        i
*>i  192.0.2.107/32  10.255.255.7      0        100         0        i
*>i  203.0.113.0/24  10.255.255.7      0        100         0        64502i
```

```
[R8]dis bgp peer
      Peer      V      AS      MsgRcvd      MsgSent      OutQ      Up/Down      State      PrefRcv
10.255.255.4    4      64500    41           46           0 00:31:16 Established 5
10.255.255.7    4      64500    31           44           0 00:23:36 Established 3
10.255.255.9    4      64500    20           23           0 00:11:33 Established 5
10.255.255.10   4      64500    24           37           0 00:19:19 Established 1
```

BGP – Route Reflectors

```
R3#show bgp ipv4 unicast 198.51.100.0
BGP routing table entry for 198.51.100.0/24, version 3
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    2
  Refresh Epoch 1
  64501
    192.0.2.1 from 192.0.2.1 (198.51.100.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      rx pathid: 0, tx pathid: 0x0
R3#show bgp ipv4 unicast 203.0.113.0
BGP routing table entry for 203.0.113.0/24, version 16
Paths: (2 available, best #1, table default)
  Advertised to update-groups:
    1
  Refresh Epoch 1
  64502
    10.255.255.7 (metric 2) from 10.255.255.4 (10.255.255.4)
      Origin IGP, metric 0, localpref 100, valid, internal, best
      Originator: 10.255.255.7, Cluster list: 10.255.255.45, 10.255.255.8
      rx pathid: 0, tx pathid: 0x0
  Refresh Epoch 1
  64502
    10.255.255.7 (metric 2) from 10.255.255.5 (10.255.255.5)
      Origin IGP, metric 0, localpref 100, valid, internal
      Originator: 10.255.255.7, Cluster list: 10.255.255.45, 10.255.255.9
      rx pathid: 0, tx pathid: 0
```

```
RP/0/0/CPU0:R4#show bgp ipv4 unicast 198.51.100.0
Sat Apr 30 10:50:08.157 UTC
BGP routing table entry for 198.51.100.0/24
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          17        17
Last Modified: Apr 30 10:48:28.569 for 00:01:39
Paths: (1 available, best #1)
  Advertised IPv4 Unicast paths to update-groups (with more than one peer):
    0.2 0.3
  Path #1: Received by speaker 0
  Advertised IPv4 Unicast paths to update-groups (with more than one peer):
    0.2 0.3
  64501, (Received from a RR-client)
    10.255.255.3 (metric 2) from 10.255.255.3 (10.255.255.3)
      Origin IGP, metric 0, localpref 100, valid, internal, best, group-best
      Received Path ID 0, Local Path ID 1, version 17
RP/0/0/CPU0:R4#show bgp ipv4 unicast 203.0.113.0
Sat Apr 30 10:50:33.786 UTC
BGP routing table entry for 203.0.113.0/24
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          18        18
Last Modified: Apr 30 10:48:28.569 for 00:02:05
Paths: (1 available, best #1)
  Advertised IPv4 Unicast paths to update-groups (with more than one peer):
    0.2
  Path #1: Received by speaker 0
  Advertised IPv4 Unicast paths to update-groups (with more than one peer):
    0.2
  64502
    10.255.255.7 (metric 3) from 10.255.255.8 (10.255.255.7)
      Origin IGP, metric 0, localpref 100, valid, internal, best, group-best
      Received Path ID 0, Local Path ID 1, version 18
      Originator: 10.255.255.7, Cluster list: 10.255.255.8
```

BGP – Route Reflectors

```
R5#show bgp ipv4 unicast 198.51.100.0
BGP routing table entry for 198.51.100.0/24, version 7
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    1          2
  Refresh Epoch 1
  64501, (Received from a RR-client)
    10.255.255.3 (metric 2) from 10.255.255.3 (10.255.255.3)
      Origin IGP, metric 0, localpref 100, valid, internal, best
      rx pathid: 0, tx pathid: 0x0
R5#show bgp ipv4 unicast 203.0.113.0
BGP routing table entry for 203.0.113.0/24, version 8
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    1
  Refresh Epoch 1
  64502
    10.255.255.7 (metric 3) from 10.255.255.9 (10.255.255.9)
      Origin IGP, metric 0, localpref 100, valid, internal, best
      Originator: 10.255.255.7, Cluster list: 10.255.255.9
      rx pathid: 0, tx pathid: 0x0
```

```
R9#show bgp ipv4 unicast 198.51.100.0
BGP routing table entry for 198.51.100.0/24, version 9
Paths: (1 available, best #1, table default)
Flag: 0x100
  Advertised to update-groups:
    1
  Refresh Epoch 1
  64501
    10.255.255.3 (metric 3) from 10.255.255.5 (10.255.255.5)
      Origin IGP, metric 0, localpref 100, valid, internal, best
      Originator: 10.255.255.3, Cluster list: 10.255.255.45
      rx pathid: 0, tx pathid: 0x0
R9#show bgp ipv4 unicast 203.0.113.0
BGP routing table entry for 203.0.113.0/24, version 6
Paths: (2 available, best #2, table default)
  Advertised to update-groups:
    1          2
  Refresh Epoch 1
  64502
    10.255.255.7 (metric 2) from 10.255.255.8 (10.255.255.8)
      Origin IGP, metric 0, localpref 100, valid, internal
      Originator: 10.255.255.7, Cluster list: 10.255.255.8
      rx pathid: 0, tx pathid: 0
  Refresh Epoch 1
  64502, (Received from a RR-client)
    10.255.255.7 (metric 2) from 10.255.255.7 (10.255.255.7)
      Origin IGP, metric 0, localpref 100, valid, internal, best
      rx pathid: 0, tx pathid: 0x0
```

BGP – Route Reflectors

```
<R8>display bgp routing-table 198.51.100.0
```

```
BGP local router ID : 10.255.255.8
Local AS number : 64500
Paths: 1 available, 1 best, 1 select, 0 best-external, 0 add-path
BGP routing table entry information of 198.51.100.0/24:
From: 10.255.255.4 (10.255.255.4)
Route Duration: 0d00h04m12s
Relay IP Nexthop: 10.4.8.4
Relay IP Out-Interface: Ethernet1/0/3
Original nexthop: 10.255.255.3
Qos information : 0x0
AS-path 64501, origin igp, MED 0, localpref 100, pref-val 0, valid, internal, best,
select, pre 255, IGP cost 3
Originator: 10.255.255.3
Cluster list: 10.255.255.45
Advertised to such 2 peers:
10.255.255.7
10.255.255.10
```


```
<R8>display bgp routing-table 203.0.113.0
```

```
BGP local router ID : 10.255.255.8
Local AS number : 64500
Paths: 2 available, 1 best, 1 select, 0 best-external, 0 add-path
BGP routing table entry information of 203.0.113.0/24:
RR-client route.
From: 10.255.255.7 (10.255.255.7)
Route Duration: 0d00h07m22s
Relay IP Nexthop: 10.7.8.7
Relay IP Out-Interface: Ethernet1/0/0
Original nexthop: 10.255.255.7
Qos information : 0x0
AS-path 64502, origin igp, MED 0, localpref 100, pref-val 0, valid, internal, best, select,
pre 255, IGP cost 2
Advertised to such 4 peers:
10.255.255.7
10.255.255.10
10.255.255.9
10.255.255.4
```

```
BGP routing table entry information of 203.0.113.0/24:
From: 10.255.255.9 (10.255.255.9)
Route Duration: 0d00h07m17s
Relay IP Nexthop: 10.7.8.7
Relay IP Out-Interface: Ethernet1/0/0
Original nexthop: 10.255.255.7
Qos information : 0x0
AS-path 64502, origin igp, MED 0, localpref 100, pref-val 0, valid, internal, pre 255, IGP
cost 2, not preferred for Cluster List
Originator: 10.255.255.7
Cluster list: 10.255.255.9
Not advertised to any peer yet
```


BGP – IBGP – Route Reflector

При наличии большой и распределенной сети можно организовывать иерархические включения рефлекторов. На иллюстрации справа видно, что каждый RR из кластеров 2 и 3 является также клиентом рефлекторов из кластера 1. На одном же уровне иерархии между рефлекторами в кластере поднимается обычное IBGP-соседство.



BGP – Diagnostic commands

Description	IOS/IOS-XE	IOS-XR	Huawei VRP
Посмотреть краткую информацию о соседях	show bgp ipv4 unicast summary	show bgp ipv4 unicast summary	display bgp peer
Посмотреть BGP RIB	show bgp ipv4 unicast	show bgp ipv4 unicast	display bgp routing-table
Посмотреть полную информацию по маршруту в BGP RIB	show bgp ipv4 unicast {{ \$IP_ADDRESS }}	show bgp ipv4 unicast {{ \$IP_ADDRESS }}	display bgp routing-table {{ \$IP_ADDRESS }}
Найти в BGP RIB все маршруты, отвечающие регулярному выражению	show bgp ipv4 unicast regexp {{ \$REGEXP }}	show bgp ipv4 unicast regexp {{ \$REGEXP }}	display bgp routing-table regular-expression {{ \$REGEXP }}
Найти в BGP RIB все маршруты, имеющие в себе указанное коммьюнити	show bgp ipv4 unicast community {{ \$COMMUNITY }}	show bgp ipv4 unicast community {{ \$COMMUNITY }}	display bgp routing-table community {{ \$COMMUNITY }}
Посмотреть получаемые от соседа маршруты	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }} routes	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }} routes	display bgp routing-table peer {{ \$NEIGHBOR_IP }} received-routes
Посмотреть передаваемые соседу маршруты	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }} advertised-routes	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }} advertised-routes	display bgp routing-table peer {{ \$NEIGHBOR_IP }} advertised-routes
Посмотрите подробную информацию о соседе	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }}	show bgp ipv4 unicast neighbor {{ \$NEIGHBOR_IP }}	display bgp peer {{ \$NEIGHBOR_IP }} verbose
Посмотреть логи по соседу (Huawei only)	-	-	display bgp peer {{ \$NEIGHBOR_IP }} log-info
Посмотреть маршруты, попадающие под политику (XR Only)	-	show bgp ipv4 unicast route-policy {{ \$RP_NAME }}	-
Посмотреть политику	show route-map {{ \$RM_NAME }}	show rpl route-policy {{ \$RP_NAME }}	display route-policy {{ \$RP_NAME }}
Посмотреть префикс-лист	show ip prefix-list {{ \$PL_NAME }}	show rpl prefix-set {{ \$PS_NAME }}	display ip ip-prefix {{ \$PL_NAME }}
Посмотреть коммьюнити-лист	show ip community-list {{ \$COMM_LIST_NAME }}	show rpl community-set {{ \$COMM_SET }}	display ip community-filter {{ \$CF_NAME }}
Посмотреть AS-Path лист	show ip as-path-access-list {{ \$ASPATH_ACL_NUM }}	show rpl as-path-set {{ \$ASPATH_SET }}	display ip as-path-filter {{ \$ASF_NAME }}

BGP – Diagnostic commands

Description	IOS-XE	IOS-XR	Huawei VRP
Посмотреть краткую информацию о соседях	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} summary	show bgp vrf {{ \$VRF_NAME }} summary	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} peer
Посмотреть BGP RIB	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }}	show bgp vrf {{ \$VRF_NAME }}	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table
Посмотреть полную информацию по маршруту в BGP RIB	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} {{ \$IP_ADDRESS }}	show bgp vrf {{ \$VRF_NAME }} {{ \$IP_ADDRESS }}	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table {{ \$IP_ADDRESS }}
Найти в BGP RIB все маршруты, отвечающие регулярному выражению	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} regexp {{ \$REGEXP }}	show bgp vrf {{ \$VRF_NAME }} regexp {{ \$REGEXP }}	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table regular-expression {{ \$REGEXP }}
Найти в BGP RIB все маршруты, имеющие в себе указанное коммьюнити	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} community {{ \$COMMUNITY }}	show bgp vrf {{ \$VRF_NAME }} community {{ \$COMMUNITY }}	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table community {{ \$COMMUNITY }}
Посмотреть получаемые от соседа маршруты	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }} routes	show bgp vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }} routes	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table peer {{ \$NEIGHBOR_IP }} received-routes
Посмотреть передаваемые соседу маршруты	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }} advertised-routes	show bgp vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }} advertised-routes	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} routing-table peer {{ \$NEIGHBOR_IP }} advertised-routes
Посмотреть подробную информацию о соседе	show bgp vpnv4 unicast vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }}	show bgp vrf {{ \$VRF_NAME }} neighbor {{ \$NEIGHBOR_IP }}	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} peer {{ \$NEIGHBOR_IP }} verbose
Посмотреть логи по соседу (Huawei only)	-	-	display bgp vpnv4 vpn-instance {{ \$VRF_NAME }} peer {{ \$NEIGHBOR_IP }} log-info
Посмотреть маршруты, попадающие под политику (XR Only)	-	show bgp vrf {{ \$VRF_NAME }} route-policy {{ \$SRP_NAME }}	-

ИСТОЧНИКИ

- RFC 4456 - <https://datatracker.ietf.org/doc/html/rfc4456>
- RFC 5065 - <https://datatracker.ietf.org/doc/html/rfc5065>