XDE130
DOUBLE-AXLE RIGID MINING TRUCK

Crossing the equator and plateaus,
Traversing through forests and seas of minerals,
Challenging the most extreme environments,
Performing the most straightforward transportation tasks,
XCMG is undoubtedly the “powerful force in transportation”

ADDRESS:
No. 169, Heping Street, Xuzhou City, Jiangsu Province

WEBSITE:
WWW.XCMG.COM

NATIONAL UNIFIED SERVICE HOT LINE:
400-110-9999

POSTAL CODE:
221000

TikTok QR code

WeChat QR code

Video Account QR code

The final interpretation rights of this manual belong to Xuzhou XCMG Mining Machinery Co., Ltd.

XDE130
DOUBLE-AXLE RIGID MINING TRUCK

120000
RATED PAYLOAD
kg

895/1200
ENGINE RATED POWER
kW/HP

73
BODY CAPACITY SAE 2:1
m^3



01 EFFICIENT TRANSPORTATION

High-Performance Engine

Equipped with original imported high-performance diesel engines, with options including Cummins and MTU powertrains.
Among them, the Cummins KTA38 engine meets U.S. EPA Tier 0 emissions standards, while the MTU engine meets China Non-Road Stage III and U.S. EPA Tier 4i emissions standards.

- Reliable performance and powerful output;
- Capable of generating clean, quiet, and efficient power;
- The engine features reliable performance, advanced technology, convenient fault diagnosis, and easy maintenance.





AC Drive System

- The AC drive system is designed, developed, and integrated by XCMG. It combines a generator, converter cabinet, traction motor, and braking resistor into an intelligent control system. It features high power density, compact size, high efficiency, low loss, and long service life;
- Compared to mechanical drive systems, the electric drive system has a simpler structure, requires less hydraulic maintenance, reduces maintenance time, and has lower maintenance costs.
- The main generator uses a three-phase brushless excitation AC generator, offering a long service life and minimal maintenance.
- The traction motor is a three-phase squirrel-cage AC variable frequency induction motor, with mature technology, reliability, durability, and a long lifespan. The system includes features for monitoring the status and temperature of the inverter, generator, and traction motor, with overheating protection, ensuring longer lifespan and lower costs.

Electric Retarder Control System

The XDE130 braking system provides a maximum braking power of 1400 kW and a continuous braking power of 1100 kW. This ensures the ability to handle full-load emergency braking and continuous braking on downhill slopes, thereby enhancing vehicle safety and operational efficiency.


Weighing System

The onboard weighing system is used for detecting vehicle load data and data analysis, aiming to optimize payloads, maximize productivity, and reduce the machine's lifecycle costs.
It tracks and records the following key production parameters:

- Total transport number
- Total transport weight
- Payload percentage distribution statistics
- Idle and full-load time and mileage



02 RELIABLE AND DURABLE



120-Ton Class Frame Design

The XDE130 frame utilizes advanced computer-aided design (CAD), finite element analysis (FEA), and comprehensive dynamic testing to ensure high structural strength and reliability for heavy load-bearing. The frame features a box-section design and is manufactured from high-strength, high-quality alloy steel plates. It exhibits excellent fatigue strength, low-temperature impact toughness, and weldability. Premium cast steel components are used in critical high-stress areas.



Simple And Reliable Hydraulic System

The hydraulic system design is simple and reliable, controlling steering, braking, and lifting functions with fewer components. A modular design integrates the hydraulic pump and lifting valve assembly onto a single bracket for quick maintenance and replace-ment. The multi-stage hydraulic oil filter design offers high filtration accuracy, large dirt-holding capacity, and extended maintenance intervals.



Two-stage NGW Planetary Gearbox

The XDE130 electric wheel gearbox features a two-stage NGW planetary gear system with power split. The high-speed stage inputs power into the sun gear, which then transfers power through the high-speed planet carrier to the low-speed stage sun gear. The torque is ultimately output through the dual-ring gear. The NGW gearbox features a compact structure, small size, high transmission ratio, large output torque, smooth operation, low noise, high efficiency, reliable performance, and long service life. The design lifespan of the gears is ≥60,000 hours.



UNLIMITED INNOVATION

03 COMFORT AND SAFETY

Ergonomically Designed Cab

The design of the cab offers a comfortable and safe working environment to meet the demands of modern mining. The cab features ROFS and FOPS structural design, complying with ISO 3471 and 3449 standards. The interior layout is ergonomically designed with a rational arrangement of components, an exceptionally spacious interior, and an integrated touch screen. The climate control system meets the requirements of most mining environments. The cab features double-laminated glass and double-layered hollow glass, a dual-seal structure for the cab door, and a pressurization system. These elements collectively ensure multi-directional and multi-angle control of the cab's airtightness and noise levels.

User-friendly Display Interface

The XDE130 is equipped with a comfortable and operationally friendly dashboard that includes a CAN bus LCD integrated instrument panel, display screen, and function switches. This setup allows the driver to conveniently monitor vehicle status parameters and fault information while driving. The combined instrument panel integrates displays for engine, hydraulic system, drive system, and weighing system status and fault information, along with features for displaying equipment information and configuring functions and permissions.





Comfortable and Durable Suspension System

The suspension system features four oil-gas adjustable suspension cylinders that reduce the impact from transport surfaces and loading, providing a smooth and comfortable ride for the driver and extending the lifespan of the chassis. The front suspension utilizes a candle-type independent suspension, symmetrically aligned on both sides to ensure reliable wheel positioning and stable, comfortable driving. The rear suspension adopts a longitudinal triangular swing arm suspension, allowing the rear axle housing to swing, effectively absorbing bending and torsional stresses generated by rough road conditions.




Reliable and safe brake control

The mature and reliable braking system ensures the vehicle's safety and efficiency during operation, enhancing the driver's confidence and allowing them to focus more on production and transport tasks. The XDE130 is equipped with high-performance dry disc hydraulic brakes on both the front and rear wheels, providing functions for service brake, loading brake, parking brake, and emergency brake. By integrating the electric drive system's electric retarder, the vehicle achieves mixed braking control, ensuring excellent braking performance at all operating speeds. The braking system is equipped with a brake accumulator. The braking system meets ISO 3450 standards.

Multi-Directional Adjustable Seat

Driver comfort is a key factor in ensuring safe and efficient production. The XDE130 is equipped with a luxurious air-suspension seat that effectively absorbs vehicle vibrations and reduces driver fatigue. The seat is multi-directionally adjustable and works in conjunction with the telescoping/tilting steering column to accommodate various driving postures, enhancing driver comfort. Accessories include armrests, seat belts, and a headrest.



Agile Steering

The XDE130 features a disconnected trapezoidal steering mechanism with dual-action hydraulic steering cylinders for power steering. It includes a steering accumulator for emergency control and meets ISO 5010 standards.. With a turning radius of 11.5 meters, the high maneuverability ensures safe and efficient operation on winding mine roads.

04 CONVENIENT MAINTENANCE

Convenient Maintenance Access

The XDE130 is designed with maintenance in mind, facilitating quick and easy servicing. Maintenance ladders are provided on both sides of the front longitudinal beams, making engine inspection and upkeep more convenient. The front of the vehicle's bumper is equipped with an engine emergency stop switch and a ladder light switch. Fuel quick-fill ports are located on both sides of the middle section of the frame, allowing maintenance personnel to operate from the ground.

Modular design, Easy To Assembly and Disassembly

The XDE130 vehicle features a modular design, making it easy to disassemble, assemble, transport, and maintain. In particular, the frame and rear axle use bolted joint bearing seats, which facilitate disassembly and assembly, reduce downtime for maintenance, and enhance the vehicle's availability.

Centralized Filling System

The centralized fuel filling system comprises a receiver, dust cap, flange plate, and dust breather. It includes facilities for the filling and discharge of engine oil, hydraulic oil, fuel, lubricating grease, and coolant. The central filling device is located on the left side of the front frame longitudinal beam. Its operational position is close to the ground, making it easy to operate.





FUNCTION

Full-Automatic Central Lubrication System

The XDE130 is equipped with a fully automatic centralized lubrication system that thoroughly lubricates 22 key pivot points of the vehicle's moving parts. This system saves maintenance time, improves maintenance quality, and reduces the workload of vehicle upkeep. The automatic lubrication system features pressure detection, alarm functions, and programmable control of lubrication intervals.



LCD Screen

- The dashboard display in the cab is used for installation, maintenance, and troubleshooting.
- Basic troubleshooting no longer requires access to the control cabinet.



XCMG 徐工集团 XDE130双桥刚性矿车 DOUBLE AXLE RIGID MINING TRUCK — 10

XCMG MINING MACHINERY'S

COMMITMENT TO YOU

Promise To You

◎""Zero" distance response: Relying on customer project sites, we establish one-stop service points to offer timely and professional proactive service, supporting continuous and efficient operations for global clients.

◎"Zero" time difference assurance: Based on customer needs, we implement a grid-based, localized management mechanism for personnel, vehicles, and parts. This ensures timely service, preventive maintenance, and adaptive upgrades, continually enhancing customer satisfaction.

◎24/7 Year-round assurance: Aiming to ensure full lifecycle support for equipment, we have established a smart aftermarket management platform. This provides global clients with round-the-clock, comprehensive, and worry-free service, deeply engaging with customer operations and continuously supporting their success.

XDE130
双桥刚性矿车

技术参数

Engine

Model ①	KTA38
Standard emission	U.S.EPA Tier0
Fuel type	diesel
Number of cylinders	12
Stroke	4-stroke
Full horsepower	895kW（1200hp）@1900
Flywheel net power	810kW（1087hp）@1900
Weight (wet)	3950kg
Weight (dry)	3723kg
Model ②	16V2000C66
Standard emission	中国GB20891-2014非道路国三
Fuel type	柴油
Number of cylinders	16
Stroke	4-stroke
Full horsepower	970kw（1301hp）@1800rpm
Flywheel net power	890kw（1194hp）@1800rpm
Weight (wet)	3350kg
Weight (dry)	3600kg

*Total horsepower refers to the output power of the engine installed on the machine. The engine speed is controlled, and the fuel settings are approved by the engine manufacturer.
Accessory losses include those from the water pump, fuel pump, and oil pump.
**Flywheel met power is the rated power of the engine flywheel minus the average accessory losses. Accessories include the fan and charging alternator.The specifications comply with SAE J1349 and ISO 3046 standards.

Electric Drive System

AC/DC current	/
Alternator	XCMG-A865
Single-blade inline blower	178.8 m3/min
Control	Ac frequency conversion control system
Electric wheel*	XCMG-M360
Speed ratio	33.85:1
Speed (maximum)	50KM/h

Tires and Rims

Tubeless, radial tires, standard tires	30.00R51
Flange-mounted, five-piece rims	22.00/4.5
Rim rated cold inflation pressure	7.2bar,105PSI
Total tire weight	10620kg

*Tires should meet specifications for tkph/tmph, tread, rubber composition, inflation pressure, cord layer rating, or equivalents.

Cab

The cab meets ISO 3471/ISO 3449 (Level II) standards for ROPS/FOPS with a spacious interior and excellent visibility. It is fully equipped with various displays, gauges, alarms, lighting, control switches, and a radio. The driver’s seat is a fully adjustable air-suspended seat with a tall backrest, complemented by a front passenger seat. It is equipped with an onboard computer, electric windows, a tilt-and-telescopic steering wheel, electric windshield wipers and washers, tinted glass, and air conditioning with heating and cooling functions. Vehicle operation data and fault alerts are displayed using an LCD screen and controllable gauges.

Suspension

Variable-rate hydraulic and pneumatic, overall rebound control	/
Maximum stroke of front suspension	320mm
Maximum stroke of rear suspension	310mm
Maximum vibration amplitude of rear axle	±6.5°

Frame

Advanced technology: The frame is an integrated box-type structure consisting of a pair of longitudinal beams and five cross beams, with key stress transition areas using cast components and a robust continuous gantry beam.

Plate material	670MPa low alloy high strength steel
Casting material	630MPa low alloy high strength steel
Longitudinal beam width	200mm
Longitudinal beam depth (minimum)	280mm
Top and bottom	25mm
Side plate thickness	16mm
Drive axle installation	The pin is hinged with the joint bearing
Drive axle positioning	Rear frame tie rod

Body

High-strength body bottom plates and side plates are used, providing a robust structure and long service life. The bottom plate features a single-slope design for clean unloading and is equipped with safety rope supports, body cushioning pads, and stone discharge devices.

Bottom plate	thickness 20mm
Front plate	thickness 12mm
Side plate	thickness 10mm
Guard plate	thickness 6mm
Struck capacity	60m³
Heaped capacity (SAE2:1)	73m³
Standard XCMG body weight	21926kg

Electrical System

6×975 CCA, 12V batteries, in series/parallel, mounted on the bumper, with a disconnect switch.

Alternator	24V/175A
Lighting equipment	24V
Starter motor	2个/24V

Hydraulic system

Steering	The accumulator assists the dual steering cylinders to provide stable and reliable steering, and the auxiliary steering system is automatically provided by the accumulator.
Turning diameter (SAE)	23m
Hydraulic oil tank	650L
Filter	Oil filter 250μm Oil return filter 12μm Lift and turn high pressure filter 12μm
Lifting	Two one-stage double acting, two-stage
Lifting time	single acting hydraulic cylinders
Lifting (load)	17S
Lowering (high idle)	22S
Lowering (low idle)	25S
Pump	Dual pump direct drive Series gear pump
Lifting and cooling	342L/min 1900rpm
Steering and braking	342L/min 1900rpm
System overflow pressure	
Lifting and cooling	17000KPa 2465psi
Steering and braking	23000KPa 3335psi

The port can be used to power faulty trucks and for system diagnostics.

Brake System

Service brake	Front wheel hydraulic drive dry disc brake side 2 Rear wheel hydraulic drive dry disc brake side 1
Traction system	Wheel non-slip control
Maximum braking pressure	Front wheel 150bar Rear wheel 100bar
Diameter of each brake	Front brake disc 1020mm Rear brake disc 600mm
Automatic application system	Automatically put in before the brake system pressure drops to meet the required limit for the auxiliary brake system
Auxiliary braking System	Compliant with ISO-3450 standards
Parking brake	Normally closed dry disc brake, hydraulic opening, spring lock, located in the rear wheel, one side
Electric retarder	1400kW/1877hp

Fuel filling capacity

Cooling system	330L
Crankcase	129L
Hydraulic system	650L
Motor gearbox (each)	40L
Fuel tank	1200L


Cooling system

XCMG radiator assembly, replaceable cooling pipes, bypass type, with a top-mounted deaerator-type expansion tank.


Radiator front area	3.14m²

Loading height


Loading height	4650mm



C:6100 H:5300 P:3500 I:10860
G:6975 R:1155 D:4900 A:12000
N:3011 M:3466 K:2181 L:1374
E:5010 Z:11310




B:6968 Q:6748 V:570
U:3860 F:4695 W:5530




T:5852 S:5484 X:1905
G:3930 Y:5640

Standard body, struck capacity 60 m³
SAE 2:1 Heaped capacity：73 m³

Performance Curve





Unladen weight (NVW))

Front axle distribution (48%)	42500 kg	93696 lbs
Rear axle distribution (52%)	42500 kg	93696 lbs
Unladen total weight	85000 kg	187392 lbs

Gross Weight (GVW)

Front axle distribution (33%)	67650 kg	149143 lbs
Rear axle distribution (67%)	137350 kg	302805 lbs
Vehicle total weight	205000 kg	451948 lbs


Payload capacity

Effective payload	120000 kg	264555 lbs

USE OF EQUIPMENT AND PRECAUTIONS

XCMG Mining Truck Loading Specifications

The loading specifications define the loading guidelines and restrictions for XCMG mining trucks:



·Gross Vehicle Weight (GVW) includes the chassis, body, tires, accessory, lubricants, fuel, operator, payload, and any excess material accumulation.
·The average monthly payload must not exceed the vehicle's rated payload.
·Actual payload ≤ 110% of rated payload, with a proportion of no less than 90%.
·110% of rated payload ≤ actual payload ≤ 120% of rated payload, with a proportion of no more than 10%.
·Under no circumstances should the actual payload exceed 120% of the rated payload.

*Rated payload includes all optional accessories.

Notes:
1. The graphics and information in this brochure reflect the technical features and configuration standards of certain models at the time. The existing information and data are based on standard usage testing. The above data and information are for reference only; please refer to the actual product.
2. This brochure is for reference only and does not constitute a contract. For detailed information, please contact your local XCMG Mining Machinery distributor.
3. The contents of this brochure may not be reproduced without authorization from Xuzhou XCMG Mining Machinery Co., Ltd. Xuzhou XCMG Mining Machinery Co., Ltd. reserves the right to interpret and modify this brochure.

Issued in September 2024

Standard Configuration

Standard configuration
Self-cleaning air Filter
Alternator (24V/175A)
Automatic lubrication system with level indicator
Reversing alarm
Battery - 6 units, 975 CCA
Battery charging/jump-start connector
Body limit device
Body safety rope
Front brakes: dry disc brakes
Rear brakes: dry disc brakes
Electric control cabinet
Electric retarder cruise control system
Electric start
Fast fuel filling system (on fuel tank and side of hydraulic oil tank)
Hydraulic high-pressure filter
Mirrors:
Left side: Flat mirror, heated
Right side: Convex mirror, heated
Mudguard
Silencer-Mounted on the deck
Power supply-24V and 12V DC
Quick connectors (lifting and diagnostics)
Radiator fluid level indicator
Removable powertrain (engine, alternator)
Reversing brakes
Fan clutch

Operating Environment and Controls

Fully hydraulic service brakes with automatic engagement feature
Power switch
Brake and traction interlock
24V Circuit breaker
Access ramp through grille
Dynamic deceleration
Engine emergency stop button-ground level
Lifting and traction interlock device
Horn (electric-front)
Integrated ROPS/FOPS (standard II) cab
Parking brake with warning light and speed application protection
Power steering system with automatic assist
Deck protection handrails
Propeller shaft protective cover
Radiator fan guard
Seatbelt: Standard three-point
Anti-slip walkway
Engine maintenance platforms: Left side / Right side

Lighting Equipment

2 reversing lights: Mounted at the rear (LED)
2 reversing lights: Mounted on the left and right sides of the deck (LED)
Brake and deceleration lights: On the top of the cab (LED)
Outline lights: (LED)
2 Dynamic deceleration lights: At the rear (LED)
Engine compartment inspection light (LED)
Axle inspection light (LED)
2 fog Lights (LED)
4 headlights (LED)
Stair and platform lights (LED)
4 rear brake and deceleration lights (LED)
Turn signals (LED)

Standard High-Visibility Luxury Cab

AC drive interface display screen
Air conditioning - R-134A
AM/FM radio with USB and MP3
Turbocharger clogging alarm
Roof lamp
Multifunction driver display panel
- Light status
- Engine hours, oil pressure, water temperature, oil temperature, fuel level

Standard High-Visibility Luxury Cab

Multifunction driver display panel
- Mileage, vehicle speed, load
- Ambient temperature, time
- System voltage
- Engine red light, yellow light alarms
- Low system voltage
- Low engine water level
- Gear position indicator
- Excitation indicator
Engine delay shutdown
Floor mat (dual-layer panel)
Cab fuel gauge
Low fuel level warning light and buzzer
Instruments (backlit)
Front working lamp switch
Heater and defroster (heavy-duty)
Heater switch
High beam selector and indicator
Horn (steering wheel center)
Weighing system display
Driver's seat: Adjustable, with air suspension, lumbar support, and armrests
Panel lighting (adjustable)
Passenger seat
Electric windows
Positive pressure driver's cab
Electric retarder brake pedal
Hydraulic brake pedal
Sun visor (adjustable)
Telescoping/Adjustable tilt steering column
Voltmeter (battery output)
Windshield (tinted safety glass)
Windshield wipers (dual) and wiper washer (electric)

Optional Equipment

Note: Optional equipment may alter the operating weight.
1000L/min fast fuel filling system (on fuel tank and side of hydraulic oil tank)
Amber signal light
Maintenance and power lock
Antifreeze: Below 40°C
Body: Standard design
Body heating
Body components, OEM bulk transport*
Body wear plates
Rock breaker rod / Rock breaker chain
Hydraulic lift platform
Hydraulic oil tank ladder
Fuel tank ladder
Low-temperature suspension system - front and rear
Electric heater (engine coolant, hydraulic oil, fuel)
Liquid fuel heater (engine coolant)
Fire extinguisher
Fully automatic fire suppression system
Central Filling - Right Side (Coolant, engine oil, hydraulic oil, grease)
Fenders - Fuel and Hydraulic Oil Tanks
XCMG-360 Panoramic Imaging System
Weighing display screens - right side and left side
Suspension filling kit
Toolbox
Tires
Driver behavior monitoring system
Blind spot monitoring system
Unmanned system
Tire temperature monitoring system
Tire pressure monitoring system

The body provided by XCMG is mandatory.It is recommended to use body designed and locally manufactured by XCMG. Not applicable to third-party organizations.