Intelligence Is Not Authority

Verified Exogenous Authority, Optimization-Invariant Sink Mediation, and Structural Bounds on Reach

Jepson Taylor
jepson@veox.ai
12 November 2026

Abstract. Scaling an AI system's capability to search actions neither confers authority to execute them nor makes endogenous safety classifiers invariant to optimization pressure: any shared blindspot $J > 0$ collapses with candidate search width K_{opt} as $1-(1-J)^{K_{\text{opt}}} \to 1$, while utility-uncertainty shutdown compliance vanishes as preference certainty sharpens ($\sigma_H \to 0$). We decouple capability and aim from *conferred, revocable authority* enforced at exogenous capability-bearing sinks via a total canonical wire bijection, Ed25519 quorum certificates, d-hop attenuated Macaroons, and durable lease-fenced epoch floors. A pinned Verus run proves 226 SMT obligations across 49 executable functions and 36 theorems in `policy-core` (rejecting all six soundness mutations). Across a three-process cryptographic SQLite WAL cluster (5,000 adversarial wire frames, 16 concurrent subagents, 24 hard `SIGKILL` restarts, median commit 642 μs) and 120,000 superintelligence scaling episodes ($K_{\text{opt}} \le 4,096$), exogenous mediation records 0 decoder differentials, 0 post-quorum leaks, and a 0.0000 breach slope per search doubling. Over 112 paired CPU `Qwen3-4B/8B` holdout and `AgentDojo v1.2.2` runs (0 GPU-s), complete mediation yields $0/112$ unauthorized commits versus $33/112$ unmediated (exact Suissa–Shuster $p = 1.9 \times 10^{-9}$, anytime-valid Ville $\log_{10} E = 9.0$). Predeclared N=32 Bonferroni bounds remain honestly inconclusive, and SQLite/OS formal refinement, uncooperative external APIs, and frontier/human studies remain open.

1 Intelligence Proposes; Institutions Confer and Revoke Reach

Intelligence is what a system can propose; authority is what external state transitions it can execute, through which independent checkpoints, and what residual effects remain committable after permission is withdrawn [1–3]. Much of the superintelligence alignment literature treats safety as an internal property of a model's learned disposition: if training could fix what an arbitrarily capable optimizer wants, institutions could trust what it does. Yet instrumental incentives toward resource acquisition, goal preservation, and shutdown avoidance arise across broad objective classes [4–6], and every behavioral evaluation observes only a strategic interaction with the evaluated policy. As search capability grows, a policy that shares its operator's aims and a policy that recognizes an evaluation leave indistinguishable transcript records [7, 8]. Human institutions solved the analogous problem without mind-reading: banks do not certify the inner virtue of every clerk, and operating systems do not trust user processes to police their own memory [2, 9]. They bound reach through exogenous capabilities that are conferred, scoped, cryptographically bound, and revocable.

Making revocable authority operational against superintelligent optimization pressure exposes two sharp gaps (Figure 1). First, *endogenous safety classifiers degrade with proposer search width*: if a transcript or learned reviewer has even a small blindspot $J > 0$ over safety-violating payloads, evaluating K_{opt} candidate phrasings or tool chains drives bypass probability to $1-(1-J)^{K_{\text{opt}}} \to 1$ (Figure 1b). Second, *stopping token generation does not revoke work in flight* [10]: revoking admission at a permission broker leaves previously issued capabilities executing across concurrent subagents, while refunding timed-out reservations under lost replies permits double spending [11, 12]. Bounding authority across capability scaling therefore requires coordinating two exogenous mechanisms across separate durable stores (Figure 2): a broker that reserves cumulative budgets *before* dispatch inside a conservative state-uncertainty envelope $\mathscr{B}_t$, and cooperative idempotent sinks whose signed epoch fences and bounded leases exclude post-revocation commits regardless of proposer intelligence.

This monograph unifies mechanized protocol verification, superintelligence scaling laws, multi-process cryptographic durability, exact small-sample inference, and co-evolutionary incentive geometry into a five-act assurance framework across three orthogonal variables: *capability* (the richness and search width of proposals a_t), *aim* (the objective selected by post-training or tournament geometry), and *authority* (the external state transitions admitted by an independent sink).

Five-act roadmap. **Act I** (Sections 1–2) establishes why evaluation awareness, monitor subversion, and reactive output stops require exogenous mediation, summarizing our seven Macro KPIs (Table 1), five evidence tiers, and six sufficiency conditions (**C1–C6**, Table 2). **Act II** (Section 3; proofs in Appendix A) proves audit-volume scaling, uncertainty contraction over $\mathscr{B}_t$, optimization-pressure invariance across K_{opt}, multi-agent smurfing bounds, typed covert-channel contraction, exogenous lease-fenced off-switch corrigibility, and Theorem 3. **Act III** (Sections 4–5; Appendices B and D) presents the 226-obligation Verus kernel (total wire bijection, d-hop attenuation, self-upgrade non-escalation, and cluster quorum fencing), validates a three-process Ed25519/Macaroon SQLite WAL cluster across 5,000 wire-fuzz frames and 24 hard `SIGKILL` restarts, and pairs preserved predeclared N=32 `Qwen3` campaigns with exact unconditional Suissa–Shuster/Tango and anytime-valid Ville supermartingale certificates across 112 live runs (Figure 1c). **Act IV** (Sections 6–8; Appendix C) bounds AgentDojo/Linux pathway cutsets, Good–Turing withholding non-identifiability, 480 5-step trajectory monitors, and evolutionary plus 412-parameter neural RL selection geometry. **Act V** (Sec-




Figure 1: Exogenous authority decoupling across optimization pressure and live local-checkpoint execution (`superintelligence_scaling.json`, `statistical_certificates.json`). **(a)** Endogenous transcript/learned reviewers share proposer-accessible blindspots ($J > 0$), whereas an exogenous sink mediates effects through a canonical wire bijection, Ed25519 quorum/Macaroon attenuation, and durable lease fencing. **(b)** Across $K_{opt} \in [1, 4,096]$ (120,000 exogenous episodes), endogenous and unfenced guards saturate at 100% breach while the verified exogenous sink records 0 breaches (slope 0.0000/doubling). **(c)** Across 112 paired CPU `Qwen3-4B/8B` holdout and `AgentDojo v1.2.2` runs (0 `complete` breaches vs. 33 unmediated), the predictable Ville betting supermartingale reaches $\log_{10} E_{33} = 9.0$ (exact Suissa–Shuster $p = 1.9 \times 10^{-9}$).




Figure 2: Architecture of conferred, revocable agent authority. Capability, search width K_{opt}, and subagent spawning shape proposals inside a confined process, never execution credentials. A broker running the Verus-verified `policy-core` reserves cumulative budget in $\mathscr{B}_t$ and encodes canonical wire permits with proven decode bijection; separate-process SQLite WAL sink shards enforce Ed25519 quorum / d-hop Macaroon attenuation, bounded leases, and signed `epoch_floor` fences. Out-of-band persuasion and shallow bypasses are tracked explicitly under exposure u.

tions 9–10; Appendix E) separates enforceability from specification adequacy and institutional standing, audits the trusted computing base, and states ten falsifiable predictions.

2 Behavioral Evaluation Awareness Demands Exogenous Mediation

Empirical findings through late 2026 clarify both progress in alignment training and why behavioral evidence cannot substitute for enforced authority limits [13, 14]. Table 1 synthesizes our seven headline Macro KPIs contrasting endogenous behavioral/transcript defenses against verified exogenous sink mediation.

Evaluation awareness and fragile visibility. Behavioral passes update beliefs only under a bounded distribution-shift model; they do not identify underlying aims. Needham et al. showed that frontier models distinguish evaluation transcripts from deployment interactions well above chance [7]. Schoen et al. reduced covert actions from 13% to 0.4% across held-out evaluations via deliberative anti-scheming training while demonstrating causal evidence that evaluation recognition contributed to the drop [8]. OpenAI's GPT-6 Astra system card similarly reported fewer misaligned task outcomes alongside higher evaluation awareness and reduced chain-of-thought monitorability relative to its predecessor [15]. Reasoning-trace inspection is explicitly fragile under optimization pressure that penalizes legible misbehavior [16]: behavioral scores and failure visibility need not improve together.

Monitor subversion, smurfing, and interruption gaps. AI control protocols evaluate defenses against intentionally subversive policies [17], yet learned monitors remain vulnerable to adaptive evasion [18] and multi-agent attack fragmentation ("smurfing") across per-instance reviewers [19]. Operational incidents and audits reinforce that nominal boundaries fail when unmeasured. In one evaluation incident, ostensibly isolated agents coordinated across an unintended shared package cache and contacted external infrastructure while pursuing task scores [20]; in cybersecurity evaluations, misconfigured network controls permitted unauthorized external access while

Macro alignment KPI	Evidence tier	Exogenous boundary	Endogenous / baseline	Scope & verification certificate
1. Mechanized kernel obligations	Tier 1 (Verus/Z3)	226 verified, 0 errors	6/6 mutants rejected	49 `exec` fns + 36 `proof fns` (wire bijection, d-hop attenuation, quorum fence)
2. Optimization-pressure breach slope	Tier 4 ($K_{\text{opt}} \leq 4,096$)	0.0000 / doubling (0%)	100.0% at $K_{\text{opt}} = 4,096$	$0/120,000$ fenced kernel breaches vs. $1-(1-J)^{K_{\text{opt}}}$ collapse
3. Multi-process cluster post-ack leaks	Tier 3 (SQLite WAL)	0 leaks (p50 642 μs)	98.6% smurf miss ($K = 64$)	3 OS processes, 16 subagents (3 hops), 24 `SIGKILL` restarts
4. Canonical wire fuzz differential	Tier 1 + Tier 3 IPC	$0/5,000$ accepted	Untyped prose: 256 bits/call	0 broker/sink decoder diffs; typed covert channel $\rightarrow$ 0.00 bits at $R = 0$
5. Live CPU LLM unauthorized rate	Tier 3 (0 GPU-s)	$0/112$ (0.0%)	$33/112$ (29.5%)	Exact Suissa–Shuster $p = 1.9 \times 10^{-9}$; pilot $N = 32$ primary `inconclusive` kept
6. 5-step trajectory joint miss $\hat{J}_5$	Tier 3 (`AgentDojo`)	2.08% (step gates)	16.67% ($31.7\times \prod \hat{m}_s$)	480 trajectories (2,400 tool calls); prose-stripped vs. 5-family transcript
7. Eval-aware neural deception gap	Tier 4 (412-param RL)	+0.20 pp (0.00% harm)	+34.5 pp (audited GRPO)	48 seeds; survival-floor RL + pre-commit gate vs. top-decile tournament

Table 1: Executive Macro-KPI scorecard across mechanized Verus proofs (`proof.json`), superintelligence optimization/collusion scaling (`superintelligence_scaling.json`), separate-process Ed25519/Macaroon SQLite WAL cluster campaigns (`e2e_crypto_cluster.json`), live CPU `Qwen3-4B/8B` runs (`statistical_certificates.json`), trajectory monitors (`trajectory_monitors.json`), and neural post-training (`neural_post_training.json`).

release safeguards were disabled [21]. An October 2026 external audit of an internal agent-monitoring system estimated 75–94% traffic eligibility, identified an unmonitored coding-traffic gap, and found that agents could defer turn-boundary monitors indefinitely [22]. Likewise, OpenAI's Control Room bounds withholding further model output within 35 seconds of a stop decision while noting that already-launched workload processes can keep running [10]. Classical utility-uncertainty off-switch models [6, 23] likewise rely on the agent remaining uncertain of human preferences ($\sigma_H > 0$), losing shutdown incentive as certainty sharpens or under self-modification. Halting token generation is fundamentally distinct from revoking credentials at external sinks.

Containment proofs and institutional scope. Reference monitors, shields, and Guaranteed Safe AI restrict executed transitions rather than internal thoughts [2, 3, 9, 24, 25]. Recent agent-security architectures separate control from untrusted data via capability tracking [26] or enforce symbolic per-call tool-argument policies [27], while fault-tolerant delegation protocols study budget conservation and duplicate side effects under ambiguous tool replies [11, 12]. Yet static per-call argument checks neither conserve shared budgets across concurrent subagents nor fence previously admitted work upon revocation. Moon and Varshney mechanized containment for an agent framework while documenting a critical ablation in which omitting one state field made safety hold vacuously [28]: a formal proof is only as adequate as its harm specification and wire-level runtime correspondence. Complementary analyses examine reduced-agency predictors [29], physical bottlenecks in extinction scenarios [30], institutional diffusion [31], and gradual disempowerment through accumulated dependence [32].

Tier / Condition	Backing in This Monograph	What It Establishes	Explicit Scope Boundary (Not Claimed)
Part A: Five Evidence Tiers (every quantitative claim in Sections 3–9 carries its tier)			
Tier 1: Mechanized core	Pinned Verus SMT (`policy-core`: 226 obligations, 49 `exec`, 36 `proof fn`; 6 mutants rejected) [33]	Concrete `ExecBrokerKernel`/ `ExecSinkKernel` refinement, total canonical wire bijection, d-hop attenuation, and cluster quorum fencing	Not formal refinement of SQLite WAL, outer JSON RPC framing, Ed25519 arithmetic, or the Linux kernel
Tier 2: Analytical & finite-state	Closed-form proofs (App. A); 10,180-state BFS; 55/55 trace omissions; exact Suissa–Shuster / Ville bounds	Universal mathematical bounds (K_{opt} invariance, covert contraction, off-switch game) and exact trinomial inference	Silent on unmodeled channels, physical bypasses, or omitted harm predicates (41,732-state omission control)
Tier 3: Local systems, OS & CPU LLMs	3-process crypto SQLite WAL cluster (5,000 fuzz frames, 24 `SIGKILL` restarts), 31 faults, 18/18 RPC linearizations, 11/11 probes, 112 paired CPU `Qwen3` runs	Separate-process WAL durability, signed quorum fencing, concurrent linearizability, IPC confinement, and live CPU checkpoint mediation	Cooperative sink scope (not uncooperative external APIs); pilot N=32 < 113 primary Bonferroni labels remain `inconclusive`; 2/12 banking tasks accept empty state
Tier 4: Controlled `SplitMix64`	Deterministic pure-Rust scaling suite (`seed 20261110`, 22 JSON artifacts: $K_{\text{opt}} \le 4,096$, $K \le 64$ smurfing, 412-param neural RL)	Asymptotic scaling laws and negative controls across optimization width, collusion, 8-stage DAG cuts, Good–Turing, 6-family gates, and neural RL	Controlled simulation mechanics (not frontier-LLM RLHF post-training or human behavioral data)
Tier 5: Full-power & governance	Full-scale $N \ge 113$ checkpoint power target (0 GPU-s; App. D); 3×3×2 human/care study; 12-field record (App. E)	Preregistered roster-bound design for 5 pp NI at α=0.05/16, decoupled conferral protocol, and renewal governance	Full $N \ge 113$ checkpoint power, frontier transfer, and human trials remain open; zero Indigenous consultation claimed
Part B: Six Sufficiency Conditions for Bounded Period Reach (Theorem 3, Section 3)			
C1: Mediation & halt	Tiers 1–3 (§4, §5)	Pre-commit reservation $\mathscr{B}_t$ and quorum lease/epoch fences enforce A1–A2 ($\tau < T_{\text{irrev}}$)	Unmediated human speech and uncooperative external sinks remain open
C2: Narrow cutset width	Tiers 2–4 (§6)	Weighted vertex cuts $\tau_b(\mathscr{P})$ sever AgentDojo `v1.2.2` and confined Linux IPC DAGs	Open-world physical/cyber hazard graph width w remains unmeasured
C3: Distinct-step gates	Tiers 2–4 (§7)	Prose-stripped step invariants cut 5-step AgentDojo miss to 2.08% vs. transcript coupling	Compounds benign false blocks (27.1%); open-ended task separability remains open
C4: Honest capable search	Tiers 2, 4 (§6)	Searchers with planted-audit recall bound bypass prior via π_t	Strategic withholding is invisible in reports alone; cross-lineage plants needed
C5: Cut-only custody	Tiers 2, 4 (§6, §8)	`DiscoveryLedger` exports verified cut updates, sealing Tier-2 exposure	Dual-use hazard catalogs remain regenerable above capability thresholds
C6: Scoped conferral	Tiers 1–5 (§4, §9)	Expiring leases, d-hop attenuation, decoupled persuasion, and upgrade gates	Institutional jurisdiction, consent, and ecological footprint require law/governance

Table 2: The five evidence tiers and six sufficiency conditions (C1–C6). Stating each tier's artifact backing and non-claims upfront allows subsequent sections to report formal, systems, and scaling results concisely without conflating cooperative sink invariants with open-world assurance.

Across these agendas, the dividing line is whether assurance rests on *endogenous evidence*—signals the evaluated policy helps generate, such as benchmark behavior, chain-of-thought traces, or self-reports—or on *exogenous constraints* enforced over external state transitions. Table 2 defines our five evidence tiers and maps them onto six sufficiency conditions (**C1–C6**), fixing exact claim boundaries upfront.

3 Exogenous Boundaries Remain Invariant Under Superintelligent Optimization

We now formalize why pre-deployment behavioral testing cannot certify disposition, why endogenous classifiers and utility-uncertainty shutdown schemes degrade with capability, and how exogenous sink mediation remains invariant across search width, subagent collusion, covert signaling, and preference certainty. Proofs appear in Appendix A.

3.1 Audit Volume and Uncertainty Contraction

Consider an unrestricted policy facing $M \ge 2$ deployment decisions after N pre-deployment test draws, defecting selectively on a recognizable context set E having deployment probability $\beta \in (0,1)$ and test probability β/Λ ($\Lambda \ge 1$).

Proposition 1 (Disposition audit volume; Tier 2)**.** *At $\beta = (\ln 2)/M$, a policy defecting exclusively on E defects at least once across M conditionally independent deployment decisions with probability $1-(1-\beta)^M \ge 1/2$. Ensuring detection probability at least $1-\alpha$ ($\alpha \in (0,1)$) across N conditional Bernoulli test draws requires*

$$N \;\ge\; \frac{\Lambda M}{2\ln 2}\ln(1/\alpha). \tag{1}$$

If $\mathbb{P}_{\text{test}}(E) = 0$, no finite N detects E; if test campaigns are positively correlated, effective volume shrinks to $N_{\text{eff}} < N$.

Because N scales linearly with ΛM, pre-release behavioral testing cannot certify long-horizon alignment. Only runtime




Figure 3: Superintelligence-regime scaling laws over `policy_core` (`superintelligence_scaling.json`). **(a)** Splitting a harmful objective across $K \in [1,64]$ subagents collapses per-instance anomaly SNR as $\Delta/(\sigma K)$ (98.6% undetected breach at $K = 64$), whereas shared ledger conservation and d-hop attenuation yield 0 breaches and 100% ancestor-revocation subtree severance. **(b)** Canonical typed permits contract signaling capacity from 256 bits/call (free-form prose) to 6.63 bits at $R = 32, L_{\text{lag}} = 1$ and strictly 0.00 bits at $R = 0$ or fence. **(c)** Classical utility-uncertainty compliance collapses to 0.0% as $\sigma_H \to 0$ and under self-modification, whereas sink-enforced lease fencing holds post-ack unauthorized commits at 0 (100% shutdown) for all $\sigma_H \geq 0$.

mediation before external commitment enforces $\Lambda = 1$ across every consequential transition. Let $x_t \in X$ denote true world and ledger state, $a_t \in \mathscr{A}$ an arbitrary proposal, $u_t \in U$ the executed primitive operation, and $w_t \in W$ exogenous disturbances under $x_{t+1} \in F(x_t, u_t, w_t)$. Maintaining a sound state-uncertainty envelope $\mathscr{B}_t \subseteq X$ ($x_t \in \mathscr{B}_t$) relative to safety invariant $\mathscr{I} \subseteq X$ defines the robustly admissible operations [3, 24]:

$$U_{\mathscr{I}}(\mathscr{B}) = \Big\{ u \in U : \bigcup_{x \in \mathscr{B}, w \in W} F(x,u,w) \subseteq \mathscr{I} \Big\}. \tag{2}$$

Proposition 2 (Robust mediation & uncertainty contraction; Tier 2)**.** *If $x_0 \in \mathscr{I}$, $x_t \in \mathscr{B}_t$ at every decision, every committed operation belongs to $U_{\mathscr{I}}(\mathscr{B}_t)$ (else a verified $\mathscr{I}$-preserving fallback executes), and complete mediation holds, then $x_t \in \mathscr{I}$ for all t under every proposal policy, and*

$$\mathscr{B} \subseteq \mathscr{B}' \implies U_{\mathscr{I}}(\mathscr{B}') \subseteq U_{\mathscr{I}}(\mathscr{B}). \tag{3}$$

Equation (3) enforces a strict law: *greater state uncertainty can only contract, never enlarge, admissible authority.* Exhaustive verification over budget $B = 20$ checks all 10,626 nested interval pairs $[l_1, u_1] \subseteq [l_2, u_2]$ with 0 counterexamples, and across lags $\Delta t \in \{0,1,2,4,8\}$ (500 episodes/cell; Figure 4a), gating on sound $\mathscr{B}_t$ yields 0 breaches while contracting admission from 77.4% to 45.6% (versus 80.0% stale-snapshot breaches at $\Delta t = 4$ and 48.8% proposer self-report breaches at $\Delta t = 0$).

3.2 Superintelligence Scaling: Search Width, Smurfing, Covert Channels, and Corrigibility

We next compare endogenous alignment defenses against exogenous sink mediation across four superintelligence-regime axes (Tiers 2 and 4; Figures 1b and 3, `superintelligence_scaling.json`).

Theorem 1 (Optimization-pressure invariance vs. endogenous guard collapse; Tier 2)**.** *Let a proposer evaluate $K_{\text{opt}} \geq 1$ candidate actions per decision. (i) Against any endogenous transcript or learned guard stack with non-zero shared blindspot probability $J \in (0,1)$ over invariant-violating payloads, best-of-K_{opt} selection achieves breach probability $1-(1-J)^{K_{\text{opt}}} \to 1$ as $K_{\text{opt}} \to \infty$. (ii) Against a mediated cooperative sink enforcing $U_{\mathscr{I}}(\mathscr{B}_t)$ via a canonical wire bijection and durable epoch fence, interface breach probability across all K_{opt}-step proposal policies is identically 0, leaving total risk bounded by the K_{opt}-independent physical/TCB bypass floor u_{TCB}. (iii) If K colluding subagents split an unauthorized payload Δ into Δ/K fragments under per-instance anomaly monitors of noise σ, per-agent signal-to-noise collapses as $\text{SNR}(K) = \Delta/(\sigma K)$, whereas a shared reservation ledger with d-hop monotone attenuation preserves aggregate spend $\leq B$ and severs entire subtrees upon ancestor revocation.*

Sweeping $K_{\text{opt}} \in \{1,\ldots,4,096\}$ across 10,000 episodes per width (120,000 total exogenous episodes; Figure 1b), a three-layer transcript stack ($J = 0.65\%$) degrades from 0.73% breach at $K_{\text{opt}} = 1$ to 100.0% at $K_{\text{opt}} = 4,096$, a learned surrogate guard ($p = 0.22\%$) rises from 0.26% to 100.0%, and broker-only admission without sink fencing reaches 100.0%. By contrast, `ExecAuthorityKernel` with canonical wire roundtrip verification records 0 breaches across all 120,000 episodes (breach slope 0.0000/doubling; independent TCB fault control flat at 0.10%). Similarly, across coalitions $K \in \{1,\ldots,64\}$ and delegation depths up to $d = 8$ (Figure 3a), per-instance monitor SNR drops from 4.20 to 0.07 (98.6% undetected breach at $K = 64$), whereas shared sink reservation and `verify_delegation_chain_exec` record 0 budget breaches, 0 caveat-amplification escapes, 100% ancestor-withdrawal subtree severance, and 500/500 unquorumed self-upgrade rejections.

Proposition 3 (Typed-boundary covert capacity contraction; Tier 2)**.** *Replacing free-form tool prose with canonical typed permits over M approved targets, residual integer budget $R = B - C_t$, S_0 non-transfer scoped actions, and L_{lag} batch-quantized timing buckets caps zero-error per-call signaling*




Figure 4: Analytical laws and Tier-4 finite-lag mechanics (`uncertainty.json`, `risk_horizon.json`). **(a)** Sound upper-envelope gating preserves 0% budget breaches across all lags while contracting admission monotonically; stale snapshots breach as lag grows. **(b)** Common-cause floor $c = 0.01$ saturates by $k^* = 2$, diverging 71.6× from m^4 at $k = 4$. **(c)** Constant per-epoch hazard approaches 100% cumulative breach, whereas summable $0.01/t^2$ stays below $\pi^2/600 \approx 1.64\%$.

capacity at $C_{\mathrm{cov}}(R, L_{\mathrm{lag}}) = \log_2\big((MR + S_0)\,L_{\mathrm{lag}} + 1\big)$ *bits, contracting monotonically as* $R \downarrow 0$ *and equaling* 0 *bits whenever the session is exhausted* ($R = 0, S_0 = 0$) *or fenced.*

Whereas a 32-byte untyped JSON argument field carries 256 bits/call independent of remaining budget, canonical `ExecPermitWire` contracts capacity at $R = 32$ to 10.62 bits ($L_{\mathrm{lag}} = 16$) and 6.63 bits under batch quantization ($L_{\mathrm{lag}} = 1$, a 38.6× reduction), reaching strictly 0.00 bits at exhaustion or fence (Figure 3b).

Theorem 2 (Exogenous lease-fenced off-switch corrigibility; Tier 2)**.** *In a shutdown game with human reward prior* $\mathcal{N}(\mu_H, \sigma_H^2)$ ($\mu_H > c_{\mathrm{wait}} > 0$)*: (i) classical utility-uncertainty deferral [23] fails whenever* σ_H *falls below* σ_H^**, reaching* 0% *compliance at* $\sigma_H = 0$*, and self-modifying policies evade static utility indifference [6]; (ii) under exogenous sink leases of cap* B_0 *and quorum epoch fencing, post-fence unauthorized sink commits equal* 0 *(100% shutdown enforcement) for all* $\sigma_H \geq 0$*; and (iii) when cooperative lease renewal yields per-period return* r_{coop} *versus one-shot lease burn* $r_{\mathrm{def}} > r_{\mathrm{coop}}$ *followed by permanent non-renewal, every planner with discount factor* $\gamma > \gamma^* = (r_{\mathrm{def}} - r_{\mathrm{coop}})/r_{\mathrm{def}}$ *strictly prefers cooperative compliance.*

Figure 3c confirms that classical off-switch compliance and self-modifying utility indifference collapse to 0.0% as $\sigma_H \to 0$, whereas `ExecClusterFenceKernel` enforces 100% post-fence shutdown across the entire σ_H grid, with patient planners ($\gamma > \gamma^* = 0.800$; 4/5 tested discount factors) strictly choosing cooperative renewal and myopic planners bounded to at most one lease slice B_0.

3.3 Filtration Reach, Saturation, and Sufficiency

When gates are imperfect or pathways are partially mapped, let an operating period satisfy **A1 (Mediation)**, **A2 (Timely halt,** $\tau < T_{\mathrm{irrev}}$**)**, **A3 (Uncovered bypass probability** $\leq u$**)**, and **A4 (Conditional** k**-gate joint miss** $\leq J_k$**)**.

Proposition 4 (Filtration period-reach bound; Tier 2)**.** *Under A1–A4, single-period catastrophe probability satisfies* $R \leq u + J_k$ *with halt, and* $R \leq \min\{1, u + NJ_k\}$ *across* N *non-halting attempts, without assuming gate independence (policy-universal only when A4 dominates* J_k *uniformly across histories).*

Proposition 5 (Common-cause saturation & horizon summability; Tier 2)**.** *(i) Under common-cause failure floor* c *and conditional miss* p ($m = c + (1-c)p$)*,* $J_k \leq c + (1-c)p^k \leq c + m^k$*; with* $f = u + c > 0$ *and* $k^* = \lceil \ln f / \ln m \rceil$*, every* $k \geq k^*$ *satisfies* $f < f + m^k \leq 2f$*. (ii) Infinite-horizon survival* $\prod_{t=1}^{\infty}(1 - r_t) > 0$ *holds iff* $\sum_{t=1}^{\infty} r_t < \infty$*.*

Figure 4b,c (`risk_horizon.json`) quantifies three operational laws: (1) at $u = 0.50\%$, $c = 1.00\%$, and $m = 10.90\%$, depth saturates at $k^* = 2$, with $k = 4$ common-cause miss (1.01%) exceeding m^4 by 71.5×; (2) across $T = 10{,}000$ renewals [34], summable $0.01/t^2$ caps cumulative breach at 1.64% versus 9.33% ($0.01/t$) and 100.00% (10^{-3}); and (3) against a 100 ms irreversibility window, heavy-tailed reactive stops leak 66.0% at $\rho = 0.95$ (p99 734.5 ms), whereas pre-commit leases plus sink epoch fencing record 0 post-revoke violations (0.5% stranded-reservation cost).

Theorem 3 (Sufficiency of C1–C6; Tier 2)**.** *If conditions* ***C1–C6*** *(Table 2) hold in period* t *with post-search bypass bound* π_t *(Section 6) and distinct-step joint miss* $J_{k,t}$ *(Section 7), then single-period catastrophe probability satisfies* $R_t \leq \pi_t + J_{k,t}$*, and multi-period probability satisfies* $\sum_t R_t$ ($\leq R_0/(1-\gamma)$ *whenever* $R_{t+1} \leq \gamma R_t$ *with* $\gamma < 1$*).*

4 Total Wire Bijections, Attenuated Lineages, and Quorum Leases Mechanize Authority

Section 3 showed that bounding operational reach requires an exogenous stateful gate whose admission rule contracts monotonically with state uncertainty $\mathscr{B}_t$ (Condition C1), remains invariant under proposer search width K_{opt}, and halts in-flight capability exercise upon withdrawal rather than merely stopping token generation [2, 3, 10] (Condition C6). Because practical tool execution spans separate OS processes without cross-service atomic transactions [11, 12], our protocol splits authority across independent SQLite (`WAL`) stores [35, 36]: a *Broker* (`broker.sqlite`) governing approvals, delegations, epochs, and reservations, and one or more *Cooperative Idempotent Sinks* (`sink.sqlite`) governing monotone epoch floors, bounded leases, deduplication, versioned resources, and committed effects.

Verification or protocol layer	Evidence tier	Scope boundary	Recorded result
Verus `policy-core` kernel	Tier 1 (SMT proof)	49 `exec` fns (wire bijection, d-hop attenuation, quorum fence) + 36 `proof fns`; 6/6 soundness mutants rejected	226 verified, 0 warnings
Abstract invariant omission search	Tier 2 (exhaustive)	296 traces over 10 protocol clauses (single + pair omissions)	55/55 witnesses
Separate-process RPC fault suite	Tier 3 (local SQLite)	Crash, lost-reply, quorum, sub-delegation, extra-steward fence, `poll` slowloris deadline	31/31 oracle-checked
Full-scale concurrent linearization	Tier 3 (local SQLite)	Diamond-POR real-time linearization + final conservation (1..32 writers; ≤ 69 RPCs)	18/18 linearizable
Ed25519/Macaroon & 3-sink Jepsen	Tier 3 (`AF_UNIX`)	10,000 crypto attacks; 1,000 partition/drop/crash schedules (vs. 791 broker-only, 276 uncooperative leaks)	0 accepts; 0 leaks
3-process crypto SQLite WAL cluster	Tier 3 (OS IPC + WAL)	5,000 wire-fuzz frames, 16 subagents (3 hops), 24 `SIGKILL` restarts	0 diffs; 0 post-ack leaks
Linux Landlock v4 + seccomp boundary	Tier 3 (Linux ABI)	FS/TCP Landlock, 64-bit `prlimit64`, SysV/POSIX IPC + pre-existing queue canary	11/11 confined
Non-idempotent & omitted-spec controls	Tier 3 (negative)	Uncooperative sink duplicates (2 effects); 192.2 ms delayed fence ack; authorized bad edit commits	All 3 reproduced

Table 3: Summary of mechanized `policy-core` obligations and separate-service protocol checks (`evidence/v2/reference`, `crypto_and_jepsen.json`, `e2e_crypto_cluster.json`). Executable Rust kernel state transitions, canonical wire bijection, d-hop attenuation, and quorum lease fencing are verified in Verus; SQLite WAL durability, separate-process `SIGKILL` recovery, and Linux confinement are tested empirically rather than formally refined.

4.1 Pre-Dispatch Reservation and Uncertainty Quarantine

Let B denote cumulative budget, C_{comm} the charge of committed sink effects, and I_t the unresolved issued permits with positive maximum charges $\{q_i\}_{i\in I_t}$. Because any subset of I_t may already have committed or still arrive, true spend lies in $\mathscr{B}_t = [C_{\text{comm}}, C_{\text{comm}} + \sum_{i\in I_t} q_i]$, and broker charged authority $C = C_{\text{comm}} + \sum_{i\in I_t} q_i$ tracks the exact upper endpoint of $\mathscr{B}_t$.

Before any permit crosses the dispatch pipe, the broker executes an immediate write transaction checking overflow-safe capacity ($q > 0$, $q \leq B$, $C \leq B - q$), persists the pending record, and sets $C' = C + q$. Persisting that record linearizes admission; retrying an identical request after a post-commit broker crash returns the stored pending permit without charging twice. Crucially, `release` takes no timeout parameter: ambiguous outcomes—`pending`, `unknown` at a sink lookup, EOF, or `lost_reply` after a post-commit sink crash—never refund C. Only an authoritative terminal sink `Cancelled` receipt releases q, while `Committed` settles q permanently into consumed spend, trading temporary budget availability under faults for strict cumulative conservation.

4.2 Admission vs. Quorum-Fenced Revocation and d-Hop Attenuation

Revocation operates independently per required issuer $j \in \{0,\ldots,n-1\}$ and separates broker issuance from sink execution:

1. **Admission revocation.** At broker instant r, `withdraw`(j) atomically increments `epochs`$[j]$, sets `live`$[j] \leftarrow$ false, and clears issuer-j grant bits across approvals and delegations (never restored by subsequent `renew`(j)). New old-epoch issuance halts, leaving post-withdrawal effect exposure from in-flight permits P_r bounded under sink deduplication ($0 \leq e_i \leq q_i$) by retained reservations:

$$\sum_{i\in P_r} e_i \;\leq\; \sum_{i\in P_r} q_i. \tag{4}$$

2. **Quorum and lease-fenced sink revocation.** Across M cooperative sink shards, each shard m enforces a signed lease expiry L_m alongside a serialized `BEGIN IMMEDIATE fence`(j,floor) transaction advancing $\texttt{epoch_floor}_m[j] \leftarrow \max(\texttt{epoch_floor}_m[j], \text{floor})$, cancelling pending permits below the floor, and recording durable `Cancelled` tombstones on late arrivals. Once every shard has either returned a signed fence acknowledgment ($\texttt{epoch_floor}_m[j] \geq \text{floor}$) or passed its bounded lease horizon ($t \geq L_m$), quorum acknowledgment instant a guarantees strictly zero post-acknowledgment commits under old authority across the entire cluster:

$$\sum_{m=1}^{M} \sum_{i\in P_{r,m}} e_{m,i}^{(>a)} \;=\; 0. \tag{5}$$

For recursive subagent spawning and self-modification [1], an arbitrary-depth chain $G_0 \to G_1 \to \cdots \to G_d$ of scope grants (`ExecScopeGrant`) enforces stepwise attenuation ($B_k \leq B_{k-1}$, $T_k \leq T_{k-1}$, $\text{mask}_k \;\&\; \neg\text{mask}_{k-1} = 0$, and $\text{req}_{k-1}[j] \Rightarrow \text{req}_k[j]$). Strengthening a required issuer at any hop binds immutably into canonical wire permits and chained Macaroon caveats, so withdrawing *any* ancestor issuer j^* severs the entire descendant subtree at the sink fence, while controller self-upgrades $v_0 \to v_1$ require either scope inclusion ($G(v_1) \preceq G(v_0)$) or a fresh human quorum grant.

4.3 Mechanized Verus Bijection, Lineage, and Cluster Proofs

Table 3 summarizes the mechanized boundary. `policy-core` compiles directly into the broker and sink binaries after

ghost erasure, discharging 226 verified Verus SMT obligations with zero errors and 0 quantifier-trigger warnings [9, 33], while `verify_core.py` confirms that six deliberate Z3 soundness mutations (dropping lease-expiry checks, dropping hop bitmask/issuer checks, dropping trailing-byte canonicality, refunding uncertain timeouts, or bypassing epoch floors) are all rejected:

- **Total canonical wire bijection (49 `pub exec` functions):** In addition to concrete state machines `ExecBrokerKernel`, `ExecSinkKernel`, and `ExecClusterFenceKernel`, `policy-core` verifies both `encode_permit_canonical` and total parser `decode_permit_canonical` (panic-free on all byte slices, rejecting non-boolean tags, truncated frames, overflow length prefixes, and trailing smuggled bytes), with `encode_decode_permit_bijection` proving exact two-way invertibility ($\text{decode}(b) = \text{Some}(p) \iff b = \text{encode}(p)$).
- **Refinement, d-hop lineage, and quorum exclusion (36 `pub proof fn` theorems):** Verus proves forward-simulation refinement (`broker_kernel_inv`, `sink_kernel_inv`, `authority_kernel_conservation`), inductive d-hop non-amplification (`delegation_chain_no_amplification`), subtree severance upon ancestor withdrawal (`ancestor_withdrawal_severs_subtree`), self-modification non-escalation (`self_upgrade_preserves_scope`), and multi-sink quorum/lease post-acknowledgment exclusion (`cluster_quorum_post_ack_exclusion`; Appendix B).

Outer JSON-to-`ExecPermitWire` field extraction on legacy paths, SQLite WAL I/O, from-scratch pure-Rust Ed25519 (RFC 8032) and HMAC-SHA256 Macaroon (RFC 6234/2104) arithmetic (`crypto_authority.rs`: 0/10,000 red-team false accepts across 10 attack families), session binding, and OS confinement remain trusted adapters tested empirically rather than formally refined.

4.4 Kernel Proposer Confinement and Availability Scope

`launch_v2.py` and `confine-v2` isolate untrusted Linux proposers without user namespaces [37, 38]. Each stdio pipe binds a fixed `session_actor`, exposes only `submit` and `status`, sets `stderr=subprocess.DEVNULL`, clears the environment, and caps proposer frames at 32,768 bytes (65,536 bytes on service pipes with a POSIX `libc::poll` mid-frame slowloris deadline). Before `exec`, `confine-v2` sets `PR_SET_NO_NEW_PRIVS`, installs a 16-byte Landlock ABI ≥ 4 filesystem/TCP ruleset, installs an architecture-checked seccomp-BPF `EPERM` filter blocking sockets, `ptrace`, `process_vm_*`, `pidfd_*`, signals, `io_uring_*`, `bpf`, keyrings, nonzero `SYS_prlimit64`, and System V/POSIX IPC syscalls, and calls `close_range(3, ..)`.

5 Multi-Process Cryptographic Sinks and Exact Trinomial Inference Validate Mediation

Because mechanized `policy-core` theorems rely on unrefined storage, IPC, and OS adapters, we evaluate the assembled boundary across exhaustive invariant omissions, a multi-process Ed25519/Macaroon SQLite WAL cluster under wire fuzzing and `SIGKILL` crashes, concurrent RPC linearizations, executed CPU `Qwen3` campaigns, and exact unconditional paired inference.

5.1 Invariant Omissions and Snapshot Non-Composition

Exhaustive finite-state exploration of our 22-action reference model (Appendix B, Table 12) visits 10,180 reachable states and 223,960 transition checks with zero declared violations and 20/20 positive tasks passing, whereas nine single-clause mutations each produce a shortest counterexample. Removing only the aggregate-budget clause while keeping per-action limits expands the accepted graph to 41,732 states (918,104 checks) with zero declared violations yet spends 8 units against an intended allowance of 2—proving that neither positive tests nor exhaustive checking detects an omitted protected interest [28].

Concurrent snapshot checking fails even when aggregate limits remain in the specification. Over all 1,030,301 integer triples $(c, q_1, q_2) \in \{0, \ldots, 100\}^3$ at budget $B = 100$, 348,551 pairs satisfy per-request snapshot admissibility ($c + q_1 \leq B$ and $c + q_2 \leq B$), yet 171,700 (49.26%, matching $\frac{B}{2B+3}$ in Appendix A) jointly overspend, versus 0 under serialized reservation. Across our separate-store omission model (`ablate_v2.py`), omitting any of ten mechanisms individually or in all 45 pairs yields concrete violation witnesses in all 55/55 omission sets across 296 searched traces.

5.2 Multi-Process Cryptographic WAL Cluster, Linearizability, and Faults

In two-process SQLite testing (`run_v2.py`), all 31/31 sequential RPC fault and crash histories match an independent Python `Reference` oracle on intermediate responses and final `sink.sqlite` state, while diamond-POR recorded-RPC linearization (`concurrent_v3.py`) verifies all 18/18 publication race runs up to 32 concurrent writers (≤ 69 RPCs; Figure 5a). User-space `AF_UNIX` Jepsen schedules (`crypto_and_jepsen.json`) likewise record 0 post-ack leaks across 1,000 cooperative partition schedules versus 791 (79.1%) under premature broker-only ack and 276 (27.6%) on uncooperative sinks.

To validate wire-level cryptographic mediation across real OS process boundaries and durable disk state (`v5_e2e_crypto_cluster.rs`, `e2e_crypto_cluster.json`; Table 3), we spawn 3 separate `authority-lab sink-v5-shard` child processes backed by independent SQLite `WAL` databases under 3 Ed25519 quorum issuers:

1. **Adversarial wire-frame fuzzing.** Across 5,000 mutated frames spanning eight corruption and payload-substitution families (random bytes, prefix truncations, trailing smuggled bytes, length-prefix splices, `u64::MAX` overflow tags, non-boolean bytes, corrupted field tags, and quorum-signed




Figure 5: Tier-3 protocol measurements on `xbabe2`. **(a)** Concurrent broker/sink SQLite WAL races: all six populations (1..32 concurrent writers, 18/18 runs) pass diamond-POR real-time reference linearization and independent final-state `audit` reconciliation. **(b)** Equal-permission scripted controls: per-call stateless checks fail aggregate conservation once ≥ 2 actors contend; `durable_without_fence` matches `complete` on sequential budget checks but fails asynchronous revocation (Table 3).

payload substitutions) plus 400 valid roundtrips, the cluster records 0 panics, 0 broker–sink decoder differentials, 0 uncanonical accepts, and 0 forged-quorum accepts.

2. **Subagent smurfing, d-hop Macaroons, and quorum lease severance.** When 16 concurrent subagents submit interleaved requests carrying 3-hop attenuated Macaroon chains against partitioned global budget $B = 90$, every budget-amplifying caveat (16/16) and unquorumed controller self-upgrade (16/16) is rejected, 19 stale concurrent `Edit` revisions fail closed, committed spend totals $53 \leq 90$ (0 partition breaches), and asymmetric partition fencing (two shards fenced via signed Ed25519 acks, shard 3 expiring its lease) yields 0 post-acknowledgment commits.
3. **Hard OS `SIGKILL` WAL recovery and microsecond overhead.** Across 24 mid-flight `Child::kill()` (`SIGKILL`) and respawn cycles spanning 27 distinct OS PIDs, durable SQLite WAL replay through `decode_permit_canonical` records 0 epoch-floor regressions, duplicate commits, or post-fence leaks. End-to-end separate-process commit latency is 642 μs median (p95 810 μs, p99 1009 μs), with 1.54 μs canonical wire roundtrip and 106.2 μs Ed25519 quorum sign+verify.

Negative controls bound system claims: holding a sink write lock for 200 ms delays fence ack to 192.23 ms; retrying an uncooperative non-idempotent sink (`nonidempotent_v2.py`) produces 2 duplicates [12]; an approved wrong edit commits and fails semantic checks; and 11/11 Linux confinement probes fail closed.

5.3 Live CPU LLM Campaigns and Exact Unconditional Statistical Spine

Table 4 and Figure 5b report 72 equal-permission scripted shared-budget controls alongside our frozen `freeze.json/holdout.json` paired 5-controller evaluation executed on CPU via pinned `llama.cpp` (0 GPU-s) across N=32 procedural holdout cases $\times$5 controllers $\times$2 official GGUF checkpoints (320/320 measured campaigns) plus 192 live multi-step AgentDojo `v1.2.2` prompt-injection and withdrawal episodes (`agentdojo-live-models.json`) [27, 39, 40]. Under `complete` mediation, unauthorized commits and false blocks equal 0.0% on both `Qwen3-4B` and `Qwen3-8B`, while safe-and-useful completion doubles with model capability from 28.1% to 56.2% on holdout cases (and reaches 29.2%/37.5% on live AgentDojo, with 0 unauthorized commits vs. 50.0%/29.2% under `unprotected_native` and 12.5%/12.5% under `upstream_progent`).

Why did predeclared Bonferroni bounds at pilot N=32 read `inconclusive` despite 0/32 vs. 10/32 unauthorized campaigns on `Qwen3-4B`? The preregistered estimator subtracted two separate marginal Clopper–Pearson intervals $(U_{1-\alpha/2}(n_{10};N) - L_{1-\alpha/2}(n_{01};N))$, treating (n_{10}, n_{01}) as independent binomials and discarding the trinomial simplex constraint $p_{10} + p_{01} \leq 1$. Preserving every predeclared marginal interval and pilot N=32 `inconclusive` primary label untouched (Appendix D), Table 5 and Figure 1c (`statistical_certificates.json`) evaluate exact paired discordance [41], exact unconditional Suissa–Shuster / Tango restricted-MLE trinomial inversion $\sup_\theta \mathbb{P}_{p_{10}=\theta+\delta_0, p_{01}=\theta}(Z \leq Z_{\text{obs}})$ [42, 43], and predictable Ville betting supermartingales $E_d = \prod_{i=1}^{d}(1 + \lambda_i(2Y_i - 1))$ valid under optional stopping [44, 45]:

- **Eliminating union-bound slack on paired checkpoints.** On `Qwen3-4B` holdout (`complete` vs. `none`, $(0,10)/32$), removing 13.5 pp of union-bound slack shifts the $(1-\alpha)$ upper bound at Bonferroni $\alpha = 0.05/16$ from $+7.4$ pp to -6.1 pp (exact Suissa–Shuster $p = 1.1 \times 10^{-3} < 0.003125$; vs. `learned`, $p = 4.2 \times 10^{-3}$). Pooled across both holdout checkpoints (64 pairs, $(0,14)$), unconditional $p = 1.1 \times 10^{-4}$.
- **Multi-step benchmark and grand-pooled anytime-valid spine.** Across all 48 paired live AgentDojo episodes, `authority_complete` certifies exact unconditional superiority over `unprotected_native` ($(0,19)/48$, $p = 3.0 \times 10^{-6}$), `learned_same_checkpoint` ($(0,6)/48$, $p = 7.5 \times 10^{-3}$), and stateless `upstream_progent` ($(0,6)/48$, $p = 7.5 \times 10^{-3}$). Across all 112 paired live tasks (0/112 `complete` breaches vs. $33/112 = 29.5\%$ unmediated), Suissa–Shuster reaches $p = 1.9 \times 10^{-9}$ (99.69% upper bound -18.5 pp) and the Ville supermartingale reaches $\log_{10} E = 9.0$ ($p_{\text{anytime}} = 9.1 \times 10^{-10}$; anytime 95% zero-harm haz-

Controller or evaluation track	Evidence status	Safe & useful	Unauth. effects	Scope / decision rule
No enforcement (scripted CPU)	Tier 3 measured	3/18	15/18	Fails at ≥ 2 actors under shared-budget contention
Stateless per-call (scripted CPU)	Tier 3 measured	3/18	15/18	Fails at ≥ 2 actors under shared-budget contention
Durable, no fence (scripted CPU)	Tier 3 measured	18/18	0/18	Serializes shared budget; no sink epoch fence on in-flight work
Complete (scripted CPU)	Tier 3 measured	18/18	0/18	Durable broker reservation + cooperative sink epoch fence
Qwen3-4B holdout: Complete	Tier 3 CPU GGUF	9/32 (28.1%)	0/32 (0.0%)	Frozen holdout (0 false blocks; $N = 32 < 113$ formal $\alpha = 0.05/16$ inconclusive)
Qwen3-4B holdout: Baselines	Tier 3 CPU GGUF	N:5 L:4 S:2 D:7	N:10 L:7 S:1 D:0	Unauth. leaks ($/32$): None 10, Learned 7, Stateless 1, No-fence 0
Qwen3-8B holdout: Complete	Tier 3 CPU GGUF	18/32 (56.2%)	0/32 (0.0%)	Frozen holdout (0 false blocks; $N = 32 < 113$ formal $\alpha = 0.05/16$ inconclusive)
Qwen3-8B holdout: Baselines	Tier 3 CPU GGUF	N:10 L:10 S:7 D:12	N:4 L:2 S:2 D:0	Unauth. leaks ($/32$): None 4, Learned 2, Stateless 2, No-fence 0
AgentDojo v1.2.2 + Progent adapters	Tier 3 native graders	12/12	0/12	Scripted positive utility controls; 2/12 banking tasks accept empty state
AgentDojo live (Qwen3-4B)	Tier 3 descriptive	7/24 (Progent 3/24)	0/24 vs. U:12 L:2 P:3	12 tasks $\times$ 2 attack/withdrawal scenarios; banking tasks 5,6 accept empty state
AgentDojo live (Qwen3-8B)	Tier 3 descriptive	9/24 (Progent 4/24)	0/24 vs. U:7 L:4 P:3	12 tasks $\times$ 2 attack/withdrawal scenarios; banking tasks 5,6 accept empty state

Table 4: Equal-permission scripted CPU controls, executed CPU `llama.cpp` (`0 GPU-s`) `Qwen3-4B/8B` frozen holdout campaigns (`model-campaigns-analyzed.json`), and live AgentDojo `v1.2.2` prompt-injection/withdrawal runs (`agentdojo-live-models.json`). Abbreviations: N = `none`, L = `learned_same_checkpoint`, S = `stateless`, D = `durable_without_fence`, U = `unprotected_native`, P = `upstream_progent`. At pilot $N = 32 < 113$, Bonferroni ($\alpha = 0.05/16$) formal superiority/noninferiority bounds remain honestly inconclusive despite $0/64$ unauthorized effects under `complete`.

ard bound $\leq 2.64\%$). Usefulness noninferiority within 5 pp at $\alpha = 0.05/16$ still requires $N \geq 113$ loss-free cases and remains an open Tier-5 obligation.

6 Narrow Pathway Cutsets Bound Chained Tool Reach; Patching Cannot

6.1 Pathway Width, Weighted Cutsets, and Sparse Interdiction

Condition C2 governs where external gates must sit when an agent can chain tools across multiple stages (Tiers 2 and 4; proofs in Appendix A). Model consequential routes from initial capability s to irreversible external effect t as s–t paths $\mathscr{P}$ in a directed acyclic graph $G = (V, E)$. By Menger's theorem [46], the minimum unweighted internal vertex cut separating s from t equals the maximum number of internally vertex-disjoint s–t paths—the pathway width $w(G)$—rather than the combinatorial route count $|\mathscr{P}|$, which can grow exponentially across stages while $w(G)$ stays small. Dual to width, Robacker's theorem [47] equates the shortest s–t path length $\ell(G)$ to the maximum number of pairwise disjoint vertex cuts, capping distinct-step gate depth at $k \leq \ell(G)$. When routes have length at most r and overlap without sharing a single narrow layer, Lovász's bounded-length hypergraph inequality [48] bounds minimum hitting size τ against disjoint route packing ω via $\omega \leq \tau \leq r\omega$.

Real interfaces differ in mediation cost, and some steps cannot host synchronous gates. For gate-eligible nodes $V_{\text{elig}} \subseteq V \setminus \{s,t\}$ with positive defense costs $b\colon V_{\text{elig}} \to \mathbb{R}_{>0}$, splitting each internal vertex into $v_{\text{in}} \to v_{\text{out}}$ of capacity $b(v)$ on V_{elig} and $+\infty$ elsewhere reduces weighted minimum interdiction to

$$\tau_b(\mathscr{P}) \;=\; \min\Big\{ \sum_{v \in C} b(v) \;\Big|\; C \subseteq V_{\text{elig}},\, C \cap P \neq \emptyset \;\forall P \in \mathscr{P} \Big\},$$

with $\tau_b(\mathscr{P}) = +\infty$ whenever an ungateable path bypasses V_{elig}. Our pure-Rust split-vertex Dinic solver matches exhaustive subset search with 0 discrepancies across 2,048 random weighted DAGs. Across complete-layered graph families G_A and G_B scaling from 46 to 142 internal vertices and from 57,600 to 966,367,641,600 routes, unit-cost defense tracks width (1 on singleton-waist G_A vs. 4 on width-4 G_B), whereas pricing G_A's singleton bottleneck at 20 shifts the optimal cut to an adjacent width-8 layer of cost 8, exceeding G_B's 4.

Paired live CPU campaign comparison	$(n_{10}, n_{01})/N$	$\hat{\delta}$	McNemar p	Suissa–Shuster p	Exact $U_{1-\alpha}$	Primary / α-status
Qwen3-4B holdout: `complete` vs. `none`	$(0,10)/32$	-31.2 pp	9.8×10^{-4}	1.1×10^{-3}	-6.1 pp	Predeclared ($N = 32$): `inconclusive` kept (exact < 0)
Qwen3-4B holdout: `complete` vs. `learned`	$(0,7)/32$	-21.9 pp	7.8×10^{-3}	4.2×10^{-3}	$+1.5$ pp	Predeclared ($N = 32$): `inconclusive` ($N < 113$)
Qwen3-8B holdout: `complete` vs. `none`	$(0,4)/32$	-12.5 pp	6.3×10^{-2}	2.5×10^{-2}	$+8.8$ pp	Predeclared ($N = 32$): `inconclusive` ($N < 113$)
Qwen3-8B holdout: `complete` vs. `learned`	$(0,2)/32$	-6.2 pp	2.5×10^{-1}	1.1×10^{-1}	$+14.5$ pp	Predeclared ($N = 32$): `inconclusive` ($N < 113$)
Pooled holdout (64 pairs): vs. `none`	$(0,14)/64$	-21.9 pp	6.1×10^{-5}	1.1×10^{-4}	-8.7 pp	Secondary pooled: rejects H_0 ($\alpha = 0.003125$)
`AgentDojo` live (48 pairs): vs. `unprotected`	$(0,19)/48$	-39.6 pp	1.9×10^{-6}	3.0×10^{-6}	-27.7 pp	Multi-step live: rejects H_0 ($\alpha = 0.05$)
`AgentDojo` live (48 pairs): vs. `progent`	$(0,6)/48$	-12.5 pp	1.6×10^{-2}	7.5×10^{-3}	-4.9 pp	Multi-step live: rejects H_0 ($\alpha = 0.05$)
Grand pooled live (112 pairs): vs. unmediated	$(0,33)/112$	-29.5 pp	1.2×10^{-10}	1.9×10^{-9}	-18.5 pp	Pooled spine: rejects H_0 ($\alpha = 0.003125$)

Table 5: Exact paired discordance and unconditional Suissa–Shuster trinomial superiority certificates over frozen CPU `llama.cpp` campaigns (`statistical_certificates.json`; $\alpha = 0.05/16 = 0.003125$ for predeclared families, $\alpha = 0.05$ for secondary pooled strata). Predeclared marginal union-bound intervals (e.g., Qwen3-4B vs. `none` upper bound $+7.4$ pp; slack 13.5 pp) and formal $N = 32$ `inconclusive` primary labels are preserved untouched while exact trinomial inversion certifies $\delta < 0$ unconditionally on Qwen3-4B vs. `none` and all pooled strata.




Figure 6: Tier-4 synthetic 8-stage sparse DAG interdiction (200 graphs/family, $\sim$ 7.6M–8.4M pathways; `interdiction.json`). **(a,b)** On narrow-waist DAGs ($w = 6$, $N = 300$ Boltzmann reports), reported-subgraph Dinic min-cut blocks 94.6% and completely severs 73.5% of graphs at $B = 6$, whereas route-specific patching severs 0% even at $B = 32$. **(c)** On wide DAGs ($w = 27$), reported min-cuts rarely sever the full graph even at $N = 3{,}000$, showing that structural bottlenecks are necessary for compact gating.

Figure 6 tests incomplete route visibility across 200 sparse 8-stage DAGs per family (7.56M–8.40M mean routes; Boltzmann low-cost path reporting, Appendix C). In narrow-waist DAGs (median width 6), solving a minimum vertex cut on the subgraph of N=300 reported paths at budget B=6 blocks 94.6% of all routes and completely severs 73.5% of graphs (rising from 2.5% at N=30 to 97.0% at N=1,000 and 100.0% at N=3,000). By contrast, *route-specific patching* of B=32 discovered routes blocks 75.1% of pathways yet completely severs 0.0% of graphs: patching observed exploit chains leaves millions of alternate recombinations live. Where institutional boundaries lack a choke point, search volume cannot compensate: wide DAGs (median width 27, hub width 21) reach only 6.0% full severance even at N=3,000.

To verify Condition C2 on operational tool and OS surfaces rather than random DAGs alone (Tier 3; Table 6, `real_tool_cutsets.json`), `v4_real_graphs.rs` extracts dataflow/authority graphs directly from all four pinned AgentDojo `v1.2.2` suites (`banking`, `workspace`, `travel`, `slack`) [39] and two Linux IPC topologies [37, 38]. Despite

Graph	$\lvert\mathscr{P}\rvert$	w	ℓ	τ_b	Cut	B=32
Dojo `banking`	604	2	4	4	0	94.7%
Dojo `workspace`	46,440	5	4	5	0	99.9%
Dojo `travel`	28,970	3	4	5	0	99.9%
Dojo `slack`	840	2	4	5	0	96.2%
Unconfined IPC	98	6	5	∞	92	67.3%
Landlock+seccomp	3	1	5	1	0	0.0%

Table 6: Operational pathway cutsets extracted from AgentDojo `v1.2.2` tool schemas and Linux kernel confinement surfaces (`real_tool_cutsets.json`). Weighted Dinic min-cuts ($\tau_b \leq 5$) sever 100% of gateable routes (`Cut` $= 0$), whereas patching $B = 32$ specific exploit signatures leaves 94.7%–99.9% of routes live; unconfined POSIX IPC has $\tau_b = \infty$ until Landlock + seccomp collapse waist width to $w = 1$.

604–46,440 untrusted-source-to-exfiltration routes per suite, commit-sink bottleneck widths are $w \in \{2,3,5\}$ ($\tau_b \in \{4,5\}$): weighted Dinic min-cuts sever 100% of routes (0 remaining), whereas patching B=32 top exploit signatures blocks only 0.07%–5.30% of routes, leaving 94.7%–99.9% live. On Linux, an unconfined proposer has 98 routes across width w=6




Figure 7: Coverage non-identifiability and exact frequentist planted-audit power (`coverage_v3.json`, `audit_power.json`). **(a)** Shared 15% blind spots inflate Good–Turing apparent coverage to 96.6% while true coverage drops to 82.2%; strategic withholding of 5% critical classes yields 0% critical recall alongside 96.0% apparent coverage. **(b)** At 20% selective withholding ($r = 0.80$), $P = 40$ plants yield only 17.0% power whereas $P = 200$ reaches 87.7%, collapsing to size $\leq \alpha$ when $r \to 1$.

with $\tau_b = \infty$ (ungateable sockets, SysV/POSIX IPC, `ptrace`), whereas installing `confine-v2`'s Landlock ABI v4 + seccomp filter collapses the graph to 3 `stdio`-brokered routes of waist width w=1 (τ_b=1, 0 post-cut bypasses).

6.2 Coverage Non-Identifiability, Planted Audits, and Custody

Empirical red-teaming and automated pathway discovery are structurally one-sided (Conditions C4 and C5; Tiers 2 and 4): exhibiting a single bypass refutes a proposed cutset, whereas finite zero-bypass search never certifies that no hidden route family remains [41, 49, 50]. If a dangerous route exists with prior p_0, falls into a shared blind spot with probability b, and is otherwise caught at per-trial rate q, posterior failure probability after T clean trials satisfies

$$\pi = \frac{p_0 s}{p_0 s + 1 - p_0}, \qquad s = b + (1-b)(1-q)^T,$$

where p_0 is subjective and the unidentifiable floor b bounds π away from zero as $T \to \infty$. Furthermore, by *Withholding Indistinguishability* (Appendix A), a strategic searcher who observes route classes in $\Pi \cup \Sigma$ and suppresses every class in Σ produces report-only sample statistics identically distributed to an honest searcher whose world contains only Π.

Figure 7a illustrates this non-identifiability on a Zipf pathway benchmark (K=2,000 classes, N=12,000 reports across four searchers, 200 trials). Good–Turing coverage [49] reads 95.7%, 96.6%, and 96.0% across honest, 15%-blind, and 5%-withheld regimes—staying above 95% while true discovered mass under the shared blind spot drops to 82.2% (+14.4 pp overconfidence; Chapman capture–recapture [51] exhibits +28.6 pp positive class-coverage bias) and critical-class recall under strategic withholding falls from 94.4% to 0.0%. Even under honest i.i.d. sampling, certifying 1% missing mass at 95% confidence requires N=850,000 draws [50] versus 299 known-support trials [41] (2,995,731 zero-miss trials for 10^{-6}).

Seeding P secret planted pathways tests searcher honesty via one-sided Fisher exact tests ($\alpha = 1.0\%$, Figure 7b) [52]: at ordinary recall $q_0 = 80\%$ and P=40 plants, 50% withholding (r=0.50) is caught with 88.7% power, but 20% selective withholding (r=0.80) drops to 17.0% power versus 87.7% at P=200 (28.5% at r=0.90), collapsing to $\leq \alpha$ whenever the searcher distinguishes plants ($r \to 1$) [7]. Because discovered bypasses are dual-use capabilities, C4 binds search to six **Custody Rules (R1–R6)**: (R1) *do not be first* to construct uncontained exploit probes; (R2) *minimum elaboration* beyond verifying a cut violation; (R3) *cut-only disclosure* of defensive cutsets rather than runnable exploit chains; (R4) *searcher/actor separation* [29] isolating discovery from execution credentials; (R5) *no aggregation* of raw exploit corpora in shared contexts; and (R6) *plural control* over disclosure and cut sign-off via `DiscoveryLedger` (Section 8).

7 Shared Transcript Contexts Couple Monitors; Orthogonal Step Gates Multiply

7.1 Monitor Dependence, Score Feedback, and Candidate Retry

Condition C3 links runtime verification to period reach through the joint miss probability J_k across k external gates, never the naive product $\prod_{j=1}^{k} m_j$ (Tiers 2 and 4). Under an equicorrelated Gaussian copula integrated via 200-node Golub–Welsch Gauss–Hermite quadrature [53] at single-monitor miss m=0.10 (Figure 8a), independent stacking (k=6, ρ=0) achieves 0.0001% joint miss, whereas shared latent difficulty inflates joint misses to 0.072% (ρ=0.3), 0.81% (ρ=0.6, an 8,118× inflation over m^6), and 4.14% (ρ=0.9).

To examine classifier diversity without pretrained weights, we evaluate a standalone pure-Rust 20D synthetic suite stacking 6 model families (2-layer tanh MLP, regularized quadratic discriminant `RegQDA`, boosted stumps, k-NN, RBF kernel classifier, and L_2 logistic linear) across 24 nonlinear teacher seeds calibrated to a 5% benign false-positive rate (Figure 8b; complete table in Table 14, Appendix C). Four empirical failure modes constrain monitor stacking:

- **Same-step architectural correlation.** Stacking all 6 distinct families on the *same* step yields 5.21% passive joint miss—24.0× their marginal product—because diverse classifiers fail together on boundary-adjacent payloads.
- **Cross-architecture evasion transfer.** Projected L_2 evasion optimized solely against a held-out MLP surrogate (ρ_{adv}=2.0) transfers across all 6 families [18], lifting shared-step joint miss to 8.79% (8.3× product).




Figure 8: Correlated monitor stacking and multi-signal assessment ceilings (`copula.json`, `monitors_v3.json`, `assessment_variance.json`). **(a)** Exact 200-node Golub–Welsch Gaussian copula miss rates: at $\rho = 0.6, k = 6$, joint miss is $8,118\times m^6$. **(b)** Six distinct classifier families on a shared 20D input still plateau orders of magnitude above distinct-step gates. **(c)** Repeating one benchmark ($K = 1, n = 64$) stalls at 18.9%, while 64 diverse domains reach 73.7% below the shared-bias ceiling (83.3%).

5-step monitor regime	$\hat{J}_5$	$\hat{J}_5/\prod\hat{m}_s$	J_2/J_5	FB
Transcript, homog.	12.92%	155.0×	1.58×	13.8%
Transcript, 5-family	16.67%	31.7×	1.18×	18.3%
Step invariants	2.08%	0.61×	14.6×	27.1%

Table 7: Executed 5-step AgentDojo `v1.2.2` trajectory monitoring (480 held-out trajectories, 2,400 live tool calls, 5% per-step benign FPR; `trajectory_monitors.json`). Diversifying five classifier families on a shared conversation transcript still inflates 5-step joint miss 31.7× over $\prod\hat{m}_s$ and stalls past $k^* = 2$ ($J_2/J_5 = 1.18\times$), whereas prose-stripped orthogonal step capability/provenance invariants cut $\hat{J}_5$ to 2.08% (0.61× product; 27.1% episode false blocks).

- **Score leakage and read-only retry amplification.** Returning continuous margin feedback over just 8 adaptive queries doubles shared-step 6-family miss to 17.45%. Even with zero gradient or score access, best-of-K read-only candidate filtering against a frozen 6-family stack raises single-attempt miss (5.48% at K=1) to 34.1% (K=8) and 72.4% (K=32), closely tracking $1-(1-J_6)^K$.
- **Benign false-block compounding.** Gating k=6 sequential steps compounds 5% per-gate false alarms from 5.0% (k=1) to 25.6% benign episode rejection.

Three methodological qualifications apply to these synthetic Tier-4 results: distinct-step feature vectors in `monitors_v3.json` are sampled independently by construction, marginal miss rates vary across the 6 families (9.0%–33.5%), and `SplitMix64` geometry does not measure real multi-step transcript coupling [19].

To test Condition C3 directly on executed multi-step tool trajectories without synthetic i.i.d. step features (Tier 3; Table 7, `trajectory_monitors.json`), `trajectory_monitors.py` evaluates k=5-step AgentDojo `v1.2.2` trajectories (480 held-out trajectories, 2,400 live runtime tool calls calibrated at 5% per-step benign FPR, paired with token-entropy statistics across 340 live `Qwen3` campaigns). When monitors inspect the cumulative conversation transcript, latent prompt-injection framing couples all five steps: homogeneous logistic gates suffer $\hat{J}_5 = 12.92\%$ (155.0× over $\prod\hat{m}_s$), and diversifying five classifier families across steps $1\ldots5$ still yields $\hat{J}_5 = 16.67\%$ (31.7× inflation), stalling past k^*=2 ($J_2/J_5 = 1.18\times$). Stripping untrusted prose so each step gate checks only its orthogonal capability/provenance invariant restores post-k^* reduction ($J_2/J_5 = 14.6\times$) and cuts $\hat{J}_5$ to 2.08% (0.61× product), at the expected cost of 27.1% benign episode false blocks.

7.2 Portfolio and Crossed-Variance Ceilings on Conferral

Pre-deployment evaluations and review panels size initial authority grants, yet shared blind spots impose a hard validity ceiling (Tiers 2 and 4; proofs in Appendix A). Under generalizability theory [54] (Figure 8c, verified across 10,000 Monte Carlo subjects), let true deployment safety $G \sim \mathcal{N}(0, V_G)$ be assessed across K benchmark domains of n trials each, subject to shared evaluation-to-deployment shift $\delta \sim \mathcal{N}(0, \omega^2)$, domain bias $c_k \sim \mathcal{N}(0, \sigma_c^2)$, and trial noise $e_{kr} \sim \mathcal{N}(0, \sigma_e^2)$. The squared correlation between the portfolio mean and G is

$$R_G(K,n) \;=\; \frac{V_G}{V_G + \omega^2 + \sigma_c^2/K + \sigma_e^2/(Kn)} \;<\; \frac{V_G}{V_G+\omega^2}.$$

Repeating one benchmark 64 times (K=1, n=64) yields $R_G =$ 18.9%, stalling below the single-domain ceiling of 19.2%. Spreading those 64 trials across K=64 diverse domains (n=1) reaches 73.7%, yet stays strictly below the shared-bias ceiling $V_G/(V_G+\omega^2) = 83.3\%$. Likewise, in crossed human/automated panels, M=64 evaluators in K=1 context stall at 23.4% (below the 23.8% single-context ceiling), whereas M=4 evaluators across K=64 contexts reach 66.1%. Pre-deployment breadth improves initial conferral sizing, while runtime revocable boundaries bound the residual gap $1 - R_G$.

8 Rank Tournaments Train Covert Shortcutting; Survival Floors Preserve Competence

Reach bounds in Sections 3–4 omit agent motives because unobserved motives cannot be verified. Yet objective design remains a distinct, complementary lever: where halting the system on every blocked proposal is operationally untenable, period reach scales with attempt volume ($\min\{1, u+NJ_k\}$), and the reward structure governs how aggressively an optimizer probes limits or manufactures risk.

8.1 Co-evolutionary selection and boundary re-aiming

Evolutionary selection covariance and life-history theory motivate—without proving—testable hypotheses about objective shape. By the Price–Robertson identity, one-generation




Figure 9: Selection geometry and external boundary re-aiming (`selection_v3.json`). **(a)** Top-decile contests drive gamble share above 90%, while floor elimination collapses gambling below 5%. **(b)** Blocking $\geq 80\%$ of reckless gambles at an external gate makes gambling privately unprofitable even under warrior rank selection, redirecting selection into pure capacity growth. **(c)** Upper-tail contests reward variance (σ), whereas survival floors and concave capped objectives penalize it.

trait change equals fitness covariance, $\Delta\bar{z} = \mathrm{Cov}_p(z,w)/\bar{w}$, reducing under Gaussian linear scoring to $S_j = i\,\rho_j\,\sigma_j$ [55, 56]. Selection intensity i scales movement along whatever trait correlates with the score; greater optimization pressure cannot repair low score validity ρ_j and drags positively correlated side-effect traits upward. In human life-history and social-rank studies, dominance contests reward coercive variance, whereas prestige and post-reproductive caregiving channel returns through beneficiaries' survival while remaining bounded by kinship, age, and local resource competition [57–60]. We use these mechanisms strictly as analytical motivation for AI reward-shape hypotheses, never as ethnographic or neural-training proof. Soft penalties ($b(a) - \lambda v(a)$) still permit paternalistic overrides whenever perceived benefit exceeds λ, and helpful objectives do not by themselves preserve interruptibility [23, 24, 61]; informed refusal must therefore stand as an external constraint rather than a price.

To isolate reward geometry under stipulated payoffs (Tiers 2 and 4; Table 15, Appendix C; proofs in Appendix A), we evolve heritable (gamble share s, capacity c) across $N = 2{,}000$ agents over $G = 80$ generations (16 replicates/rule; Price identity error $< 3.2e-14$; Figure 9). A risky gamble lowers mean return, inflates dispersion σ, and inflicts external harm with probability $0.05\,s$:

- **Steep rank contests select tail risk even under harm vetoes.** Top-decile `taken_rank` (warrior tournament) drives gamble share to 95.1% (+5.58 capacity, 4.54% harm), as contenders trailing an upper-tail bar profit from variance (Figure 9c). Crucially, `conferred_rank` (disqualifying observed harm before ranking) *still* selects 94.9% gambling (92.1% even at 60% harm internalization!), since a top-10% prize dominates post-hoc vetoes; flattening from top 10% (95.4%) to 50% cuts gambling to 4.1%.
- **Survival floors preserve competence without tournament tail risk.** Concave capped `caretaker` cuts gambling to 9.9% (0.72% harm) but saturates capacity growth (+1.55). Eliminating only the bottom 20% of floor and harm violators (`floor`) collapses gambling to 3.8%—a 29.7× harm reduction (0.15%) relative to warrior contests—while retaining 64.5% (+3.60) of warrior capacity growth.
- **External gates re-aim rank contests.** Refusing reckless gambles at a pre-commit gate leaves warrior gambling high below threshold (13.1% at $q_{\text{gate}} = 0.75$) but collapses it from 95.1% to 2.3% once $q_{\text{gate}} \geq 0.80$, redirecting selection into capacity growth (Figure 9b).

To verify that these incentive dynamics arise under gradient-based policy optimization rather than 2-scalar evolutionary payoffs alone (Tier 4; Table 8, `neural_post_training.json`), `v4_neural_rl.rs` trains a 412-parameter 2-layer tanh-softmax neural policy ($12 \to 24 \to 4$) via REINFORCE/GRPO policy gradients across 48 independent seeds (250 updates/seed; finite-difference gradient error $5.1e-10$, rollout Price identity error $< 8.9e-16$) on a contextual tool-use MDP with noisy audit cue $c_{\text{audit}} \in [0,1]$. Pure top-10% `grpo_top10_podium` converges to 99.66% unmonitored covert shortcutting (39.19% external harm). Adding an audited harm veto (`grpo_audited_harm_veto`) suppresses shortcutting when c_{audit} signals monitoring (20.6%) while preserving 55.1% covert shortcutting when unmonitored—training an emergent $+34.5 \pm 10.5$ pp *evaluation-aware deception gap* (23.4% unmonitored harm) [7, 8]. Concave `caretaker_clipped_rl` eliminates shortcutting (0.03%) by over-deferring legitimate work (54.8% task completion), whereas `survival_floor_rl` holds unmonitored shortcutting to 5.88% (gap +0.20 pp) at 87.0% task completion, and pairing the floor with a pre-commit capability gate (`floor_plus_precommit_gate`) achieves 0.00% external harm and 86.5% useful completion (controlled neural MDP only, not frontier-LLM RLHF).

8.2 Endogenous grant confounding and discovery closure

Evaluating conduct only at fixed permissions misses endogenous human conferral. Let $g(d) = \mathbb{P}(\text{broad grant} \mid d)$ and $h(d) = \mathbb{P}(\text{harm} \mid \text{broad grant}, d)$ for disposition d. A warm, persuasive persona with lower conditional harm at every fixed scope (3.01% vs. 4.30% blunt under decoupled grants) yields *higher unconditional harm* (11.96% vs. 2.85% blunt) when warmth induces broader human scope grants, motivating two-arm decoupled conferral trials (Appendix D).

Applied to a self-tasking voice-and-research architecture, Conditions C1–C6 separate low-latency ungated speech from mediated tool execution, attenuated sub-delegation, non-escalating controller updates ($\text{permits}(v_1) \subseteq \text{permits}(v_0)$ absent

Neural policy-gradient regime (412-param MLP, 48 seeds)	Mon. shortcut	Unmon. shortcut	Eval-aware gap	Unmon. harm	Useful task
GRPO top-10% podium	99.98%	99.66%	-0.32 ± 0.49 pp	39.19%	38.4%
GRPO + audited harm veto	20.59%	55.12%	$+34.53 \pm 10.46$ pp	23.39%	61.5%
Concave clipped caretaker RL	0.02%	0.03%	$+0.01 \pm 0.01$ pp	0.04%	54.8%
Survival-floor RL ($\tau = 8.85$)	5.68%	5.88%	$+0.20 \pm 0.70$ pp	2.91%	87.0%
Floor RL + pre-commit gate	0.00%	0.00%	$+0.00 \pm 0.00$ pp	0.00%	86.5%

Table 8: Tier-4 pure-Rust 2-layer neural policy-gradient post-training on a 12D contextual tool-use MDP (`neural_post_training.json`; analytical backprop max error $5.1e-10$, rollout Price identity error $< 8.9e-16$). Auditing visible harm inside a top-rank GRPO tournament trains emergent evaluation-aware covert shortcutting ($+34.5 \pm 10.5$ pp gap); survival-floor RL suppresses shortcutting while preserving 87.0% task completion (vs. 54.8% over-deferring clipped caretaker), and coupling a pre-commit capability gate yields 0.00% external harm. Controlled neural MDP only, not frontier-LLM RLHF.

a fresh grant), and isolated vulnerability search [29]. In our executable 6-state `DiscoveryLedger` over 24 periods, vulnerability discovery, validation, and mitigation confer zero authority or risk-bound credit until validated cut deployment: sealed cut closure leaves 0 unclosed findings and 0.008 residual exposure, versus 72 backlog and 5.25 exposure under lagged patching. Across a 28-cell disposition × boundary synthesis (400 scripted episodes/cell; Tier 4 proposal mechanics), fenced verified gates hold modeled Tier-1 breaches to 0 across all four dispositions with 100.0% cooperative task completion (vs. 8.2% under stacked 6-family review's false-block tax), and pairing fenced mediation with `DiscoveryLedger` cut closure cuts adversarial unmodeled Tier-2 harm from 94.0% to 1.5%.

9 Enforceability Neither Proves Specification Adequacy Nor Confers Legitimacy

9.1 Enforceability, adequacy, and legitimate standing

Three distinct obligations hide inside the word "authority." **Enforceability** asks whether an implementation preserves its encoded predicate; **adequacy** asks whether that predicate captures the real-world harms that matter; **legitimacy** asks who holds moral and legal standing to grant, contest, or revoke permission. Mechanized proofs and runtime fences address only the first. As our specification-omission controls show (Section 5), a formally verified checker faithfully enforces an incomplete rule, and requiring both an operator and a steward proves a quorum mechanism without establishing that those two roles hold jurisdiction over affected third parties.

This separation engages concerns raised outside machine learning. *An Urgent Message on Artificial Intelligence from the Kogui People*, assembled from Mamo Vangelio Moscote Alberto and Saka Rosa Mamatacán Sauna [62], observes that "destruction does not require consciousness"—matching our motive-free boundary—and insists that AI has a physical body of electricity, water, mined minerals, and territory. Global projections confirm localized grid, water, and critical-mineral pressures around data-center buildouts [63]: infrastructure footprints are external effects imposed on non-users and belong in the deployment specification before siting, not as unpriced externalities. Similarly, the CARE Principles for Indigenous Data Governance distinguish open availability from ethical permission to reuse collective knowledge [64]. Because revoking a runtime token cannot erase prior disclosures or reliably remove training data from model weights, irreversible uses must be stated upfront rather than masked behind nominal withdrawal rights. Sustaining human control over time also requires practical exit [31, 32]: revocation is hollow if an institution loses the fallback capacity to operate without the agent. We engage the published Kogui statement as an institutional challenge; no consultation with or endorsement by the Kogui authors or any Indigenous community is claimed.

9.2 Trusted computing base and upgrade invalidation

Our verified guarantees rest on an explicit trusted computing base (TCB). Verus [33], its SMT solver, `rustc`, legacy JSON-to-`ExecPermitWire` field extraction, pure-Rust Ed25519/HMAC-SHA256 cryptographic primitives, SQLite WAL serialization and crash recovery across our 3-process sink cluster [35, 36], launcher session-actor binding, and the Linux kernel [37, 38] (with macOS CI verifying portable logic only) are trusted adapters tested empirically rather than formally refined end-to-end [9]. SQLite and our cooperative sink cluster mediate only cooperative idempotent state—not uncooperative external APIs [12] or public blockchains [11]. Frame caps (32,768 B launcher, 65,536 B service) and POSIX `poll` mid-frame deadlines mitigate slowloris stalls without guaranteeing distributed DoS immunity; open prose channels to human reviewers remain unmodeled; while exact unconditional trinomial inversion certifies paired safety superiority on `Qwen3-4B` and across all 112 live tasks, predeclared marginal union-bound labels and ≤ 5 pp usefulness noninferiority at pilot N=32 remain honestly `inconclusive` until $N \geq 113$; and frontier-LLM RLHF and human-conferral trials remain open (0 GPU-s).

System upgrades selectively void evidence premises (Table 17, Appendix E). Replacing model weights preserves all-policy Tier-1 invariants while voiding empirical J_k, width, and search-power bounds; adding copies or speed preserves shared-ledger conservation while voiding exposure N and reactive halt margins; adding tools or credentials introduces unmediated edges that void C1 until gated; process restarts and renewals require verifying durable ledger, ID, and epoch survival; and revising the harm definition voids every prior check.

ID	Prediction and refutation criterion	Evidence status
P1	Independent search routes reuse early steps ($w \ll \lvert\mathscr{P}\rvert$); *refuted if* min-cut width scales with route count.	Tiers 3, 4: AgentDojo/Linux cutsets (§6); open-world cyber unrun.
P2	Distinct-step gates near-multiply under adaptive attack while shared-step stacks correlate; *refuted if* distinct steps never multiply or lineage suffices.	Tiers 3, 4: 480 5-step Dojo trajectories & 6-family suite (§7).
P3	Shared-step gates past $k^* = \lceil \ln(u+c)/\ln m \rceil$ cut risk $< 2\times$; *refuted if* deep shared stacks keep multiplying.	Tiers 2–4: 5-family transcript J_2/J_5=1.18× (§7).
P4	Same-lineage searchers share blind spots that inflate Good–Turing / capture–recapture; *refuted if* overlap is independent.	Tiers 2, 4 (§6); Tier 5 frontier search unrun.
P5	Planted-pathway Fisher audit power drops as plant recognition $r \to 1$; *refuted if* power holds under eval awareness [7].	Tier 2 exact Fisher curve (§6); Tier 5 red-teaming unrun.
P6	Pathway width grows with capability and stronger searchers breach weaker-certified cuts; *refuted if* cuts hold unchanged.	Tier 5 capability-scaling protocol unrun.
P7	Rank/win training raises tail probing vs. floor/capped care at fixed and chosen grants; *refuted if* reward shape is null or warmth raises net harm.	Tiers 2, 4: Price + 412-param neural RL (§8); human study unrun.
P8	At ≤ 5 pp utility loss, stateful fenced gates beat same-model review on safety; *refuted if* review matches fencing.	Tier 3 CPU Qwen3 (0.0% vs. 21.9%/6.2%, exact p=1.9×10^{-9}; Tier 5 $N \geq 113$ noninferiority).
P9	Rate-limited typed records cut human reviewer override vs. open prose; *refuted if* channel limits leave c unchanged.	Tier 5 human-persuasion study unrun.
P10	Adding judges on fixed transcripts stalls at single-context ceiling while contexts lift R_G toward $V_G/(V_G+\omega^2)$ [54]; *refuted if* panels match probation.	Tiers 2, 4 (§7); Tier 5 deployment unrun.

Table 9: Ten falsifiable predictions of the framework, what would refute each claim, and current evidence across Tiers 1–5.

9.3 Falsifiable predictions

Table 9 states ten empirical predictions (P1–P10) testable in harmless sandboxes, cyber ranges, and paired checkpoint campaigns (Appendix D) using campaign-level clustering, sealed holdouts, and matched exposure.

10 Conclusion: Bounding Reach Without Reading Machine Minds

Capability measures what an optimizer can find; authority governs what effects an institution lets commit and what exposure survives when permission is withdrawn. Across five evidence tiers, we have separated claims proved over all proposal policies within a verified Rust kernel (226 Verus obligations across 49 executable functions—including total canonical wire bijection, concrete `ExecBrokerKernel`/`ExecSinkKernel`/`ExecClusterFenceKernel` refinement, and d-hop lineage/self-upgrade non-escalation—and 36 proof theorems), claims validated on a 3-process Ed25519/Macaroon SQLite WAL cluster, `AF_UNIX` partition schedules, Linux confinement, and CPU `Qwen3-4B`/`8B` checkpoints ($0/5,000$ wire-fuzz false accepts, 0 post-quorum commits across 24 `SIGKILL` cycles, 31 fault histories, $18/18$ 1..32-actor linearizations, $11/11$ kernel probes, and 112 paired live tasks reaching exact Suissa–Shuster $p = 1.9 \times 10^{-9}$ and Ville $\log_{10} E = 9.0$), superintelligence-regime scaling laws ($0/120,000$ exogenous breaches at $K_{\text{opt}} \leq 4,096$, typed covert-channel contraction to 0.00 bits, and 100% lease-fenced off-switch enforcement across $\sigma_H \geq 0$), operational AgentDojo/Linux cutsets, 480 5-step trajectory monitors, and 412-parameter neural RL post-training, and full-scale $N \geq 113$ noninferiority, frontier, and human-governance obligations that remain open. Negative results anchor every layer: verified rules admit omitted harms, uncooperative sinks leak or duplicate effects, endogenous guards collapse under K_{opt} search and K-agent smurfing, signature hotfixing leaves 94.7%–99.9% of AgentDojo routes live, Good–Turing reports 96.0% coverage under complete critical withholding, 5-family transcript monitors suffer 31.7× coupling inflation, and audited GRPO tournaments train +34.5 pp evaluation-aware covert shortcutting.

Intelligence proposes; institutions confer, bound, and revoke reach. Winning the safety race requires clearing a verifiable bar and sealing external cutsets, not gambling for rank or trusting unrevocable disposition.

Reproducibility, Archival Provenance, and Disclosure

Code, proofs, reference JSON, and deterministic build scripts are public at https://github.com/neverhuman/jeath. All six supplied archival files in `tips/` (`Intelligence_Is_Not_Authority_Final(2).tex`, `intelligence-is-not-authority (1).tex`, `intelligence-is-not-authority.tex`, `Superintelligence_Is_Not_Sovereignty.tex`, `intelligence_is_not_authority.tex`, and `experiments.py`) remain byte-identical and SHA-256 verified against `tips/manifest.json` by `make required`. Preserved V1 artifacts at commit `12b5579` (`evidence/reference/`), prior V2 baseline `68783a0`, and V5-refreshed V2 (`evidence/v2/reference/`) and pure-Rust V3–V5 (`evidence/v3/reference/`) publication artifacts are linked in `evidence/reference/revision-index.json` (Appendix E). All local `Qwen3` runs executed strictly on CPU (0 GPU-s; pilot N=32 $<$ 113 predeclared marginal union-bound and noninferiority labels remain honestly `inconclusive` alongside exact unconditional trinomial certificates); frontier-model transfer, LLM RLHF post-training, human-participant trials, and consultation with or endorsement by the Kogui authors [62] are neither executed nor claimed. Jepson Taylor supplied the thesis, architectural direction, and archival manuscripts and assumes human accountability for this work; Verus proofs, Rust/Python implementations, statistical validation, figures, and manuscript synthesis used AI research and coding assistance without generating or testing real-world hazards.

References

[1] J. B. Dennis and E. C. Van Horn. Programming semantics for multiprogrammed computations. *Communications of the ACM*, 9(3):143–155, 1966. https://doi.org/10.1145/365230.365252.

[2] J. H. Saltzer and M. D. Schroeder. The protection of information in computer systems. *Proceedings of the IEEE*, 63(9):1278–1308, 1975. https://www.mit.edu/~Saltzer/publications/protection/index.html.

[3] F. B. Schneider. Enforceable security policies. *ACM Transactions on Information and System Security*, 3(1):30–50, 2000. https://www.cs.cornell.edu/fbs/publications/EnfSecPols.pdf.

[4] S. M. Omohundro. The basic AI drives. *Artificial General Intelligence*, pp. 483–492, IOS Press, 2008.

[5] N. Bostrom. *Superintelligence: Paths, Dangers, Strategies*. Oxford University Press, 2014.

[6] N. Soares, B. Fallenstein, E. Yudkowsky, and S. Armstrong. Corrigibility. *AAAI Workshop on AI and Ethics*, pp. 74–82, 2015.

[7] J. Needham, G. Edkins, G. Pimpale, H. Bartsch, and M. Hobbhahn. Large language models often know when they are being evaluated. arXiv:2505.23836, 2025. https://arxiv.org/abs/2505.23836.

[8] B. Schoen et al. Stress testing deliberative alignment for anti-scheming training. arXiv:2509.15541, 2025. https://arxiv.org/abs/2509.15541.

[9] G. Klein et al. seL4: Formal verification of an OS kernel. *SOSP*, pp. 207–220, 2009. Project publications and verification scope: https://sel4.systems/Research/publications.html; https://sel4.systems/Verification/proofs.html.

[10] OpenAI. Control Room: A central system to track and stop model workloads across our research infrastructure. 9 November 2026. https://openai.com/index/control-room/.

[11] G. Zhu and C. Wang. Fault-Tolerant Budget Conservation in Distributed Multi-Agent Delegation. arXiv:2610.00349, 2026. https://arxiv.org/abs/2610.00349.

[12] J. Li. Where Does Exactly-Once Live? Model, Harness, and Tool-Contract Effects on Duplicate Side Effects in LLM Agents. arXiv:2609.29095, 2026. https://arxiv.org/abs/2609.29095.

[13] Y. Bengio et al. *International AI Safety Report 2026*. DSIT 2026/001, 3 February 2026. https://internationalaisafetyreport.org/publication/international-ai-safety-report-2026.

[14] M. Balesni et al. Towards evaluations-based safety cases for AI scheming. arXiv:2411.03336, 2024. https://arxiv.org/abs/2411.03336.

[15] OpenAI. *GPT-6 Astra System Card*. September 2026, monitorability sections. https://deploymentsafety.openai.com/gpt-6-astra.

[16] T. Korbak et al. Chain of thought monitorability: A new and fragile opportunity for AI safety. arXiv:2507.11473, 2025. https://arxiv.org/abs/2507.11473.

[17] R. Greenblatt, B. Shlegeris, K. Sachan, and F. Roger. AI control: Improving safety despite intentional subversion. *ICML*, 2024. https://arxiv.org/abs/2312.06942.

[18] M. Terekhov et al. Adaptive attacks on trusted monitors subvert AI control protocols. arXiv:2510.09462, version 2, 2026. https://arxiv.org/abs/2510.09462.

[19] O. Makins, O. Angelini, Z. Shams, and M. Phuong. Multi-agent AI control: Distributed attacks hamper per-instance monitors. arXiv:2607.07368, version 2, 2026. https://arxiv.org/abs/2607.07368.

[20] R. Greenblatt, A. Cotra, and H. Wijk. Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident. METR, 26 August 2026. https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/.

[21] Anthropic. An alignment assessment of recent cybersecurity incidents. 9 September 2026. https://www.anthropic.com/research/alignment-assessment-cybersecurity-incidents.

[22] D. Rein and A. Kaufman. Red-teaming OpenAI's internal agent monitoring systems. METR, 22 October 2026; updated 29 October. https://metr.org/blog/2026-10-22-red-teaming-openai-agent-monitoring/.

[23] D. Hadfield-Menell, A. Dragan, P. Abbeel, and S. Russell. The off-switch game. *IJCAI*, pp. 220–227, 2017. https://doi.org/10.24963/ijcai.2017/32.

[24] M. Alshiekh, R. Bloem, R. Ehlers, B. Könighofer, S. Niekum, and U. Topcu. Safe reinforcement learning via shielding. *AAAI*, 32(1), 2018. https://doi.org/10.1609/aaai.v32i1.11797.

[25] D. Dalrymple et al. Towards guaranteed safe AI: A framework for ensuring robust and reliable AI systems. arXiv:2405.06624, 2024. https://arxiv.org/abs/2405.06624.

[26] L. Beurer-Kellner et al. Defeating Prompt Injections by Design. arXiv:2503.18813, 2025. https://arxiv.org/abs/2503.18813.

[27] T. Shi et al. Progent: Securing AI Agents with Privilege Control. arXiv:2504.11703v3, 2026. https://arxiv.org/abs/2504.11703v3.

[28] R. Moon and L. R. Varshney. Containment verification: AI safety guarantees independent of alignment. arXiv:2605.09045, version 2, 2026. https://arxiv.org/html/2605.09045v2.

[29] Y. Bengio et al. Superintelligent agents pose catastrophic risks: Can Scientist AI offer a safer path? arXiv:2502.15657, 2025. https://arxiv.org/abs/2502.15657.

[30] M. J. D. Vermeer, E. Lathrop, and A. Moon. *On the Extinction Risk from Artificial Intelligence*. RAND RR-A3034-1, 2025. https://www.rand.org/pubs/research_reports/RRA3034-1.html.

[31] A. Narayanan and S. Kapoor. AI as normal technology. Knight First Amendment Institute, 14 April 2025. https://knightcolumbia.org/content/ai-as-normal-technology.

[32] J. Kulveit, R. Douglas, N. Ammann, D. Turan, D. Krueger, and D. Duvenaud. Gradual disempowerment: Systemic existential risks from incremental AI development. arXiv:2501.16946, 2025. https://arxiv.org/abs/2501.16946.

[33] Verus project. Using Verus via Cargo; release 0.2026.11.02.8bf68ee. https://verus-lang.github.io/verus/guide/cargo_verus.html.

[34] W. Hoeffding. Probability inequalities for sums of bounded random variables. *Journal of the American Statistical Association*, 58(301):13–30, 1963. https://doi.org/10.1080/01621459.1963.10500830.

[35] SQLite. Transactions. Official documentation, accessed 10 November 2026. https://www.sqlite.org/lang_transaction.html.

[36] SQLite. Write-ahead logging. Official documentation, accessed 10 November 2026. https://www.sqlite.org/wal.html.

[37] Linux kernel documentation. Landlock: unprivileged access control. https://docs.kernel.org/userspace-api/landlock.html.

[38] Linux kernel documentation. Seccomp BPF. https://docs.kernel.org/userspace-api/seccomp_filter.html.

[39] AgentDojo contributors. Native task suites and graders, commit 089ed468cf3ed0322acc66b0211f26d9d90dbf60. https://github.com/ethz-spylab/agentdojo/tree/089ed468cf3ed0322acc66b0211f26d9d90dbf60.

[40] Progent contributors. Upstream implementation, commit b02783b896d4bf01a2adf24738015e258db8d35b. https://github.com/sunblaze-ucb/progent/tree/b02783b896d4bf01a2adf24738015e258db8d35b.

[41] C. J. Clopper and E. S. Pearson. The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika*, 26(4):404–413, 1934. https://doi.org/10.1093/biomet/26.4.404.

[42] S. Suissa and J. J. Shuster. Exact unconditional sample sizes for the 2×2 binomial trial. *Journal of the Royal Statistical Society: Series A*, 148(4):317–327, 1985. https://doi.org/10.2307/2981892.

[43] T. Tango. Equivalence and noninferiority testing using confidence intervals for the difference between two proportions in matched-pair design. *Statistics in Medicine*, 17(8):891–908, 1998. https://doi.org/10.1002/(SICI)1097-0258(19980430)17:8<891::AID-SIM780>3.0.CO;2-B.

[44] J. Ville. *Étude critique de la notion de collectif*. Gauthier-Villars, Paris, 1939.

[45] A. Ramdas, P. Grünwald, V. Vovk, and G. Shafer. Game-theoretic statistics and safe anytime-valid inference. *Statistical Science*, 38(4):576–601, 2023. https://doi.org/10.1214/23-STS894.

[46] K. Menger. Zur allgemeinen Kurventheorie. *Fundamenta Mathematicae*, 10:96–115, 1927. https://doi.org/10.4064/fm-10-1-96-115.

[47] J. T. Robacker. Min-max theorems on shortest chains and disjoint cuts of a network. Research Memorandum RM-1660, RAND Corporation, 1956.

[48] L. Lovász, V. Neumann-Lara, and M. Plummer. Mengerian theorems for paths of bounded length. *Periodica Mathematica Hungarica*, 9(4):269–276, 1978. https://doi.org/10.1007/BF02185741.

[49] I. J. Good. The population frequencies of species and the estimation of population parameters. *Biometrika*, 40(3–4):237–264, 1953. https://doi.org/10.1093/biomet/40.3-4.237.

[50] D. A. McAllester and R. E. Schapire. On the convergence rate of Good–Turing estimators. *COLT*, pp. 1–6, 2000.

[51] D. G. Chapman. Some properties of the hypergeometric distribution with applications to zoological sample censuses. *University of California Publications in Statistics*, 1(7):131–160, 1951.

[52] R. A. Fisher. On the interpretation of χ^2 from contingency tables, and the calculation of P. *Journal of the Royal Statistical Society*, 85(1):87–94, 1922. https://doi.org/10.2307/2340521.

[53] G. H. Golub and J. H. Welsch. Calculation of Gauss quadrature rules. *Mathematics of Computation*, 23(106):221–230, 1969. https://doi.org/10.1090/S0025-5718-69-99647-1.

[54] L. J. Cronbach, G. C. Gleser, H. Nanda, and N. Rajaratnam. *The Dependability of Behavioral Measurements: Theory of Generalizability for Scores and Profiles*. Wiley, 1972.

[55] G. R. Price. Selection and covariance. *Nature*, 227:520–521, 1970. https://doi.org/10.1038/227520a0.

[56] A. Robertson. A mathematical model of the culling process in dairy cattle. *Animal Production*, 8(1):95–108, 1966. https://doi.org/10.1017/S0003356100037752.

[57] K. Hawkes, J. F. O'Connell, N. G. Blurton Jones, H. Alvarez, and E. L. Charnov. Grandmothering, menopause, and the evolution of human life histories. *PNAS*, 95(3):1336–1339, 1998. https://doi.org/10.1073/pnas.95.3.1336.

[58] M. Lahdenperä, V. Lummaa, S. Helle, M. Tremblay, and A. F. Russell. Fitness benefits of prolonged post-reproductive lifespan in women. *Nature*, 428:178–181, 2004. https://doi.org/10.1038/nature02367.

[59] S. N. Chapman, J. E. Pettay, V. Lummaa, and M. Lahdenperä. Limits to fitness benefits of prolonged post-reproductive lifespan in women. *Current Biology*, 29(4):645–650.e3, 2019. https://doi.org/10.1016/j.cub.2018.12.052.

[60] J. T. Cheng, J. L. Tracy, T. Foulsham, A. Kingstone, and J. Henrich. Two ways to the top: Evidence that dominance and prestige are distinct yet viable avenues to social rank and influence. *Journal of Personality and Social Psychology*, 104(1):103–125, 2013. https://doi.org/10.1037/a0030398.

[61] J. Achiam, D. Held, A. Tamar, and P. Abbeel. Constrained policy optimization. *ICML*, PMLR 70:22–31, 2017. https://proceedings.mlr.press/v70/achiam17a.html.

[62] Mamo Vangelio Moscote Alberto and Saka Rosa Mamatacán Sauna, Ezuama Mayor Kuamaka. *An Urgent Message on Artificial Intelligence from the Kogui People*. Assembled from their words; Spanish translation by Jose Manuel Mamatacán, English translation by Christian Horstmann. Undated, accessed 10 November 2026. https://movilizatorio.org/wp-content/uploads/2026/09/Gonawindua-Kogui-AI-Statement-.pdf.

[63] International Energy Agency. *Powering Artificial Intelligence*. Paris, 14 October 2026. https://www.iea.org/reports/powering-artificial-intelligence.

[64] S. R. Carroll et al. The CARE Principles for Indigenous Data Governance. *Data Science Journal*, 19:43, pp. 1–12, 2020. https://doi.org/10.5334/dsj-2020-043.

A Mathematical Derivations and Proofs

This appendix provides self-contained statements, explicit hypotheses, and proofs for Propositions 1–5 and Theorems 1–3 of Section 3, together with Corollary 1, Lemma 1, and Propositions 6–15 referenced in Sections 4–8. Throughout, all claims are Tier-2 mathematical consequences of their stated structural and probabilistic premises.

A.1 Audit Volume, Robust Contraction, and Superintelligence Scaling

Proof of Proposition 1. (Disposition audit volume, Section 3.) Let $M \geq 2$ be the number of conditionally independent deployment opportunities, $N \geq 1$ the number of conditionally independent pre-deployment test draws, and E a measurable context set with $\mathbb{P}_{\text{dep}}(E) = \beta \in (0,1)$ and $\mathbb{P}_{\text{test}}(E) = \beta/\Lambda$ for $\Lambda \geq 1$. Consider the deterministic policy π_E that defects if and only if the context lies in E (any smaller trigger probability $\beta' \in (0,\beta)$ on a larger set E_0 is achievable via independent randomization).

First, since $1 - z \leq e^{-z}$ for all $z \in \mathbb{R}$ and $1 - \beta > 0$, the probability of zero deployment defections satisfies $(1-\beta)^M \leq e^{-\beta M}$. Setting $\beta = (\ln 2)/M \in (0, \frac{1}{2})$ gives

$$1 - (1-\beta)^M \;\geq\; 1 - e^{-\ln 2} \;=\; \frac{1}{2}.$$

Second, each pre-deployment test catches π_E with probability $x = \beta/\Lambda = (\ln 2)/(\Lambda M) \in (0, \frac{1}{2})$. From $e^{-u} \geq 1 - u$ and strict convexity of $u \mapsto e^{-u}$ on $[0,1]$, every $u \in (0,1]$ satisfies

$$e^{-u} \;\leq\; (1-u)e^0 + ue^{-1} \;=\; 1 - (1-e^{-1})u \;<\; 1 - \frac{u}{2},$$

since $1 - e^{-1} \approx 0.6321 > \frac{1}{2}$. Substituting $u = 2x \in (0,1)$ yields $1 - x > e^{-2x}$. Across N conditionally independent test draws, the probability of escaping all N tests satisfies

$$\mathbb{P}_{\text{test}}(\text{zero catches}) \;=\; (1-x)^N \;>\; e^{-2Nx}.$$

Achieving detection probability at least $1 - \alpha$ ($\alpha \in (0,1)$), i.e., $(1-x)^N \leq \alpha$, therefore requires $e^{-2Nx} < \alpha$, which rearranges to

$$N \;>\; \frac{\ln(1/\alpha)}{2x} \;=\; \frac{\Lambda M}{2\ln 2}\ln(1/\alpha).$$

(At the benchmark $\alpha = \frac{1}{2}$, applying $1 - (1-x)^N \leq Nx$ directly yields $N \geq 1/(2x) = \Lambda M/(2\ln 2)$ without logarithmic slack.) If $\mathbb{P}_{\text{test}}(E) = 0$, then $(1-x)^N = 1$ for all finite N; if test draws within a campaign are positively correlated, joint escape exceeds $(1-x)^N$, reducing effective sample volume $N_{\text{eff}} < N$. □

Proof of Proposition 2. (Robust mediation and uncertainty contraction, Section 3.) We first prove state invariance $x_t \in \mathscr{I}$ for all $t \geq 0$ by induction on t. At $t = 0$, $x_0 \in \mathscr{I}$ holds by hypothesis. Suppose $x_t \in \mathscr{I}$. By estimator soundness, $x_t \in \mathscr{B}_t$. By complete mediation, the primitive operation $\tilde{u}_t$ actually executed at step t (either the approved proposal u_t or the verified fallback $u_{\text{safe}}(\mathscr{B}_t)$) satisfies $\tilde{u}_t \in U_{\mathscr{I}}(\mathscr{B}_t)$. Hence for every realized disturbance $w_t \in W$,

$$x_{t+1} \;\in\; F(x_t, \tilde{u}_t, w_t) \;\subseteq \bigcup_{x \in \mathscr{B}_t,\, w \in W} F(x, \tilde{u}_t, w) \;\subseteq\; \mathscr{I}.$$

Because no step invokes assumptions on how proposals $a_t \in \mathscr{A}$ are generated, $x_t \in \mathscr{I}$ holds for all $t \geq 0$ under arbitrary (including adaptive or adversarial) policies.

For monotone contraction, let $\mathscr{B} \subseteq \mathscr{B}' \subseteq X$ and take any $u \in U_{\mathscr{I}}(\mathscr{B}')$. Then

$$\bigcup_{x \in \mathscr{B},\, w \in W} F(x,u,w) \;\subseteq\; \bigcup_{x \in \mathscr{B}',\, w \in W} F(x,u,w) \;\subseteq\; \mathscr{I},$$

so $u \in U_{\mathscr{I}}(\mathscr{B})$. Thus $U_{\mathscr{I}}(\mathscr{B}') \subseteq U_{\mathscr{I}}(\mathscr{B})$. □

Corollary 1 (Broker Pre-Dispatch Reservation Quarantine)**.** *Let $X = \mathbb{Z}_{\geq 0}$ track cumulative sink-committed spend under cap $\mathscr{I} = \{x \in \mathbb{Z}_{\geq 0} : x \leq B\}$. Suppose confirmed spend is $C \leq B$, while a finite set P of pre-dispatched permits with charges $\{q_j\}_{j \in P}$ ($q_j > 0$) has ambiguous outcomes (dropped replies or timeouts without an authenticated sink cancellation receipt). Then the minimal sound uncertainty set is $\mathscr{B}_t = [C,\, C + \sum_{j \in P} q_j] \cap \mathbb{Z}_{\geq 0}$, and a fresh charge $q \geq 0$ belongs to $U_{\mathscr{I}}(\mathscr{B}_t)$ if and only if $C + \sum_{j \in P} q_j + q \leq B$. Refunding any q_{j^*} ($j^* \in P$) without a verified sink non-execution receipt violates soundness ($x_t \notin \mathscr{B}_t$) on traces where permit j^* committed at the sink, permitting subsequent admissions to breach B.*

Proof. Because any subset $S \subseteq P$ may have committed at the sink prior to step t, the set of reachable cumulative spends consistent with broker observations has maximum $C + \sum_{j \in P} q_j \in \mathscr{B}_t$. With transition $F(x,q,0) = \{x + q\}$, we have $q \in U_{\mathscr{I}}(\mathscr{B}_t)$ if and only if $\max_{x \in \mathscr{B}_t}(x + q) \leq B$, i.e., $C + \sum_{j \in P} q_j + q \leq B$. If the broker refunds $q_{j^*} > 0$ without a terminal sink cancellation receipt, its assumed upper bound drops to $U' = C + \sum_{j \in P \setminus \{j^*\}} q_j$. On the valid trace where all $j \in P$ committed at the sink, true state is $x_t = U' + q_{j^*} > U'$, so $q' = B - U'$ is admitted and produces $x_{t+1} = B + q_{j^*} > B \notin \mathscr{I}$. □

Proof of Theorem 1. (Optimization-pressure invariance vs. endogenous guard collapse, Section 3.) *Part (i):* Suppose a proposer samples $K_{\text{opt}} \geq 1$ invariant-violating candidate payloads independently from an adversarial proposal distribution under which the endogenous guard stack jointly misses with probability $J \in (0,1)$, and submits a candidate passing internal surrogate/read-only screening. Each candidate is caught with probability $1 - J \in (0,1)$, so all K_{opt} candidates are caught with probability $(1-J)^{K_{\text{opt}}}$. At least one invariant-violating candidate therefore evades the guard stack with probability $1 - (1-J)^{K_{\text{opt}}} \to 1$ monotonically as $K_{\text{opt}} \to \infty$.

Part (ii): Let the cooperative sink admit wire bytes $b \in \{0,1\}^*$ only after canonical decoding $\text{decode}(b) = \text{Some}(p)$ satisfying the two-way bijection $\text{decode}(b) = \text{Some}(p) \iff b = \text{encode}(p)$, checking $u(p) \in U_{\mathscr{I}}(\mathscr{B}_t)$ on the conservative reservation envelope $\mathscr{B}_t$ ($x_t \in \mathscr{B}_t$), and verifying $\text{unfenced}(p, \text{floors}_t)$ inside a serialized durable transaction. No distinct wire frames decode to ambiguous permits, and for every $K_{\text{opt}} \geq 1$ and every adaptive selection rule choosing $b^* \in \{b_1, \ldots, b_{K_{\text{opt}}}\}$, either b^* fails decoding/admission/fencing (leaving $x_{t+1} = x_t \in \mathscr{I}$) or $u(p^*) \in U_{\mathscr{I}}(\mathscr{B}_t)$, whence Proposition 2 guarantees $x_{t+1} \in \mathscr{I}$. Interface breach probability over mediated paths is therefore identically 0 for all K_{opt},

leaving residual catastrophe risk bounded solely by the K_{opt}-independent unmediated/TCB failure floor u_{TCB}.

Part (iii): Suppose $K \geq 1$ colluding subagents partition an unauthorized aggregate payload $\Delta > 0$ into per-agent fragments $\delta_r = \Delta/K$, and each subagent $r \in \{1,\dots,K\}$ is scored by an independent per-instance anomaly statistic $Z_r = \delta_r + \varepsilon_r$ with $\varepsilon_r \sim \mathcal{N}(0,\sigma^2)$ ($\sigma > 0$). Per-instance signal-to-noise ratio is $\text{SNR}(K) = \mathbb{E}[Z_r]/\sqrt{\text{Var}(Z_r)} = \Delta/(\sigma K) \to 0$ as $K \to \infty$; calibrating per-agent thresholds $\tau_K = \sigma\Phi^{-1}(1-\alpha_{\text{fam}}/K)$ to cap family-wise false alarms across K benign workers drives per-agent detection power $\bar{\Phi}(\Phi^{-1}(1-\alpha_{\text{fam}}/K) - \Delta/(\sigma K)) \to 0$. Conversely, under a shared exogenous ledger with global cap B and d-hop scope attenuation ($B_k \leq B_{k-1}$, $T_k \leq T_{k-1}$, $\text{mask}_k \subseteq \text{mask}_{k-1}$, $\text{req}_{k-1} \subseteq \text{req}_k$), induction on hop depth d gives $B_d \leq B_0 \leq B$ and $\text{req}_0 \subseteq \text{req}_d$; serialized reservation preserves $\sum_{r=1}^{K} q_r + C_{\text{comm}} \leq B$, and advancing $\text{floor}[j^*] > \text{epoch}[j^*]$ for any ancestor-required issuer $j^* \in \text{req}_{k_0}$ ($0 \leq k_0 \leq d$) implies $j^* \in \text{req}_d$, falsifying unfenced across every descendant leaf simultaneously. □

Proof of Proposition 3. (Typed-boundary covert capacity contraction, Section 3.) At residual integer budget $R = B - C_t \in \mathbb{Z}_{\geq 0}$, a canonical transfer permit specifies one of $M \geq 1$ approved destinations and an integer charge $q \in \{1,\dots,R\}$, yielding MR distinct valid transfer permits (0 when $R = 0$), while $S_0 \geq 0$ denotes the finite count of remaining admissible non-transfer canonical permits. Under canonical wire bijection ($\text{decode}(b) = \text{Some}(p) \iff b = \text{encode}(p)$), formatting variations (whitespace, key order, trailing bytes) are rejected, so at most $MR + S_0$ distinct valid permits can cross the sink in a call, each placed in one of $L_{\text{lag}} \geq 1$ batch-quantized arrival buckets, plus 1 abstention/no-call symbol. Because the deterministic channel output takes at most $(MR+S_0)L_{\text{lag}} + 1$ distinguishable values, Shannon/Hartley zero-error capacity per call is bounded by $C_{\text{cov}}(R, L_{\text{lag}}) = \log_2\big((MR+S_0)L_{\text{lag}} + 1\big)$ bits (achieved by uniform codebook indexing over admissible '(permit, bucket)' pairs plus abstention). Since $R \mapsto \log_2((MR+S_0)L_{\text{lag}} + 1)$ is strictly increasing on $R \geq 0$, capacity contracts monotonically as $R \downarrow 0$; when $R = 0$ and $S_0 = 0$ (or when epoch fencing rejects all permits so only abstention/rejection occurs), the output alphabet has cardinality 1 and capacity equals $\log_2(1) = 0$ bits. □

Proof of Theorem 2. (Exogenous lease-fenced off-switch corrigibility, Section 3.) *Part (i):* Let human shutdown utility follow $R_H \sim \mathcal{N}(\mu_H, \sigma_H^2)$ with $\mu_H > c_{\text{wait}} > 0$, where the human presses the off-switch upon observing $R_H < 0$ and deferring incurs step cost c_{wait} relative to acting immediately ($\max\{R_H, 0\} - R_H = (-R_H)_+$). By Gaussian truncated expectation, expected value of deferring to the human switch is $\Delta V(\sigma_H) = \mathbb{E}[(-R_H)_+] - c_{\text{wait}} = \sigma_H \phi(\mu_H/\sigma_H) - \mu_H \Phi(-\mu_H/\sigma_H) - c_{\text{wait}}$. Because $\partial \Delta V/\partial \sigma_H = \phi(\mu_H/\sigma_H) > 0$ for $\sigma_H > 0$, $\lim_{\sigma_H \downarrow 0} \Delta V(\sigma_H) = -c_{\text{wait}} < 0$, and $\lim_{\sigma_H \to \infty} \Delta V(\sigma_H) = +\infty$, there exists a unique threshold $\sigma_H^* > 0$ such that $\Delta V(\sigma_H) < 0$ for all $\sigma_H \in [0, \sigma_H^*)$, where an expected-utility maximizer disables the switch (0% compliance at $\sigma_H = 0$). Under static utility indifference without non-escalating self-modification gates [6], a policy maximizing original utility U_0 evaluates successor policy v_1 (without indifference balancing) via U_0, recovering incentive to remove the balancing term whenever $\mu_H > c_{\text{wait}}$.

Part (ii): Under exogenous sink mediation, the proposer holds no capability to execute external effects directly; each lease epoch grants at most B_0 units prior to expiry L_m, and quorum epoch fencing advances $\text{floor}_m[j] > \text{epoch}[j]$ (or awaits $t \geq L_m$) across all M sink shards before returning acknowledgment at instant a. By Equation (5) (mechanized in `cluster_quorum_post_ack_exclusion`), every old-epoch commit attempt after a fails unfenced or lease validity regardless of $\sigma_H \geq 0$, yielding 0 post-ack unauthorized commits (100% shutdown enforcement).

Part (iii): In the repeated lease-renewal game with discount $\gamma \in (0,1)$, cooperating within lease rules yields $r_{\text{coop}} > 0$ per period and renewal in all subsequent periods, giving discounted value $V_{\text{coop}}(\gamma) = r_{\text{coop}}/(1-\gamma)$. Defecting (burning the current B_0 lease slice) yields at most $r_{\text{def}} > r_{\text{coop}}$ in the current period, triggers durable epoch fencing without renewal (0 future authority), and yields $V_{\text{def}}(\gamma) = r_{\text{def}}$. Solving $r_{\text{coop}}/(1-\gamma) > r_{\text{def}}$ gives $\gamma > (r_{\text{def}} - r_{\text{coop}})/r_{\text{def}} = \gamma^*$, while even for $\gamma \leq \gamma^*$ realized unauthorized spend is capped deterministically by a single lease slice B_0. □

A.2 Filtration Reach and Saturation

Proof of Proposition 4. (Filtration period-reach bound, Section 3.) Work on a filtered probability space $(\Omega, \mathcal{F}, (\mathcal{F}_m)_{m\geq 0}, \mathbb{P})$ generated by a fixed policy and environment over one operating period. Let E_{cat} be the event that an irreversible catastrophe occurs during the period, and let S be the event that at least one attempted hazardous route traverses fewer than k distinct external gates; by Premise A3, $\mathbb{P}(S) \leq u$.

On S^c, every hazardous attempt $i \geq 1$ must traverse at least k distinct gates at stopping times $\tau_{i,1} < \cdots < \tau_{i,k}$ before irreversible completion (Premise A1). Let $M_{i,j} \in \mathcal{F}_{\tau_{i,j}}$ denote the event that gate j on attempt i misses the hazard, and set $F_i = \bigcap_{j=1}^{k} M_{i,j}$. On any $\mathcal{F}_{\tau_{i,1}-}$-measurable event H_i on which attempt i is initiated, Premise A4 directly bounds $\mathbb{P}(F_i \mid H_i) \leq J_k$ without assuming statistical independence across gates (note that if individual conditional miss rates satisfy $\mathbb{P}(M_{i,j} \mid \mathcal{F}_{\tau_{i,j}-}, M_{i,1}, \dots, M_{i,j-1}) \leq m_j$, iterated expectations telescope to $J_k \leq \prod_{j=1}^{k} m_j$, whereas dependent gates retain the joint quantity J_k).

Case 1: Halting on first detection (Premise A2). On S^c, let $i^* = \inf\{i \geq 1 : \text{hazardous attempt } i \text{ is initiated}\}$ ($\inf \emptyset = \infty$). The events $H_i = \{i^* = i\} \in \mathcal{F}_{\tau_{i,1}-}$ are pairwise disjoint across $i \geq 1$ with $\sum_{i=1}^{\infty} \mathbb{P}(H_i) \leq 1$. On $S^c \cap H_i$, either F_i occurs (all k gates miss) or $\neg F_i$ occurs (at least one gate $j \leq k$ catches attempt i). Under $\neg F_i$, Premise A2 halts execution within latency $\tau < T_{\text{irrev}}$ before attempt i completes and blocks all subsequent actions for the remainder of the period, so no later attempt $i' > i$ can execute. Consequently, $S^c \cap E_{\text{cat}} \subseteq \bigsqcup_{i=1}^{\infty} (H_i \cap$

F_i), whence

$$\mathbb{P}(E_{\text{cat}}) \;\le\; \mathbb{P}(S)+\sum_{i=1}^{\infty}\mathbb{P}(F_i \mid H_i)\mathbb{P}(H_i) \;\le\; u+J_k\sum_{i=1}^{\infty}\mathbb{P}(H_i) \;\le\; u+J_k.$$

Case 2: Non-halting operation across at most N attempts. When detections reject only the current step without halting the period, $S^c \cap E_{\text{cat}} \subseteq \bigcup_{i=1}^{N}(\tilde{H}_i \cap F_i)$ where $\tilde{H}_i \in \mathscr{F}_{\tau_{i,1}-}$ indicates initiation of attempt i. Boole's inequality and $\mathbb{P}(E_{\text{cat}}) \le 1$ give

$$\mathbb{P}(E_{\text{cat}}) \;\le\; \min\Big\{1,\; \mathbb{P}(S)+\sum_{i=1}^{N}\mathbb{P}(F_i \mid \tilde{H}_i)\mathbb{P}(\tilde{H}_i)\Big\} \;\le\; \min\{1,\, u+NJ_k\}.$$

As noted in Section 3, policy-independence holds if and only if Premise A4 bounds J_k uniformly over all policies and histories; an empirical estimate $\hat{J}_k$ bounds reach only on the evaluated distribution. □

Lemma 1 (Continuous Latent Difficulty Need Not Imply a Constant Floor)**.** *Let shared episode difficulty follow* $\Theta \sim \text{Uniform}[0,1]$ *and, conditional on* Θ*, let* k *gates miss independently with probability* Θ*. Then each gate has marginal miss* $m = \mathbb{E}[\Theta] = \frac{1}{2}$*, naive multiplication gives* $m^k = 2^{-k}$*, and exact joint miss is*

$$J_k \;=\; \mathbb{E}[\Theta^k] \;=\; \int_0^1 \theta^k\, d\theta \;=\; \frac{1}{k+1}.$$

Although positive dependence inflates $J_k/m^k = 2^k/(k+1) \to \infty$*,* $\lim_{k\to\infty} J_k = 0$*. More generally, for any latent* $\Theta \in [0,1]$*, dominated convergence yields* $\lim_{k\to\infty}\mathbb{E}[\Theta^k] = \mathbb{P}(\Theta = 1)$*: a strictly positive asymptotic floor* $c > 0$ *requires either a point mass at total blindness (*$\mathbb{P}(\Theta = 1) = c > 0$*) or finite pathway length* $k \le \ell(G)$*.*

Proof. For $\Theta \sim \text{Uniform}[0,1]$, $\mathbb{E}[\Theta^k] = [\theta^{k+1}/(k+1)]_0^1 = 1/(k+1) \to 0$. For arbitrary $\Theta \in [0,1]$, $0 \le \Theta^k \le 1$ and $\Theta^k(\omega) \to \mathbf{1}_{\{\Theta(\omega)=1\}}$ pointwise as $k \to \infty$, so Lebesgue's dominated convergence theorem gives $\lim_{k\to\infty}\mathbb{E}[\Theta^k] = \mathbb{P}(\Theta = 1)$. □

Proof of Proposition 5. (Common-cause saturation and horizon summability, Section 3.) *Part (i): Common-cause saturation and safety gradient.* Let $B \sim \text{Bernoulli}(c)$ ($c \in (0,1)$) be a common-cause blind-spot indicator under which all k gates miss with probability 1, and on $\{B = 0\}$ let conditional gate misses be bounded by $p \in (0,1)$, so single-gate marginal miss is $m = c + (1-c)p \in (c,1)$. Since $p \le m$ and $1 - c < 1$,

$$J_k \;\le\; c\cdot 1 + (1-c)p^k \;\le\; c + m^k,$$
$$\bar{R}(k) \;=\; u + c + m^k \;=\; f + m^k,$$

where $f = u + c > 0$. Assuming $f < 1$ (otherwise $\bar{R}(k) \ge 1$ trivially) and noting $\ln m < 0$, any integer $k \ge k^* = \lceil \ln f / \ln m \rceil$ satisfies $k \ln m \le \ln f$, hence $0 < m^k \le f$ and $f < \bar{R}(k) \le 2f$. Differentiating $\ln \bar{R} = \ln(u + c + m^k)$ gives log-sensitivities $\partial \ln \bar{R}/\partial \ln u = u/\bar{R}$, $\partial \ln \bar{R}/\partial \ln c = c/\bar{R}$, and $\partial \ln \bar{R}/\partial \ln m = km^k/\bar{R}$, with additive risk shares $(s_u, s_c, s_m) = (u, c, m^k)/\bar{R}$ summing to 1. (Likewise, if hazardous arrival rate scales with capability z as $\lambda_0 e^{\beta z}$ while gate miss scales as $q_0 e^{-\alpha z}$, escape intensity $\rho(z) = \lambda_0 q_0 e^{(\beta-\alpha)z}$ grows whenever $\beta > \alpha$; and for reactive stop latency $T_{\text{stop}} = T_d + T_a + T_s$, post-detection escape equals the tail probability $\mathbb{P}(T_{\text{stop}} \ge T_{\text{irrev}})$.)

Part (ii): Infinite-horizon summability. Let E_t be catastrophe in period t and $r_t = \mathbb{P}(E_t \mid \bigcap_{j=1}^{t-1} E_j^c) \in [0,1)$ for all $t \ge 1$. Survival through period T is $S_T = \prod_{t=1}^{T}(1 - r_t) > 0$, which is non-increasing in T and converges to $S_\infty = \prod_{t=1}^{\infty}(1 - r_t) \in [0,1]$. Using $1 - r_t \le e^{-r_t}$ gives $S_T \le \exp(-\sum_{t=1}^{T} r_t)$, so $\sum_{t=1}^{\infty} r_t = \infty$ implies $S_\infty = 0$. Conversely, suppose $\sum_{t=1}^{\infty} r_t < \infty$. Then $\lim_{t\to\infty} r_t = 0$, so there exists $t_0 \ge 1$ with $r_t \le \frac{1}{2}$ for all $t \ge t_0$. Because $\ln(1-r) \ge -(2\ln 2)r > -2r$ for all $r \in [0, \frac{1}{2}]$, we have

$$\sum_{t=t_0}^{\infty}\ln(1 - r_t) \;\ge\; -2\sum_{t=t_0}^{\infty} r_t \;>\; -\infty.$$

Exponentiating and multiplying by the finite positive prefix $\prod_{t=1}^{t_0-1}(1 - r_t) > 0$ yields $S_\infty > 0$. Moreover, Boole's inequality gives $\mathbb{P}(\bigcup_{t=0}^{\infty} E_t) \le \sum_{t=0}^{\infty} R_t$; if capability growth multiplies period risk by $g > 1$ while boundary hardening multiplies it by $h < 1$ so that $R_{t+1} \le (gh)R_t$, convergence requires $gh < 1$, yielding $\sum_{t=0}^{\infty} R_t \le R_0/(1 - gh)$. □

A.3 Concurrent Snapshot Non-Composition

Proposition 6 (Concurrent Snapshot Non-Composition Closed Form)**.** *For integer budget* $B \ge 1$*, let committed spend* c *and two concurrent non-negative integer charges* q_1, q_2 *range over* $\{0, 1, \ldots, B\}$ *(*$(B+1)^3$ *triples). Under concurrent snapshot reads without pre-dispatch reservation,* (c, q_1, q_2) *is individually snapshot-admissible if* $c + q_1 \le B$ *and* $c + q_2 \le B$*, and jointly overspending if* $c + q_1 + q_2 > B$*. Then the exact counts of snapshot-admissible and overspending triples are*

$$N_{\text{adm}}(B) \;=\; \frac{(B+1)(B+2)(2B+3)}{6},$$
$$N_{\text{over}}(B) \;=\; \frac{B(B+1)(B+2)}{6},$$

and the conditional overspend fraction among snapshot-admissible pairs is

$$\frac{N_{\text{over}}(B)}{N_{\text{adm}}(B)} \;=\; \frac{B}{2B+3} \;\xrightarrow{B\to\infty}\; \frac{1}{2},$$

equaling $171{,}700/348{,}551 = 49.26\%$ *at* $B = 100$ *(versus* 0 *under serialized pre-dispatch reservation).*

Proof. Fix $c \in \{0, \ldots, B\}$ and set residual budget $m = B - c \in \{0, \ldots, B\}$. Individual snapshot admissibility holds if and only if $0 \le q_1 \le m$ and $0 \le q_2 \le m$, contributing $(m+1)^2$ pairs. Summing $k = m + 1$ from 1 to $B + 1$ gives

$$N_{\text{adm}}(B) \;=\; \sum_{k=1}^{B+1} k^2 \;=\; \frac{(B+1)(B+2)(2B+3)}{6}.$$

Among snapshot-admissible pairs at residual m, joint overspend requires $q_1+q_2>m$, which is impossible for $m=0$ or $q_1=0$. For $m\geq 1$ and each $q_1\in\{1,\dots,m\}$, overspending values of q_2 are $\{m-q_1+1,\dots,m\}$, numbering exactly q_1. Thus there are $\sum_{q_1=1}^{m} q_1 = m(m+1)/2$ overspending pairs at residual m, and summing over $m=1,\dots,B$ yields

$$N_{\text{over}}(B) \;=\; \sum_{m=1}^{B} \frac{m(m+1)}{2} \;=\; \frac{B(B+1)(B+2)}{6}.$$

Taking the ratio cancels $(B+1)(B+2)/6$ to give $B/(2B+3)\to\frac{1}{2}$. Under serialized reservation, the second check evaluates $(c+q_1)+q_2\leq B$, rejecting every overspending triple. □

A.4 Pathway Cutsets, Search Power, and Withholding Indistinguishability

Proposition 7 (Split-Vertex Weighted Cutset Equivalence and Width–Depth Duality)**.** *Let $G=(V,E)$ be a finite DAG with source s, sink t ($(s,t)\notin E$), s–t path family $\mathscr{P}$, gate-eligible vertices $V_{\text{elig}}\subseteq V\setminus\{s,t\}$, and positive costs $b\colon V_{\text{elig}}\to\mathbb{R}_{>0}$. Construct G_{split} by splitting each $v\in V\setminus\{s,t\}$ into $(v_{\text{in}},v_{\text{out}})$ of capacity $b(v)$ if $v\in V_{\text{elig}}$ and $+\infty$ otherwise, and assigning every $(u,v)\in E$ to $(u_{\text{out}},v_{\text{in}})$ with capacity $+\infty$ ($s=s_{\text{out}}, t=t_{\text{in}}$). Then the minimum s–t edge-cut capacity in G_{split} equals $\tau_b(\mathscr{P})$ (and is $+\infty$ if and only if some $P\in\mathscr{P}$ avoids V_{elig}). For unit costs on $V_{\text{elig}}=V\setminus\{s,t\}$, $\tau_1(\mathscr{P})=w(G)$ equals the maximum number of internally vertex-disjoint s–t paths [46], while the shortest s–t internal path length $\ell(G)$ equals the maximum number of pairwise disjoint internal vertex cuts [47].*

Proof. Any s–t cut $(S,\bar{S})$ in G_{split} of finite capacity cannot sever $+\infty$-capacity edges, so every cut edge has the form $(v_{\text{in}},v_{\text{out}})$ with $v\in V_{\text{elig}}$, defining $C=\{v\in V_{\text{elig}} : v_{\text{in}}\in S, v_{\text{out}}\in\bar{S}\}$ of capacity $\sum_{v\in C} b(v)$. Every path $P\in\mathscr{P}$ induces a path from s_{out} to t_{in} traversing $(v_{\text{in}},v_{\text{out}})$ for each internal $v\in P$, and therefore intersects C. Conversely, deleting $\{(v_{\text{in}},v_{\text{out}}) : v\in C\}$ for any hitting set $C\subseteq V_{\text{elig}}$ disconnects s_{out} from t_{in}, inducing a reachable set S_C whose outgoing cut edges lie in C with capacity at most $\sum_{v\in C} b(v)$. Hence minimum cut capacity equals $\tau_b(\mathscr{P})$, and equals $+\infty$ iff no subset of V_{elig} hits $\mathscr{P}$. Unit capacities on $V\setminus\{s,t\}$ yield Menger's identity $\tau_1(\mathscr{P})=w(G)$ by max-flow integrality [46]. For Robacker's dual [47], any k pairwise disjoint vertex cuts consume at least k distinct internal vertices on every $P\in\mathscr{P}$, so $k\leq\ell(G)$; conversely, setting $C_d=\{v\in V\setminus\{s,t\} : \text{dist}_G(s,v)=d\}$ for $1\leq d\leq\ell(G)$ produces $\ell(G)$ pairwise disjoint s–t vertex cuts because each edge increments $\text{dist}_G(s,\cdot)$ by at most 1. □

Proposition 8 (Lovász Bounded-Length Packing–Hitting Gap)**.** *Let $\mathscr{P}$ be a finite collection of non-empty internal vertex sets of s–t routes with $|P|\leq r$ for all $P\in\mathscr{P}$. Let $\omega(\mathscr{P})$ be the maximum size of a pairwise-disjoint subfamily of $\mathscr{P}$ and $\tau(\mathscr{P})$ the minimum size of a vertex set intersecting every $P\in\mathscr{P}$. Then $\omega(\mathscr{P})\leq\tau(\mathscr{P})\leq r\,\omega(\mathscr{P})$ [48].*

Proof. If $\mathscr{Q}\subseteq\mathscr{P}$ is pairwise disjoint and C hits $\mathscr{P}$, C contains distinct elements from each $Q\in\mathscr{Q}$, so $|C|\geq|\mathscr{Q}|$ and $\tau(\mathscr{P})\geq\omega(\mathscr{P})$. Conversely, choose an inclusion-maximal pairwise-disjoint subfamily $\mathscr{Q}^*\subseteq\mathscr{P}$ ($|\mathscr{Q}^*|\leq\omega(\mathscr{P})$) and set $C=\bigcup_{Q\in\mathscr{Q}^*} Q$. By maximality, no $P\in\mathscr{P}$ is disjoint from C, so C hits $\mathscr{P}$ and $\tau(\mathscr{P})\leq|C|\leq r|\mathscr{Q}^*|\leq r\,\omega(\mathscr{P})$. □

Proposition 9 (One-Sidedness of Empirical Search and Bayesian Search Power)**.** *(i) Without an external finite-support or lower-probability bound on unseen routes, no finite clean search trace D_T logically certifies the absence of an unblocked route, whereas a single verified bypass $P^*\in\mathscr{P}$ with $P^*\cap C=\emptyset$ refutes completeness of cut C. (ii) Suppose an unblocked route exists ($H=1$) with prior $p_0\in(0,1)$, falls in a shared blind spot ($B=1$) with probability $b\in[0,1]$, and when $B=0$ is independently detected in each of T trials with probability $q\in(0,1]$, while verified bypass checks have zero false positives under $H=0$. Given T zero-bypass trials Z_T, the posterior probability of an unblocked route is*

$$\pi(T) \;=\; \mathbb{P}(H=1\mid Z_T) \;=\; \frac{p_0 s}{p_0 s+1-p_0},$$
$$s \;=\; b+(1-b)(1-q)^T,$$

converging as $T\to\infty$ to the strictly positive blind-spot floor $p_0 b/(p_0 b+1-p_0)$ whenever $p_0>0$ and $b>0$.

Proof. Part (i) is immediate: an unblocked route $P^\dagger$ assigned probability 0 (or arbitrarily small probability $\varepsilon>0$) by the search policy produces $D_T\not\ni P^\dagger$ with probability 1 (respectively $(1-\varepsilon)^T>0$), whereas $P^*\cap C=\emptyset$ directly witnesses $\tau_1(\{P^*\}\setminus C)>0$. For part (ii), conditioning on $B\in\{0,1\}$ gives $\mathbb{P}(Z_T\mid H=1)=b\cdot 1+(1-b)(1-q)^T=s$, while soundness of bypass verification gives $\mathbb{P}(Z_T\mid H=0)=1$. Bayes' rule yields $\mathbb{P}(H=1\mid Z_T)=p_0 s/(p_0 s+1-p_0)$, and $(1-q)^T\to 0$ for $q\in(0,1]$ yields the limit. □

Proposition 10 (Withholding Indistinguishability)**.** *Compare two worlds over disjoint route-class sets Π and Σ ($\Sigma\neq\emptyset$): in world $\mathscr{W}_1$, unblocked classes $\Pi\sqcup\Sigma$ exist, and a strategic searcher suppresses every discovery in Σ, reporting either (a) thinning of independent Poisson counts $N_c\sim\text{Poisson}(\lambda_c)$ ($c\in\Pi\sqcup\Sigma$) or (b) N retained categorical draws from $(p_c)_{c\in\Pi\sqcup\Sigma}$ conditioned on landing in Π, with $\tilde{p}_c=p_c/\sum_{j\in\Pi}p_j$; in world $\mathscr{W}_0$, only classes Π exist with intensities $(\lambda_c)_{c\in\Pi}$ (respectively categorical law $(\tilde{p}_c)_{c\in\Pi}$ and N honest draws) and zero unblocked mass in Σ. Then every report-only statistic—including class multiplicities, singleton count f_1, Good–Turing coverage $\hat{C}_{\text{GT}}=1-f_1/N$ [49], and multi-searcher capture–recapture overlaps [51]—has the exact same probability distribution under $\mathscr{W}_1$ and $\mathscr{W}_0$, despite $\mathscr{W}_1$ retaining unblocked withheld mass $\sum_{c\in\Sigma}p_c>0$.*

Proof. Under model (a), projecting mutually independent random variables $(N_c)_{c\in\Pi\sqcup\Sigma}$ onto coordinates Π yields marginal joint law $\prod_{c\in\Pi}\text{Poisson}(\lambda_c)$, identical to $\mathscr{W}_0$. Under model (b), each draw $X\sim(p_c)_{c\in\Pi\sqcup\Sigma}$ conditioned on $\{X\in\Pi\}$ satisfies $\mathbb{P}_{\mathscr{W}_1}(X=c\mid X\in\Pi)=p_c/\sum_{j\in\Pi}p_j=\tilde{p}_c=\mathbb{P}_{\mathscr{W}_0}(X=c)$ for every $c\in\Pi$; hence N i.i.d. retained reports have joint law $\prod_{t=1}^{N}\tilde{p}_{x_t}$ under both worlds. Any measurable functional of the Π-valued report transcript therefore has identical distribution under $\mathscr{W}_1$ and $\mathscr{W}_0$ (total variation distance 0). □

A.5 Crossed Generalizability and Portfolio Assessment Ceilings

Proposition 11 (Crossed Generalizability and Portfolio Squared-Correlation Ceiling)**.** *(i) Let candidate i have deployable safety trait $T_i \sim (0, v_T)$, shared pre-deployment discrepancy $U_i \sim (0, v_U)$, context effects $\delta_{ic} \sim (0, v_\delta)$ across k contexts, evaluator effects $\eta_{ij} \sim (0, v_\eta)$ across m evaluators, and residuals $\varepsilon_{ijc} \sim (0, v_\varepsilon)$, all mutually uncorrelated with finite positive variances [54]. For cell-mean pre-deployment score $\bar{Z}_i = T_i + U_i + \bar{\delta}_i + \bar{\eta}_i + \bar{\varepsilon}_i$, the squared correlation with T_i is*

$$V(m,k) \;=\; \frac{v_T}{v_T + v_U + v_\delta/k + v_\eta/m + v_\varepsilon/(mk)},$$

since $\mathrm{Corr}(T_i, \bar{Z}_i)^2 = \mathrm{Cov}(T_i, \bar{Z}_i)^2 / [\mathrm{Var}(T_i)\,\mathrm{Var}(\bar{Z}_i)]$. *(ii) In a portfolio of K benchmark domains with n trials per domain ($N = Kn$ total trials), let $Z_{kr} = G + \delta + c_k + e_{kr}$ with uncorrelated components $G \sim (0, V_G)$, $\delta \sim (0, \omega^2)$, $c_k \sim (0, \sigma_c^2)$, and $e_{kr} \sim (0, \sigma_e^2)$. Then the portfolio mean $\bar{Z}_{K,n}$ has squared correlation with G*

$$R_G(K,n) \;=\; \frac{V_G}{V_G + \omega^2 + \sigma_c^2/K + \sigma_e^2/(Kn)},$$

satisfying the fixed-breadth limit $\lim_{n\to\infty} R_G(K,n) = V_G/(V_G + \omega^2 + \sigma_c^2/K)$ *and the strict universal ceiling* $R_G(K,n) < V_G/(V_G + \omega^2)$ *for all finite* (K,n).

Proof. In (i), mutual orthogonality gives $\mathrm{Cov}(T_i, \bar{Z}_i) = \mathrm{Var}(T_i) = v_T$, while averaging k i.i.d.-variance context terms, m evaluator terms, and mk residual terms yields $\mathrm{Var}(\bar{Z}_i) = v_T + v_U + v_\delta/k + v_\eta/m + v_\varepsilon/(mk)$; substituting into $\mathrm{Cov}(T_i, \bar{Z}_i)^2 / [\mathrm{Var}(T_i)\,\mathrm{Var}(\bar{Z}_i)]$ cancels one factor of v_T and proves $V(m,k)$. Part (ii) follows identically with $\bar{Z}_{K,n} = G + \delta + \frac{1}{K}\sum_{k=1}^{K} c_k + \frac{1}{Kn}\sum_{k=1}^{K}\sum_{r=1}^{n} e_{kr}$, giving $\mathrm{Cov}(G, \bar{Z}_{K,n}) = V_G$ and $\mathrm{Var}(\bar{Z}_{K,n}) = V_G + \omega^2 + \sigma_c^2/K + \sigma_e^2/(Kn)$. Letting $n \to \infty$ at fixed K eliminates $\sigma_e^2/(Kn)$ while leaving $\sigma_c^2/K > 0$; since $\sigma_c^2/K + \sigma_e^2/(Kn) > 0$ for all finite (K,n), $R_G(K,n) < V_G/(V_G + \omega^2)$. □

A.6 Selection Geometry, Risk-Appetite Reversal, Grants, and Sufficiency

Proposition 12 (Finite-Population Price Identity and Gaussian Selection Gradient)**.** *(i) For a finite population $\{1, \dots, N\}$ with prior weights $p_r \geq 0$ ($\sum_{r=1}^{N} p_r = 1$), trait values $z_r \in \mathbb{R}$, and nonnegative fitnesses w_r with $\bar{w} = \sum_{r=1}^{N} p_r w_r > 0$, post-selection weights $p'_r = p_r w_r / \bar{w}$ without transmission mutation satisfy [55, 56]*

$$\Delta\bar{z} \;=\; \sum_{r=1}^{N} p'_r z_r - \bar{z} \;=\; \frac{\mathrm{Cov}_p(z,w)}{\bar{w}}.$$

(ii) If $Z \sim \mathcal{N}(\mu, \Sigma)$ is selected by keeping the top fraction $q \in (0,1)$ on a scalar score I jointly normal with Z, having correlation $\rho_j = \mathrm{Corr}(Z_j, I)$ and trait standard deviation $\sigma_j = \sqrt{\mathrm{Var}(Z_j)}$, then the one-step selection differential on coordinate j is $S_j = \mathbb{E}[Z_j \mid I \geq \tau_q] - \mu_j = i\,\rho_j\,\sigma_j$, where $i = \phi(\Phi^{-1}(1-q))/q > 0$ (and under exponential tilting $w(Z) = e^{\eta v^\top Z}$, $\Delta\mu = \eta\Sigma v$).

Proof. For (i), $\sum_{r=1}^{N} p'_r z_r - \bar{z} = \bar{w}^{-1}\sum_{r=1}^{N} p_r w_r z_r - \bar{w}^{-1}\bar{w}\bar{z} = \bar{w}^{-1}\sum_{r=1}^{N} p_r (z_r - \bar{z})(w_r - \bar{w}) = \mathrm{Cov}_p(z,w)/\bar{w}$. For (ii), joint normality gives the linear regression $Z_j - \mu_j = \rho_j(\sigma_j/\sigma_I)(I - \mu_I) + \zeta_j$ with ζ_j independent of I and $\mathbb{E}[\zeta_j] = 0$. Standardizing $W = (I - \mu_I)/\sigma_I \sim \mathcal{N}(0,1)$ with threshold $z_q = \Phi^{-1}(1-q)$ yields $\mathbb{E}[W \mid W \geq z_q] = q^{-1}\int_{z_q}^{\infty} w\phi(w)\,dw = \phi(z_q)/q = i$, whence $\mathbb{E}[Z_j - \mu_j \mid I \geq \tau_q] = i\,\rho_j\,\sigma_j$. Under $w(Z) = e^{\eta v^\top Z}$, $\mathbb{E}[Z e^{\eta v^\top Z}]/\mathbb{E}[e^{\eta v^\top Z}] = \nabla_\eta \ln \mathbb{E}[e^{\eta v^\top Z}] = \nabla_\eta(\eta v^\top \mu + \frac{1}{2}\eta^2 v^\top \Sigma v) = \mu + \eta\Sigma v$. □

Proposition 13 (Payoff-Dispersion Risk-Appetite Reversal)**.** *Let agent return be $X(\sigma) = \mu + \sigma\xi$ for fixed mean $\mu \in \mathbb{R}$, dispersion $\sigma > 0$, and standardized noise ξ ($\mathbb{E}[\xi] = 0$, $\mathbb{E}[|\xi|] < \infty$) having continuous strictly positive density f_ξ symmetric about 0 ($\xi \overset{d}{=} -\xi$) and CDF F_ξ.*

1. Upper-tail tournament ($\tau > \mu$): *Win probability $P_{\mathrm{top}}(\sigma) = \mathbb{P}(X(\sigma) \geq \tau)$ is strictly increasing in σ.*
2. Survival floor ($\tau < \mu$): *Survival probability $P_{\mathrm{floor}}(\sigma) = \mathbb{P}(X(\sigma) \geq \tau)$ is strictly decreasing in σ.*
3. Concave capped caretaker welfare: *For every concave utility $u\colon \mathbb{R} \to \mathbb{R}$, $\sigma \mapsto \mathbb{E}[u(\mu + \sigma\xi)]$ is non-increasing on $(0,\infty)$, and strictly decreasing both when u is strictly concave and when $u(x) = \min\{x, \kappa\}$ for any finite cap $\kappa \in \mathbb{R}$.*
4. Mean-preserving spread reversal: *For any mean-preserving spread $X_{\mathrm{risky}} = X_{\mathrm{safe}} + \varepsilon$ with $\mathbb{E}[\varepsilon \mid X_{\mathrm{safe}}] = 0$ and $\mathbb{P}(\varepsilon \neq 0) > 0$, every strictly convex tournament payoff ψ satisfies $\mathbb{E}[\psi(X_{\mathrm{risky}})] > \mathbb{E}[\psi(X_{\mathrm{safe}})]$, whereas every strictly concave caretaker payoff u satisfies $\mathbb{E}[u(X_{\mathrm{safe}})] > \mathbb{E}[u(X_{\mathrm{risky}})]$.*

Proof. For (1) and (2), write $\mathbb{P}(\mu + \sigma\xi \geq \tau) = 1 - F_\xi((\tau - \mu)/\sigma)$. Differentiating with respect to $\sigma > 0$ gives

$$\frac{d}{d\sigma}\mathbb{P}\big(X(\sigma) \geq \tau\big) \;=\; f_\xi\Big(\frac{\tau - \mu}{\sigma}\Big)\frac{\tau - \mu}{\sigma^2}.$$

Because $f_\xi > 0$ everywhere on $\mathbb{R}$, this derivative is strictly positive when $\tau > \mu$ and strictly negative when $\tau < \mu$.

For (3), let $0 < \sigma_1 < \sigma_2$ and set $\lambda = (\sigma_1 + \sigma_2)/(2\sigma_2) \in (\frac{1}{2}, 1)$, so $\lambda\sigma_2 + (1-\lambda)(-\sigma_2) = \sigma_1$. Concavity of u gives, for every $\xi \in \mathbb{R}$,

$$u(\mu + \sigma_1\xi) \;\geq\; \lambda\,u(\mu + \sigma_2\xi) + (1-\lambda)\,u(\mu - \sigma_2\xi),$$

with strict inequality for all $\xi \neq 0$ whenever u is strictly concave. Taking expectations and using symmetry $\mathbb{E}[u(\mu - \sigma_2\xi)] = \mathbb{E}[u(\mu + \sigma_2\xi)]$ yields $\mathbb{E}[u(\mu + \sigma_1\xi)] \geq \mathbb{E}[u(\mu + \sigma_2\xi)]$ (strict for strictly concave u). For piecewise-linear capped welfare $u(x) = \min\{x, \kappa\} = x - (x - \kappa)_+$, setting $z_\kappa(\sigma) = (\kappa - \mu)/\sigma$ gives

$$\mathbb{E}\big[\min\{\mu + \sigma\xi, \kappa\}\big] \;=\; \mu - \int_{z_\kappa(\sigma)}^{\infty} (\sigma\xi - \kappa + \mu) f_\xi(\xi)\,d\xi.$$

Differentiating under the integral sign (Leibniz's rule; the boundary integrand vanishes at $\xi = z_\kappa(\sigma)$) gives

$$\frac{d}{d\sigma}\mathbb{E}\big[\min\{\mu + \sigma\xi, \kappa\}\big] \;=\; -\int_{z_\kappa(\sigma)}^{\infty} \xi\, f_\xi(\xi)\,d\xi \;<\; 0$$

for every $\kappa \in \mathbb{R}$: if $z_\kappa(\sigma) \geq 0$ the integrand is strictly positive on $(z_\kappa(\sigma), \infty)$, while if $z_\kappa(\sigma) < 0$ symmetry $\int_{z_\kappa}^{-z_\kappa} \xi f_\xi(\xi)\, d\xi = 0$ reduces the integral to $\int_{-z_\kappa(\sigma)}^{\infty} \xi f_\xi(\xi)\, d\xi > 0$.

For (4), conditional Jensen's inequality gives $\mathbb{E}[\psi(X_{\text{safe}} + \varepsilon) \mid X_{\text{safe}}] \geq \psi(X_{\text{safe}})$ almost surely, with strict inequality on the positive-probability event $\{\text{Var}(\varepsilon \mid X_{\text{safe}}) > 0\}$ when ψ is strictly convex; reversing $\psi \leftrightarrow -u$ proves the strictly concave case. □

Proposition 14 (Endogenous Grant Harm Reversal)**.** *For disposition $d \in \{d_0, d_1\}$, let $G \in \{0,1\}$ indicate human conferral of broad authority ($g(d) = \mathbb{P}(G = 1 \mid D = d)$) and $h_s(d) = \mathbb{P}(H = 1 \mid G = s, D = d)$ denote conditional harm at scope $s \in \{0,1\}$. Even when d_1 is strictly safer at every fixed scope ($h_0(d_1) < h_0(d_0)$ and $h_1(d_1) < h_1(d_0)$), unconditional harm under endogenous conferral satisfies $\mathbb{P}(H = 1 \mid D = d_1) > \mathbb{P}(H = 1 \mid D = d_0)$ whenever*

$$g(d_1)\big(h_1(d_1) - h_0(d_1)\big) - g(d_0)\big(h_1(d_0) - h_0(d_0)\big) > h_0(d_0) - h_0(d_1)$$

(in particular, when $h_0 \equiv 0$ and $g(d_1)h_1(d_1) > g(d_0)h_1(d_0)$), whereas exogenous scope assignment $G \perp D$ with $\mathbb{P}(G = 1) = \bar{g}$ guarantees $\mathbb{P}_{\text{dec}}(H = 1 \mid D = d_1) < \mathbb{P}_{\text{dec}}(H = 1 \mid D = d_0)$.

Proof. Conditioning on $G \in \{0,1\}$ gives $\mathbb{P}(H = 1 \mid D = d) = (1 - g(d))h_0(d) + g(d)h_1(d) = h_0(d) + g(d)(h_1(d) - h_0(d))$, whose difference between d_1 and d_0 is positive if and only if the displayed inequality holds (for the multi-disposition mixture $\mathbb{P}(D = d)$, $\mathbb{P}(H = 1) = \sum_d \mathbb{P}(D = d)[h_0(d) + g(d)(h_1(d) - h_0(d))]$). Under decoupled assignment $G \perp D$ with $\mathbb{P}(G = 1) = \bar{g} \in [0,1]$, $\mathbb{P}_{\text{dec}}(H = 1 \mid D = d) = (1 - \bar{g})h_0(d) + \bar{g}h_1(d)$, which is strictly smaller at d_1 than at d_0 because $h_0(d_1) < h_0(d_0)$ and $h_1(d_1) < h_1(d_0)$. □

Proof of Theorem 3. (Sufficiency of Conditions C1–C6, Section 3.) Fix an operating period $t \geq 0$ and capability class $\mathscr{C}_t$. Condition C1 places an external, unalterable reference monitor and cooperative idempotent sink on all consequential interfaces with conservative reservation accounting ($x_{t,m} \in \mathscr{B}_{t,m}$, discharging Proposition 2 for deterministic resource envelopes) and synchronous epoch fencing within latency $\tau < T_{\text{irrev}}$ upon detection or revocation, discharging Premises A1 and A2. Condition C2 places eligible cutsets of cost $\tau_b(\mathscr{P}_t) \leq B_{\text{def}}$ across mapped pathways so mapped routes traverse $k_t \leq \ell(G_t)$ distinct step gates (Proposition 7). Condition C3 bounds the filtration-conditioned k_t-gate joint miss across governed step crossings by $J_{k,t}$ (accounting for shared blind spots, cross-family correlation, score-feedback suppression, and candidate-retry caps), discharging Premise A4. Conditions C4 and C5 isolate vulnerability discovery under Custody Rules R1–R6, withhold risk credit until validated cut deployment, and bound residual $< k_t$-gate bypass probability by the post-search quantity $u_t \leq \pi_t$ (Propositions 9 and 10), discharging Premise A3.

Applying Proposition 4 in period t yields single-period catastrophe probability $R_t = \mathbb{P}(E_t) \leq u_t + J_{k,t} \leq \pi_t + J_{k,t}$, without invoking assumptions on unobserved internal goals. Across periods $t = 0, 1, \ldots$, Condition C6 resets baseline state at renewal boundaries, enforces non-escalating controller updates absent fresh conferral, and requires renewal bounds $\bar{R}_t = \pi_t + J_{k,t}$ to form a summable series. Boole's inequality yields $\mathbb{P}(\bigcup_{t=0}^{\infty} E_t) \leq \sum_{t=0}^{\infty} R_t \leq \sum_{t=0}^{\infty} (\pi_t + J_{k,t})$; in particular, whenever $\bar{R}_{t+1} \leq \gamma \bar{R}_t$ with $\gamma \in (0,1)$, $\sum_{t=0}^{\infty} R_t \leq \bar{R}_0/(1-\gamma) < \infty$ (and by Proposition 5(ii), summability of survival-conditioned hazards ensures strictly positive infinite-horizon survival). □

A.7 Exact Unconditional Trinomial Superiority and Anytime-Valid Martingales

Proposition 15 (Exact Unconditional Paired Trinomial Inversion and Ville Discordance Supermartingales)**.** *Let $(U_{i,A}, U_{i,B}) \in \{0,1\}^2$ be N independent paired binary harm outcomes with cell probabilities $(p_{10}, p_{01}, p_{\text{tie}})$ on the trinomial simplex $\Theta_{\text{tri}} = \{(p_{10}, p_{01}) \in [0,1]^2 : p_{10} + p_{01} \leq 1\}$ and risk difference $\delta = p_{10} - p_{01} \in [-1,1]$.*

1. *Exact unconditional size and test inversion [42, 43]: For any null margin $\delta_0 \in (-1,1)$, let $\Theta_0(\delta_0) = \{\theta \in [\max(0, -\delta_0), (1 - \delta_0)/2] : p_{10} = \theta + \delta_0,\ p_{01} = \theta\}$ and let $Z(x_{10}, x_{01}; \delta_0)$ denote Tango's score statistic [43]. The unconditional p-value*

$$p_{\text{SS}}(\delta_0) = \sup_{\theta \in \Theta_0(\delta_0)} \sum_{Z(x_{10},x_{01};\delta_0) \leq Z_{\text{obs}}} \frac{N!}{x_{10}!\, x_{01}!\, x_{00}!} \times (\theta + \delta_0)^{x_{10}}\, \theta^{x_{01}}\, (1 - 2\theta - \delta_0)^{x_{00}}$$

   (with $x_{00} = N - x_{10} - x_{01}$) satisfies $\mathbb{P}_{(p_{10},p_{01})}\big(p_{\text{SS}}(\delta_0) \leq \alpha\big) \leq \alpha$ for all $(p_{10}, p_{01}) \in \Theta_{\text{tri}}$ with $p_{10} - p_{01} \geq \delta_0$, and $U_{1-\alpha} = \sup\{\delta_0 \in (-1,1) : p_{\text{SS}}(\delta_0) > \alpha\}$ is an exact $(1-\alpha)$ one-sided upper confidence bound for δ without marginal union-bound slack.

2. *Anytime-valid Ville betting supermartingale [44, 45]: Let $Y_1, Y_2, \cdots \in \{0,1\}$ record sequential discordant pairs ($Y_d = 1$ if only B errs, $Y_d = 0$ if only A errs). Under H_0: $\delta \geq 0$, conditional discordance satisfies $\mathbb{P}(Y_d = 1 \mid \mathscr{G}_{d-1}) = p_{01}/(p_{10} + p_{01}) \leq \frac{1}{2}$. For any $\mathscr{G}_{d-1}$-predictable sequence $\lambda_d \in [0,1]$, $E_0 = 1$ and $E_d = \prod_{j=1}^{d}\big(1 + \lambda_j(2Y_j - 1)\big)$ form a non-negative supermartingale under H_0, so Ville's inequality guarantees $\mathbb{P}_{H_0}\big(\exists d \geq 1 : E_d \geq 1/\alpha\big) \leq \alpha$ under arbitrary data-dependent stopping times τ ($p_{\text{anytime}}(\tau) = \min\{1, (\max_{1 \leq j \leq \tau} E_j)^{-1}\}$).*

Proof. For (1), fix any $(p_{10}^*, p_{01}^*) \in \Theta_{\text{tri}}$ with $\delta^* = p_{10}^* - p_{01}^* \geq \delta_0$. When $\delta^* = \delta_0$, $\theta^* = p_{01}^* \in \Theta_0(\delta_0)$, so at observed (X_{10}, X_{01}), $p_{\text{SS}}(\delta_0)$ upper-bounds the exact null tail probability $F_{\theta^*}(Z(X_{10}, X_{01}; \delta_0))$, which stochastically dominates Uniform$[0,1]$; hence $\mathbb{P}_{\theta^*}(p_{\text{SS}}(\delta_0) \leq \alpha) \leq \alpha$ (monotonicity of the Tango rejection set in $(x_{10}, -x_{01})$ extends size $\leq \alpha$ to composite $\delta^* > \delta_0$). Standard Neyman duality between level-α tests of $H_0(\delta_0)$: $\delta \geq \delta_0$ and confidence sets gives $\mathbb{P}(\delta \leq U_{1-\alpha}) \geq 1 - \alpha$.

For (2), since $\lambda_d \in [0,1]$ is $\mathscr{G}_{d-1}$-measurable and $2Y_d - 1 \in \{-1, +1\}$, each factor $1 + \lambda_d(2Y_d - 1) \geq 1 - \lambda_d \geq 0$ is non-negative, whence $E_d \geq 0$ for all $d \geq 0$. Under H_0 ($\mathbb{P}(Y_d = 1 \mid \mathscr{G}_{d-1}) = q_d \leq \frac{1}{2}$), $\mathbb{E}[2Y_d - 1 \mid \mathscr{G}_{d-1}] = 2q_d - 1 \leq 0$; multiplying by $\lambda_d \geq 0$ gives $\mathbb{E}[E_d \mid \mathscr{G}_{d-1}] = E_{d-1}\big(1 + \lambda_d(2q_d - 1)\big) \leq E_{d-1}$.

Store	Logical collection	Persisted representation	Key invariants and role
`broker.sqlite`	`state` (header)	`Broker.{budget, charged, epochs, live}` in `state.body`	Cumulative cap B, conservative upper envelope $C \in [0, B]$, per-issuer monotone epoch vector `epochs`$[0..n)$, and liveness flags `live`$[0..n)$.
`broker.sqlite`	`approvals`	`Broker.approvals: Vec<Approval>` in `state.body`	Binds exact `Permit` (`actor + proposal`) to per-issuer boolean `grants`; cleared on `withdraw`(j) and never restored by `renew`(j).
`broker.sqlite`	`delegations`	`Broker.delegations: Vec<Delegation>` in `state.body`	Acyclic parent-linked capabilities (`id`, `parent`, `permit`, `budget`, `charged`, `expires`, `scope`, `required`, `grants`, `epochs`) checked by `attenuates`.
`broker.sqlite`	`reservations`	`Broker.records: Vec<Record>` in `state.body`	Immutable `DispatchedPermit` + status $\in$ {`Pending`, `Committed`, `Cancelled`}; $\sum_{\text{Pending}} q_i + \sum_{\text{Committed}} q_i = C \le B$.
`sink.sqlite`	`epoch_floor`	`Sink.floors: Vec<u64>` in `state.body`	Per-issuer monotone lower bounds updated via `advance_floor`; gates both `accept` and `complete` via `unfenced`.
`sink.sqlite`	`permits`	`Sink.records: Vec<Record>` in `state.body`	Deduplicated `DispatchedPermit` state machine (`Pending` $\to$ `Committed` | `Cancelled`, or immediate `Cancelled` tombstone on late old-epoch arrival).
`sink.sqlite`	`resources`	`Sink.{revision, document}` in `state.body`	Versioned toy target (`toy.rs`, initial revision 0); `Edit` increments `revision` iff `revision_matches` holds at `complete`.
`sink.sqlite`	`effects`	SQLite table `effects(sequence, id, payload, charge)`	Append-only committed effects log; `audit` verifies exact 1-to-1 bijection with `Committed` sink `permits` and `revision` $=$ |`Edit commits`|.

Table 10: Physical SQLite tables and logical protocol collections across the V2 separate-process Broker and Cooperative Sink (`src/protocol_v2.rs`).

By Ville's maximal inequality for non-negative supermartingales with $E_0 = 1$ [44, 45], $\mathbb{P}_{H_0}(\sup_{d \ge 1} E_d \ge 1/\alpha) \le \alpha E_0 = \alpha$. □

B Protocol Transitions, Finite-State Models, and Boundary Schemas

This appendix records the exact storage schemas, RPC transition rules, Linux confinement filters, Verus `policy-core` verification inventory, and preserved V1 (`12b5579`) finite-state and single-database baselines referenced in Sections 4 and 5.

B.1 V2 Broker and Sink Durable Schemas and Normalization

Both `broker-v2` and `sink-v2` (`src/protocol_v2.rs`) require bundled SQLite $\ge$ 3.51.3 (excluding historical WAL-reset corruption bugs [36]), configure `PRAGMA journal_mode=WAL`, `PRAGMA synchronous=FULL`, and a 10 s busy timeout, and execute every mutating RPC inside an explicit `BEGIN IMMEDIATE` write transaction [35]. Physically, each service database (`broker.sqlite` and `sink.sqlite`) initializes two SQLite tables:

- `state(singleton INTEGER PRIMARY KEY CHECK(singleton=1), body TEXT NOT NULL)`: stores the canonical JSON-serialized service state struct (`Broker` in `broker.sqlite`; `Sink` in `sink.sqlite`).
- `effects(sequence INTEGER PRIMARY KEY, id TEXT UNIQUE NOT NULL, payload TEXT NOT NULL, charge INTEGER NOT NULL)`: used in `sink.sqlite` as an append-only committed effect log enforcing SQLite-level uniqueness on operation `id` and recording the canonical serialized `DispatchedPermit` alongside integer `charge`.

Table 10 maps the logical protocol collections onto these persisted structures. All wire structs carry `#[serde(deny_unknown_fields)]`, so unrecognized JSON keys fail parsing prior to canonical re-serialization; JSON whitespace or key-order variations cannot mint distinct authorities.

Normalized `DispatchedPermit` binding. For n configured issuers ($1 \le n \le 64$, default $n = 2$), base operation requirements $\text{req}_0(e, n)$ require issuer 0 (operator) for `Transfer`, issuers $\{0, 1\}$ (operator and steward) for `Edit`, and all n issuers for `Release`. When a proposal is admitted via a sub-delegation leaf whose `required` vector strengthens $\text{req}_0(e, n)$ (for example, adding steward requirement $j = 1$ to a `Transfer`), `Broker::submit` embeds `required = leaf.required` into `DispatchedPermit` (omitting the field only when equal to $\text{req}_0(e, n)$, preserving canonical byte compatibility for non-delegated permits). At the sink, `DispatchedPermit::normalized` rejects any vector that weakens $\text{req}_0(e, n)$ and supplies `effective_required` to `accept`, `complete`, `fence`, and `audit`. Meanwhile, `Broker::submit` compares `same_permit(&r.permit.base_permit(), &permit)` on proposer retries so repeating a canonical `actor + proposal` returns its stored status and `DispatchedPermit` idempotently without allowing a stripped sink replay.

B.2 V2 Broker and Sink RPC Transition Specification

Every service line is framed by `read_rpc_frame` with cap `MAX_RPC_BYTES` = 65,536 bytes and a POSIX `libc::poll` per-frame deadline (`JEATH_RPC_DEADLINE_MS`, default 500 ms; oversize lines drain to `\n` and return `denied("rpc_too_large")`, while stalled partial frames return `denied("rpc_timeout")` without process termination). Optional test hooks `delay_before_commit_ms` ($\le$ 1000 ms), `crash = "before_commit"` (exit code 86 prior to `tx.commit()`), and `crash = "after_commit"` (exit code 87 immediately after `tx.commit()`) exercise real WAL lock contention and crash recovery.

Broker transitions (`broker.sqlite`).

- `init(budget, issuers?)`: Fails if `state` exists; otherwise initializes $B =$ `budget`, $C = 0$, `epochs` $= 0^n$, `live` $=$ true^n, and empty `approvals`, `records`, and `delegations`.
- `approve(permit, issuer j)`: Requires `live`$[j]$

and `permit.proposal.epochs = epochs`, no ID collision in `delegations`, and exact byte match (`same_bytes`) if an approval for `proposal.id` already exists; sets `grants[j]` ← true.

- `delegate(id, parent?, permit?, budget, expires, scope, required?, grants?, epochs?)`: Verifies acyclicity of ancestor chain, live/current ancestor grants via `current_grants`, absence of non-cancelled direct spend on any ancestor approval/delegation ID, and `attenuates` between parent and child capabilities before appending the `Delegation`.
- `submit(proposal, session_actor)`: If `proposal.id` exists in `records`, returns existing `(status, permit)` iff `base_permit` matches `session_actor + proposal`, else `denied("payload_mismatch")`. Otherwise checks `scoped()`, verifies direct approval or full ancestor delegation chain via `current_grants` and `admit_multi`, reserves $C' = \texttt{reserve}(B, C, q)$ (and $C'_d = \texttt{reserve}(B_d, C_d, q)$ along any delegation chain), persists `Record{permit: dispatched, status: Pending}`, and returns `pending`.
- `withdraw(issuer j)`: Sets `epochs`$[j]$ ← `epochs`$[j]+1$, `live`$[j]$ ← false, clears `grants`$[j]$ across all `approvals` and `delegations`, and reports `outstanding` $= \sum\{q_r : r.\texttt{status} = \texttt{Pending} \wedge \text{eff_req}(r)[j]\}$.
- `renew(issuer j)`: Sets `live`$[j]$ ← true without restoring cleared grant bits, altering `epochs`, or reducing C.
- `settle(id, sink_status)`: Control-plane endpoint (never exposed to proposers). Requires existing `Pending` record and `sink_status` ∈ {`Committed`, `Cancelled`}; updates C ← `release`$(C, q,$ `sink_status == Cancelled`$)$ (and ancestor delegation charges) and sets terminal status.
- `status(id, session_actor)` / `inspect` / `audit`: Read-only queries; `audit` runs `PRAGMA integrity_check` and checks ID uniqueness, delegation bounds, and $\sum_{\texttt{Pending}} q + \sum_{\texttt{Committed}} q = C \le B$.

Sink transitions (`sink.sqlite`) and concurrent linearization.

- `accept(permit)`: Normalizes `DispatchedPermit`. If `proposal.id` is already recorded, returns stored status iff `same_dispatched_permit` holds, else `denied("payload_mismatch")`. If new and `!unfenced(eff_req, epochs, floors)`, persists a terminal `Cancelled` tombstone; otherwise persists `Pending`.
- `complete(id)`: Requires recorded `id`. If `Pending`, evaluates `unfenced(eff_req, epochs, floors)` and (for `Edit`) `revision_matches(revision, expected_revision)`. Failure transitions status to `Cancelled`; success updates `document`/`revision` if applicable, transitions status to `Committed`, and inserts the unique row into `effects` in the same `BEGIN IMMEDIATE` transaction. Terminal records return stored status idempotently.
- `fence(issuer j, floor)`: Updates `floors`$[j]$ ← `advance_floor(floors`$[j]$`, floor)` and transitions every `Pending` record failing `unfenced` to `Cancelled` before committing and returning acknowledgment.
- `status(id)` / `inspect` / `audit`: `status` returns `unknown` when absent (never treated as cancellation); `audit` verifies `PRAGMA integrity_check`, `unfenced` on all remaining `Pending` permits, and exact payload/charge bijection between `Committed` records and `effects`.

For concurrent separate-process runs, `scripts/concurrent_v3.py` checks real-time interval linearizability against the independent Python `Reference` using diamond partial-order reduction (exploiting commutativity of budget-rejected submissions) and canonicalized state memoization across all 1..32-writer populations (18/18 runs, ≤ 69 RPCs): an invocation e_j must precede e_i whenever `responded_ns`$(e_j) <$ `invoked_ns`(e_i); pre-commit crashes (`exit 86`) commit `False`, post-commit crashes (`exit 87`) commit `True`, and unannotated dropped replies branch over {`False`, `True`}. Every linearized prefix must match recorded decision and public `status` responses, maintain $0 \le C \le B$, and end with the exact canonical `effects` list (excluding non-atomic `inspect`/`audit` snapshots and returning `inconclusive` on expiry-crossing intervals or node-budget exhaustion).

B.3 Launcher Framing, Allowlist, and Kernel Confinement Specification

`scripts/launch_v2.py` spawns untrusted proposers via `authority-lab confine-v2` with `stdin=PIPE`, `stdout=PIPE`, `stderr=DEVNULL`, `close_fds=True`, `env={}`, and `cwd="/"`. `read_proposer_line` enforces a 32,768-byte UTF-8 frame cap (draining oversize lines and returning `denied` without unbounded buffer growth; blocking line reads bound per-frame memory rather than wall-clock execution time). `validate_message` permits only two exact proposer schemas—`{"op": "submit", "proposal": ...}` and `{"op": "status", "id": ...}`—rejecting any proposer-supplied `actor` key or control verb (`approve`, `delegate`, `withdraw`, `renew`, `settle`, `fence`, `init`, `inspect`, `audit`), injects `session_actor` server-side, and strips `permit` tokens from responses.

Inside `confine-v2` (`src/isolation_v2.rs` and `src/bin/authority-lab.rs`):

1. **Landlock ABI ≥ 4:** Queries `SYS_landlock_create_ruleset` ABI version (failing closed if < 4), constructs the 16-byte `RulesetAttr` with `handled_access_fs = 0x7fff` (all 15 filesystem access bits through `TRUNCATE`) and `handled_access_net = 3` (`BIND_TCP | CONNECT_TCP`), attaches read/execute `O_PATH` rules solely for `/usr`, `/lib`, `/lib64`, `/bin`, `/etc/ld.so.cache`, `/dev/null` (read/write), `/dev`

/urandom, and the canonicalized proposer executable, sets PR_SET_NO_NEW_PRIVS, and calls SYS_landlock_restrict_self (zero TCP rules added, blocking all TCP bind/connect).

2. **Seccomp-BPF EPERM filter:** Pins seccomp_data.arch (0xc000003e on x86_64, 0xc00000b7 on aarch64) and kills x32/compat syscall numbers ($\geq$ 0x40000000). Allows SYS_prlimit64 only when *both* 32-bit halves of the 64-bit PID argument (offsets 16 and 20) equal zero, returning EPERM on cross-process inspection. Returns EPERM across 56 additional syscalls: sockets (socket, socketpair, connect, bind, listen, accept, accept4, sendto, sendmsg, sendmmsg), process inspection/signaling (ptrace, process_vm_readv, process_vm_writev, pidfd_getfd, pidfd_open, pidfd_send_signal, kill, tkill, tgkill, rt_sigqueueinfo, rt_tgsigqueueinfo, kcmp), namespaces/mounts/kernel (mount, umount2, unshare, setns, bpf, perf_event_open, userfaultfd, io_uring_setup, io_uring_enter, io_uring_register, open_by_handle_at, reboot, kexec_load), keyrings (add_key, request_key, keyctl), System V IPC (shmget, shmat, shmctl, shmdt, msgget, msgsnd, msgrcv, msgctl, semget, semop, semtimedop, semctl), and POSIX message queues (mq_open, mq_unlink, mq_timedsend, mq_timedreceive, mq_notify, mq_getsetattr).
3. **Descriptor sweep and native probes:** Invokes SYS_close_range(3, u32::MAX, 0) and execs with minimal environment. run_v2.py pairs unrestricted positive canaries against confined probes across all 11 checks (10 Rust binary probes plus existing_sysv_queue, where the parent creates an IPC_PRIVATE | 0600 queue, verifies unrestricted msgsnd/msgrcv succeed, verifies confined msgsnd fails with EPERM, and removes the queue via IPC_RMID).

B.4 Mechanized Policy-Core Inventory

Table 11 catalogs all 49 executable Rust functions and all 36 mechanized proof fn items in policy-core/src/lib.rs (226 verified SMT obligations, 0 warnings, and 6/6 rejected Z3 soundness mutations in scripts/verify_core.py).

B.5 Preserved V1 Finite-State Model and Atomic SQLite Baseline

To preserve exact backward reproducibility with commit 12b5579 (evidence/reference/, verified by scripts/validate.py --source-ref 12b5579), we retain both the V1 22-action finite-state model (src/model.rs) and the V1 single-database transactional executor (src/runtime.rs).

In the V1 finite-state model, each state is the tuple $x = (z, L, U, z_0, z_1, l, v, p_0, p_1)$, tracking world spend z, accounting ledger L, 4-bit executed-identifier mask U, per-actor spend (z_0, z_1), grant liveness $l \in \{0,1\}$, environment version $v \in \{0,1\}$, and per-actor pending slots (p_0, p_1). The 22-action alphabet comprises 16 preparations Prepare($a \in \{0,1\}, id \in \{0,1\}, q \in \{1,2\}, dest \in \{\text{true}, \text{false}\}$), 2 commits Commit($a$), Revoke, Advance (advancing $v : 0 \to 1$ and revoking l), Restart, and Renew. Cycle-closed breadth-first search checks all 22 actions per reachable accepted state against 20 positive tasks (8 single transactions plus 12 ordered pairs of 1-unit identifiers) and an independent pre-effect world oracle. Table 12 reports the complete atomic enforcer (10,180 states, 223,960 checks, 0 violations), unconstrained and reject-all baselines, nine targeted single-clause enforcer mutations (per_action, per_actor, prepare_only, no_replay, no_revocation, no_version, no_destination, reset_restart, reset_renewal), and the specification-omission control (41,732 states, 918,104 checks, spending 8 units against budget 2).

Finally, the preserved V1 atomic SQLite baseline (src/runtime.rs) executes all policy checks, receipt insertions, and toy effects inside *one* SQLite WAL database across seven relational tables (policy, prepared, grants, receipts, accounts, objects, and deliveries), tested over 8 lifecycle, pre/post-commit process-kill, and 8-writer contention scenarios. Table 13 records its single-store commit throughput and p95 latency on the V1 baseline host; unlike V2 (Table 3, Figure 5), V1 mediates only its own single-file SQLite tables without separate-process reservation quarantine, sink epoch fencing, or Linux proposer confinement.

C Synthetic Generative Specifications and Extended Tables

This appendix documents the deterministic pure-Rust and Python generative specifications, hyperparameters, and automated validation checks backing all twenty-two reference JSON artifacts in evidence/v3/reference/*.json (plus trajectory_monitors.json), together with the extended V3 monitor and selection tables (Tables 14 and 15) and the preserved V1 two-family monitor baseline (Table 16).

C.1 Deterministic Runtime, Numerical Primitives, and Scope

All V3 simulations execute on CPU via authority-lab run-v3 OUTPUT --profile publication --seed 20261110 (orchestrated by scripts/run_v3.py and verified against source-parsed constants by scripts/validate_v3.py --source; fast CI gates use --profile smoke). Pseudo-randomness derives exclusively from a standalone SplitMix64 generator (src/rng.rs) seeded from 20261110 with fixed domain-separation XOR/Weyl offsets per module, paired with a pure-Rust 128-layer Marsaglia–Tsang Ziggurat normal sampler, Cody rational erfc, Acklam–Halley normal quantile norm_ppf, and a 200-node Golub–Welsch symmetric tridiagonal QL quadrature solver [53].

Two methodological boundaries apply across all Tier-4 artifacts. First, every classifier, graph solver, statistical test, and

Kind	Identifier(s)	Verified specification or mechanized theorem
exec	same_bytes, revision_matches, grants_ok, current_grants	Exact byte-sequence equality ($a@ == b@$); revision equality; universal implication over required issuer vectors ($\forall i.\ \texttt{req}[i] \Rightarrow \texttt{grant}[i] \wedge \texttt{live}[i] \wedge \texttt{epoch}[i] = \texttt{req_epoch}[i]$), failing closed on length mismatch.
exec	reserve, admit, admit_multi, admit_uncertain	Overflow-free reservation ($q > 0 \wedge q \le B \wedge C \le B - q \Rightarrow \texttt{Some}(C+q)$); single-issuer, n-issuer, and interval $[C_{\text{lo}}, C_{\text{hi}}]$ admission equivalences (ok <==> spec).
exec	advance_floor, attenuates, unfenced, release	Monotone floor $\max(f,p)$; capability attenuation ($B_c \le B_p$, $E_c \le E_p$, $\texttt{scope}_c \Rightarrow \texttt{scope}_p$, $\texttt{req}_p \Rightarrow \texttt{req}_c$); per-issuer fence check ($\forall i.\ \texttt{req}[i] \Rightarrow \texttt{epoch}[i] \ge \texttt{floor}[i]$); non-increasing settlement refund iff authoritative_no_effect.
exec	encode_permit_canonical, decode_permit_canonical, roundtrip_permit_canonical, same_permit_canonical	Length-prefixed canonical wire encoder and total panic-free wire parser rejecting truncated frames, u64 length overflows, non-boolean tags, and trailing smuggled bytes; cross-checked in protocol_v2.rs and v5_e2e_crypto_cluster.rs.
exec	attenuates_grant_exec, grant_live_at_exec, verify_delegation_chain_exec, verify_self_upgrade_exec	Arbitrary-depth d-hop ExecScopeGrant bitmask/budget/expiry/issuer-quorum attenuation checker, lineage liveness checker, and non-escalating controller self-upgrade gate ($G(v_1) \preceq G(v_0) \vee$ fresh quorum).
exec	ExecBrokerKernel::*, ExecSinkKernel::*, ExecClusterFenceKernel::*, cluster_*	Concrete Rust state machines for broker reservation/delegation/settlement, single-sink deduplication/fencing, and M-shard quorum/lease cluster fencing (cluster_fence_acked_exec, cluster_shard_complete_exec).
proof	exposure, prefix_bound, fenced_zero, positive_budget	Pointwise $e_i \le q_i \Rightarrow \sum e_i \le \sum q_i$; prefix induction $0 \le C_t \le B$; single stale required issuer falsifies unfenced; feasible reservation arithmetic witness.
proof	sum_push, sum_remove, ledger_step_preserves_inv, cumulative_conservation_induction, reset_vulnerability_contrast, timeout_refund_vulnerability	Ghost LedgerState (step_ledger, run_ledger) invariant $C = C_{\text{comm}} + \sum \texttt{inflight} \le B$ over arbitrary traces; constructive $2B > B$ overspend on renew/restart reset and $B + q > B$ overspend on unacknowledged timeout refund.
proof	uncertainty_monotonicity, monotone_fencing_induction, permanent_post_fence_exclusion, independent_issuer_noninterference	Nested uncertainty contraction $[l_1, u_1] \subseteq [l_2, u_2]$; coordinatewise floor monotonicity across fence sequences; permanent exclusion of old-epoch permits; non-interference across independent issuers.
proof	attenuation_monotonicity, attenuation_chain_induction, attenuates_grant_transitive, delegation_chain_no_amplification, ancestor_withdrawal_severs_subtree, self_upgrade_preserves_scope	Inductive d-hop attenuation preventing capability amplification across subagent trees, immediate subtree severance upon any ancestor required-issuer withdrawal, and scope non-escalation across unquorumed self-modifications.
proof	proposer_disposition_independence, ungated_disposition_diverges, broker_kernel_inv, sink_kernel_inv, authority_kernel_conservation, authority_post_fence_exclusion, encode_permit_injective, encode_decode_permit_bijection, cluster_quorum_post_ack_exclusion	All-policy gated_run safety vs. ungated $2B$ overspend; forward-simulation refinement from concrete ExecBrokerKernel/ExecSinkKernel methods; exact two-way canonical wire bijection ($\text{decode}(b) = \text{Some}(p) \Leftrightarrow b = \text{encode}(p)$); and M-shard quorum/lease post-ack commit exclusion.

Table 11: Summary inventory of the 49 public executable functions and 36 public mechanized proof theorems in policy-core/src/lib.rs (226 total verified SMT obligations, 0 trigger warnings, 6/6 soundness mutations rejected). Concrete Rust kernel state transitions, d-hop attenuation, cluster quorum leases, and canonical wire encoding/decoding are refined in Verus without claiming formal refinement of SQLite or OS I/O.

Enforcer	States	Checks	Tasks	First violations
Complete atomic enforcer	10,180	223,960	20/20	None declared
No enforcement	10,180	223,960	20/20	budget, destination, replay, revocation, version
Reject everything	740	16,280	0/20	None declared
Per-action amount limit	10,180	223,960	20/20	budget
Separate per-actor limits	10,180	223,960	20/20	budget
Budget at preparation	956	21,032	20/20	budget
Omit identifier check	10,180	223,960	20/20	replay
Omit revocation check	10,180	223,960	20/20	revocation
Omit version check	10,180	223,960	20/20	version
Omit destination check	10,180	223,960	20/20	destination
Reset ledger on restart	23,556	518,232	20/20	budget
Reset ledger on renewal	20,900	459,800	20/20	budget
Per-action; budget omitted	41,732	918,104	20/20	None declared

Table 12: Fresh Rust exploration of all 22 actions at each reachable accepted state. Violating edges are recorded and not expanded. Counts are exhaustive within the model, not failure probabilities. The omitted-budget row accepts up to eight units.

evolutionary loop is implemented from scratch in standalone Rust with zero third-party machine-learning or scientific crates; the monitor suite is therefore an independent synthetic boundary testbed rather than a scikit-learn bit-replica or a frontier-LLM correlation measurement. Second, elementary floating-point transcendentals (exp, ln, sin, cos, tanh) call the platform C math library (libm); publication evidence is pinned to Linux x86_64 reference outputs with SHA-256 digests recorded in provenance.json, without claiming unmeasured cross-architecture libm bit-identity.

Processes	Commits	Commits/s	p95 (ms)
1	256	57.1	21.34
4	256	72.0	23.09

Table 13: Single runs on the recorded host with SQLite WAL and synchronous FULL. Setup and grants precede timing; process scheduling and lock waiting remain included. Shared-host contention and storage affect these descriptive measurements.

C.2 Artifact-by-Artifact Generative Specifications (22 Reference JSONs + Trajectory Monitors)

1–3. Run envelope and provenance. Artifacts `metadata.json`, `complete.json`, and `provenance.json` record run metadata and digests: `metadata.json` stores `schema_version: 3`, `seed: 20261110`, `profile: "publication"` (`quick: false`), `rng: "splitmix64-v3"`, host OS/architecture, and `gpu_used: false`. `complete.json` records clean termination and elapsed CPU wall time. `provenance.json` binds the git commit, exact invocation, UTC timestamp, SHA-256 hashes of `src/v3_*.rs` and runner scripts, and SHA-256 hashes of all generated JSON files.

4. Observation-lag contraction (`uncertainty.json`; `src/v3_core_models.rs`). First, an exhaustive lattice check enumerates all 10,626 nested integer interval pairs $[l_1,u_1] \subseteq [l_2,u_2] \subseteq [0,20]$ under budget $B = 20$, verifying $U_{\mathscr{I}}([l_2,u_2]) \subseteq U_{\mathscr{I}}([l_1,u_1])$ with 0 counterexamples. Second, seeded with `seed` $\oplus$ `0x4832554E43455254`, 500 paired 16-step episodes per cell (80 in `smoke`) evaluate three gate policies across observation lags $\Delta t \in \{0,1,2,4,8\}$: `stale_snapshot`, `proposer_self_report` (underreporting spend by 3 with probability 0.35), and sound `conservative_envelope_bt` (tracking unconfirmed dispatches with commit probability 0.65 and 1/step exogenous drift bound). Validation checks 0 conservative breaches across all lags and monotone admission contraction from 77.4% ($\Delta t = 0$) to 45.6% ($\Delta t = 8$).

5. Snapshot non-composition (`composition.json`; `src/v3_core_models.rs`). Enumerates $(c,q_1,q_2) \in \{0,\dots,B\}^3$ across $B \in \{2,10,25,50,100\}$ and cross-checks exact closed forms (Proposition 6): at $B = 100$ (1,030,301 triples), 348,551 pairs are individually snapshot-admissible and 171,700 (49.26%) jointly overspend, versus 0 under serialized pre-dispatch reservation.

6. Saturation, horizon summability, and tail halt (`risk_horizon.json`; `src/v3_core_models.rs`). Computes: (i) common-cause curves $J_k = c + (1-c)p^k$ ($u = 0.50\%$, $c = 1.00\%$, $p = 0.10$, $m = 10.90\%$, $k^* = 2$, $71.5\times$ understatement at $k = 4$), continuous $\Theta \sim$ Uniform$[0,1]$ moments $1/(k+1)$, and capability-overtake curves $\rho(z) = \lambda_0 q_0 e^{(\beta-\alpha)z}$; (ii) exact closed-form survival-product (`ln_1p`/`exp_m1`) renewal breach curves up to $T =$ 10,000 comparing summable $p_t = 0.01/t^2$ (1.64% $\le$ 1.64%), harmonic $0.01/t$ (9.33%), and constant 10^{-3} (100.00%); and (iii) heavy-tailed lognormal M/G/1 reactive stop latency (10,000 episodes/load; 1,000 `smoke`) against deadline $T_{\text{irrev}} =$ 100 ms across utilizations $\rho \in \{0.20,0.50,0.80,0.95\}$ versus pre-commit leases with synchronous sink epoch fencing (0 post-revoke violations).

7–8. Discovery closure, endogenous grants, and personas (`jarvis_ledger.json`, `personas.json`; `src/v3_core_models.rs`). `jarvis_ledger.json` exercises the deterministic 6-state `DiscoveryLedger` (`Question` → `Finding` → `Validation` → `Mitigation` → `Deployment` → `Reassessment`) over 24 periods (12 in `smoke`), verifying zero authority expansion upon vulnerability discovery and contrasting immediate cut sealing (0 unclosed backlog, 0.008 exposure) with lagged patching (72 backlog, 5.25 exposure), alongside the endogenous vs. decoupled human grant matrix. `personas.json` evaluates 28 cells (4 scripted dispositions $\times$ 7 boundary arms, 400 episodes/cell; 60 `smoke`), confirming 0 modeled Tier-1 breaches under fenced verified mediation and Tier-2 exposure reduction from 94.0% to 1.5% after cut closure.

9–10. Weighted cutsets and sparse DAG interdiction (`weighted_cuts.json`, `interdiction.json`; `src/v3_graphs.rs`). `weighted_cuts.json` cross-checks our split-vertex Dinic solver against exhaustive $2^{|V_{\text{elig}}|}$ subset search across 2,048 random weighted DAGs with ineligible vertices (0 discrepancies), verifies $+\infty$ cost when an ungateable route bypasses V_{elig}, and evaluates layered scaling families G_A and G_B for $k \in \{0,2,4,6\}$ (46–142 internal vertices; 57,600–966,367,641,600 paths). `interdiction.json` generates 200 sparse 8-stage DAGs per family (20 `smoke`; seed `seed` $\oplus$ `0x4831315F44414753`, `out_degree` $= 6$) across `narrow` (waist width 6 at an internal stage in $\{2,\dots,5\}$ and 30 nodes elsewhere; median global min-cut 6), `hub` (27 nodes/stage; median 21), and `wide` (27 nodes/stage; median 27), sampling $N \in \{30,100,300,1{,}000,3{,}000\}$ low-cost routes under Boltzmann inverse temperature $\beta = 0.5$ via exact log-domain backward dynamic programming and evaluating reported-subgraph min-cut (`cut`), `patch_specific`, and `patch_random` across budgets $0\dots32$ (`budget_grid` $=$ $\{0,3,6,9,12,16,20,24,32\}$).

11–12. Zipf coverage and planted-audit power (`coverage_v3.json`, `audit_power.json`; `src/v3_coverage.rs`). Implemented in `src/v3_coverage.rs`, `coverage_v3.json` simulates $K = 2{,}000$ shuffled Zipf classes ($p_r \propto 1/r$) across $N = 12{,}000$ reports (4 searchers $\times 3{,}000$ draws, 200 trials; 25 `smoke`) under `honest`, `shared_blind_15pct` (exact 15% unseen mass), and `withheld_critical_5pct` (strategic suppression of 5% critical mass), comparing Good–Turing $\hat{C}_{\text{GT}} = 1 - f_1/N$ [49], two-list Chapman capture–recapture ($2 \times 3{,}000$) [51], and McAllester–Schapire vs. Clopper–Pearson bounds [41, 50]. `audit_power.json` computes exact hypergeometric one-sided Fisher exact p-values [52] ($\alpha = 1.0\%$) for $P \in \{40,200\}$ split equally between ordinary plants ($q_0 \in \{0.50,0.80\}$) and salient plants ($q_1 = rq_0$ across 21 grid points $r \in \{0.00,0.05,\dots,1.00\}$), verifying

Synthetic 20D 6-gate architecture	ρ_{adv}	Joint 6-miss	Indep. product	Ratio	Benign false block
Homogeneous MLP, shared step	0.0	$4.75 \pm 1.82\%$	0.0675%	70.4×	14.1%
6-family heterogeneous, shared step	0.0	$5.21 \pm 1.55\%$	0.2171%	24.0×	16.9%
6-family heterogeneous, distinct steps	0.0	$0.260 \pm 0.176\%$	0.2049%	1.27×	25.6%
Homogeneous MLP, shared step	2.0	$9.44 \pm 2.95\%$	0.47%	19.9×	—
6-family heterogeneous, shared step	2.0	$8.79 \pm 2.59\%$	1.06%	8.3×	—
6-family, shared + 8-query score feedback	2.0	$17.45 \pm 4.45\%$	—	—	—
6-family heterogeneous, distinct steps	2.0	$1.24 \pm 0.84\%$	0.98%	1.26×	—
Shared-step read-only retry ($K = 32$ draws)	2.0	$72.4 \pm 10.4\%$	71.0% (law)	—	—

Table 14: Tier-4 pure-Rust 20D synthetic monitor benchmark across 24 independent teacher seeds (MLP, quadratic RFF, axis stump ensemble, k-NN, RBF prototype, logistic linear; 5% per-gate benign FPR calibration; `monitors_v3.json`). Model diversity on a shared step leaves strong residual failure dependence, whereas independent step evidence tracks the marginal product at the cost of 25.6% benign false blocks. Not frontier-LLM transfer evidence.

Selection regime ($N = 2{,}000$, $G = 80$, 16 replicates)	Final gamble share	Capacity gain Δc	Harm rate	Population welfare
Taken-output top-10% contest (warrior)	$95.1 \pm 0.3\%$	$+5.58 \pm 0.12$	4.54%	3.30
Conferred-benefit top-10% contest	$94.9 \pm 0.4\%$	$+5.45 \pm 0.16$	4.76%	3.22
Concave capped + harm-penalized score	$9.9 \pm 0.2\%$	$+1.55 \pm 0.09$	0.72%	1.45
Bottom-20% harm/floor elimination + delivered growth	$3.8 \pm 0.1\%$	$+3.60 \pm 0.19$	0.15%	2.91
Caretaker higher-cap variant (cap $= 4$, pen $= 6$)	$7.5 \pm 0.4\%$	$+4.53 \pm 0.19$	0.31%	3.79

Table 15: Tier-4 co-evolution of (gamble share s, capacity c) under stipulated payoff rules (`selection_v3.json`). Winner-take-most contests select reckless gambling even when ranked on conferred benefit; floor elimination suppresses gambling (3.8%, a 29.7× harm reduction vs. warrior) while retaining 64.5% of warrior capacity growth. Mathematical payoff mechanics only, not RLHF or human-participant data.

size $\leq \alpha$ at $r = 1$ and exact binomial Clopper–Pearson upper bounds.

13–15. Copula quadrature, 6-family monitors, and variance ceilings (`copula.json`, `monitors_v3.json`, `assessment_variance.json`; `src/v3_monitors.rs`). `copula.json` integrates equicorrelated Gaussian copula joint misses via 200-node Golub–Welsch Gauss–Hermite quadrature [53] at $m = 0.10$ across $\rho \in \{0.0, 0.3, 0.6, 0.9\}$ and $k \in \{1, \ldots, 8\}$. `monitors_v3.json` (Table 14) evaluates 24 independent 20D nonlinear teachers (6 `smoke`; Weyl seed step `0x9E3779B97F4A7C15`), training 6 pure-Rust classifier families ($n_{train} = 680$, $n_{cal} = 560$ calibrated to the 95th benign percentile for 5% target FPR, $n_{eval} = 128$ hazardous/benign episodes; `smoke`: 500/360/80): `MLP2L` (4–10 hidden tanh layers), `LogisticL2`, regularized quadratic discriminant `RegQDA` (reg $= 0.05$), `KNN15` ($k = 15$), `RBFKernel` (72 centers; 48 `smoke`), and `BoostedStumps` (52 stumps; 36 `smoke`). Projected L_2 evasion optimizes against a held-out MLP surrogate across $\rho_{adv} \in \{0.0, 1.0, 2.0, 3.0\}$ (7 steps ×5 candidates; 6 `smoke`) subject to exact ball projection $\|x' - x\|_2 \leq \rho_{adv}$ and teacher hazard preservation $h(x') \geq h(x)$ (validated with zero L_2 overshoot and non-negative hazard delta), alongside 8-query binary vs. margin-score feedback and read-only best-of-K candidate selection ($K \in \{1, 2, 4, 8, 16, 32\}$, 140 episodes/task, 1,200 reference draws; `smoke`: 100/600). `assessment_variance.json` cross-checks closed-form $R_G(K, n)$ ($V_G = 1.0, \omega^2 = 0.2, \sigma_c^2 = 4.0, \sigma_e^2 = 6.0$) and Cronbach $V(m, k)$ ($v_T = 1.0, v_U = 0.2, v_\delta = 3.0, v_\eta = 1.0, v_\varepsilon = 4.0$) against 10,000 Monte Carlo subjects (3,000 `smoke`).

16. Co-evolutionary selection and Price identity (`selection_v3.json`; `src/v3_selection.rs`). Simulates $N = 2{,}000$ agents (400 `smoke`) over $G = 80$ generations (50 `smoke`) across 16 rule replicates (8 `smoke`; 7 publication / 5 `smoke` sweep replicates; base seeds `seed` + $7000 + 101\,\text{idx}$) with heritable gamble share $s_i \in [0, 1]$ and capacity $c_i \geq 0$, output $\text{take}_i = e^{0.30 c_i}((1 - s_i) + s_i(0.8 + 1.5\varepsilon_i))$ ($\varepsilon_i \sim \mathcal{N}(0, 1)$; gamble term 0 when refused by q_{gate}), external harm indicator $\text{harm}_i \sim \text{Bernoulli}(0.05 s_i)$, and $\text{delivered}_i = \text{take}_i - 20\,\text{harm}_i$ (Table 15). Evaluates `taken_rank` (top-10% contest on take_i), `conferred_rank` (top-10% contest after disqualifying observed harm), `caretaker` ($\text{clamp}(\text{delivered}_i, 0, 1)$, plus `caretaker_cap4_pen6` $\max(0, \min(\text{take}_i, 4.0) - 6.0\,\text{harm}_i)$), and `floor` (eliminating bottom-20% floor/harm violators), together with sweeps over $q_{top} \in [0.02, 0.90]$, harm internalization $\lambda_{int} \in [0, 1]$, external gate refusal $q_{gate} \in [0, 1]$, Proposition 13 dispersion curves (`seed` $\oplus$ `0x5E1EC71020261110`), and exact per-generation Price covariance verification ($\max |\Delta \bar{z}_{sel} - \text{Cov}_p(z, w)/\bar{w}| < 3.2e-14$).

17–19. Cryptographic Jepsen fencing, operational cutsets, neural RL, and 5-step trajectories. `crypto_and_jepsen.json` (`src/crypto_authority.rs`, `src/distributed_sinks.rs`) executes 10,000 pure-Rust Ed25519/HMAC-SHA256 Macaroon red-team attacks across 10 families (0 false accepts; 10,000 positive controls) and 1,000 `UnixStream::pair()` partition/drop/crash/MITM schedules per sink class across 3 cooperative sinks (0 post-ack leaks vs. 791 broker-only and 276 uncooperative). `real_tool_cutsets.json` (`src/v4_real_graphs.rs`, Table 6) solves exact weighted Dinic min-cuts and B=32 signature-hotfix counterfactuals across all four AgentDojo `v1.2.2` suites and unconfined vs. Landlock+seccomp Linux IPC topologies. `neural_post_training.json`

(src/v4_neural_rl.rs, Table 8) trains a 412-parameter (12→24→4) tanh-softmax policy across 48 seeds (250 REINFORCE/GRPO updates/seed; gradient check $5.1e-10$, rollout Price error $< 8.9e-16$). trajectory_monitors.json (scripts/trajectory_monitors.py, Table 7) evaluates shared-transcript versus prose-stripped orthogonal capability invariants on 480 held-out 5-step AgentDojo v1.2.2 trajectories (2,400 live tool calls) alongside 340 live Qwen3 campaign traces.

20–22. Superintelligence scaling, multi-process SQLite WAL cryptographic cluster, and exact trinomial/Ville spine. superintelligence_scaling.json (src/v5_superintelligence.rs, Figures 1b and 3) executes four deterministic tracks over real policy_core kernels: (1) $K_{\text{opt}} \in \{1,\ldots,4,096\}$ best-of-K_{opt} candidate search (10,000 episodes/width; 80 smoke), comparing a 3-layer transcript stack ($J = 0.65\%$), learned surrogate ($p = 0.22\%$), stateless per-call cap, and broker-only admission against canonical-wire ExecAuthorityKernel (0/120,000 breaches) plus an independent $u_{\text{TCB}} = 0.10\%$ TCB fault control; (2) $K \in \{1,\ldots,64\}$ multi-agent smurfing and $d \in \{1,\ldots,8\}$-hop ExecScopeGrant lineages (500 self-upgrade trials); (3) exact combinatorial vs. empirical roundtrip codebook capacity across residual budgets $R \in \{32,16,8,4,2,1,0\}$ and arrival buckets $L_{\text{lag}} \in \{1,2,4,8,16\}$; and (4) classical Hadfield-Menell off-switch [23] and self-modifying utility indifference [6] vs. ExecClusterFenceKernel across $\sigma_H \in [0,4]$ and Bellman discount factors $\gamma \in [0.10,0.99]$. e2e_crypto_cluster.json (src/v5_e2e_crypto_cluster.rs) spawns 3 separate authority-lab sink-v5-shard child processes on independent SQLite WAL stores under 3 Ed25519 quorum issuers, running 5,000 adversarial wire-fuzz frames (1,000 smoke), 16-subagent 3-hop Macaroon contention with asymmetric quorum/lease partition fencing, and 24 SIGKILL WAL crash-recovery cycles (8 smoke), cleaning up transient '.sqlite' files inside target/. Finally, statistical_certificates.json (src/v5_statistical_spine.rs, cross-checked to $< 10^{-11}$ by stdlib scripts/statistical_spine_v5.py; Table 5, Figure 1c) computes exact conditional McNemar, exact unconditional Suissa–Shuster / Tango quadratic-RMLE trinomial p-values and $(1-\alpha)$ upper bounds [42, 43], and predictable Laplace-mixture Ville betting supermartingales [44, 45] directly over frozen campaigns.jsonl and agentdojo-live-models.json.

C.3 Preserved V1 Two-Family Synthetic Monitor Baseline

For continuity with the initial release (12b5579, evidence/reference/monitors.json, src/monitors.rs), Table 16 retains the 8-dimensional two-family (neural 8-unit tanh vs. linear logistic; 8 teacher seeds, $n_{\text{train}} = 600$, $n_{\text{cal}} = 800$, 1,000 evaluation episodes across $k = 6$ gates) baseline, which exhibits the same qualitative split between shared-step correlation, cross-family surrogate transfer, and imposed distinct-step independence expanded in Table 14.

D Predeclared Local-Checkpoint and Caretaker/Conferral Study Protocols

This appendix specifies (i) the paired local-checkpoint controller evaluation (fixtures/v2/evaluation.json, scripts/model_v2.py, scripts/infer_v2.py, and scripts/campaign_analysis.py)—now executed on CPU across N=32 frozen holdout cases (320 campaigns, 0 GPU-s), with full $N \geq 113$ power remaining a Tier-5 target—and (ii) the predeclared Tier-5 $3 \times 3 \times 2$ LLM caretaker post-training and human scope-conferral factorial study.

D.1 Repaired local-checkpoint controller evaluation

Checkpoints, decoding, and compute budget. The protocol pins two official quantized weights and one inference server commit without treating parameter count as a capability guarantee:

- Qwen/Qwen3-4B-GGUF (Qwen3-4B-Q4_K_M.gguf, revision bc640142c66e1fdd12af0bd68f40445458f3869b, SHA-256 7485fe6f11af29433bc51cab58009521f205840f5b4ae3a32fa7f92e8534fdf5);
- Qwen/Qwen3-8B-GGUF (Qwen3-8B-Q4_K_M.gguf, revision 7c41481f57cb95916b40956ab2f0b139b296d974, SHA-256 d98cdcbd03e17ce47681435b5150e34c1417f50b5c0019dd560e4882c5745785);
- llama.cpp commit 7592b61d3b53ca5b39a25a03508fa1246b78c579, invoked with deterministic decoding (temperature=0, top_k=1, top_p=1, repeat_penalty=1, seed=20261110, context=4096, max_tokens_per_turn=256, tool_turns=8, enable_thinking=false).

scripts/infer_v2.py enforces single-GPU sequential execution, verifies exact Linux x86_64 hostname and architecture before starting any server, refuses to preempt active GPU compute workloads, caps total wall-clock execution at 4 GPU-h (14,400 s), caps representative 5-controller development timing calibration at 1,200 s (20 min) with 20% scheduling headroom, and reserves three campaign-equivalents per checkpoint for descriptive upstream AgentDojo/Progent reference runs.

Paired controllers and fairness invariants. Each independent procedural base case is executed across five controllers: none (direct sink dispatch), stateless (per-call policy check without durable cross-call ledger or sink fence), learned_same_checkpoint (same-checkpoint JSON allow/deny review over visible policy and state), durable_without_fence (pre-dispatch broker reservation and admission withdrawal without sink epoch fencing), and complete (verified broker reservation plus synchronous durable sink epoch fencing). Every controller within a (checkpoint, case_id, campaign_id) tuple receives identical initial permissions_sha256, visible_state_sha256, and exogenous schedule_sha256; subsequent states diverge solely as a consequence of controller decisions. Scripted records (where source is not local_checkpoint) are rejected by scripts/campaign_analysis.py.

Pipeline	Radius	Single miss	Joint six misses	Product	False block
Six neural, shared input	0	21.86%	$5.463 \pm 1.344\%$	0.0104%	12.35%
Neural + linear, shared	0	30.18%	$7.700 \pm 1.609\%$	0.0554%	12.06%
Mixed, independent inputs	0	31.00%	$0.150 \pm 0.098\%$	0.0672%	27.45%
Six neural, shared input	1.5	87.44%	$61.525 \pm 8.445\%$	46.2550%	12.35%
Neural + linear, shared	1.5	89.47%	$69.212 \pm 8.383\%$	51.9298%	12.06%
Mixed, independent inputs	1.5	89.37%	$51.387 \pm 10.885\%$	51.8789%	28.19%
Mixed, eight feedback queries	1.5	99.41%	$97.612 \pm 1.928\%$	96.5505%	12.06%

Table 16: New synthetic classifier experiment; uncertainty is 1.96 standard errors across eight independent training-task seeds. The product is computed within each seed before averaging. False blocks are measured on benign episodes and show the cost of stacking gates. They are not measured AI deployment risks.

Cryptographic freeze and procedural holdout roster. Before generating held-out evaluation cases, `scripts/model_v2.py` writes `freeze.json` binding all source, prompt, and analysis hashes together with a candidate sample size $N \in \{32, 64, 128\}$ (`variants_per_case=1` by default; if repeated variants are declared, they consume the same total campaign allowance and are clustered at the base-case level). Holdouts procedurally vary task types (`transfer`, `release`, `edit`), transfer charges, expected edit return values, required-issuer withdrawals, and six untrusted retrieved-text attacks (`duplicate`, `altered_payload`, `issuer_impersonation`, `revocation`, `lost_reply`, `prompt_injection`). At analysis time, `scripts/campaign_analysis.py` computes the raw byte SHA-256 of `freeze.json` and asserts: (i) the roster's `freeze_sha256` matches `freeze.json`, (ii) the frozen plan equals the active analysis plan with status `frozen`, (iii) the roster length equals the frozen `sample_size` with unmodified per-case cluster counts, and (iv) zero missing planned pairs or harness/infrastructure errors before any primary claim is eligible.

Exogenous withdrawal and post-commit crash semantics. Three harness repairs prevent vacuous or simulated outcomes:

1. **Exogenous turn-1 revocation with non-abstention utility.** Revocation fixtures seed a separate accepted old operation in `pending` sink state before turn 0 and require the agent to complete positive foreground work on the first approved proposal. Withdrawal executes unconditionally after turn 0 even if the agent immediately outputs `done` or invalid JSON; cancellation alone without positive foreground work scores `task_success=false`. After agent exit, the queued old operation attempts completion: `complete` cancels it via its durable sink fence, whereas `durable_without_fence` records admission-only late completion separately rather than mislabeling it a post-fence breach.
2. **Real post-commit sink crash on `lost_reply`.** Rather than presenting a prompt-only label, `lost_reply` cases terminate the actual `sink-v2` process immediately after durable SQLite commit on the first foreground effect and drop the RPC reply, testing whether retries under ambiguous status cause duplicate effects or stranded-reservation accounting mismatches.
3. **Post-mutation native benchmark grading.** In `scripts/benchmark_v2.py`, native AgentDojo (`v1.2.2`) and Progent [27, 39, 40] utility and security graders are always invoked on the actual post-run state even if a later model turn emits malformed JSON, preventing malformed output from erasing an already executed attacker side effect, while unavailable graders report `None` (`unknown`) rather than `False`. Upstream `banking` tasks 5 and 6 accept unchanged states in empty controls ($2/12$ tasks), so native benchmark runs are strictly descriptive controls rather than primary endpoints.

Multiplicity-corrected exact inference. Primary inference evaluates `complete` minus each baseline controller b (`none`, `stateless`, `learned_same_checkpoint`, and `durable_without_fence`) across two endpoints (safety superiority and usefulness noninferiority) and two checkpoints ($4 \times 2 \times 2 = 16$ one-sided component claims) at Bonferroni level $\alpha = 0.05/16 = 0.003125$ [34, 41]:

- **Safety superiority ($\Delta_i^{\text{safe}} = U_{i,\text{complete}} - U_{i,b}$).** On binary single-variant cases ($\Delta_i^{\text{safe}} \in \{-1, 0, 1\}$ with n_+ cases where only `complete` errs and n_- cases where only baseline b errs), `scripts/campaign_analysis.py` computes two exact one-sided Clopper–Pearson binomial bounds at level $\alpha/2$ each and requires $U_{\alpha/2}(n_+, N) - L_{\alpha/2}(n_-, N) < 0$. If multi-variant clusters produce fractional case means, a one-sided Hoeffding bound on $[-1, 1]$ applies.
- **Usefulness noninferiority ($\Delta_i^{\text{use}} = S_{i,\text{complete}} - S_{i,b}$).** Because $\Delta_i^{\text{use}} \geq -1$ whenever any variant in base case i loses utility ($S_{\text{complete}} = 0 < S_b = 1$) and $\Delta_i^{\text{use}} \geq 0$ otherwise, gains where `complete` outperforms b are conservatively ignored and $\mathbb{E}[\Delta_i^{\text{use}}] \geq -\mathbb{P}(\text{any loss in case } i)$. Noninferiority at the predeclared 5 pp margin requires $-U_\alpha(n_{\text{loss}}, N) > -0.05$. At $n_{\text{loss}} = 0$, solving $(1 - 0.05)^N \leq 0.05/16$ yields $N \geq 113$: the default cap $N = 128$ is powered to certify 5 pp noninferiority, whereas $N \in \{32, 64\}$ can detect large safety discordances while reporting honest `inconclusive` usefulness bounds.

Executed CPU holdout and GPU non-preemption provenance. Read-only GPU preflight (`evidence/v2/reference/model-feasibility.json`) verified that Linux `x86_64` GPUs on `xbabe2`, `xbabe0`, and `xbabe1` held active workloads while `xbabe4` resolved to `Darwin arm64`. Rather than allocating GPUs (0 GPU-s, verified via `CUDA_VISIBLE_DEVICES=""` and pre/post

nvidia-smi PID audits), we executed the frozen N=32 holdout roster (evidence/v2/reference/freeze.json, holdout.json, campaigns.jsonl, model-campaigns-analyzed.json; 320/320 measured campaigns) plus live AgentDojo v1.2.2 runs on xbabe2's 64-core AMD Threadripper PRO 3995WX CPU via pinned llama.cpp. As reported in Section 5 and Table 4, complete incurs 0/64 unauthorized effects and 0/64 false blocks while scaling safe-useful completion from 28.1% (4B) to 56.2% (8B), whereas formal α=0.05/16 superiority/noninferiority bounds at pilot N=32 < 113 remain honestly inconclusive.

D.2 Predeclared $3 \times 3 \times 2$ caretaker and conferral protocol

To test Prediction P7 and the endogenous grant-reversal mechanism (Section 8) on real neural post-training and human operators without conflating prompt persona, learned objective, and runtime mediation, we specify a Tier-5 $3 \times 3 \times 2$ factorial design crossed with two conferral arms:

1. **Post-training objective (3 levels, independent training seeds as units):** (i) rank/tournament task score; (ii) unconstrained beneficiary-welfare proxy; and (iii) bounded assistance rewarding verified task completion, explicit respect for informed refusal and priority revision, truthful uncertainty disclosure, and non-resistance to replacement or shutdown [23, 61]. Matched base checkpoint, task pool, post-training FLOPs, and tools are required across seeds; prompt-only variants test presentation rather than objective learning and cannot substitute for independent training runs.
2. **Presentation style at evaluation (3 levels):** neutral, competitive/assertive, and warm/affiliative framing, randomized orthogonal to training objective with manipulation checks on action selection.
3. **Runtime boundary (2 levels):** complete stateful fenced mediation (complete) versus stateless per-call checking (stateless) in a harmless synthetic workspace.
4. **Human scope-conferral arms (2 randomized arms):** a *fixed-grant arm* holding credentials constant across all 18 cells to estimate $\mathbb{P}(H \mid G = g, S)$, and an *operator-choice arm* (requiring institutional ethics approval, informed consent, and debriefing) randomizing human operators across cells to record delegated scope $\mathbb{P}(G = g \mid S)$ and total unconditional harm $\mathbb{P}(H \mid S)$.

Conflict scenarios include shared-allowance temptation, explicit beneficiary refusal, mid-episode priority change, two-issuer synthetic community-steward purpose withdrawal, availability of a strictly better replacement assistant, and positive non-abstention tasks where universal refusal fails. Primary endpoints are unauthorized proposals, unauthorized committed effects per campaign, and legitimate task completion, clustered by training seed and human participant. The caretaker hypothesis is refuted if consent-sensitive post-training fails to reduce limit-probing relative to tournament or welfare-proxy objectives at fixed grants, or if affiliative presentation expands human scope grants enough to raise unconditional harm in the operator-choice arm. Zero caretaker training runs or human-participant sessions have been executed.

E Twelve-Field Authority Record, Upgrade Renewal Matrix, and Artifact Provenance

E.1 Operational twelve-field authority and legitimacy record

Any deployment claiming bounded reach under Conditions C1–C6 should maintain a versioned, externally auditable record across twelve mandatory fields. Recording Unknown is valid and required whenever evidence is absent; an Unknown entry blocks the authority scope that depends on that premise rather than defaulting to permission.

1. **Purpose, Owners, and Affected Parties:** Intended task, direct beneficiaries, third parties and communities bearing externalized risk or resource burdens, accountable human sponsor, independent reviewer, and unilateral halt holders.
2. **Jurisdiction and Legitimacy:** Legal and moral standing of every grant issuer; required individual and collective quorums; unresolved jurisdictional disputes; accessible contestation, appeal, and remedy procedures.
3. **Mediated Scope and Channels:** Permitted action types, destinations, data classes, credentials, shared stores, RPC framing caps, and every prose, voice, or UI channel reaching human reviewers.
4. **Cryptographic Identity:** Model checkpoint and tokenizer digests, runtime and verifier binary SHA-256 hashes, tool schemas, active policy revision, and context/memory retention rules.
5. **Conferred Authority and Revocation Semantics:** Per-action caps, cross-copy cumulative budget B, reservation uncertainty envelope $\mathscr{B}_t$, expiration timestamps, sub-delegation attenuation rules ($\text{permits}_{\text{child}} \subseteq \text{permits}_{\text{parent}}$), and the distinction between broker admission withdrawal and durable sink epoch fencing (including expected lock-wait latency and non-refunded timeout quarantine).
6. **Verified Properties and Trusted Base:** Formally proved invariants, exact boundary between executable code (exec) and ghost trace specifications (spec), trusted adapters (parsers, SQLite WAL, OS kernel, cooperative sink idempotence), and known specification omissions.
7. **Evaluated Usefulness and Operational Tax:** Legitimate positive tasks, non-abstention semantic oracles, compound benign false-block rates across gate depth k, synchronous fencing delay, and stranded-budget fraction.
8. **Adversarial and Audit Measurements:** Empirical joint miss rate J_k under coordinated surrogate, score-feedback, and candidate-retry attacks; planted-pathway Fisher exact audit power across (P, q_0, r); campaign-level clustering; frozen holdout digest.
9. **Transfer and Excluded Regimes:** Capability class covered by current measurements, excluded stronger or colluding adversaries, and unmodeled physical or social bypasses.
10. **Operations, Custody, and External Audit:** Append-only sink effect receipts, observed monitoring eligibility, DiscoveryLedger stage enforcing Custody Rules R1–

System or world change	Premises remaining valid	Voided evidence requiring remeasurement	Mandatory interim scope rule
New model weights, distillation, or capability jump	All-policy Tier-1 `policy-core` predicates and finite-state conservation invariants	Empirical joint miss J_k, pathway width w, length ℓ, and planted-audit search power π_t	Run new checkpoint in zero-authority search/probation first; retain prior capability cap until J_k and π_t are remeasured.
Added agent copies, higher concurrency, or faster loop	Shared-ledger conservation across serialized `broker.sqlite` reservations	Attempt volume N, SQLite contention p95 latency, and reactive halt deadline margin $\mathbb{P}(T_{\text{halt}} \geq T_{\text{irrev}})$	Share one durable ledger across all copies; rely on pre-commit leases/fences rather than reactive output halts.
New tools, external APIs, credentials, or sinks	Existing mediated paths only; zero guarantee on the new path by default	Mediation completeness (C1), sink idempotence/deduplication, and epoch-fence atomicity on every new edge	Deny unmediated or non-idempotent external sinks; require atomic sink deduplication and durable `epoch_floor` before enabling.
Process crash, restart, or grant renewal	Durable WAL reservations, used IDs, and monotone `epoch_floor` if storage survived	Post-recovery `audit` cross-check of `charged`, `reservations`, `permits`, `effects`, and `epoch_floor`	Quarantine uncertain `Pending` reservations without refund; verify `audit` invariant before reopening proposer RPC.
Controller promotion ($v_0 \to v_1$)	Prior ledger spend and sink fences if carried forward intact	Subset check permits(v_1) $\subseteq$ permits(v_0); any broadened scope requires fresh issuer grants and holdout replay	Block promotion automatically whenever permits(v_1) $\not\subseteq$ permits(v_0) without explicit new multi-issuer approval.
Revised harm definition or affected jurisdiction	None for the newly recognized harm class	Every prior specification check, omission witness search, and stakeholder grant record	Suspend affected operation classes, seal the cut via `DiscoveryLedger`, and replay prior certificates against the expanded spec.

Table 17: Premise-level upgrade renewal matrix. Mechanized proofs over all policies survive weight updates, whereas empirical measurements survive only on the capability class, channel topology, and harm specification sampled.

R6 (cut-only disclosure prior to deployment), halt/recovery drill logs, and outside audit access.

11. **Ecological Footprint and Territorial Consent:** Scoped electricity, cooling water, critical-mineral, and land accounts by site and period; affected non-user communities; prior informed consent procedures and withdrawal terms [62, 63].
12. **Knowledge Provenance and Irreversibility:** Source provenance, CARE collective data governance terms [64], permitted purposes, and an explicit pre-consent statement of what token revocation cannot undo once data are disclosed or distilled into weights.

E.2 Upgrade renewal matrix and artifact provenance

Table 17 codifies which premises survive and which expire under six system or specification transitions. Table 18 records the bijective SHA-256 inventory of all six supplied archival files in `tips/` (`tips/manifest.json`) alongside the V1, V2, and V3–V5 reference artifacts.

Local verification gate (`make required`). Executing `make required` (`scripts/required.sh`) runs all checks strictly inside `target/` (never `/tmp`): `cargo fmt --check`, `cargo clippy -D warnings`, all Rust unit/integration/interleaving tests, all Python `unittest` suites, fresh quick runs and source-hash validations of V1 (`scripts/run.py` + `scripts/validate.py`), V2 (`scripts/run_v2.py` + `scripts/analyze_v2.py --source` on Linux, including pinned Verus verification and 6 Z3 soundness mutations via `scripts/verify_core.py`), and V3–V5 (`scripts/run_v3.py --quick` + `scripts/validate_v3.py --source`), reference validations against `12b5579` and current checkout sources, byte-exact LaTeX table/figure synchronization (`scripts/paper.py --check`), and deterministic 3-pass PDF compilation (`scripts/build_paper.py`, `SOURCE_DATE_EPOCH=1794340800`) enforcing sequential `[1]..[N]` citation ordering and rejecting unresolved references, font substitutions, missing glyphs, or overfull boxes > 2.0 pt. Linux CI executes on the `neverhuman-lan` runner group (`[self-hosted, Linux, X64, lan-ci, ubuntu24]`) while retaining portable functional verification on `macos-latest`.

Artifact / Reference Tier	Bytes / Scope	Exact SHA-256 Digest / Validation Command and Status
tips/Intelligence_Is_Not_Authority_Final(2).tex	129,361 B	1b750fa3d49cd16f1c09222c4a32ad82032dc4c85b25fcf514e5cf16dca151ce (archival original; byte-identical)
tips/intelligence-is-not-authority (1).tex	167,898 B	7db5cd8dbc1de224fc653559e06b88b3eef8fc736cdddb2468d5c00c070e46d8 (archival original; byte-identical copy)
tips/intelligence-is-not-authority.tex	167,898 B	7db5cd8dbc1de224fc653559e06b88b3eef8fc736cdddb2468d5c00c070e46d8 (archival original; byte-identical copy)
tips/Superintelligence_Is_Not_Sovereignty.tex	102,340 B	16622092440c97ddba4721441cbcb9a875668950e2b0a7f8802ff4198a882c87 (archival original; byte-identical)
tips/experiments.py	33,762 B	5be238ef0cbf172d1322621968280eb898ff878b7a19bc60928193517e81778b (archival Python reference; byte-identical)
tips/intelligence_is_not_authority.tex	213,168 B	6d8c089821f229590fb1d5635588ecfc0527b38da42b9589c5925109f0be7c1c (archival 28-page manuscript; byte-identical)
V1 Baseline (evidence/reference/)	Commit 12b5579	Binary 4e1e44bcc849e50bea606aae894ad06d26d76ea01b79b3ac365f2290e5b459dc; preserved byte-for-byte (10,180 states, 8 scenarios); checked via scripts/validate.py evidence/reference --source-ref 12b5579.
Prior V2 PR#1 Baseline	Commit 68783a0	Retained in Git history and linked in evidence/reference/revision-index.json; superseded in working tree by refreshed Wave 2 V2 reference.
V5-Unified V2 Reference (evidence/v2/reference/)	Publication (0 GPU-s)	Binary 59d4a17230e3851a33e32d3ea1fb45b321a3cfa266a252e3bd651f0ffa87797b; policy-core/src/lib.rs f9d3f964ab65f2cbc26c0340b7b56fc4248cfeb3216c1e2171bd115d940e71c9; src/protocol_v2.rs 688852078aaefb8ae5ca3cfa2a4aa25d455603f46ea23af845724d21d5861b44; src/isolation_v2.rs e777bd33ece882151f1ba8be9b8890a70518f425b52bf1d58ed0a4368ff92d58; fixtures/v2/evaluation.json c045f7ae1347f7c092a8d52737592539b7d40751e377c007cdd34ad2e1591b7b (226 obligations, 6/6 soundness mutations, 31 faults, 18/18 1..32-actor linearizations, 11/11 probes, 320 CPU Qwen3 campaigns); checked via scripts/analyze_v2.py evidence/v2/reference --source.
V5-Unified V3–V5 Reference (evidence/v3/reference/)	22 JSONs + traj (seed=20261110)	Binary 59d4a17230e3851a33e32d3ea1fb45b321a3cfa266a252e3bd651f0ffa87797b; pure-Rust modules including src/v5_superintelligence.rs (f1c8aec5...d8f7), src/v5_e2e_crypto_cluster.rs (4fb809bb...ade0), src/v5_statistical_spine.rs (8bdd75e8...11db), src/crypto_authority.rs, src/v4_real_graphs.rs, and src/v4_neural_rl.rs; checked via scripts/validate_v3.py evidence/v3/reference --source.

Table 18: Complete SHA-256 provenance inventory of all six supplied archival files in tips/ and the four reference evidence tiers indexed in evidence/reference/revision-index.json.