

ECE102, Fall 2019

Department of Electrical and Computer Engineering
University of California, Los Angeles

Midterm

Prof. J.C. Kao
TAs: W. Feng, J. Lee & S. Wu

UCLA True Bruin academic integrity principles apply.

Open: Two cheat sheets allowed.

Closed: Book, computer, internet.

2:00-3:50pm.

Wednesday, 13 Nov 2019.

State your assumptions and reasoning.

No credit without reasoning.

Show all work on these pages.

There is an extra blank space on page 16 to show your work if you run out of space on any questions.

Name: _____

Signature: _____

ID#: _____

Problem 1 _____ / 35

Problem 2 _____ / 20

Problem 3 _____ / 20

Problem 4 _____ / 25

BONUS _____ / 6 bonus points

Total _____ / 100 points + 6 bonus points

1. **Signal and System Properties + Convolution** (35 points).

(a) (15 points) Determine if each of the following statements is true or false. Briefly explain your answer to receive full credit.

i. (5 points) $x(t) = \cos(\sqrt{3}t) + \sin(-3t)$ is a periodic signal.

ii. (5 points) A signal can be neither energy signal nor power signal.


iii. (5 points) Let $f(t) * g(t)$ denote the convolution of two signals, $f(t)$ and $g(t)$. Then,

$$f(t)[\delta(t) * g(t)] = [f(t)\delta(t)] * g(t)$$

(b) (10 points) Determine if the following system is an LTI system. Explain your answer.


$$y(t) = \frac{x(t-1)}{t} + x(t-2) \quad (1)$$

- (c) (10 points) For signals $f(t)$ and $g(t)$ plotted below, graphically compute the convolution signal $h(t) = f(t) * g(t)$. To receive partial credit, you may show $h(0)$, $h(1/4)$ and $h(5/8)$ in the graph when illustrating the convolution using the “flip and drag” technique.



2. **LTI Systems** (20 points).

Consider the following LTI system S :



Consider an input signal $x_1(t) = e^{-2t}u(t-2)$. It is given that

$$\begin{aligned} x_1(t) &\xrightarrow{S} y_1(t) \\ \frac{dx_1(t)}{dt} &\xrightarrow{S} -2y_1(t) + e^{-2t}u(t) \end{aligned}$$

(a) (4 points) Show that:

$$\frac{dx_1(t)}{dt} = -2x_1(t) + e^{-2t}\delta(t-2)$$

(b) (10 points) Find the impulse response $h(t)$ of S .

Hint: Since we have not provided S , we cannot straightforwardly input an impulse into the system and measure the output. One approach is to solve for $h(t)$ by writing the output of S in terms of a convolution when the input is $dx_1(t)/dt$, i.e.,

$$\frac{dx_1(t)}{dt} * h(t)$$

- (c) (6 points) Consider a new system, S_2 , whose impulse response is $h_2(t) = e^{-3t}u(t+3)$. Find this system's output to the following input signal:

$$x_2(t) = \cos\left(\frac{\pi}{4}t\right)\delta(t-1)$$

3. **Fourier Series** (20 points).

- (a) (10 points) Let the Fourier Series coefficients of $f(t)$ be denoted f_k , and the Fourier Series coefficients of $g(t)$ denoted g_k . Let T_o be the period of $f(t)$. If $g(t) = f(a(t-b))$, where $a > 0$, show that

$$g_k = e^{-j2\pi \frac{ab}{T_o} k} f_k.$$

- (b) (10 points) Let the Fourier Series coefficients of $x(t)$ and $y(t)$ be x_k and y_k respectively, with respective periods T_1 and T_2 . We define $f(t) = \alpha_1 x(t) + \alpha_2 y(t)$ with non-zero α_1, α_2 , with period $T_o = m_1 T_1 = m_2 T_2$. What are the Fourier Series coefficients f_k in terms of x_k and y_k ?

4. **Fourier Transform** (25 points).

Consider the signal

$$x(t) = \text{sinc}(2t)$$

and let the Fourier transform of $x(t)$ be denoted $X(j\omega)$. We are interested in calculating the area under the curve of $x(t)$.

(a) (10 points) Prove that the following relationship holds.

$$\int_{-\infty}^{\infty} x(t) dt = X(j\omega)|_{\omega=0}$$

(b) (5 points) Use the result of part (a) to calculate:

$$\int_{-\infty}^{\infty} x(t) dt$$

for $x(t) = \text{sinc}(2t)$.

(c) (5 points) Consider the following system:

$$y(t) = e^{-j\omega_0 t} x(t)$$

Let $x(t) = \text{sinc}(2t)$ and consider only $\omega_0 > 0$. Are there any values of ω_0 for which

$$\int_{-\infty}^{\infty} y(t) dt = 0$$

and if so, what value(s) of ω_0 does this hold for?

(d) (5 points) Consider the following system:

$$y(t) = x(t) + \alpha \text{rect}(t)$$

Let $x(t) = \text{sinc}(2t)$. Are there any values of α for which

$$\int_{-\infty}^{\infty} y(t) dt = 0$$

and if so, what value(s) of α does this hold for?

Bonus (6 points) Suppose $x(t) = \cos(\omega_o t)$ is an eigenfunction of an LTI system S for any ω_o , and S cannot be defined as $S[x(t)] = ax(t)$ for some constant a . Is the system S causal? Justify your answer.

This is an extra piece of paper to show your work. If you use this space for a question, for that question, please write "Refer to page 16."

Property	Signal	Transform
Linearity	$\alpha x_1(t) + \beta x_2(t)$	$\alpha X_1(j\omega) + \beta X_2(j\omega)$
Duality	$X(t)$	$2\pi x(-\omega)$
Conjugate symmetry	$x(t)$ real	$X^*(j\omega) = X(-j\omega)$ Magnitude: $ X(-j\omega) = X(j\omega) $ Phase: $\Theta(-\omega) = -\Theta(\omega)$ Real part: $X_r(-j\omega) = X_r(j\omega)$ Imaginary part: $X_i(-j\omega) = -X_i(j\omega)$
Conjugate antisymmetry	$x(t)$ imaginary	$X^*(j\omega) = -X(-j\omega)$ Magnitude: $ X(-j\omega) = X(j\omega) $ Phase: $\Theta(-\omega) = -\Theta(\omega) \mp \pi$ Real part: $X_r(-j\omega) = -X_r(j\omega)$ Imaginary part: $X_i(-j\omega) = X_i(j\omega)$
Even signal	$x(-t) = x(t)$	$X(j\omega)$: even
Odd signal	$x(-t) = -x(t)$	$X(j\omega)$: odd
Time shifting	$x(t - \tau)$	$X(j\omega) e^{-j\omega\tau}$
Frequency shifting	$x(t) e^{j\omega_0 t}$	$X(j(\omega - \omega_0))$
Modulation property	$x(t) \cos(\omega_0 t)$	$\frac{1}{2} [X(j(\omega - \omega_0)) + X(j(\omega + \omega_0))]$
Time and frequency scaling	$x(at)$	$\frac{1}{ a } X\left(\frac{j\omega}{a}\right)$
Differentiation in time	$\frac{d^n}{dt^n} [x(t)]$	$(j\omega)^n X(j\omega)$
Differentiation in frequency	$(-jt)^n x(t)$	$\frac{d^n}{d\omega^n} [X(j\omega)]$
Convolution	$x_1(t) * x_2(t)$	$X_1(j\omega) X_2(j\omega)$
Multiplication	$x_1(t) x_2(t)$	$\frac{1}{2\pi} X_1(j\omega) * X_2(j\omega)$
Integration	$\int_{-\infty}^t x(\lambda) d\lambda$	$\frac{X(j\omega)}{j\omega} + \pi X(0) \delta(\omega)$
Parseval's theorem	$\int_{-\infty}^{\infty} x(t) ^2 dt$	$= \frac{1}{2\pi} \int_{-\infty}^{\infty} X(j\omega) ^2 d\omega$

Table 4.4 – Fourier transform properties.

Additional properties:	$x(t)$: even and real	$X(j\omega)$: even and real
	$x(t)$: odd and real	$X(j\omega)$: odd and imaginary
	$x(t)$: even and imaginary	$X(j\omega)$: even and imaginary
	$x(t)$: odd and imaginary	$X(j\omega)$: odd and real

Name	Signal	Transform
Rectangular pulse	$x(t) = A \text{rect}(t/\tau)$	$X(j\omega) = A\tau \text{sinc}\left(\frac{\omega\tau}{2\pi}\right)$
Triangular pulse	$x(t) = A \Lambda(t/\tau)$	$X(j\omega) = A\tau \text{sinc}^2\left(\frac{\omega\tau}{2\pi}\right)$
Right-sided exponential	$x(t) = e^{-at} u(t)$	$X(j\omega) = \frac{1}{a + j\omega}$
Two-sided exponential	$x(t) = e^{-a t }$	$X(j\omega) = \frac{2a}{a^2 + \omega^2}$
Signum function	$x(t) = \text{sgn}(t)$	$X(j\omega) = \frac{2}{j\omega}$
Unit impulse	$x(t) = \delta(t)$	$X(j\omega) = 1$
Sinc function	$x(t) = \text{sinc}(t)$	$X(j\omega) = \text{rect}\left(\frac{\omega}{2\pi}\right)$
Constant-amplitude signal	$x(t) = 1, \text{ all } t$	$X(j\omega) = 2\pi \delta(\omega)$
	$x(t) = \frac{1}{\pi t}$	$X(j\omega) = -j \text{sgn}(\omega)$
Unit-step function	$x(t) = u(t)$	$X(j\omega) = \pi \delta(\omega) + \frac{1}{j\omega}$
Modulated pulse	$x(t) = \text{rect}\left(\frac{t}{\tau}\right) \cos(\omega_0 t)$	$X(j\omega) = \frac{\tau}{2} \text{sinc}\left(\frac{(\omega - \omega_0)\tau}{2\pi}\right) + \frac{\tau}{2} \text{sinc}\left(\frac{(\omega + \omega_0)\tau}{2\pi}\right)$

Note:

$$\text{sinc}(\alpha) = \frac{\sin(\pi\alpha)}{\pi\alpha}$$

$$\text{rect}(t/\tau) = u(t + \tau/2) - u(t - \tau/2)$$

Table 4.5 – Some Fourier transform pairs.