



# WebSystique

learn together

## Spring Auto-detection autowire & Component-scanning Example With Annotations

🕒 August 18, 2014    👤 websystiqueadmin

In this post we will see how Spring can `auto-detect` the beans configured in your application using `component-scanning`, wire them where required without even declaring as `@Bean` methods in `@Configuration` class ( or in XML terms, without declaring bean in Spring XML Configuration file). We will also see corresponding XML configuration side-by-side for comparison.

We will proceed with help of a typical enterprise level application setup example showing different layers(Service, DAO) involved in application development.

### Other interesting posts you may like

- [Spring MVC 4+AngularJS Example](#)
- [Spring MVC 4+Hibernate 4 Many-to-many JSP Example](#)
- [Spring MVC 4+Hibernate 4+MySQL+Maven integration example using annotations](#)
- [Spring MVC4 FileUpload-Download Hibernate+MySQL Example](#)

WebSyst

G+ Foll

+ 127

### Recent Posts

[Spring 4 MVC+AngularJS  
CRUD Application using  
ngResource](#)

[Angularjs Server  
Communication using  
ngResource-CRUD  
Application](#)

[AngularJS Custom-Directives  
controllers, require option  
guide](#)

[AngularJS Custom-Directives  
transclude, ngTransclude  
guide](#)

[AngularJS Custom-Directives  
replace option guide](#)


- [TestNG Mockito Integration Example Stubbing Void Methods](#)
- [Maven surefire plugin and TestNG Example](#)
- [Spring MVC 4 Form Validation and Resource Handling](#)

### Following technologies being used:

- Spring 4.0.6.RELEASE
- Joda-time 2.3
- Maven 3
- JDK 1.6
- Eclipse JUNO Service Release 2

## Project directory structure

Following will be the final project directory structure for this example:



Let's add the content mentioned in above directory structure.

## Step 1: Provide Spring dependencies in Maven pom.xml

```
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://mave
<modelVersion>4.0.0</modelVersion>

<groupId>com.websystique.spring</groupId>
<artifactId>Spring4AutoScanning</artifactId>
<version>1.0.0</version>
<packaging>jar</packaging>

<name>Spring4AutoScanning</name>
<properties>
  <springframework.version>4.0.6.RELEASE</springframework.ver
  <joda-time.version>2.3</joda-time.version>
</properties>

<dependencies>
  <!-- Spring -->
  <dependency>
    <groupId>org.springframework</groupId>
    <artifactId>spring-core</artifactId>
    <version>${springframework.version}</version>
  </dependency>
  <dependency>
    <groupId>org.springframework</groupId>
    <artifactId>spring-context</artifactId>
    <version>${springframework.version}</version>
  </dependency>

  <!-- Joda-Time -->
  <dependency>
    <groupId>joda-time</groupId>
    <artifactId>joda-time</artifactId>
    <version>${joda-time.version}</version>
  </dependency>
</dependencies>

</project>
```

We need Spring core and Spring context dependencies to work with this example. Additionally in our example we will be doing some date calculation using JodaTime LocalDate class, so joda-time dependency is in there.

## Step 2: Create Spring Configuration Class

Spring configuration class are the ones annotated with `@Configuration`. These classes contains methods annotated with `@Bean`. These `@Bean` annotated methods generates beans managed by Spring container.

```
package com.websystique.spring.configuration;

import org.springframework.context.annotation.ComponentScan;
import org.springframework.context.annotation.Configuration;

@Configuration
@ComponentScan(basePackages = "com.websystique.spring")
public class AppConfig {

}
```

You might have noticed that above class is Empty, no `@Bean` methods, acting as a placeholder instead. So where will the beans come from?

Actually, they will be auto-detected, thanks to `@ComponentScan` annotation.

```
@ComponentScan(basePackages = "com.websystique.spring")
```

`@ComponentScan` `basePackages` attribute takes package name[s] as input which will be search for to find any class annotated with Spring specific annotations.

Below are commonly used Spring annotation which makes a bean auto-detectable:

`@Repository` - Used to mark a bean as DAO Component on persistence layer

`@Service` - Used to mark a bean as Service Component on business layer

`@Controller` - Used to mark a bean as Controller Component on Presentation layer

`@Configuration` - Used to mark a bean as Configuration Component.

`@Component` - General purpose annotation, can be used as a replacement for above annotations.

Note that all above mentioned annotations are internally annotated with `@Component`, so indeed you can use `@Component` everywhere, but to keep the design & intention clean, it's advisable to use different annotation based on different condition.

Remark: In our example, you can even discard the Configuration class altogether as it does not contain any `@Bean` method. We will see how to scan the beans in that case below.

Same Configuration in **XML terms** can be expressed as below (let's name it app-config.xml)

```
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:context="http://www.springframework.org/schema/context"
  xsi:schemaLocation="http://www.springframework.org/schema/beans
    http://www.springframework.org/schema/beans
    http://www.springframework.org/schema/context http://www.springframework.org/schema/context"
  >
  <context:component-scan base-package="com.websystique.spring" />
</beans>
```

### Step 3: Create DAO Layer Classes

```
package com.websystique.spring.dao;

import com.websystique.spring.model.Employee;

public interface EmployeeDao {

    void saveInDatabase(Employee employee);

}
```

```
package com.websystique.spring.dao;

import org.springframework.stereotype.Repository;
import com.websystique.spring.model.Employee;

@Repository("employeeDao")
public class EmployeeDaoImpl implements EmployeeDao{

    public void saveInDatabase(Employee employee) {

        /*
         * Logic to save in DB goes here
         */
        System.out.println("Employee "+employee.getName()+" is regi

    }

}
```

`@Repository` annotation marks this class as an Auto-detectable bean on persistence layer. Parameter to this annotation `employeeDao` provides a name to this bean. We will inject this class into main service bean.

### Step 4: Create Service Layer Classes

```
package com.websystique.spring.service;

import org.joda.time.LocalDate;

public interface DateService {

    LocalDate getNextAssessmentDate();

}
```

```
package com.websystique.spring.service;

import org.joda.time.LocalDate;
import org.springframework.stereotype.Service;

@Service("dateService")
```

```
public class DateServiceImpl implements DateService{

    public LocalDate getNextAssessmentDate() {
        return new LocalDate(2015,10,10);
    }

}
```

`@Service` marks this class as Auto-detectable bean on business layer.  
We will inject this class into main service bean.

```
package com.websystique.spring.service;

import com.websystique.spring.model.Employee;

public interface EmployeeService {

    void registerEmployee(Employee employee);

}
```

```
package com.websystique.spring.service;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import com.websystique.spring.dao.EmployeeDao;
import com.websystique.spring.model.Employee;

@Service("employeeService")
public class EmployeeServiceImpl implements EmployeeService{

    @Autowired
    private DateService dateService;

    @Autowired
    private EmployeeDao employeeDao;

    public void registerEmployee(Employee employee) {
        employee.setAssessmentDate(dateService.getNextAssessmentDate());
        employeeDao.saveInDatabase(employee);
    }

}
```

EmployeeService is our main service class. Notice that we have injected both DateService and EmployeeDao in this.

`@Autowired` on dateService property marks the DateService to be auto-wired by Spring's dependency injection with the appropriate bean in Spring context. In our case, we have already declared a DateService bean using `@Service`, so that bean will be injected here. Similarly, employeeDao will be injected by EmployeeDao annotated with `@Repository`.

Below is the model class `Employee` used in our example

```
package com.websystique.spring.model;
```

```

import org.joda.time.LocalDate;

public class Employee {

    private int id;

    private String name;

    private LocalDate assessmentDate;

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public LocalDate getAssessmentDate() {
        return assessmentDate;
    }

    public void setAssessmentDate(LocalDate assessmentDate) {
        this.assessmentDate = assessmentDate;
    }

    @Override
    public String toString() {
        return "Employee [id=" + id + ", name=" + name + ", assessm"
            + assessmentDate + "]";
    }

}

```

## Step 5: Create Main to run as Java Application

```

package com.websystique.spring;

import org.springframework.context.annotation.AnnotationConfigAppli
import org.springframework.context.support.AbstractApplicationConte

import com.websystique.spring.configuration.AppConfig;
import com.websystique.spring.model.Employee;
import com.websystique.spring.service.EmployeeService;

public class AppMain {

    public static void main(String args[]){
        AbstractApplicationContext context = new AnnotationConfigAppli

        EmployeeService service = (EmployeeService) context.getBear

        /*
         * Register employee using service
         */
        Employee employee = new Employee();
        employee.setName("Danny Theys");
        service.registerEmployee(employee);
    }
}

```

```
        context.close();
    }
}
```

Run above program as Java Application, you should see following output

```
Employee Danny Theys is registered for assessment on 2015-10-10
```

Now, in case you decided to discard the configuration class `AppConfig` you can do so with following changes

```
package com.websystique.spring;

import org.springframework.context.annotation.AnnotationConfigApplicati
import com.websystique.spring.model.Employee;
import com.websystique.spring.service.EmployeeService;

public class AppMain {

    public static void main(String args[]){
        //AbstractApplicationContext context = new AnnotationConfigApplicati
        AnnotationConfigApplicationContext context = new AnnotationConfigApplicati
        context.scan("com.websystique.spring");
        context.refresh();

        EmployeeService service = (EmployeeService) context.getBean("employeeService");

        /*
         * Register employee using service
         */
        Employee employee = new Employee();
        employee.setName("Danny Theys");
        service.registerEmployee(employee);

        context.close();
    }
}
```

`AnnotationConfigApplicationContext.scan` method performs a scan of all class in specified package[s], registering all the beans annotated with `@Component` (even `@configuration` itself is internally annotated with `@component`) in application context. A caveat here is that refresh must be called after scan in order to fully process the registered classes.

Run above program as Java Application, you should see same output as before.

That's it.

For **XML based configuration** , replace



```
AbstractApplicationContext context = new AnnotationConfigApplicati
```

with

```
AbstractApplicationContext context = new ClassPathXmlApplicationCor
```

in above main, no other changes. Run the program and you will see same output.

## **Download Source Code**

[Download Now!](#)

## References

- [Spring framework](#)
- [@ComponentScan](#)



### websystiqueadmin

If you like tutorials on this site, why not take a step further and connect me on [Facebook](#) , [Google Plus](#) & [Twitter](#) as well? I would love to hear your thoughts on these articles, it will help me improve further our learning process.

If you appreciate the effort I have put in this learning site, help me improve the visibility of this site towards global audience by sharing and linking this site from within and beyond your network. You & your friends can always link my site from your site on [www.websystique.com](http://www.websystique.com), and share the learning.

After all, we are here to learn together, aren't we?



## Related Posts:

1. [Spring Beans Auto-wiring Example using XML Configuration](#)
2. [Spring 4 + Hibernate 4 + MySQL+ Maven Integration example](#)

**(Annotations+XML)**

3. **Spring Dependency Injection Annotation Example, Beans Auto-wiring using @Autowired, @Qualifier & @Resource Annotations Configuration**
4. **TestNG Mockito Example Stubbing Void Methods**

 [spring.](#)  [permalink.](#)

← [Spring 4 Hello World Example](#)

[Spring @PropertySource & @Value annotations example](#) →

0 Comments

**websystique**

 **Login** ▾

 **Recommend**

 **Share**

**Sort by Best** ▾

Start the discussion...

Be the first to comment.

**ALSO ON WEBSYSTIQUE****WHAT'S THIS?****Spring Security 4 Logout Example**

5 comments • 7 months ago



**Muhammed Abdul** — Thank you for your swift response. As of now, i am using mvn clean

**Spring Security 4 Hibernate Integration Annotation+XML**

43 comments • 7 months ago



**websystique** — Glad you liked it Imad. Thanks a lot.

**Spring MVC 4 FileUpload-Download Hibernate+MySQL**

34 comments • 6 months ago



**Kamal** — Did it work for you finally ? You may try creating the war and then depolying it to

**AngularJS Tutorial**

6 comments • 6 months ago



**websystique** — Hi Alim, Glad you liked it.

