



DEM



DEM



4. Sampling Design for Digital Soil Mapping

Canadian Digital Soil Mapping Workshop, 2020

About Us

Brandon Heung

Dalhousie University

Brandon.Heung@dal.ca



Daniel Saurette

Ontario Ministry of Agri-Food and Rural Affairs

University of Guelph

Daniel.Saurette@ontario.ca


Outline

1. **Harmonizing soil profile data**
2. **Sampling Design**




Depth Functions

- Soil sampling traditionally completed by pedogenic horizon (e.g., Ah, Ae, Bt, Ck)
- Bulk sample is collected from each horizon
- Analyses are completed and results represent the mean for that horizon
- In Digital Soil Mapping, we need the ability to predict for any depth interval
- 2 common approaches:
 - 3D predictions
 - stacked 2D predictions
- We will deal with stacked 2D approach



Depth Functions – 2D Stacking Approach

- To allow us to set prediction intervals, we need to convert the horizon data to a continuous function
- Most common approach is to use a mass preserving spline, or equal area quadratic spline function
- 2 parameters:
 - lam – controls smoothness
 - d – depth intervals
- User can specify as many depth intervals as wanted
- GlobalSoilMap.net specifications: 0-5, 5-15, 15-30, 30-60, 60-100 and 100-200 cm



Fun Fact:

One of the early pioneers of this approach, Dr. Ponce-Hernandez, is professor at Trent University!

Module 4.1: Depth Functions

- Hypothetical soil profile was sampled on a horizon basis.
- Particle size fractions, SOC, and pH were measured.
- Equal-area spline function will be used to convert the data into standard depth increments
 - 0-5 cm
 - 5-15 cm
 - 15-30 cm
 - 30-60 cm
 - 60-100 cm



Outline

1. Harmonizing soil profile data
2. **Sampling Design**




Sampling Design

- Sampling design is a critical first step in DSM, much like any experiment
- Two high-level types of sampling:
 - Probability sampling (design-based)
 - Non-probability sampling (model-based)
- Design-based Sampling must meet 2 requirements:
 - All units of the population have a probability of being selected
 - Selection probability of each unit is known
- Today we will review design-based sampling approaches:
 - Simple Random Sampling
 - Stratified Random Sampling – Equal
 - Stratified Random Sampling – Proportional
 - Grid Sampling
 - Conditioned Latin Hypercube Sampling


Simple Random Sampling

- All samples within the region have equal probability of being selected
- Advantages
 - Simple
 - Prior knowledge of the population not required
- Disadvantages
 - May not consider feature attributes (covariates)
 - Potential for clustered sampling
 - Efficiency may be reduced



Stratified Random Sampling

- Divide the population into strata (e.g. elevation)
- Sampling is random within the strata
- Equal sampling or proportional sampling by strata
- Advantages
 - Higher accuracy (if strata are meaningful)
- Disadvantages
 - May not consider feature attributes (covariates)
 - Strata knowledge may be flawed





Grid Sampling

- Systematic sampling approach
- Must determine adequate grid spacing
- Advantages
 - Simple
 - Efficient
 - Low Cost
- Disadvantages
 - May not consider feature attributes (covariates)
 - Hard to determine appropriate grid size
 - Coarse grid could miss small-scale variability

.		
.		
.		
.		
.		


Conditioned Latin Hypercube Sampling (cLHS)

- Type of stratified sampling
- Full factorial experiment is not feasible with many covariates
- Covariates are each split into intervals based on their CDFs
- Selects one observation per partition of the CDF for each covariate
- Advantages
 - Closely resembles the distribution of the population of the covariates
 - Sample plan always optimized for feature space
- Disadvantages
 - Determining sample size
 - Access to sites can be difficult
 - No spatial component (e.g., potential for clustering and dispersion)




Assessing the Feature Space Coverage of a Sampling Plan

- Visual assessment comparing histograms
- Visual assessment comparing cumulative distribution functions
- Kolmogorov-Smirnov test
 - Non-parametric test of the equality of continuous distributions
 - Compares the CDFs
 - Null hypothesis is that both samples come from the same distribution
 - Reject at $p < 0.05$




Module 4.2: Sampling Designs


- Generate sampling designs in R for Keene, ON:
 - Simple Random Sampling
 - Stratified Random Sample: Equal Sampling within Strata
 - Stratified Random Sampling: Proportional Sampling within Strata
 - Grid sampling
 - Conditioned Latin Hypercube Sampling
- Evaluating sampling designs



DEM



DEM



4. Sampling Design for Digital Soil Mapping

Canadian Digital Soil Mapping Workshop, 2020