

# RNN Bitesized Pieces

Reuben Brasher

March 21, 2022

RNNs

RNN with attention

# Basic RNNs

- ▶ Any feedforward NN architecture can be used to define RNN

# Basic RNNs

- ▶ Any feedforward NN architecture can be used to define RNN
- ▶ For each time  $t$  let  $x_t$  be a feature vector

# Basic RNNs

- ▶ Any feedforward NN architecture can be used to define RNN
- ▶ For each time  $t$  let  $x_t$  be a feature vector
- ▶ Concatenate with previous output and feed into net

$$y_t = F(x_t, y_{t-1})$$

# LSTM and GRU

“Long short-term memory” Hochreiter and Schmidhuber, 1997  
“Empirical evaluation of gated recurrent neural networks on sequence modeling” Chung et al., 2014

# LSTM and GRU secret sauce

- ▶ Entrywise multiplication of two previous layers outputs

$$(x \odot y)_i = x_i y_i$$

# LSTM and GRU secret sauce

- ▶ Entrywise multiplication of two previous layers outputs

$$(x \odot y)_i = x_i y_i$$

- ▶ Called gates because they are continuous analogs of boolean and gates. If  $x$  and  $y$  are strictly 1 or 0, then

$$x \wedge y = x \times y$$



# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .

# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .
- ▶ Output gate,  $\sigma_t^j = \sigma(W_o x_t + U_o h_{t-1} + V_o c_t)$

# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .
- ▶ Output gate,  $\sigma_t^j = \sigma(W_o x_t + U_o h_{t-1} + V_o c_t)$
- ▶ Memory cell,  $c_t^j = f_t^j c_{t-1}^j + i_t^j \tilde{c}_t^j$

# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .
- ▶ Output gate,  $\sigma_t^j = \sigma(W_o x_t + U_o h_{t-1} + V_o c_t)$
- ▶ Memory cell,  $c_t^j = f_t^j c_{t-1}^j + i_t^j \tilde{c}_t^j$
- ▶ Memory content,  $\tilde{c}_t^j = \tanh(W_c x_t + U_c h_{t-1})$

# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .
- ▶ Output gate,  $\sigma_t^j = \sigma(W_o x_t + U_o h_{t-1} + V_o c_t)$
- ▶ Memory cell,  $c_t^j = f_t^j c_{t-1}^j + i_t^j \tilde{c}_t^j$
- ▶ Memory content,  $\tilde{c}_t^j = \tanh(W_c x_t + U_c h_{t-1})$
- ▶ Forget gate,  $f_t^j = \sigma(W_f x_t + U_f h_{t-1} + V_f c_{t-1})$

# LSTM suggestive names

- ▶ Activation,  $h_t^j = \sigma_t^j \tanh(c_t^j)$ .
- ▶ Output gate,  $\sigma_t^j = \sigma(W_o x_t + U_o h_{t-1} + V_o c_t)$
- ▶ Memory cell,  $c_t^j = f_t^j c_{t-1}^j + i_t^j \tilde{c}_t^j$
- ▶ Memory content,  $\tilde{c}_t^j = \tanh(W_c x_t + U_c h_{t-1})$
- ▶ Forget gate,  $f_t^j = \sigma(W_f x_t + U_f h_{t-1} + V_f c_{t-1})$
- ▶ Input gate,  $i_t^j = \sigma(W_i x_t + U_i h_{t-1} + V_i c_{t-1})$

# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .

# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .
- ▶ Output gate,  $o_t = \sigma(A_o(x_t, h_{t-1}, c_t))$



# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .
- ▶ Output gate,  $o_t = \sigma(A_o(x_t, h_{t-1}, c_t))$
- ▶ Memory cell,  $c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$

# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .
- ▶ Output gate,  $o_t = \sigma(A_o(x_t, h_{t-1}, c_t))$
- ▶ Memory cell,  $c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$
- ▶ Memory content,  $\tilde{c}_t = \tanh(A_c(x_t, h_{t-1}))$

# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .
- ▶ Output gate,  $o_t = \sigma(A_o(x_t, h_{t-1}, c_t))$
- ▶ Memory cell,  $c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$
- ▶ Memory content,  $\tilde{c}_t = \tanh(A_c(x_t, h_{t-1}))$
- ▶ Forget gate,  $f_t = \sigma(A_f(x_t, h_{t-1}, c_{t-1}))$

# LSTM rewritten

- ▶ Activation,  $h_t = o_t \odot \tanh(c_t)$ .
- ▶ Output gate,  $o_t = \sigma(A_o(x_t, h_{t-1}, c_t))$
- ▶ Memory cell,  $c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$
- ▶ Memory content,  $\tilde{c}_t = \tanh(A_c(x_t, h_{t-1}))$
- ▶ Forget gate,  $f_t = \sigma(A_f(x_t, h_{t-1}, c_{t-1}))$
- ▶ Input gate,  $i_t = \sigma(A_i(x_t, h_{t-1}, c_{t-1}))$

# GRU suggestive names

- ▶ Activation,  $h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$ .

## GRU suggestive names

- ▶ Activation,  $h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$ .
- ▶ Update gate,  $z_t = \sigma(A_z(x_t, h_{t-1}))$

## GRU suggestive names

- ▶ Activation,  $h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$ .
- ▶ Update gate,  $z_t = \sigma(A_z(x_t, h_{t-1}))$
- ▶ Candidate activations,  $\tilde{h}_t = \tanh(A(x, r \odot h_{t-1}))$

## GRU suggestive names

- ▶ Activation,  $h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$ .
- ▶ Update gate,  $z_t = \sigma(A_z(x_t, h_{t-1}))$
- ▶ Candidate activations,  $\tilde{h}_t = \tanh(A(x, r \odot h_{t-1}))$
- ▶ Reset gate,  $r_t = \sigma(A_r(x_t, h_{t-1}))$



# Sequence to sequence with attention

“Neural machine translation by jointly learning to align and translate” Bahdanau, Cho, and Bengio, 2014

# Attention Layers

- ▶ Let  $x_j$  be the input sequence and  $h_j$  encoding by RNN.

# Attention Layers

- ▶ Let  $x_j$  be the input sequence and  $h_j$  encoding by RNN.
- ▶ Let  $y_i$  be the target sequence, and  $s_i$  a hidden state.

# Attention Layers

- ▶ Let  $x_j$  be the input sequence and  $h_j$  encoding by RNN.
- ▶ Let  $y_i$  be the target sequence, and  $s_i$  a hidden state.
- ▶

$$s_i = f(s_{i-1}, y_{i-1}, c_i)$$

# Attention Layers

- ▶ Let  $x_j$  be the input sequence and  $h_j$  encoding by RNN.
- ▶ Let  $y_i$  be the target sequence, and  $s_i$  a hidden state.
- ▶

$$s_i = f(s_{i-1}, y_{i-1}, c_i)$$

- ▶  $c_i$ , called the context vector is

$$c_i = \sum_j \alpha_{ij} h_j$$

# Attention Layers

- ▶ Let  $x_j$  be the input sequence and  $h_j$  encoding by RNN.
- ▶ Let  $y_i$  be the target sequence, and  $s_i$  a hidden state.
- ▶

$$s_i = f(s_{i-1}, y_{i-1}, c_i)$$

- ▶  $c_i$ , called the context vector is




$$c_i = \sum_j \alpha_{ij} h_j$$

- ▶  $\alpha_{ij}$  is the importance of  $h_j$  for  $s_i$

$$\alpha_{ij} = \frac{\exp(e_{ij})}{\sum_k \exp(e_{ik})}$$

where  $e_{ij} = a(a_{i-1}, h_j)$ .

# References I

-  Bahdanau, Dzmitry, Kyunghyun Cho, and Yoshua Bengio (2014). “Neural machine translation by jointly learning to align and translate”. In: *arXiv preprint arXiv:1409.0473*.
-  Chung, Junyoung et al. (2014). “Empirical evaluation of gated recurrent neural networks on sequence modeling”. In: *arXiv preprint arXiv:1412.3555*.
-  Hochreiter, Sepp and Jürgen Schmidhuber (1997). “Long short-term memory”. In: *Neural computation* 9.8, pp. 1735–1780.