

Latent Diffusion

Reuben Brasher

April 26, 2023

Diffusion models

Diffusion objective function

$$L_{DM} = \mathbb{E}_{x, \epsilon \sim \mathcal{N}(0,1)} \left[\|\epsilon - \epsilon_{\theta}(x_t, t)\|_2^2 \right]$$

Latent diffusion objective function

Encode x into a *Latent space* as $z = \mathcal{E}(x)$.

$$L_{DM} = \mathbb{E}_{\mathcal{E}(x), \epsilon \sim \mathcal{N}(0,1)} \left[\|\epsilon - \epsilon_{\theta}(z_t, t)\|_2^2 \right]$$

Cross-attention mechanism

If y is a modal input, such a text description compute Q, K, V by

$$Q = W_Q \varphi(z_t)$$

$$K = W_K \tau(y)$$

$$V = W_V \tau(y)$$

Then $\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d}}\right) \dot{V}$.

Conditional latent diffusion objective function



$$L_{DM} = \mathbb{E}_{\mathcal{E}(x), \epsilon \sim \mathcal{N}(0,1)} \left[\|\epsilon - \epsilon_{\theta}(z_t, t, \tau(y))\|_2^2 \right]$$

Futher reading

Rombach et al., 2022

Zhang and Agrawala, 2023

References I

-  Rombach, Robin et al. (2022). “High-resolution image synthesis with latent diffusion models”. In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695.
-  Zhang, Lvmin and Maneesh Agrawala (2023). “Adding conditional control to text-to-image diffusion models”. In: *arXiv preprint arXiv:2302.05543*.