

Efficient GPU training of LSNNs using eProp

James C Knight
J.C.Knight@sussex.ac.uk

University of Sussex
School of Engineering and Informatics
Brighton, United Kingdom

Thomas Nowotny
T.Nowotny@sussex.ac.uk

University of Sussex
School of Engineering and Informatics
Brighton, United Kingdom

ABSTRACT

Taking inspiration from machine learning libraries – where techniques such as parallel batch training minimise latency and maximise GPU occupancy – as well as our previous research on efficiently simulating Spiking Neural Networks (SNNs) on GPUs for computational neuroscience, we have extended our GeNN SNN simulator to enable spike-based machine learning research on general purpose hardware. We demonstrate that SNN classifiers implemented using GeNN and trained using the eProp learning rule can provide comparable performance to those trained using Back Propagation Through Time and show that the latency and energy usage of our SNN classifiers is up to $7\times$ lower than an LSTM running on the same GPU hardware.

CCS CONCEPTS

• **Computing methodologies** → *Bio-inspired approaches; Supervised learning; Vector / streaming algorithms.*

KEYWORDS

datasets, neural networks, gaze detection, text tagging

ACM Reference Format:

James C Knight and Thomas Nowotny. 2021. Efficient GPU training of LSNNs using eProp. In *NICE '21: Proceedings of the Neuro-inspired Computational Elements Workshop*. ACM, New York, NY, USA, 3 pages. <https://doi.org/10.1145/1122445.1122456>

1 INTRODUCTION

In recent years, several new techniques for directly training spiking neural networks (SNNs) have been developed. One approach is to replace the non-differentiable ‘transfer function’ of a spiking neuron with a differentiable surrogate function [3, 5, 25], allowing SNNs to be trained with the same algorithms used to train rate-based Recurrent Neural Network (RNNs) such as Back Propagation Through Time (BPTT). While BPTT is computationally efficient – because it requires gradients to be stored during the forward pass in order for them to be applied during a backward pass – it has a memory requirement which grows with time preventing it from being applied to long input sequences or used online. RTRL [20] is an alternative ‘forward mode’ algorithm for training

RNNs but, in its general form, it is too computationally expensive to be practical. However, if the gradients flowing through the ‘explicit’ recurrent connections are ignored and only those flowing through the ‘implicit’ recurrence represented by the dynamics of individual neurons is considered, much more computationally tractable learning rules can be derived [24]. Learning rules of this sort include SuperSpike [23], eProp [3] and Decolte [15]. **(TODO: SOME BACKGROUND ON SPIKE-TIME BASED LEARNING)** However, in order to apply new spike-based machine learning techniques to larger models and data-sets as well as prototyping algorithms for neuromorphic hardware [1, 8, 11], new tools are required which can efficiently simulate SNNs on existing hardware. The development of efficient SNN simulators has been a key area of computational neuroscience research for several decades [2, 6, 12, 13, 21] but, these simulators **(TODO: MORE)**, making them ill-suited for spike-based machine learning research. As such, many ML researchers have chosen to build libraries [9, 10, 14, 18] on top of more familiar tools such as PyTorch. However, while libraries like PyTorch are highly-optimised for rate-based models, they does not take advantage of the spatio-temporal sparsity of SNNs which have the potential to enable massive computational savings over rate-based networks [22].

While our GeNN simulator [16, 17, 21] was originally developed for Computational Neuroscience research, its longstanding focus on flexibility and its targeting of GPU accelerators make it well-suited to the needs of spike-based ML. **(TODO: TALK ABOUT ADDITIONS TO GENN)** Here we demonstrate this by training SNN classifiers on the Spiking Heidelberg Digits [7] and the Spiking Sequential MNIST [19] datasets. In section 2.1 we compare the trained performance of these classifiers to those trained using BPTT, in section 2.2 we compare the time taken to train these models and in section 2.3 we compare the latency and energy usage of our SNN classifiers to LSTMs running on the same GPU hardware.

2 RESULTS

We trained LSNNs of various sizes with feedforward and recurrent connectivity on the Spiking Heidelberg Digits (SHD) [7] and spiking sequential MNIST [19] datasets using eProp with the default parameters employed by Bellec et al. [4].

2.1 Accuracy

In figure 2 we compare the performance of our models trained on the SHD dataset with results obtained by Zenke and Vogels [25] using BPTT. There is no significant **(TODO: SUITABLE SIGNIFICANCE TEST?)** difference between the performance of the 256 neuron models and, because the reduced memory requirement of eProp allow larger models to be trained, we show that the performance can be significantly improved by increasing the number of neurons to 512.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted by ACM, provided that the copies are not made for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

NICE '21, March 28–April 1, 2021, San Antonio, TX

© 2021 Association for Computing Machinery.

ACM ISBN 9978-1-4503-9559-5...\$15.00

<https://doi.org/10.1145/1122445.1122456>

2021-11-24 10:17. Page 1 of 1-3.




Figure 1: 1907 Franklin Model D roadster. Photograph by Harris & Ewing, Inc. [Public domain], via Wikimedia Commons. (<https://goo.gl/VLCRBB>).




Figure 2: Performance comparison of LSNNs trained with eProp using GeNN and SNNs trained with BPTT using PyTorch [25] on Spiking Heidelberg Digits dataset. Bars signify the mean and error bars the standard deviation over 5 (GeNN) and 10 (PyTorch) simulations.

2.2 Training time

While being able to train networks with high classification accuracy is important, training also needs to be fast. In figure 3 we compare the time taken to train recurrent LSNNs using eProp with GeNN against recurrent LIF networks training using BPTT with PyTorch. When using short input sequences, training using GeNN is slower (probably due to PyTorch’s use of our GPU’s tensor cores) but, as sequence length increases, GeNN becomes faster and the memory requirements of BPTT mean that PyTorch is unable to train models larger than 256 neurons on 1370 timestep input sequences.

2.3 Inference time

In figure 1, we compare the inference time and energy delay products (TODO: CITE) of LSNNs simulated using GeNN against LSTM




Figure 3: Training times comparison of LSNNs trained with eProp using GeNN and SNNs trained with BPTT using PyTorch on Spiking Heidelberg Digits dataset. A 12 GB Titan V GPU is used for all experiments. Input spike trains are binned to achieve different numbers of timesteps. Missing bars indicate insufficient memory for experiment.

models running on the same hardware [19] as well as LSNNs running on the Loihi neuromorphic system [8]. On the same Titan V GPU, LSNNs are faster than LSTMs and have a lower EDP across all batch sizes. Compared to inference using LSTMs, LSNN inference has a much lower arithmetic intensity meaning that, at batch size 1, not only is the CPU code generated by GeNN faster than TensorFlow running on CPU but it is also faster than GeNN running on GPU. Finally, although LSNN inference on Loihi has a much lower Energy-Delay Product, inference on both GPU and CPU using GeNN has lower latency.

3 FUTURE WORK

(TODO: EVENTPROP, CONVOLUTIONAL NETWORKS, DEEPER NETWORKS)

4 CONCLUSIONS

By adding additional functionality aimed at accelerating spike-based machine learning workflows to our GeNN simulator, we have demonstrated that training using ‘forward-mode’ learning rules like eProp can not only result in competitive accuracy in classification tasks but also allow larger models to be trained on longer input sequences than is possible when using BPTT. Finally we demonstrate that, by exploiting temporal sparsity, standard CPU and GPU hardware can perform inference faster and with less energy using LSNNs than it can using standard LSTM models.

ACKNOWLEDGMENTS

To Robert, for the bagels and explaining CMYK and color spaces.

REFERENCES

- [1] 2014. A million spiking-neuron integrated circuit with a scalable communication network and interface. *Science* 345, 6197 (2014), 668–673. <https://doi.org/10.1126/science.1254642>
- [2] Nora Abi Akar, Ben Cumming, Vasileios Karakasis, Anne Kusters, Wouter Klijn, Alexander Peyser, and Stuart Yates. 2019. Arbor – A Morphologically-Detailed Neural Network Simulation Library for Contemporary High-Performance Computing Architectures. In *2019 27th Euromicro International Conference on Parallel, Distributed and Network-Based Processing (PDP)*. IEEE, 274–282. <https://doi.org/10.1109/EMPDP.2019.8671560> arXiv:1901.07454
- [3] Guillaume Bellec, Darjan Salaj, Anand Subramoney, Robert Legenstein, and Wolfgang Maass. 2018. Long short-term memory and learning-to-learn in networks of spiking neurons. In *Advances in Neural Information Processing Systems*, Vol. 2018-December. 787–797. arXiv:1803.09574
- [4] Guillaume Bellec, Franz Scherr, Anand Subramoney, Elias Hajek, Darjan Salaj, Robert Legenstein, and Wolfgang Maass. 2020. A solution to the learning dilemma for recurrent networks of spiking neurons. *Nature Communications* 11, 1 (dec 2020), 3625. <https://doi.org/10.1038/s41467-020-17236-y>
- [5] Sander M. Bohte. 2011. Error-backpropagation in networks of fractionally predictive spiking neurons. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)* 6791 LNCS, PART 1 (2011), 60–68. https://doi.org/10.1007/978-3-642-21735-7_8
- [6] Nicholas T Carnevale and Michael L Hines. 2006. *The NEURON book*. Cambridge University Press.
- [7] Benjamin Cramer, Yannik Stradmann, Johannes Schemmel, and Friedemann Zenke. 2020. The Heidelberg Spiking Data Sets for the Systematic Evaluation of Spiking Neural Networks. *IEEE Transactions on Neural Networks and Learning Systems* (2020). <https://doi.org/10.1109/TNNLS.2020.3044364> arXiv:1910.07407
- [8] Mike Davies, Narayan Srinivasa, Tsung-han Lin, Gautham Chinya, Yongqiang Cao, Sri Harsha Choday, Georgios Dimou, Prasad Joshi, Nabil Imam, Shweta Jain, Yuyun Liao, Chit-kwan Lin, Andrew Lines, Ruokun Liu, Deepak Mathaikutty, Steve McCoy, Arnab Paul, Jonathan Tse, Guruguhathan Venkataramanan, Yihsin Weng, Andreas Wild, Yoonseok Yang, and Hong Wang. 2018. Loihi : a Neuromorphic Manycore Processor with On-Chip Learning. *IEEE Micro* 30, 1 (2018), 82–99. <https://doi.org/10.1109/MM.2018.112130359>
- [9] Jason K Eshraghian, Max Ward, Emre Neftci, Xinxin Wang, Gregor Lenz, Girish Dwivedi, Mohammed Bannamoun, Doo Seok Jeong, and Wei D Lu. 2021. Training spiking neural networks using lessons from deep learning. *arXiv preprint arXiv:1906.09395* (2021).
- [10] Wei Fang, Yanqi Chen, Jianhao Ding, Ding Chen, Zhaofei Yu, Huihui Zhou, Yonghong Tian, and other contributors. 2020. SpikingJelly. <https://github.com/fangwei123456/spikingjelly>.
- [11] Stephen B Furber, Francesco Galluppi, S Temple, and Luis A Plana. 2014. The SpiNNaker Project. *Proc. IEEE* 102, 5 (may 2014), 652–665. <https://doi.org/10.1109/JPROC.2014.2304638>
- [12] Marc-Oliver Gewaltig and Markus Diesmann. 2007. NEST (NEural Simulation Tool). *Scholarpedia* 2, 4 (2007), 1430.
- [13] Bruno Golosio, Gianmarco Tiddia, Chiara De Luca, Elena Pastorelli, Francesco Simula, and Pier Stanislao Paolucci. 2021. Fast Simulations of Highly-Connected Spiking Cortical Models Using GPUs. *Frontiers in Computational Neuroscience* 15, February (feb 2021), 1–17. <https://doi.org/10.3389/fncom.2021.627620>
- [14] Hananel Hazan, Daniel J. Saunders, Hassaan Khan, Devdhar Patel, Darpan T. Sanghavi, Hava T. Siegelmann, and Robert Kozma. 2018. BindsNET: A Machine Learning-Oriented Spiking Neural Networks Library in Python. *Frontiers in Neuroinformatics* 12, December (dec 2018), 1–18. <https://doi.org/10.3389/fninf.2018.00089> arXiv:1806.01423
- [15] Jacques Kaiser, Hesham Mostafa, and Emre Neftci. 2020. Synaptic Plasticity Dynamics for Deep Continuous Local Learning (DECOLLE). *Frontiers in Neuroscience* 14, May (may 2020), 1–11. <https://doi.org/10.3389/fnins.2020.00424> arXiv:1811.10766
- [16] James C Knight, Anton Komissarov, and Thomas Nowotny. 2021. PyGeNN: A Python Library for GPU-Enhanced Neural Networks. *Frontiers in Neuroinformatics* 15, April (apr 2021). <https://doi.org/10.3389/fninf.2021.659005>
- [17] James C. Knight and Thomas Nowotny. 2018. GPUs Outperform Current HPC and Neuromorphic Solutions in Terms of Speed and Energy When Simulating a Highly-Connected Cortical Model. *Frontiers in Neuroscience* 12, December (2018), 1–19. <https://doi.org/10.3389/fnins.2018.00941>
- [18] Christian Pehle and Jens Egholm Pedersen. 2021. *Norse - A deep learning library for spiking neural networks*. <https://doi.org/10.5281/zenodo.4422025> Documentation: <https://norse.ai/docs/>.
- [19] Philipp Plank, Arjun Rao, Andreas Wild, and Wolfgang Maass. 2021. A Long Short-Term Memory for AI Applications in Spike-based Neuromorphic Hardware. (2021). arXiv:2107.03992 <http://arxiv.org/abs/2107.03992>
- [20] Ronald J. Williams and David Zipser. 1989. A Learning Algorithm for Continually Running Fully Recurrent Neural Networks. *Neural Computation* 1, 2 (1989), 270–280. <https://doi.org/10.1162/neco.1989.1.2.270>
- [21] Esin Yavuz, James Turner, and Thomas Nowotny. 2016. GeNN: a code generation framework for accelerated brain simulations. *Scientific Reports* 6, 1 (may 2016), 18854. <https://doi.org/10.1038/srep18854>
- [22] Bojian Yin, Federico Corradi, and Sander M. Bohte. 2021. Accurate and efficient time-domain classification with adaptive spiking recurrent neural networks. (2021), 1–15. arXiv:2103.12593 <http://arxiv.org/abs/2103.12593>
- [23] Friedemann Zenke and Surya Ganguli. 2018. SuperSpike: Supervised Learning in Multilayer Spiking Neural Networks. *Neural Computation* 30, 6 (jun 2018), 1514–1541. https://doi.org/10.1162/neco_a_01086 arXiv:NIHMS150003
- [24] Friedemann Zenke and Emre O. Neftci. 2021. Brain-Inspired Learning on Neuromorphic Substrates. *Proc. IEEE* (2021), 1–16. <https://doi.org/10.1109/JPROC.2020.3045625> arXiv:2010.11931
- [25] Friedemann Zenke and Tim P. Vogels. 2021. The Remarkable Robustness of Surrogate Gradient Learning for Instilling Complex Function in Spiking Neural Networks. *Neural computation* 33, 4 (2021), 899–925. https://doi.org/10.1162/neco_a_01367