








		APVD	LDJ	1.5.2024	PLANETARY GEARBOX
		CHKD			
	1:1	DRN	YSX	1.5.2024	MG17-G5
	SCALE	SIGNATURE		DATE	



SPECIFICATION	CONNECTION	VALUE
GEAR RATIO		10
EFFICIENCY		90.00%
BACKLASH@NO-LOAD(arcmin)		<=30
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]		5.00[44.25]
SHAFT MAXIMUM AXIAL LOAD(N)		100
SHAFT MAXIMUM RADIAL LOAD(N)		300
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)		6.5-10.5
RATED INPUT SPEED(RPM)		1000
MAX. INPUT SPEED(RPM)		2000
NOISE(dB)		<=55
WATERPROOF RATING		IP54
WORKING TEMPERATURE		-20°C~150°C[-4°F~302°F]






STEPPERONLINE®

	APVD	YSX	1.5.2024
	CHKD		
1:1	DRN		
SCALE	SIGNATURE	DATE	

PLANETARY GEARBOX

MG17-G10




SPECIFICATION	CONNECTION	VALUE
GEAR RATIO		20
EFFICIENCY		80.00%
BACKLASH@NO-LOAD(arcmin)		<=45
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]		10.00[88.51]
SHAFT MAXIMUM AXIAL LOAD(N)		100
SHAFT MAXIMUM RADIAL LOAD(N)		300
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)		6.5-10.5
RATED INPUT SPEED(RPM)		1000
MAX. INPUT SPEED(RPM)		2000
NOISE(dB)		<=55
WATERPROOF RATING		IP54
WORKING TEMPERATURE		-20°C~150°C[-4°F~302°F]




STEPPERONLINE®

	APVD	LDJ	1.5.2024
	CHKD		
1:1	DRN	YSX	1.5.2024
SCALE	SIGNATURE	DATE	

PLANETARY GEARBOX

MG17-G20






SPECIFICATION	CONNECTION	VALUE
GEAR RATIO		50
EFFICIENCY		80.00%
BACKLASH@NO-LOAD(arcmin)		≤ 45
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]		10.00[88.51]
SHAFT MAXIMUM AXIAL LOAD(N)		100
SHAFT MAXIMUM RADIAL LOAD(N)		300
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)		6.5-10.5
RATED INPUT SPEED(RPM)		1000
MAX. INPUT SPEED(RPM)		2000
NOISE(dB)		≤ 55
WATERPROOF RATING		IP54
WORKING TEMPERATURE		$-20^{\circ}\text{C} \sim 150^{\circ}\text{C} [-4^{\circ}\text{F} \sim 302^{\circ}\text{F}]$




STEPPERONLINE®

	APVD	LDJ	1.5.2024
	CHKD		
1:1	DRN	YSX	1.5.2024
SCALE	SIGNATURE	DATE	

PLANETARY GEARBOX

MG17-G50





SPECIFICATION	CONNECTION	VALUE
GEAR RATIO		100
EFFICIENCY		80.00%
BACKLASH@NO-LOAD(arcmin)		<=45
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]		5.00[44.25]
SHAFT MAXIMUM AXIAL LOAD(N)		100
SHAFT MAXIMUM RADIAL LOAD(N)		300
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)		6.5-10.5
RATED INPUT SPEED(RPM)		1000
MAX. INPUT SPEED(RPM)		2000
NOISE(dB)		<=55
WATERPROOF RATING		IP54
WORKING TEMPERATURE		-20°C~150°C[-4°F~302°F]

STEPPERONLINE®

	APVD	LDJ	1.5.2024
	CHKD		
1:1	DRN	YSX	1.5.2024
SCALE	SIGNATURE	DATE	

PLANETARY GEARBOX

MG17-G100

