SLIP-1

Q1.

```
<?php
session_start();
if(isset($_SESSION['cnt']))
{
$_SESSION['cnt']=$_SESSION['cnt']+1;
}
else
$_SESSION['cnt']=1;
echo"<body bgcolor=red> the web page has been accesed ".$_SESSION['cnt'] ."times</body>";
?>
```

Q2.

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
df=pd.read_csv(r"/home/comp-14/Position_Salaries.csv");
print(df)
X=df[['Position','Level']]
y=df['Salary']
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size =0.3)
print("\n training set of X=\n",X_train.head(5))
print("\n testing set of X=\n",X_test.head(5))
print("\n training set of y=\n",y_train.head(5))
print("\n testing set of y=\n",y_train.head(5))
lg=LinearRegression()
lg.fit(X_train,y_train)
pred_x=lg.predict(X_test)
print("\n predicted value of x is=",pred_x)
acc=lg.score(X_test,y_test)
print("\n accuracy of model=",acc)
```

SLIP-2

Q1.

- Slip2.html

```
<HTML>
  <FORM method="get" action="A1SAQ2.php">
    Select Font Style<input type="text" name=a><br>
    Select Font Size<input type="text" name=b><br>
    Select Font Color<input type="text" name=c><br>
    Select Background Color<input type="text" name=d><br>
    <input type="submit">
  </FORM>
</HTML>
```

- display.php

```
<?php
setcookie("fn",$_GET['s1']);
setcookie("fs",$_GET['s2']);
setcookie("fc",$_GET['s3']);
setcookie("bc",$_GET['s4']);
echo"selected settings are<br>";
echo"<br>font Name".$_GET['s1'];
echo"<br>font size".$_GET['s2'];
echo"<br>font color".$_GET['s3'];
echo"<br>Background Color".$_GET['s4'];
?>
<form action=seta2_apply.php method=get>
  <input  value=apply type=submit>
</form>
```

- apply.php

```
<?php
$fn=$_COOKIE['fn'];
$fc=$_COOKIE['fc'];
$fs=$_COOKIE['fs'];
$bc=$_COOKIE['bc'];
echo"<body bgcolor=$bc><font face=$fn size=$fs  color=$fc>
welcome to the college </font></body>";
?>
```

Q2.

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
df=pd.read_csv(r"/home/comp-14/Salary.csv");
print(df)
X=df[['YearsExperience’]]
y=df['Salary']
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size =0.3)
print("\n training set of X=\n",X_train.head(5))
print("\n testing set of X=\n",X_test.head(5))
print("\n training set of y=\n",y_train.head(5))
print("\n testing set of y=\n",y_train.head(5))
lg=LinearRegression()
lg.fit(X_train,y_train)
pred_x=lg.predict(X_test)
print("\n predicted value of x is=",pred_x)
acc=lg.score(X_test,y_test)
print("\n accuracy of model=",acc)
```

SLIP-3

Q1.

- Slip3.php

```
<?php
session_start();

if(isset($_SESSION['cnt']))
{
   $_SESSION['cnt']=$_SESSION['cnt']+1;
   if($_SESSION['cnt']>=3)
   {
      header("Location:A1fail.php");
   }
   echo "login failed".$_SESSION['cnt']."times";
}
else
{
   $_SESSION['cnt']=0;
}
?>

<FORM method=get action=A1login.php>
   User Name<input type=text name=n><br>
   Password<input type=text name=p><br>
   <input type=submit value=Login>
</FORM>
```

- A1fail.php

```
<?php
session_start();
echo "login failed".$_SESSION['cnt']."times";
echo "<br>Your chances are finished";
session_destroy();
?>
```

- A1login.php

```
<?php
session_start();

if($_GET['n']=="abc" && $_GET['p']==12345)
{
   session_destroy();
   header("Location:A1welcome.php");
}
else
{
   header("Location:Slip3.php");
}
?>
```

- A1welcome.php

```
<?php
  echo "Welcome";
?>
```

Q2.

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn import metrics
import seaborn as sn
import matplotlib.pyplot as plt
data = pd.read_csv(r"d:\Python\Data Analytics\Ass1\User_Data.csv")
print(data)
# Splitting our Data set in Dependent and Independent variables.
x= data[['Age','EstimatedSalary']]
y= data['Purchased']
#print(x[:10])
#print(y[:10])
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.25)
#Performing simple logistic regression (create regression model)
lg= LogisticRegression()
lg.fit(x_train,y_train)
y_pred=lg.predict(x_test)
# Print the Accuracy and plot the Confusion Matrix
confusion_matrix = pd.crosstab(y_test, y_pred, rownames=['Actual'], colnames=['Predicted'])
sn.heatmap(confusion_matrix, annot=True)
print('Accuracy: ',metrics.accuracy_score(y_test, y_pred))
plt.show()
# Print test data and predicted data Predictions on the test set
print (" Test data values \n",x_test[:10])
print (" \n Predicated values \n",y_pred)
new_pred=lg.predict([[18,50000]])
print("person with given age and salary will buy a car?:",new_pred)
```

SLIP-4

Q1.

- Slip4.html

```
<HTML>
  <FORM method="get" action="secondpage.php">
    Eno<input type="text" name="a"><br>
    Ename<input type="text" name="b"><br>
    Eadd<input type="text" name="c"><br>
    <input type="submit" value="Next">
  </FORM>
</HTML>
```

- secondpage.php

```
<?php
session_start();
$_SESSION['eno']=$_GET['a'];
$_SESSION['ename']=$_GET['b'];
$_SESSION['eadd']=$_GET['c'];
?>

<FORM method="get" action="display.php">
  Basic<input type="text" name="1"><br>
  HRA<input type="text" name="2"><br>
  DA<input type="text" name="3"><br>
  <input type="submit" value="Result">
</FORM>
```

- display.php

```
<?php
session_start();
echo "EmpNo.:".$_SESSION['eno'];
echo "<br>EmpName:".$_SESSION['ename'];
echo "<br>EmpAdd:".$_SESSION['eadd'];

echo "<table border=5";
echo "<tr><th>DETAILS</th><th>AMOUNT</th></tr>";
echo "<tr><td>BASIC</td><td>".$_GET['1']."</td></tr>";
echo "<tr><td>HRA</td><td>".$_GET['2']."</td></tr>";
echo "<tr><td>DA</td><td>".$_GET['3']."</td></tr>";
$t=$_GET['1']+$_GET['2']+$_GET['3'];
echo "<tr><td>TOTAL</td><td>$t</td></tr>";
echo "</table>"
?>
```

Q2.

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
df=pd.read_csv(r"d:\Python\Data Analytics\Ass1\Fish.csv");
print(df.head(5));
#Identifying Independent and target variables
X = df[['Length1','Length2','Length3','Height','Width']]
y = df['Weight']
# spliting datasets into training and traget variables
X_train,X_test,y_train,y_test = train_test_split(X,y, test_size = 0.3)
# print the data
print("\n Training set of X=\n",X_train.head(5))
print("\n Testing set of X=\n",X_test.head(5))
print("\n Training set of y=\n",y_train.head(5))
print("\n Testing set of y=\n",y_test.head(5))
#creating object of linear regression
lg = LinearRegression() # Creating a regressior
lg.fit(X_train,y_train) # Fiting the dataset into the model
# predicting output by passing X_test
pred_x=lg.predict(X_test)
print("\n prdictaed value of x is=",pred_x)
# Test accuracy
acc=lg.score(X_test,y_test)
print("\n Accuracy of model=",acc)
```

SLIP-5

Q1. 5 different items

```
<?php
$s=<<<xml
<?xml version="1.0" ?>
<Itemdet>
<item>
   <itemno> 101</itemno>
   <name>book</name>
   <price>300</price>
   <qty>20</qty>
</item>
<item>
   <itemno> 102</itemno>
   <name>pen</name>
   <price>30</price>
   <qty>20</qty>
</item>
</Itemdet>
xml;
$fname="itm.xml";
$fp=fopen($fname,'w');
fwrite($fp,$s);
fclose($fp);
echo"File created sucessfully<br>";
$x = simplexml_load_file("itm.xml")   or die("Error: Cannot create object");
echo $x->asXML();
?>
```

Q2.

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn import metrics
import seaborn as sn
import matplotlib.pyplot as plt
data = pd.read_csv(r"d:\Python\Data Analytics\Ass1\Iris.csv")
print('Iris-setosa')
setosa=data['Species']=='Iris-setosa'
print(data[setosa].describe())
print('\n Iris-versicolor')
setosa=data['Species']=='Iris-versicolor'
print(data[setosa].describe())
print('Iris-virginica')
setosa=data['Species']=='Iris-virginica'
print(data[setosa].describe())
```

```
# Splitting our Data set in Dependent and Independent variables.
x = data[['SepalLengthCm','SepalWidthCm','PetalLengthCm','PetalWidthCm']]
y = data['Species']
print(x[:10])
print(y[:10])
x_train,x_test,y_train,y_test =
train_test_split(x,y,test_size=0.25,random_state=0)
#Performing simple logistic regression (create regression model)
lg= LogisticRegression()
lg.fit(x_train,y_train)
y_pred=lg.predict(x_test)
# Print the Accuracy and plot the Confusion Matrix
confusion_matrix = pd.crosstab(y_test, y_pred, rownames=['Actual'],
colnames=['Predicted'])
sn.heatmap(confusion_matrix, annot=True)
print('Accuracy: ',metrics.accuracy_score(y_test, y_pred))
plt.show()
# Print test data and predicted data Predictions on the test set
print (" Test data values \n",x_test[:10])
print (" \n Predicated values \n",y_pred)
new_pred=lg.predict([[4.9,3.0,1.4,3.0]])
print("predicated species:",new_pred)
```

SLIP-6

Q1.

- Slip6.php

```php
<?php
  $r=simplexml_load_file("book.xml");
  echo
"<table><tr><th>Code</th><th>Bname</th><th>Aname</th><th>Price</th><th>Year</th></tr>";
  foreach($r->children() as $b)
  {
   print_r($b);
   echo "<tr>";
   echo "<td>".$b["code"]."</td>";
   echo "<td>".$b->bname."</td>";
   echo "<td>".$b->aname."</td>";
   echo "<td>".$b->price."</td>";
   echo "<td>".$b->year."</td>";
   echo "</tr>";
  }
  echo "</table>";
?>
```

- book.xml

```xml
<?xml version="1.0"?>
<Bookdet>
 <Book>
   <1>
   <bname>JAVA</bname>
   <aname>Balguru Swami</aname>
   <price>250</price>
   <year>2006</year>
 </Book>
 <Book>
   <2>
   <bname>C</bname>
   <aname>Denis Ritchie</aname>
   <price>500</price>
   <year>1971</year>
 </Book>
</Bookdet>
```

Q2.

```python
import pandas as pd
#Create the sample dataset
transactions = [['bread','milk'],
['bread','diaper','beer','eggs'],
['milk', 'diaper','beer','coke'],
['bread', 'milk','diaper','beer'],
['bread', 'milk','diaper','coke']]
#transform it into the right format via the TransactionEncoder as follows:
from mlxtend.preprocessing import TransactionEncoder
te=TransactionEncoder()

te_array=te.fit(transactions).transform(transactions)
df=pd.DataFrame(te_array, columns=te.columns_)
print(df)
# Find the frequent itemsets
from mlxtend.frequent_patterns import apriori, association_rules
freq_items = apriori(df, min_support = 0.5, use_colnames = True)
print("\n FREQ ITEMS \n",freq_items)
# Generate the association rules
rules = association_rules(freq_items, metric ='support', min_threshold=0.05)
rules = rules.sort_values(['support', 'confidence'], ascending =[False,False])
print(rules)
```

SLIP-8

Q1.

```
<html>
   <head>
      <script>
         var t = confirm("Are u preparing for exam?");
         if(t==true)
        {
         var s = prompt("Enter ur name:");
         if((s.length)>0)
         {
            alert("ALL THE BEST");
         }
        }
        else
        {
          alert("Start ur preparation");
        }
      </script>
   </head>
   <body>Hello</body>
</html>
```

Q2.

```
import pandas as pd
from mlxtend.frequent_patterns import apriori, association_rules
from mlxtend.preprocessing import TransactionEncoder
df=pd.read_csv(r"d:\Python\Data Analytics\Ass2\Groceries_dataset.csv")
print(df.head(5))
# Preprocess the data (drop null values etc.)
df=df.dropna(inplace=True)
te=TransactionEncoder()

te_array=te.fit(df.values).transform(df.values)
df=pd.DataFrame(te_array, columns=te.columns_)
# Find the frequent itemsets
freq_items = apriori(df, min_support = 0.01, use_colnames = True)
print("\n FREQ ITEMS \n",freq_items)
# Generate the association rules
rules = association_rules(freq_items, metric ='lift', min_threshold=1)
rules = rules.sort_values(['support', 'confidence'], ascending =[False,False])
print(rules)
```

SLIP-9

Q1.

```
<html>
  <head>
    <script>
      function validate()
      {
        var un = document.getElementById('n1').value;
        var pwd = document.getElementById('n2').value;
        if(un==null || un==="")
        {
          alert('please enter username');
          return false;
        }
        else if(pwd==null || pwd==="")
        {
          alert('please enter password');
          return false;
        }
        else if(pwd.length<8)
        {
          alert('password should contain 8 char');
          return false;
        }
        else
          return true;
      }
    </script>
  </head>
  <body>
    <form method="get" action="sum.html" onsubmit="return validate()">
      username<input type="text" id="n1"><br>
      password<input type="text" id="n2"><br>
      <input type="submit">
    </form>
  </body>
</html>
```

➢ sum.html

```
<html>
  <head>
    <script>
      function add()
      {
        var a = document.getElementById('n1').value;
        var b = document.getElementById('n2').value;
        var c = parseInt(a)+parseInt(b);
        document.getElementById('n3').value=c;
      }
    </script>
  </head>
  <body>
    number 1<input type="text" id="n1"><br>
    number 2<input type="text" id="n2"><br>
    result<input type="text" id="n3"><br>

    <button onclick="add()" value="add"></button>
  </body>
</html>
```

Q2.

```
import pandas as pd
from mlxtend.frequent_patterns import apriori, association_rules
#Create the sample dataset
transactions =[['eggs', 'milk','bread'],
['eggs', 'apple'],
['milk', 'bread'],
['apple', 'milk'],
['milk', 'apple', 'bread']]
```

```
#transform it into the right format via the TransactionEncoder as follows:
from mlxtend.preprocessing import TransactionEncoder
te=TransactionEncoder()
te_array=te.fit(transactions).transform(transactions)
df=pd.DataFrame(te_array, columns=te.columns_)
print(df)
# Find the frequent itemsets
freq_items = apriori(df, min_support = 0.5, use_colnames = True)
print(freq_items)
# Generate the association rules
rules = association_rules(freq_items, metric ='support',
min_threshold=0.05)
rules = rules.sort_values(['support', 'confidence'], ascending
=[False,False])
print(rules)
```

SLIP-10

Q1.

```
<html>
   <head>
      <script src = "jquery-3.6.0.min.js"></script>
      <script>
         $(document).ready(function()
         {
            $("#b1").click(function()
            {
               $("img").before("<b>Welcome</b>");
            });
            $("#b2").click(function()
            {
               $("img").after("<b>Welcome</b>");
            });
         });
      </script></head>
   <body>
      <img src = "imp.jpeg" width="100" height="100"><br>

      <button id = "b1">Insert before</button>
      <button id = "b2">Insert after</button>
   </body>
</html>
```

Q2.

Same as above - Q.2

SLIP-11

Q1.

```
<html>
   <head>
      <script>
         function large()
         {
            document.getElementById("i").height=500;
            document.getElementById("i").width=500;
         }

         function small()
         {
            document.getElementById("i").height=100;
            document.getElementById("i").width=100;
         }
         function display()
         {
            var s = document.getElementById("n").value;
            if(s==null || s==="")
            {
               document.getElementById("d").innerHTML="<img id=i src=’location' height=200
width=200 onmouseover='large()' onmouseover='small()'>";
            }
         }
         function colour()
         {
            s = document.getElementById('n');
            s.style.color = "red";
            s.style.fontsize = "20px";
         }
      </script>
   </head>
   <body>
      <input type="text" id="n" onclick="display()" onblur="colour()">
      <div id="d"></div>
</html>
```

Q2.

Same as Slip 9 Q.2

SLIP-12

Q1.

- slip12.php

```php
<?php
  $fp = fopen('contact.dat','r');
  echo "<table border=1>";
  $h = array("SNO","NAME","RESIDENCY NO","MBNO","ADDRESS");
  echo "<tr>";
  foreach($h as $v)
  {
    echo "<th>$v</th>";
  }
  echo "</tr>";

  while($row = fscanf($fp,"%s%s%s%s%s"))
  {
    echo "<tr>";
    foreach($row as $r)
    {
      echo "<td>$r</td>";
    }
    echo "</tr>";
  }
  echo "</table>";
  fclose($fp);
?>
```

- contact.dat

101 Ravi 1005 9536745225 Vapi

```html
<html>
  <head>
    <script type = "text/javascript">
      function showdet()
      {
        if(window.XMLHttpRequest)
        {
          XHRobj = new XMLHttpRequest();
        }
        else
        {
          XHRobj = new ActiveXObject("Microsoft.XMLHTTP");
        }
        XHRobj.onreadystatechange = function()
        {
          if(XHRobj.readyState == 4 && XHRobj.status == 200)
          {
            document.getElementById("myDiv").innerHTML = XHRobj.responseText;
          }
        }
        XHRobj.open("GET","slip12.php",true);
        XHRobj.send();
      }
      </script></head>
      <body>
        <form>
          <br><input type = button value = getinfo onclick = "showdet()">
        </form>
        <div id = "myDiv"><b>Contact Details will be listed here.....</b></div>
      </body>
</html>
```

Q2.

```python
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
df=pd.read_csv(r"/home/comp-14/SOCR-HeightWeight.csv");
print(df)
X=df[['Index']]
y=df['Height(Inches)','Weight(Pounds)']
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size =0.3)
print("\n training set of X=\n",X_train.head(5))
print("\n testing set of X=\n",X_test.head(5))
print("\n training set of y=\n",y_train.head(5))
print("\n testing set of y=\n",y_train.head(5))
lg=LinearRegression()
lg.fit(X_train,y_train)
pred_x=lg.predict(X_test)
print("\n predicted value of x is=",pred_x)
acc=lg.score(X_test,y_test)
print("\n accuracy of model=",acc)
```

SLIP-13

Q1.

- slip13.php

```php
<?php
$q = isset($_GET['q']) ? trim($_GET['q']) : '';
$q = strtoupper($q);

if (strlen($q) === 0) {
   echo "Stranger";
} else {
   switch ($q) {
      case 'ROHIT':
         echo "Hello master Rohit";
         break;
      case 'DHONI':
         echo "Hello master Dhoni";
         break;
      default:
         echo "$q I don't know you";
         break;
   }
}
?>
```

```html
<html>
   <head>
      <script type = "text/javascript">
         function showdet(str)
         {
            if(window.XMLHttpRequest)
            {
               XHRobj = new XMLHttpRequest();
            }
            else
            {
               XHRobj = new ActiveXObject("Microsoft.XMLHTTP");
            }
            XHRobj.onreadystatechange = function()
            {
               if(XHRobj.readyState == 4 && XHRobj.status == 200)
               {
                  document.getElementById("myDiv").innerHTML = XHRobj.responseText;
               }
            }
            XHRobj.open("GET","slip13.php?q="+str,true);
            XHRobj.send();
         }
         function msg()
         {
            document.getElementById("myDiv").innerHTML = "user is typing";
         }
         </script></head>
         <body>
            <form>
               Enter Name<input type ="text" name ="n1" onkeyup="msg()">
               <br><input type = button value = getinfo onclick =
"showdet(form.n1.value)">
            </form>
            <div id = "myDiv">
            </div>
         </body>
</html>
```

Q2.

Same as Slip 9 Q.2

SLIP-14

Q1.

- slip14.php

```
<?php
   $q = $_GET["q"];
   echo $q;
   $c = pg_connect(" host=localhost port=5432 dbname=tycs user=postgres password=ssr");
   $sql = "select* from teacher where tname='".$q."'";

   $result = pg_query($c,$sql);
pg_fetc
   if(pg_num_rows($result)>0)
   {
     $r = pg_fetch_rows($result);
     echo "tno=".$r[0];
     echo "<br>tname=".$r[1];
     echo "<br>qualification=".$r[2];
     echo "<br>salary=".$r[3];
   }
   else
   {
     echo "no record";
   }
   ?>
```

*Create table Teacher in the database with values

Q2.

Same as Slip 9 Q.2

```
<html>
  <head>
    <script type="text/javascript">
     function showdet(str)
       {

          if(window.XMLHttpRequest)
          {
             XHRobj= new XMLHttpRequest();

          }
          else
          {
             XHRobj=new ActiveXobject("Microsoft.XMLHTTP");
          }
          XHRobj.onreadystatechange=function()
          {

          if(XHRobj.readyState==4 && XHRobj.status==200)
          {
             document.getElementById("myDiv").innerHTML=XHRobj.responseText;
          }
          }
       XHRobj.open("GET","slip14.php?q="+str,true);
       XHRobj.send();
       }
    </script>
  </head>
  <body>
    <form>
       enter Teacher Name<input type =text name=n1>
       <br><input type =button value=getinfo onclick="showdet(form.n1.value)">
    </form>
    <div id="myDiv"><b>Teacher Details will be listed here...</b></div>
  </body>
</html>
```

SLIP-18

Q1.

```
<html>
<head>
   <title>Fibonacci Generator</title>
</head>
<body>
   <h2>Fibonacci Sequence Generator</h2>
   <button onclick="generateFibonacci()">Click Me</button>
   <div id="output"></div>
   <script>
      let a = 0, b = 1;
      function generateFibonacci()
      {
         let next = a + b;
         a = b;
         b = next;

         let p = document.createElement("p");
         p.textContent = next;
         document.getElementById("output").appendChild(p);
      }
   </script>
</body>
</html>
```

Q2.

```
import nltk
from nltk.tokenize import word_tokenize
nltk.download('stopwords')
from nltk.corpus import stopwords
# Import FreqDist package belonging to nltk.probability
from nltk.probability import FreqDist
# Textual data for word tokenization
paragraph_text="""Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice
platform to learn new programming skills. It is difficult to get enrolled in this Academy."""
# Word Tokenization
tokenized_words=word_tokenize(paragraph_text)
# It will find the stowords in English language.
stop_words_data=set(stopwords.words("english"))
filtered_words_list=[]
for words in tokenized_words:
   if words not in stop_words_data:
    filtered_words_list.append(words)
 # Pass the tokenized words to FreqDist
frequency_distribution=FreqDist(filtered_words_list)
print(frequency_distribution)
print(frequency_distribution.most_common(2))
import matplotlib.pyplot as plt
frequency_distribution.plot(23,cumulative=False)
plt.show()
```

SLIP-19

Q1.

```
<html>
<head>
   <title>Login Validation</title>
</head>
<body>
  <h2>Login Form</h2>
  <form onsubmit="return validateForm()">
    <label>Username:</label>
    <input type="text" id="username"><br><br>

    <label>Password:</label>
    <input type="password" id="password"><br><br>

    <button type="submit">Login</button>
  </form>
  <p id="error" style="color: red;"></p>
```

```
  <script>
    function validateForm() {
      let user = document.getElementById("username").value;
      let pass = document.getElementById("password").value;
      let errorMsg = document.getElementById("error");

      if (user === "") {
        errorMsg.textContent = "Username cannot be empty!";
        return false;
      }

      if (pass.length < 6) {
        errorMsg.textContent = "Password must be at least 6 characters!";
        return false;
      }

      errorMsg.textContent = ""; // Clear error if valid
      alert("Login Successful!");
      return true;
    }
  </script>

</body>
</html>
```

Q2.

```
import pandas as pd
from textblob import TextBlob
from wordcloud import WordCloud, STOPWORDS
import matplotlib.pyplot as plt

df = pd.read_csv(r"C:\wamp\www\Heenal\movie_reviews.csv")
df['Sentiment'] = df['text'].apply(lambda x: TextBlob(x).sentiment.polarity)
pos_df = df[df['Sentiment']>0.2]

wordcloud = WordCloud(width = 800,height = 800,background_color='white',stopwords =
STOPWORDS,min_font_size = 10).generate(''.join(pos_df['text']))

plt.figure(figsize = (8,8),facecolor = None)
plt.imshow(wordcloud)
plt.axis("off")
plt.tight_layout(pad = 0)
plt.show()
```

SLIP-20

Q1. 5 students information

```
<?php
$s=<<<xml
<?xml version="1.0" ?>
<studdet>
<stud>
   <studno> 101</studno>
   <name>xyz </name>
    <age>20</age>
    <per >78</per >
</stud >
<stud>
   <studno> 102</studno>
   <name>abc </name>
    <age>20</age>
    <per >67</per >
</stud >
</studdet >
xml;
$fname="stud.xml";
$fp=fopen($fname,'w');
fwrite($fp,$s);
fclose($fp);
echo"File created sucessfully<br>";
$x = simplexml_load_file("stud.xml")   or die("Error: Cannot create object");
echo $x->asXML();
?>
```

Q2.

```
import nltk
nltk.download('punkt')
nltk.download('stopwords')

from nltk.corpus import stopwords
stop_words = set(stopwords.words("english"))
print(stop_words)
from nltk.tokenize import word_tokenize
paragraph_text = "So, keep working. Keep striving, Never give up. Fall down seven times, get up eight. Ease is a
greater threat to progress."

tokenized_words = word_tokenize(paragraph_text)

filtered_words_list = []
for words in tokenized_words:
   if words not in stop_words:
       filtered_words_list.append(words)
print("Tokenized Words: \n",tokenized_words,"\n")
print("Filtered Words: \n",filtered_words_list,"\n")
```

SLIP-24

Q1.

- studdet.html

```
<html>
  <form method="get" action="studdet.php">
    Enter course name:<input type="text" name="n">
    <input type="submit">
  </form>
</html>
```

- studdet.php

```
<?php
  $c=$_GET['n'];
  echo($n);
  $r=simplexml_load_file("stud.xml");

  echo "<table border='1>";
  echo "<tr><th>ROllNO</th><th>NAME</th><th>ADD</th><th>CLG</th><th>COURSE</th></tr>";

  foreach ($r->children() as $b)
  {
    if($b->course==$c)
    {
      echo "<tr>";
      echo "<td>".$b['rollno']."</td>";
      echo "<td>".$b->name."</td>";
      echo "<td>".$b->add."</td>";
      echo "<td>".$b->clg."</td>";
      echo "<td>".$b->course."</td>";
      echo "</tr>";
    }
  }
  echo "</table>";
?>
```

- stud.xml

```
<?xml version="1.0"?>
<studet>
  <stud rollno="101">
    <name>Raj</name>
    <add>Vapi</add>
    <clg>ssr</clg>
    <course>bca</course>
    </stud>
  <stud rollno="102">
    <name>Laxmi</name>
    <add>Rakholi</add>
    <clg>ssr</clg>
    <course>bcs</course>
  </stud>
</studet>
```

Q2.

```
import pandas as pd
df = pd.read_csv(r"C:\wamp\www\Heenal\INvideos.csv");
df = df.drop(['video_id','trending_date','title','channel_title','category_id','publish_time','tags','thumbnail_link','comments_disabled',
'ratings_disabled','video_error_or_removed','description'],axis=1);
print(df[:10]);

df[['views','likes','dislikes','comment_count']] = df[['views','likes','dislikes','comment_count']].astype(int);
print(df[:10])

tv = df['views'].sum()
print("\n Total views:",tv)
tl = df['likes'].sum()
print("\n Total likes:",tl)
td = df['dislikes'].sum()
print("\n Total dislikes:",td)
tc = df['comment_count'].sum()
print("\n Total comment_count:",tc)
```

SLIP-25

Q1. Multiple entries

```
<?php
$s=<<<xml
<?xml version="1.0" ?>
<cricketteam>
   <team country="india">
      <player>rahul</player>
      <runs>20000</runs>
      <wicket>50</wicket>
   </team>
   <team country="austra">
   <player>ram</player>
   <runs>20000</runs>
   <wicket>50</wicket>
   </team>
</cricketteam>
xml;
$fname="cricket.xml";
$fp=fopen($fname,'w');
fwrite($fp,$s);
fclose($fp);
echo"File created sucessfully<br>";
$x = simplexml_load_file("cricket.xml")   or die("Error: Cannot create object");
echo $x->asXML();
?>
```

Q2.

```
import pandas as pd
import nltk
from nltk.sentiment.vader import SentimentIntensityAnalyzer
# read the dataset
df = pd.read_csv(r"d:\Python\Data Analytics\Slips\movie_reviews.csv")
# remove null values and duplicates
df.dropna(inplace=True)
df.drop_duplicates (subset='text', inplace=True)
#tokenize comments in words
nltk.download('punkt')
df['tokens'] = df['text'].apply(nltk.word_tokenize)
# perform sentiment analysis
nltk.download('vader_lexicon')
sia = SentimentIntensityAnalyzer()
df['sentiment'] = df['text'].apply(lambda x: sia.polarity_scores(x)['compound'])
print(df)
# calculate percentage of positive, negative, and neutral comments
total_comments = len(df)
positive_comments = len(df[df['sentiment'] >0])
negative_comments = len(df[df['sentiment'] <0])
neutral_comments = len(df[df['sentiment'] == 0])
positive_percentage = (positive_comments/total_comments)*100
negative_percentage = (negative_comments/total_comments)*100
neutral_percentage = (neutral_comments/total_comments)*100
#print the results
print('Total Comments:', total_comments)
print('Positive Comments:', positive_comments, '(', positive_percentage, '%)')
print('Negative Comments:', negative_comments, '(', negative_percentage, '%)')
print('Neutral Comments:', neutral_comments, '(', neutral_percentage, '%)')
```

SLIP-29

Q1. menudriven.php (whole code in .php)

```
<html>
  <form action="<?php echo $_SERVER['PHP_SELF']?>" method="post">
    Enter the value of n<input type="text" name="n"><br>
    Select an option:<br>
    <input type="radio" name="r" value="1">Fibonaci Series<br>
    <input type="radio" name="r" value="2">Sum of Digits
    <input type="submit" name="s">
  </form>
```

continue

```
<?php
  if(isset($_POST['s']))
  {
    $n = $_POST['n'];
    if($_POST['r']=='1')
    {
      $n1=0;
      $n2=1;
      echo "<h2>Fibonaci Series:</h2>";
      echo "\n";
      echo "$n1<br>$n2";
      while($num<$n-2)
      {
        $n3 = $n2 + $n1;
        echo "<br>$n3";
        $n1 = $n2;
        $n2 = $n3;
        $num = $num + 1;
      }
    }
    else if($_POST['r']=='2')
    {
      while($n<>0)
      {
        $r=$n%10;
        $s=$s+$r;
        $n=(int)$n/10;
      }
      echo "Sum of digits is $s";
    }
    else echo "invalid";
  }
?>
</html>
```

Q2.

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn import metrics
import seaborn as sn
import matplotlib.pyplot as plt
data = pd.read_csv(r"d:\Python\Data Analytics\Ass1\User_Data.csv")
print(data)
# Splitting our Data set in Dependent and Independent variables.
x= data[['Age','EstimatedSalary']]
y= data['Purchased']
#print(x[:10])
#print(y[:10])
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.25)
#Performing simple logistic regression (create regression model)
lg= LogisticRegression()
lg.fit(x_train,y_train)
y_pred=lg.predict(x_test)
```

SLIP-30

Q1.

```
<?php
$s=<<<xml
<?xml version="1.0" ?>
<Bookdet>
<book type=’Yoga’>
        <title > ..</ title >
        <author >xyz </ author >
        <price>300</price>
</book>
<book type=’Story’>
        < title > …</ title >
        < author >abc </ author >
        <price>400</price>
</book>
<book type=’Techanical’>
        < title > …</ title >
        < author >hij </ author >
        <price>400</price>
</book>
</Bookdet>
xml;
$fname="bookcategory.xml";
$fp=fopen($fname,'w');
fwrite($fp,$s);
fclose($fp);
echo"File created sucessfully<br>";
$x = simplexml_load_file("bookcategory.xml")   or die("Error: Cannot create object");
echo $x->asXML();
?>
```

Q2.Same as Slip-9 Q.2