



IMPLEMENTATION GUIDE

Sembule Media Discovery System

A practical guide to connect, test, host and manage the NEXT discovery form and private client inbox.

- 01 Connect the separate Supabase project
- 02 Test submissions, files and team access
- 03 Publish at discovery.nextafrica.ai
- 04 Review responses and receive email alerts

Prepared by The Next Africa Team

hello@nextafrica.ai | +44 7466 387462

START HERE

Your setup route

The form and private viewer are already built. Complete these four stages in order, then send the live link to Tony.

1. DATABASE

Create the separate Supabase project, run setup.sql and approve the first NEXT viewer account.

2. CONNECTION

Add the public Supabase URL and publishable key to discovery.html and viewer.html.

3. LIVE TEST

Send a test response with files, confirm the row and private downloads, then remove the test data.

4. PUBLISH

Upload the pages to discovery.nextafrica.ai, enable HTTPS and send Tony only the main form link.

Keep private

Never place a secret key, service-role key, database password or email API key in either HTML file. Use only the public publishable key.

This package is ready for Tony at Sembule Media. It contains:

- `discovery.html`: the client-facing discovery form
- `viewer.html`: the private NEXT team inbox
- `setup.sql`: the Supabase database, storage and access rules
- `MESSAGES.md`: the WhatsApp and email invitation copy

The form and viewer are self-contained HTML files. The NEXT logo, design, questions, styles and scripts are inside each file, so hosting does not need a framework or build process.

1. Create the separate Supabase project

- 01 Sign in to Supabase and create a new project dedicated to discovery submissions. Do not use a production project that already holds unrelated client data.
- 02 Open SQL Editor, create a new query, paste all of `setup.sql`, and run it once.
- 03 Open Authentication → Users and create the NEXT team member who should use the private viewer. Use a strong password and confirm the account's email.
- 04 Copy that user's UUID from the Users table.
- 05 In SQL Editor, run this statement after replacing the placeholder:

```
insert into public.discovery_admins (user_id)
values ('YOUR-AUTH-USER-UUID');
```

Only users added to `discovery_admins` can read submissions or download files. Being signed in is not enough.

2. Connect the two pages

- 01 In Supabase, open Project Settings → Data API and copy the Project URL.
- 02 Open Project Settings → API Keys and copy the public publishable key. A legacy public anon key also works.
- 03 In both `discovery.html` and `viewer.html`, replace:

- `[SUPABASE_URL]` with the Project URL - `[SUPABASE_ANON_KEY]` with the public publishable or anon key

Never place a secret key, service-role key or account password in either HTML file. These files are sent to every visitor's browser. The public key is designed for browser use and is restricted by the policies in `setup.sql`.

3. What the access rules do

- A public visitor can add one submission and upload new files.
- A public visitor cannot read, list, change or delete submissions or files.
- The upload bucket is private.
- Files are limited to 10 MB each and to the approved image, PDF, Word, Excel and CSV formats.
- The form gives every file a random storage name and does not overwrite files.
- A signed-in NEXT account can read only after its user UUID is explicitly added to `discovery_admins`.
- There are no browser-visible administrator or database secrets.

The form also limits a visitor to 20 selected files. Supabase enforces the size and type limits again on the server.

4. Test before publishing

Use a local web server or a temporary subdomain. Do not test by double-clicking the file because browser privacy rules can behave differently for local files.

- 01 Open `discovery.html`.
- 02 Confirm the yellow “Preview version” notice is gone. If it remains, one of the two Supabase placeholders has not been replaced correctly.
- 03 Complete a short test submission using non-sensitive sample information.
- 04 Attach one small PDF and one image.
- 05 Submit and confirm that the thank-you page shows an “Answers received” reference.
- 06 In Supabase, open Table Editor → `discovery_submissions` and check the new row.
- 07 Open Storage → `discovery-uploads` and confirm that the files sit inside a folder named with the same reference UUID.
- 08 Open `viewer.html`, sign in with the approved NEXT account, open the submission and download both files.
- 09 Sign out and confirm the submissions disappear from the screen.
- 10 Repeat the client form on a phone using mobile data, including Save and finish later, Review and Print / save PDF.
- 11 Delete the test row and its test folder from the Supabase dashboard before sharing the live link.

The local automated checks are recorded in `tests/results.json`. They cover every section at desktop and phone widths, conditional questions, browser saving, validation, uploads, submission failure and retry, safe viewer rendering, access rejection and private downloads. A final live test is still required after the real Supabase values are connected because local tests cannot prove the deployed project's policies or DNS.

5. Host on `discovery.nextafrica.ai`

For a typical cPanel hosting account:

- 01 In cPanel, open Domains and create `discovery.nextafrica.ai`.
- 02 Let cPanel create the document root, usually a folder similar to `public_html/discovery`.
- 03 In File Manager, upload `discovery.html` to that folder and rename it to `index.html`.
- 04 Upload `viewer.html` beside it. The private address will be `https://discovery.nextafrica.ai/viewer.html`.
- 05 In SSL/TLS Status, issue or enable the free SSL certificate for the subdomain.
- 06 Visit both HTTPS addresses and repeat the live test above.
- 07 Send only the main discovery link to Tony. Keep the viewer address within the NEXT team.

If DNS is managed outside the hosting account, create the subdomain in the hosting account first, then add the exact A or CNAME record supplied by the host. DNS changes can take time to appear globally.

For a cleaner private address, create a second subdomain such as `discovery-inbox.nextafrica.ai` and upload `viewer.html` there as `index.html`. Supabase login and the database allowlist remain the real access controls.

6. View answers and files

The preferred method is the private viewer:

- 01 Open the private viewer URL.
- 02 Sign in using an approved NEXT account.
- 03 Choose a submission from the left-hand list.
- 04 Read the answers by section, download the JSON copy if needed, or print the page as a PDF.
- 05 Click a file name to download it through the authenticated session.
- 06 Sign out when finished, especially on a shared computer. The viewer also signs out after 20 minutes.

The Supabase dashboard is the backup method. Use Table Editor → `discovery_submissions` for answers and Storage → `discovery-uploads` → reference number for files. Do not make the storage bucket public.

7. Get an email alert for each new submission

The simplest reliable route is a Supabase Database Webhook connected to Make, Zapier or another service that can receive a webhook and send email.

- 01 In Make or Zapier, create a workflow with Custom Webhook as the trigger and Send Email as the action.
- 02 Set the email recipient to `hello@nextafrica.ai` and use a subject such as New NEXT discovery: `{{client_company}}`.
- 03 Include the company, contact name, contact email, contact phone, reference and submission time in the email. Do not include the full answers or files in email.
- 04 Copy the webhook URL from Make or Zapier.
- 05 In Supabase, open Database → Webhooks and create a webhook named `discovery-email-alert`.
- 06 Choose table `public.discovery_submissions`, event INSERT, method POST, and paste the webhook URL.
- 07 Save it and send another test submission.
- 08 Confirm the email arrives and that the workflow history shows a successful request.

Supabase database webhooks run after the row is inserted. If the alert service is temporarily unavailable, the submission remains safely stored. Keep the webhook URL private because it authorises calls to the email workflow.

For a fully NEXT-controlled solution, replace the no-code workflow later with a Supabase Edge Function that sends through the NEXT email provider. Store the email API key as an Edge Function secret, never in either HTML page.

8. Safe operating routine

- Add only the minimum number of viewer accounts.
- Remove an account from `discovery_admins` when it no longer needs access.
- Keep Supabase multi-factor authentication enabled for project administrators.

- Review storage usage and failed webhook logs monthly.
- Download only the documents needed for the project and store them in an approved NEXT client folder.
- Never ask Tony to send passwords, payment PINs, card numbers or streaming keys in the form or WhatsApp group.

9. Reuse for the next client

The current page is intentionally personalised to Tony and Sembule Media. To reuse it, change the company, contact and draftKey values near the top of `discovery.html`. Give every client a unique draftKey. Update any industry-specific defaults, then test the conditional sections before sharing the new link.

The source question file and page templates are kept in `source/` for future structured changes. After editing them, run `python3 source/build.py` from the `discovery` folder to rebuild both self-contained pages.