

[← Back to API reference](#)

Integration surface for 3rd-party telehealth companies that prescribe in their own e-Rx system and route fulfillment through PrescribeRx. Two endpoints to register prescribers + look them up, one to submit fully-formed prescription orders. Webhook subscribers receive status callbacks back as orders progress.

At a glance

Endpoint	Purpose	Ability
<code>POST /api/v1/external-telehealth/providers</code>	Register prescriber (idempotent on NPI+client)	<code>external-telehealth:providers:write</code>
<code>GET /api/v1/external-telehealth/providers/{npi}</code>	Look up provider(s) — poll for admin approval state	<code>external-telehealth:providers:read</code>
<code>POST /api/v1/external-telehealth/orders</code>	Submit a fully-formed prescription order	<code>external-telehealth:orders:write</code>

The interactive Try-It client for all three endpoints is on the main [API reference](#), under the **ExternalTelehealth** tag.

1 — How tenancy works

The effective sales-org id resolves from either side of the user identity graph:

```
effective_sales_org_id = user.sales_organization_id
                        ?? user.client.sales_organization_id
```

Both token shapes are supported:

Token shape	What it can do
<code>Sales-org</code>	Submit orders / register providers against any <code>client_id</code> under its sales org. Use this when a 3rd-party telehealth company serves multiple of your clinics.
<code>Client</code>	Effectively pinned to its own <code>client_id</code> — the only payload value that resolves to its sales org's client tree. Use this when a single clinic / practice integrates directly.

Cross-tenant `client_id` → **HTTP 403** with: *"API user must belong to a sales organization (directly, or via their client)."*

2 — Onboarding (one-time)

1. Your account rep creates either a SalesOrganization (multi-clinic integrator) or a Client (single-clinic) for you, plus an API user.
2. The rep issues a Sanctum bearer token for that API user with these abilities, which are granted manually (NOT in any default ability set):
 - `external-telehealth:providers:write`
 - `external-telehealth:providers:read`
 - `external-telehealth:orders:write`
 Webhook abilities (`webhook:*`) are already in the default set for both sales-org and client user types.
3. Save the token securely — it's not retrievable from our side once issued.
4. Test against `https://demo.prescribe-rx.com` first. Production is `https://prescribe-rx.com` with identical shapes.

3 — Register a provider

Every prescriber must exist + be admin-approved before any order can reference them by NPI.

cURL

```
curl -X POST https://demo.prescribe-rx.com/api/v1/external-telehealth/providers
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
-d '{
  "client_id": "<your client UUID>",
  "npi": "1234567890",
  "dea": "BX1234567",
  "first_name": "Alex",
  "last_name": "Smith",
  "prefix": "DR",
  "suffix": "MD",
  "designation": "MD",
}
```

```
"dob": "1980-01-15",
"gender": 1,
"email": "alex.smith@example-clinic.com",
"state_licenses": [
  {"state": "GA", "license_type": "MD", "license_number": "GA-12345", "expir
  {"state": "FL", "license_type": "MD", "license_number": "FL-67890", "expir
]
```

Response codes

Status	Meaning
201	New provider registered. <code>data.status = "PENDING"</code> . Wait for admin approval before submitting orders.
409	A provider with this <code>(npi, client_id)</code> already exists. Response includes the existing <code>data.provider_profile_id</code> .
403	The <code>client_id</code> does not belong to your sales org tree.
422	Validation error. Check <code>errors[]</code> for field-level details.

Poll for approval

```
curl https://demo.prescribe-rx.com/api/v1/external-telehealth/providers/12345678
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json"
```

Returns an array (same NPI can have multiple rows when the prescriber works at multiple of your clients). Loop until `data[].status === "ACTIVE"` .

4 — Submit an order

Idempotency-Key header is REQUIRED. Any unique string per order (UUID v4 recommended). Re-POSTing the same key within 24h returns the original order as HTTP 200 (not 201). Keys are scoped to the caller's sales org.

cURL — happy path (non-compounded SKU)

```
curl -X POST https://demo.prescribe-rx.com/api/v1/external-telehealth/orders \
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json" \
```

```

-H "Content-Type: application/json" \
-H "Idempotency-Key: ${uuidgen}" \
-d '{
  "client_id": "<your client UUID>",
  "provider_npi": "1234567890",
  "external_order_id": "ACME-2026-05-14-00042",
  "patient": {
    "first_name": "Jane",
    "last_name": "Doe",
    "email": "jane.doe@example.com",
    "date_of_birth": "1985-03-12",
    "phone": "+15555550100",
    "gender": 2,
    "address": {"line1": "123 Main St", "city": "Atlanta", "state": "GA", "pos
  },
  "shipping_address": {"line1": "123 Main St", "city": "Atlanta", "state": "GA
  "prescription": {
    "pdf_base64": "JVBERi0xLjcKJWZha2UgcGRmCg==",
    "signed_at": "2026-05-14T14:00:00Z",
    "signed_by_name": "Dr. Alex Smith, MD"
  },
  "lines": [
    {
      "sku": "GLPSEMA-12-TABLET",
      "quantity": 1,
      "sig": "Take one 12 mg tablet by mouth once weekly",
      "days_supply": 28,
      "dose_amount": "12",
      "dose_unit": "mg",
      "frequency": "weekly",
      "refills": 0
    }
  ]
}
```

cURL — compounded SKU (requires compounding_reason_slug)

```

...
  "lines": [
    {
      "sku": "COMP-SEMA-2.5",
      "quantity": 1,
      "sig": "Inject 2.5 mg subcutaneously once weekly",
      "days_supply": 28,
      "dose_amount": "2.5",
      "dose_unit": "mg",

```

```

    "frequency": "weekly",
    "refills": 2,
    "compounding_reason_slug": "dose-not-commercially-available"
  }
]
...

```

Common compounding-reason slugs (ask your account rep for the current full list, since admins can add new ones):

Slug	When to use
<code>dose-not-commercially-available</code>	Strength/dose not sold commercially
<code>commercial-shortage</code>	Commercial product on shortage
<code>commercial-excipient-allergy</code>	Patient allergic to a commercial excipient
<code>combination-not-commercial</code>	Custom multi-ingredient compound
<code>titration-flexibility</code>	Provider titrating dose up/down
<code>b-complex-metabolic-support</code>	B3/B6/B12 metabolic support add-on

Idempotency replay test

Re-send the same payload with the same `Idempotency-Key`. The second response is `HTTP 200` (not 201) and the body matches the original — regardless of what the payload says. No duplicate order is created. Use this to safely retry on network failures.

5 — Response codes

Status	Meaning
201 Created	Order accepted, routed to fulfillment. Includes <code>order_id</code> , <code>order_number</code> , <code>prescription_id</code> , <code>prescription_pdf_path</code> .
200 OK	Idempotency replay — same key was used within 24h. Body matches the original 201.
404 Not Found	The NPI isn't registered at this client. Call <code>POST /providers</code> first.
403 Forbidden	Provider exists but is still PENDING admin approval, OR <code>client_id</code> is not in your sales org tree.

422 Unprocessable Entity	Validation error: unknown SKU, malformed PDF, missing <code>compounding_reason_slug</code> on a compounded product, NPI doesn't normalize to 10 digits, missing Idempotency-Key header.
401 Unauthorized	Missing / invalid token.

6 — Webhook callbacks

Status updates flow back via the standard webhook subscription system. Subscribe once for your sales-org / client; you'll receive events for every order it owns. See the dedicated [Webhooks Guide](#) for HMAC signature verification + retry policy.

Subscribe

```
curl -X POST https://demo.prescribe-rx.com/api/v1/webhooks \
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
-d '{
  "url": "https://your-platform.com/webhooks/prescribe-rx",
  "events": [
    "order.placed",
    "order.status_changed",
    "order.cancelled",
    "fulfillment.shipped",
    "fulfillment.delivered",
    "fulfillment.cancelled"
  ],
  "subscriber_type": "sales_organization",
  "subscriber_id": "<your sales-org UUID>"
}'
```

Use `"subscriber_type": "client"` + your client UUID instead for client-token integrators.

The response's `data.secret` (starts with `whsec_`) signs every outgoing payload — store it securely. Outgoing requests carry the signature in `X-PrescribeRx-Signature` (HMAC-SHA256 of the raw body).

Events you'll receive (External Telehealth orders)

Event	When	Payload key
<code>order.placed</code>	Immediately after our 201 to your <code>POST /orders</code>	<code>order_id</code> , <code>order_number</code> , <code>total_amount</code> ,

		<code>external_order_id</code>
<code>order.status_changed</code>	<code>workflow_status</code> transitions	<code>old_status</code> , <code>new_status</code> , <code>external_order_id</code>
<code>order.cancelled</code>	Admin or system cancels	<code>reason</code> , <code>cancelled_at</code> , <code>external_order_id</code>
<code>fulfillment.shipped</code>	FC reports the order shipped	<code>tracking_number</code> , <code>tracking_url</code> , <code>carrier</code> , <code>shipped_at</code> , <code>external_order_id</code>
<code>fulfillment.delivered</code>	Carrier reports delivered	<code>tracking_number</code> , <code>delivered_at</code> , <code>external_order_id</code>
<code>fulfillment.cancelled</code>	FC cancellation (rare; usually inventory)	<code>reason</code> , <code>cancelled_at</code> , <code>external_order_id</code>

Every payload includes your supplied `data.external_order_id` when the order originated from this API — use it to correlate with your internal records.

7 — Troubleshooting

Symptom	Likely cause	Fix
401 Unauthorized	Token expired or wrong header	Reissue. Header is <code>Authorization: Bearer <token></code> with the full <code><id> <random></code> string.
403 "missing ability"	Token issued without the right abilities	Ask your rep to re-issue with <code>external-telehealth:*</code> abilities.
403 "client_id does not belong to your sales organization"	Wrong client UUID or cross-tenant	Verify the UUID against the list your rep provided. Client-token integrators must use their own client_id.
404 "No provider found for this NPI at the given client"	Not yet registered, OR registered at a different client	Call <code>POST /providers</code> first, or fix the <code>client_id</code> in your payload.
403 "Provider is registered but not yet ACTIVE"	Admin hasn't approved yet	Wait; poll <code>GET /providers/{npi}</code> .
422 "Unknown product SKU"	SKU isn't in our catalog or was retired	Ask your rep for the current SKU list. Case-sensitive.

422 "is compounded and requires `compounding_reason_slug`"	Compounded product without a slug	Add <code>compounding_reason_slug</code> to the line.
422 "Header `Idempotency-Key` is required"	Forgot the header	Add <code>Idempotency-Key: <uuid></code> to every order POST.
422 "prescription.pdf_base64 does not contain a valid PDF"	Decoded bytes don't start with <code>%PDF-</code>	Re-export from your e-Rx. Common cause: double base64 encoding, or sending raw text.
200 OK instead of 201 on a fresh POST	Reused an Idempotency-Key from a prior order	Generate a fresh UUID per distinct order.

Need a sandbox-ready token? The sandbox tokens panel on the [main API reference](#) auto-rotates one every 12h. Look for the SALESORGANIZATION entry, or ask an admin to issue an explicit External Telehealth token via tinker (procedure documented internally).

[← Back to API reference](#)