

HEATER TREATERS & VESSEL SOLUTIONS · 100% MADE IN THE USA

Protect Your Vessels From the Inside Out

Houston Anodes manufactures aluminum and zinc sacrificial anodes engineered specifically for internal vessel applications — protecting against corrosion in the harshest conditions.

DRAFT

40%

LONGER ANODE LIFE

0

CLAIMS IN 47 YRS

50%

FASTER PROCESSING

725

TONS/MONTH

ISO 9001:2015 · ISO 17025 · DNV

VESSEL & TANK ANODE PRODUCTS

Heater Treater & Tank Anodes Designed for Maximum Protection

Superior Technology

Electromagnetic induction melting — not gas furnaces. 100% homogeneous alloys with zero porosity and perfect density.

- 5–1,650 lbs
- Aluminum alloys
- Zinc alloys
- Any core configuration

Proven Quality

Not a single product claim in 47 years. In-house ISO 17025–accredited laboratory.

- NACE SP-0387 & SP-0492
- DNV RP B401
- NORSOK M-503
- ISO 15589–2

Vessel & Tank Anodes

Custom-engineered for internal vessel applications in refining and chemical processing.

- Heater Treater
- Heater Treater Eyebolt
- Bowling Ball
- Drum

HOW IT WORKS

Why Induction Makes the Difference

Anodes manufactured by gas furnaces produce heterogeneous alloys where indium is only partially induced — creating passive material that never contributes to protection. At end of life, gas-furnace anodes leave 41% of material wasted.

Houston Anodes' electromagnetic induction technology achieves 100% homogeneous indium activation with complete anode mass depletion — zero waste, maximum protection.

41%

GAS: PASSIVE WASTED

0%

INDUCTION: PASSIVE WASTED

CUSTOM ENGINEERING

Tailored to Your Specifications

Heater Treater Anodes can be supplied with Red/Blue caps and nuts upon customer's request. Houston Anodes can cast anodes for any sort of tank bottom or vessel interior to the exact specifications required.

- Available in aluminum and zinc alloys
- Specify metal and chemical composition when ordering
- 2–4 week standard lead times
- In-house metallurgical lab and mold manufacturing
- Contact our engineering team for custom anode optimization