

# Detecting contours of human organs in CT images using the Marr-Hildreth edge detector

Neža Belej (63120340)

January 16, 2017

## 1 Abstract

In the following report we represent our program for edge detection in CT images of human organs. We achieve this by using Marr-Hildreth algorithm. We use images from CTMRI database [3]. In the end, we discuss the advantages and disadvantages of Marr-Hildreth algorithm and propose possible improvements.

## 2 Introduction

Edge detection is one of the most commonly used operations in image analysis. An edge is defined by a discontinuity in gray level values. In other words, an edge is the boundary between an object and the background [1]. Most popular edge detecting algorithms are The Marr-Hildreth Edge Detector, The Canny Edge Detector, The Local Threshold and Boolean Function Based Edge Detection, Color Edge Detection Using Euclidean Distance and Vector Angle. [2]

## 3 Methods

We used Marr-Hildreth edge detection algorithm. The steps are following:

1. Calculate coefficients of the LoG operator (mask).
2. Apply this mask on the image to enhance edges.
3. Searching for zero crossings and perform binarization.

Zero crossings are the key feature of the Marr-Hildreth edge detection method. For every pixel  $p$ :

- we used a  $3 \times 3$  neighborhood centered at  $p$ ,
- the signs of at least two of opposing neighboring pixels of a pixel  $p$  considered must differ,
- the neighboring pixels absolute difference must be less than threshold  $T$ .

## 4 Results

We tested our algorithm on the CT images of CTMRI database. Results shows that edge detector successfully detects edges. It finds the correct places of edges, but the edges are not always thin and they are too spotty.

## 5 Discussion

The MarrHildreth detector perceives many edges, but they are too spotty and wide to really identify any features. In Marr-Hildreth, locality is not especially good and the edges are not always thin.

We could improve our edge detection with using Canny Edge Detector, which is more accurate and good with locality. We could also combine different parameters (sigma and threshold in zero crossing) to get the best effect.

## References

- [1] Sharifi, Mohsen and Fathy, Mahmood and Mahmoudi, Maryam Tayefeh, *A classified and comparative study of edge detection algorithms*, Information Technology: Coding and Computing, 2002. Proceedings. International Conference on, IEEE, 2002.
- [2] Ehsan Nadernejad, Sara Sharifzadeh : *Edge Detection Techniques: Evaluations and Comparisons*, Applied Mathematical Sciences, Vol. 2, 2008, no. 31, 1507 - 1520
- [3] <http://lbc.si.fri.uni-lj.si/OBSS/Data/CTMRI/>