	CABLE PACKAGE OVERVIEWS					
PACKAGE NAME	CABLING INCLUDED					
СОМВО	RG-6	CAT6	l			
	QTY: 1	QTY: 1				
				1415 OU 1505		
DAVP	RG-6	CAT6	CAT6	MMF SIMESE		
	QTY: 1	QTY: 1	QTY: 1	QTY: 1		
	DC C	CATC	CATC	CAT6A SHIELDED	MMF SIMESE	
FUTURE PROOF TV OUTLET	RG-6 QTY: 1	CAT6 QTY: 1	CAT6 QTY: 1	QTY: 1	QTY: 1	
	Q11.1	QII.I	QIII.I	QII.I	Q11.1	
	CAT6	CAT6	CAT6A SHIELDED	HDMI CABLE	CARLON TUBE	
PROJECTOR PRE-WIRE*	QTY: 1	QTY: 1	QTY: 1	QTY: 1	QTY: 1	
*NOTE: CAT6 GRAY Can be used to d	onnect to the back					s - ATT. We can
also utilize the Cat6 for a HDMI Extend	der with Control.					
	40/434"	40/0 \4" !! !!				
WHA 16ga*	16/4 WHITE	16/2 WHITE				
******	QTY: 1	QTY: 1	<u> </u>			
*NOTE: Run 16/4 to closest speaker to	nomerun, then run	16/2 jumper from s	speaker to speaker			
	14/4 WHITE	14/2 WHITE	ı			
WHA 14ga*	QTY: 1	QTY: 1	ł			
*NOTE: Run 14/4 to closest speaker to			anaakar ta anaakar			
NOTE. Run 14/4 to closest speaker to	nomerum, memrum	i 14/2 juilipei iloili s	speaker to speaker			
	14/2 BLACK	14/4 BLACK				
SURROUND W/ PASSIVE SUB*	QTY: 5-8	QTY: 1	ł			
*NOTE: Homerun 14/2 Black from DE			■ are installed, run a 1	4/4 Black with a 14	/2 going from first s	ubwoofer to next
subwoofer.						
SURROUND W/ POWER SUB*	14/2 BLACK	RG-6 BC	ļ			
	QTY: 5-7	QTY: 1-2		_		
*NOTE: Homerun 14/2 Black from DE	B to each speaker.	If dual subwoofers	are installed, run a F	RG-6 Black to each	location	
	0.470					
DATA	CAT6					
	QTY: 1					
	CAT6					
DUAL DATA	QTY: 2					
	QII.Z					
PHONE	CAT6					
	QTY: 1					
1446 <del>-</del>	CAT6					
WAP	QTY: 1					
TOUCH PANEL	CAT6					
	QTY: 1					

			= =====================================	=======================================	
	CAT6				
IP CAMERA	QTY: 1				
	CAT6	18/4			
DOORBELL/DOORSTATION	QTY: 1	QTY: 1	ł		
	QTT.T	Q11.1			
	RG-6	CAT6	SMF SIMESE		
DEMARK	QTY: 1				
*NOTE: Run out the side of house who		QTY: 1	QTY: 1	s the Electrical Group	nding Rod to ground their feed
Place in Weatherproof Box to protect the					raing roa to ground then reed.
SECURITY - KEYPADS /	22/4				
WIRELESS RECEIVERS	QTY: 1				
*NOTE: Top of Box at 60". If you we ca			above light switches s	o keypad can be mou	ınted centered. Keypads are
installed 60" Above Finished Floor to t	he top of the keypad	d.			
SECURITY - DOOR CONTACTS	22/4				
	QTY: 1				
*NOTE: The wiring should be drilled of door to be installed.	ıt of Jamb side of do	oor with 3/4" hole. V	When you leave pre-w	ire, the wire should b	e stubbed out so it is ready for the
door to be installed.					
2=211=121 11111=2111	22/4				
SECURITY - WINDOW CONTACTS	22/4				
*NOTE: Drill either side of 2x4 holding	QTY: 1	ow - 6" above botto	om of window seal M	a typically use surface	a mount contacts to avoid voiding
the window warranty.	the side of the willow	ow - o above boll	oni oi window seai. We	e typically use surface	e mount contacts to avoid voiding
	22/4				
SECURITY - GLASS BREAKS	QTY: 1				
*NOTE: GB's must be centered in wind		a 2x4 to get it cent	ered, do it. If there is	a floor joist in the way	y, use a nail and we will install a
surface mount glass break. Use Blue E					
SECURITY - MOTION	22/4				
DETECTORS	QTY: 1				
*NOTE: Nail Motion Detector Wiring of		p nail with wire, ma	ake sure there is enou	gh slack inside wall ii	n case the wire is damaged by the
drywaller so we can pull it out and use	the good wire.				
	00/4				
SECURITY - WATER SENSORS	22/4				
	QTY: 1				
*NOTE: Sump pits, Ejector pits, mecha	inical rooms				
SECURITY - SMOKE	18/4				
DETECTORS	QTY: 1				
*NOTE: Run Red 18/6 Fire Wire. Homeone, home run the end of line too. Mu					
entrances. Install a blue box for the dea		nighest Follit ill ed	acii iooiii al least 5 av	vay IIOIII ariy FIVAC V	rent, 10 IIOIII Batillooni
SECURITY - HEAT	18/4				
DETECTORS	QTY: 1				
*NOTE: Run Red 18/4 Fire Wire. Home		a detector Install a	hlue hov for the dete	ctor	
		Lococor. motali e	DOX TOT LITE GELE	··	
	22/4				
SECURITY - GAS DETECTORS					
MOTE: Diese D. 1075	QTY: 1	D			
*NOTE: Place Box 12" from ceiling to t	op ot box. Use Blue	ROX			
SECURITY - SIREN/SPEAKERS	22/4				
	QTY: 1				
*NOTE: 1G ring installed at outlet heigh	tht typically in hedro	oom hallways			

	-	=	=

		_				
SECURITY - CELL RADIO	CAT6	16/4			<del>-</del>	
	QTY: 1	QTY: 1				
*NOTE: Generally installed in the 2nd	Floor closet or Attic	:				
GARAGE DOOR CONTROL	CAT6	22/4				
	QTY: 1	QTY: 1				
*NOTE: CAT6 runs to operator (motor) and 22/4 in same box	, 22/4 runs to the a	oor for contact. At o	perator, install Blue	e box and land CAT6	6. If sidemount operator, land con	rol
	Who	does the proce	ess transfer to	next?		
Name		Department or Function		Milestone		
Project Manager		Project Manager		Rough-In Complete		
	•					