

**FAMU-FSU College of Engineering**  
**Project Hazard Assessment Policy and Procedures**

## **INTRODUCTION**

University laboratories are not without safety hazards. Those circumstances or conditions that might go wrong must be predicted and reasonable control methods must be determined to prevent incident and injury. The FAMU-FSU College of Engineering is committed to achieving and maintaining safety in all levels of work activities.

## **PROJECT HAZARD ASSESSMENT POLICY**

Prior to starting an experiment, laboratory workers must conduct a project hazard assessment (PHA) to identify health, environmental and property hazards and the proper control methods to eliminate, reduce or control those hazards. PI/instructor must review, approve, and sign the written PHA and provide the identified hazard control measures. PI/instructor continually monitor projects to ensure proper controls and safety measures are available, implemented, and followed. PI/instructor are required to reevaluate a project anytime there is a change in scope or scale of a project and at least annually after the initial review.

## **PROJECT HAZARD ASSESSMENT PROCEDURES**

It is FAMU-FSU College of Engineering policy to implement followings:

1. Laboratory workers (i.e. graduate students, undergraduate students, postdoctoral, volunteers, etc.) performing a research in FAMU-FSU College of Engineering are required to conduct PHA prior to commencement of an experiment or any project change in order to identify existing or potential hazards and to determine proper measures to control those hazards.
2. PI/instructor must review, approve and sign the written PHA.
3. PI/instructor must ensure all the control methods identified in PHA are available and implemented in the laboratory.
4. In the event laboratory personnel are not following the safety precautions, PI/instructor must take firm actions (e.g. stop the work, set a meeting to discuss potential hazards and consequences, ask personnel to review the safety rules, etc.) to clarify the safety expectations.
5. PI/instructor must document all the incidents/accidents happened in the laboratory along with the PHA document to ensure that PHA is reviewed/modified to prevent reoccurrence. In the event of PHA modification a revision number should be given to the PHA, so project members know the latest PHA revision they should follow.
6. PI/instructor must ensure that those findings in PHA are communicated with other students working in the same laboratory (affected users).
7. PI/instructor must ensure that approved methods and precautions are being followed by :
  - a. Performing periodic laboratory visits to prevent the development of unsafe practice.
  - b. Quick reviewing of the safety rules and precautions in the laboratory members meetings.
  - c. Assigning a safety representative to assist in implementing the expectations.
  - d. Etc.
8. A copy of this PHA must be kept in a binder inside the laboratory or PI/instructor's office (if experiment steps are confidential).

Project Hazard Assessment Worksheet				
PI/instructor: Dr. Reginald Perry	Phone #: 850-410-6465	Dept.: ECE	Start Date: 11/18/2022	Revision number: 1
Project: DTMF Signal Generator/Detector - Team 306			Location(s): Home, Senior Design Lab	
Team member(s):	Alejandro Chong		Phone #: 850-938-7889	Email: ac17an@fsu.edu
	Najeeb Eeso		Phone #: 904-294-6782	Email: nfe19@fsu.edu
	Adorah Allard		Phone #: 407-530-9454	Email: ama19z@fsu.edu
	Evan Charles		Phone #: 561-789-8926	Email: edc19@fsu.edu

Experiment Steps	Location	Person assigned	Identify hazards or potential failure points	Control method	PPE	List proper method of hazardous waste disposal, if any.	Residual Risk	Specific rules based on the residual risk
Analog portion, MCU programming and testing	Home	Najeeb Evan Adorah	Carpal tunnel, Digital Eye Strain	Frequent and scheduled breaks to look away from computer and stretch hands / hand massage or exercises	None	None	HAZARD: 1 CONSEQ: Negligible	Safety controls planned by worker and supervisor, supervisor authorization
							Residual: Low	
Digital portion, FPGA programming and testing, ASIC layout generation	Home	Alejandro Evan	Carpal tunnel, Digital Eye Strain	Frequent and scheduled breaks to look away from computer and stretch hands / hand massage or exercises	None	None	HAZARD: 1 CONSEQ: Negligible	Safety controls planned by worker and supervisor, supervisor authorization
							Residual: Low	
Door lock assembly	SD Lab	Najeeb Evan Adorah Alejandro	Physical exertion from assembly and drilling. Physical injuries due to accidents with cutting or drilling equipment, or metal shavings / particles entering the eyes.	Avoid working for long periods of time (split work). Work only at full physical and mental capacity. Have a clean working space. Fasten and secure parts so they do not move while working on them.	Protective goggles. Long pants and closed shoes. Rubber coated and cut resistant gloves.	None	HAZARD: 3 CONSEQ: Minor	Safety controls planned by worker and supervisor, buddy system, supervisor authorization
							Residual: Low Med	
Electrical and electronic wiring	SD Lab	Najeeb Alejandro	High energy (voltage and current) sources. Electrical shock or fire due to live parts not covered by	Make sure there are no parts connected to a power source while wiring. Check for any undesired live parts. Have a ground-fault	Long pants and closed shoes. Insulating Gloves.	None	HAZARD: 3 CONSEQ: Minor	Safety controls planned by worker and supervisor, buddy system,
							Residual: Low Med	

			insulating materials, or bad or wrong electrical connection.	protection. Carefully read manuals for correct installation of components. Have a clean space with no flammable or combustible substances / objects. Create strong wire connections and have them checked by a faculty member before covering with insulator (heat shrink, etc.)				supervisor authorization
Testing	SD Lab	Najeeb Evan Adorah Alejandro	Physical exertion from reassembly and handling. High energy sources. Electrical shock from contact with live parts or faulty components. Minor explosion or fire caused by wrong installation of electrical components or faulty components.	Use two or more members or any other helper to lift, handle, assemble, and fasten the door. Re-check for undesired live parts in the wiring. Have a clean and controlled initial test space with ground-fault protection.	Long pants and closed shoes. Insulating Gloves.	None	HAZARD: 3 CONSEQ: Minor Residual: Low Med	Safety controls planned by worker and supervisor, buddy system, supervisor authorization

**Principal investigator(s) PHA certification:** I certify that I have reviewed and approved the PHA worksheet and will ensure the control measures are available and implemented in the laboratory.

Name	Signature	Date	Name	Signature	Date
_____	_____	_____	_____	_____	_____
Dr. Reginald Perry					

**Team members' certification:** I certify that I have reviewed the PHA worksheet, am aware of the hazards, and will ensure the control measures are followed.

Name	Signature	Date	Name	Signature	Date
_____	_____	_____	_____	_____	_____
Alejandro Chong	AC	11/18/2022	Najeeb Eeso	NE	11/18/2022
_____	_____	_____	_____	_____	_____
Adorah Allard	AA	11/18/2022	Evan Charles	EC	11/18/2022

## DEFINITIONS:

**Hazard:** Any situation, object, or behavior that exists, or that can potentially cause ill health, injury, loss or property damage e.g. electricity, chemicals, biohazard materials, sharp objects, noise, wet floor, etc. OSHA defines hazards as “*any source of potential damage, harm or adverse health effects on something or someone*”. A list of hazard types and examples are provided in appendix A.

**Hazard control:** Hazard control refers to workplace measures to eliminate/minimize adverse health effects, injury, loss, and property damage. Hazard control practices are often categorized into following three groups (priority as listed):

- 1. Engineering control:** physical modifications to a process, equipment, or installation of a barrier into a system to minimize worker exposure to a hazard. Examples are ventilation (fume hood, biological safety cabinet), containment (glove box, sealed containers, barriers), substitution/elimination (consider less hazardous alternative materials), process controls (safety valves, gauges, temperature sensor, regulators, alarms, monitors, electrical grounding and bonding), etc.
- 2. Administrative control:** changes in work procedures to reduce exposure and mitigate hazards. Examples are reducing scale of process (micro-scale experiments), reducing time of personal exposure to process, providing training on proper techniques, writing safety policies, supervision, requesting experts to perform the task, etc.
- 3. Personal protective equipment (PPE):** equipment worn to minimize exposure to hazards. Examples are gloves, safety glasses, goggles, steel toe shoes, earplugs or muffs, hard hats, respirators, vests, full body suits, laboratory coats, etc.

**Team member(s):** Everyone who works on the project (i.e. grads, undergrads, postdocs, etc.). The primary contact must be listed first and provide phone number and email for contact.

**Safety representative:** Each laboratory is encouraged to have a safety representative, preferably a graduate student, in order to facilitate the implementation of the safety expectations in the laboratory. Duties include (but are not limited to):

- Act as a point of contact between the laboratory members and the college safety committee members.
- Ensure laboratory members are following the safety rules.
- Conduct periodic safety inspection of the laboratory.
- Schedule laboratory clean up dates with the laboratory members.
- Request for hazardous waste pick up.

**Residual risk:** Residual Risk Assessment Matrix are used to determine project's risk level. The hazard assessment matrix (table 1) and the residual risk assessment matrix (table2) are used to identify the residual risk category.

The instructions to use hazard assessment matrix (table 1) are listed below:

1. Define the workers familiarity level to perform the task and the complexity of the task.
2. Find the value associated with familiarity/complexity (1 – 5) and enter value next to: HAZARD on the PHA worksheet.

**Table 1. Hazard assessment matrix.**

		Complexity		
		Simple	Moderate	Difficult
Familiarity Level	Very Familiar	1	2	3
	Somewhat Familiar	2	3	4
	Unfamiliar	3	4	5

The instructions to use residual risk assessment matrix (table 2) are listed below:

1. Identify the row associated with the familiarity/complexity value (1 – 5).
2. Identify the consequences and enter value next to: CONSEQ on the PHA worksheet. Consequences are determined by defining what would happen in a worst case scenario if controls fail.
  - a. Negligible: minor injury resulting in basic first aid treatment that can be provided on site.
  - b. Minor: minor injury resulting in advanced first aid treatment administered by a physician.
  - c. Moderate: injuries that require treatment above first aid but do not require hospitalization.
  - d. Significant: severe injuries requiring hospitalization.
  - e. Severe: death or permanent disability.
3. Find the residual risk value associated with assessed hazard/consequences: Low –Low Med – Med– Med High – High.
4. Enter value next to: RESIDUAL on the PHA worksheet.

**Table 2. Residual risk assessment matrix.**

Assessed Hazard Level	Consequences				
	Negligible	Minor	Moderate	Significant	Severe
5	Low Med	Medium	Med High	High	High
4	Low	Low Med	Medium	Med High	High
3	Low	Low Med	Medium	Med High	Med High
2	Low	Low Med	Low Med	Medium	Medium
1	Low	Low	Low Med	Low Med	Medium

**Specific rules for each category of the residual risk:**

Low:

- Safety controls are planned by both the worker and supervisor.
- Proceed with supervisor authorization.

Low Med:

- Safety controls are planned by both the worker and supervisor.
- A second worker knowledgeable of the task and hazards is in the vicinity (buddy system).
- Proceed with supervisor authorization.

Med:

- After approval by the PI, the Safety Committee and/or EHS must review and approve the completed PHA.
- A written safety plan is required and must be approved by the PI before proceeding. A copy must be sent to the Safety Committee.
- A second worker must be in place before work can proceed (buddy system).
- Limit the number of authorized workers in the hazard area.

Med High:

- After approval by the PI, the Safety Committee and/or EHS must review and approve the completed PHA.
- A written safety plan is required and must be approved by the PI and the Safety Committee before proceeding.
- Two qualified workers must be in place before work can proceed.
- Limit the number of authorized workers in the hazard area.

High:

The activity will not be performed. The activity must be redesigned to fall in a lower hazard category.

## Appendix A: Hazard types and examples

Types of Hazard	Example
Physical hazards	Wet floors, loose electrical cables objects protruding in walkways or doorways
Ergonomic hazards	Lifting heavy objects Stretching the body Twisting the body Poor desk seating
Psychological hazards	Heights, loud sounds, tunnels, bright lights
Environmental hazards	Room temperature, ventilation contaminated air, photocopiers, some office plants acids
Hazardous substances	Alkalis solvents
Biological hazards	Hepatitis B, new strain influenza
Radiation hazards	Electric welding flashes Sunburn
Chemical hazards	Effects on central nervous system, lungs, digestive system, circulatory system, skin, reproductive system. Short term (acute) effects such as burns, rashes, irritation, feeling unwell, coma and death. Long term (chronic) effects such as mutagenic (affects cell structure), carcinogenic (cancer), teratogenic (reproductive effect), dermatitis of the skin, and occupational asthma and lung damage.
Noise	High levels of industrial noise will cause irritation in the short term, and industrial deafness in the long term.
Temperature	Personal comfort is best between temperatures of 16°C and 30°C, better between 21°C and 26°C. Working outside these temperature ranges: may lead to becoming chilled, even hypothermia (deep body cooling) in the colder temperatures, and may lead to dehydration, cramps, heat exhaustion, and hyperthermia (heat stroke) in the warmer temperatures.
Being struck by	This hazard could be a projectile, moving object or material. The health effect could be lacerations, bruising, breaks, eye injuries, and possibly death.
Crushed by	A typical example of this hazard is tractor rollover. Death is usually the result
Entangled by	Becoming entangled in machinery. Effects could be crushing, lacerations, bruising, breaks amputation and death.
High energy sources	Explosions, high pressure gases, liquids and dusts, fires, electricity and sources such as lasers can all have serious effects on the body, even death.
Vibration	Vibration can affect the human body in the hand arm with `white-finger' or Raynaud's Syndrome, and the whole body with motion sickness, giddiness, damage to bones and audits, blood pressure and nervous system problems.
Slips, trips and falls	A very common workplace hazard from tripping on floors, falling off structures or down stairs, and slipping on spills.
Radiation	Radiation can have serious health effects. Skin cancer, other cancers, sterility, birth deformities, blood changes, skin burns and eye damage are examples.
Physical	Excessive effort, poor posture and repetition can all lead to muscular pain, tendon damage and deterioration to bones and related structures
Psychological	Stress, anxiety, tiredness, poor concentration, headaches, back pain and heart disease can be the health effects
Biological	More common in the health, food and agricultural industries. Effects such as infectious disease, rashes and allergic response.