

Mockingbird Semantics

Nicolas Feltman

July 5, 2013

1 MbFilter

1.1 Grammar

$$\langle breakMethodG \rangle = 1G \mid 2.GP$$
$$\langle breakMethodS \rangle = 1S \mid 16^2.SP$$
$$\langle breakMethodH \rangle = 1H$$
$$\begin{aligned} \langle expr \rangle = & \langle expr \rangle > \langle expr \rangle \\ & \mid \textbf{fix } x. \langle expr \rangle \\ & \mid x \\ & \mid \textbf{test} \{ \langle expr \rangle \} \\ & \mid \textbf{hit} \\ & \mid \textbf{Shade} \\ & \mid \textbf{if } |g| > n \textbf{ then } \langle expr \rangle \textbf{ else } \langle expr \rangle \\ & \mid \textbf{BreakMapReduceG}(\langle breakMethodG \rangle) \{ \langle expr \rangle \} \\ & \mid \textbf{BreakMapReduceS}(\langle breakMethodS \rangle) \{ \langle expr \rangle \} \\ & \mid \textbf{BreakMapReduceH}(\langle breakMethodH \rangle) \{ \langle expr \rangle \} \end{aligned}$$
$$\langle sizeRange \rangle = [a, b] \mid [a+]$$
$$\langle entity-type \rangle = \textbf{GeoSamp } \langle sizeRange \rangle \langle sizeRange \rangle$$
$$\mid \textbf{Hit } \langle sizeRange \rangle$$
$$\mid \textbf{Frag } \langle sizeRange \rangle$$
$$\langle transition-type \rangle = \langle entity-type \rangle \rightarrow \langle entity-type \rangle$$
$$\langle breakG-type \rangle = (\langle sizeRange \rangle \rightarrow \langle sizeRange \rangle) \langle sizeRange \rangle$$
$$\langle breakS-type \rangle = \langle sizeRange \rangle (\langle sizeRange \rangle \rightarrow \langle sizeRange \rangle)$$
$$\langle breakH-type \rangle = \langle sizeRange \rangle \rightarrow \langle sizeRange \rangle$$

1.2 Typing Rules

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau' \rightarrow \tau''}{\Gamma \vdash e_1 >> e_2 : \tau \rightarrow \tau''} \quad (1)$$

$$\frac{\Gamma, x : \phi \vdash e : \phi}{\Gamma \vdash \mathbf{fix} \ x.e : \phi} \quad (2)$$

$$\frac{\Gamma(x) = \phi}{\Gamma \vdash \mathbf{call} \ x : \phi} \quad (3)$$

$$\frac{\Gamma \vdash e : \mathbf{GeoSamp} \ \sigma_1 \ \sigma_2 \rightarrow \tau}{\Gamma \vdash \mathbf{test}\{e\} : \mathbf{GeoSamp} \ \sigma_1 \ \sigma_2 \rightarrow \tau} \quad (4)$$

$$\frac{\cdot}{\Gamma \vdash \mathbf{hit} : \mathbf{GeoSamp} \ [1, 1] \ [1, 1] \rightarrow \mathbf{Hit}} \quad (5)$$

$$\frac{\cdot}{\Gamma \vdash \mathbf{Shade} : \mathbf{Hit} \ [1, 1] \rightarrow \mathbf{Frag}} \quad (6)$$

$$\frac{\Gamma \vdash e_1 : \mathbf{GeoSamp} \ [n + 1, b] \ \sigma \rightarrow \tau \quad \Gamma \vdash e_2 : \mathbf{GeoSamp} \ [a, n] \ \sigma \rightarrow \tau}{\Gamma \vdash \mathbf{if} \ |g| > n \ \mathbf{then} \ e_1 \ \mathbf{else} \ e_2 : \mathbf{GeoSamp} \ [a, b] \ \sigma \rightarrow \tau} \quad (7)$$

$$\frac{\Gamma \vdash e : \mathbf{GeoSamp} \rightarrow \tau}{\Gamma \vdash \mathbf{BreakMapReduceG}(d)\{e\} : \mathbf{GeoSamp} \rightarrow \tau} \quad (8)$$

$$\frac{\Gamma \vdash e : \mathbf{GeoSamp} \rightarrow \tau}{\Gamma \vdash \mathbf{BreakMapReduceS}(d)\{e\} : \mathbf{GeoSamp} \rightarrow \tau} \quad (9)$$

$$\frac{\Gamma \vdash e : \mathbf{Hit} \rightarrow \tau}{\Gamma \vdash \mathbf{BreakMapReduceH}(d)\{e\} : \mathbf{Hit} \rightarrow \tau} \quad (10)$$

1.3 Denotational Semantics

$$|e_1 > e_2| = |e_2| \circ |e_1| \quad (11)$$

$$|\mathbf{fix} \ x.e| = |[(\mathbf{fix} \ x.e)/(\mathbf{call} \ x)]e| \quad (12)$$

$$|\mathbf{test}\{e\}| = |e| \circ id_{\emptyset} \cup (\lambda(G, S). \{(\perp, k) : (s, k) \in S\}) \circ id_{\emptyset} \quad (13)$$

$$|\mathbf{hit}| = \{(\{(g), \{(s, k)\}), \{(h, k)\}) : h = isect(g, s)\} \quad (14)$$

$$|\mathbf{Shade}| = \{(\{(s, k)\}, \{(f, k)\}) : f = shade(h)\} \quad (15)$$

$$|\mathbf{if} \ |g| > n \ \mathbf{then} \ e_1 \ \mathbf{else} \ e_2| = |e_1| \circ id_{|g| > n} \cup |e_2| \circ id_{|g| \leq n} \quad (16)$$

$$|\mathbf{BreakMapReduceG}(d)\{e\}| = \begin{aligned} & \{((G, S), \{F_1 \oplus \dots \oplus F_n\}) \\ & : ((G_i, S), f_i) \in |e|, (G, \{G_1, \dots, G_n\}) \in |d|\} \end{aligned} \quad (17)$$

$$|\mathbf{BreakMapReduceS}(d)\{e\}| = \begin{aligned} & \{((G, S), \{F_1 \cup \dots \cup F_n\}) \\ & : ((G, S_i), f_i) \in |e|, (S, \{S_1, \dots, S_n\}) \in |d|\} \end{aligned} \quad (18)$$

$$|\mathbf{BreakMapReduceH}(d)\{e\}| = \begin{aligned} & \{(H, \{F_1 \cup \dots \cup F_n\}) \\ & : (H_i, F_i) \in |e|, (H, \{H_1, \dots, H_n\}) \in |d|\} \end{aligned} \quad (19)$$

1.4 Theorems

1. For any expression e , if $((G, S), F) \in |e|$, then $keys(S) = keys(F)$.
2. For any expression $e : \mathbf{GeoSamp} \rightarrow \mathbf{Frag}$, if $((G, S), F) \in |e|$, then for all $(s, k) \in S$, $(\bigoplus_{g \in G} shade(isect(g, s)), k) \in F$.

2 MbOrder

2.1 Grammar

```
e = e >> e
  | fix x. e
  | x
  | hit
  | test{e}
  | filt{e}
  | ifsizeG(> n) e else e
  | buildG(dG)
  | buildS(dS)
  | unboundG
  | unboundS
  | mmrG{e}
  | mmrS{e}

dα = id
  | pα >=> dα
  | fix x. dα
  | x
  | bound(dα)
  | ifsizeα(> n) dα else dα

pG = 1G | 2_GP
pS = 1S | 162_SP

τ = σ → σ
σ = GeoSamp δ δ
  | Hit δ
δ = *
  | [δ]
  | #δ
  | δ + δ
  | μ α. δ
  | α
```

2.2 Typing Rules

$$\frac{\Gamma \vdash e_1 : \sigma \rightarrow \sigma' \quad \Gamma \vdash e_2 : \sigma' \rightarrow \sigma''}{\Gamma \vdash e_1 > e_2 : \sigma \rightarrow \sigma''} \quad (20)$$

$$\frac{\Gamma, x : \tau \vdash e : \tau}{\Gamma \vdash \text{fix } x.e : \tau} \quad (21)$$

$$\frac{\Gamma(x) = \tau}{\Gamma \vdash x : \tau} \quad (22)$$

$$\frac{\Gamma \vdash e : \text{GeoSamp } \# \delta_1 \# \delta_2 \rightarrow \sigma}{\Gamma \vdash \text{test}\{e\} : \text{GeoSamp } \# \delta_1 \# \delta_2 \rightarrow \sigma} \quad (23)$$

$$\frac{\cdot}{\Gamma \vdash \text{hit} : \text{GeoSamp } * * \rightarrow \text{Hit } *} \quad (24)$$

$$\frac{\Gamma \vdash e : \text{GeoSamp } \delta_1 \delta_2 \rightarrow \text{Hit } *}{\Gamma \vdash \text{mmrG}\{e\} : \text{GeoSamp } [\delta_1] \delta_2 \rightarrow \text{Hit } *} \quad (25)$$

$$\frac{\Gamma \vdash e_1 : \text{GeoSamp } \delta_1 \delta_2 \rightarrow \sigma \quad \Gamma \vdash e_2 : \text{GeoSamp } \delta_1 \delta_2 \rightarrow \sigma}{\text{ifsizeG}(> n) e_1 \text{ else } e_2 : \text{GeoSamp } \delta_1 \delta_2 \rightarrow \sigma} \quad (26)$$

$$\frac{\cdot}{\text{unboundG} : \text{GeoSamp } \# \delta_1 \delta_2 \rightarrow \text{GeoSamp } \delta_1 \delta_2} \quad (27)$$

$$\frac{\cdot}{\text{unboundS} : \text{GeoSamp } \delta_1 \# \delta_2 \rightarrow \text{GeoSamp } \delta_1 \delta_2} \quad (28)$$

$$\frac{d : \delta_1}{\text{buildG}(d) : \text{GeoSamp } * \delta_2 \rightarrow \text{GeoSamp } \delta_1 \delta_2} \quad (29)$$

$$\frac{d : \delta_2}{\text{buildS}(d) : \text{GeoSamp } \delta_1 * \rightarrow \text{GeoSamp } \delta_1 \delta_2} \quad (30)$$

2.3 Big Step Semantics

$$\begin{aligned} g &= [t, \dots, t] \\ &| [g, \dots, g] \\ &| (bound, g) \\ &| inL(g) \\ &| inR(g) \\ s &= [r, \dots, r] \\ &| [s, \dots, s] \\ &| (bound, s) \\ &| inL(s) \\ &| inR(s) \\ v &= (g, s) \end{aligned}$$

$$\frac{e_1 \ v \Downarrow v' \quad e_2 \ v' \Downarrow v''}{(e_1 >> e_2) \ v \Downarrow v''} \quad (31)$$

$$\frac{h = \text{intersect}(g, s)}{\text{hit} \ ([g], [s]) \Downarrow [h]} \quad (32)$$

$$\frac{d \ g \Downarrow_G g'}{\text{buildG}(d) \ (g, s) \Downarrow (g', s)} \quad (33)$$

$$\frac{d \ g \Downarrow_G g'}{\text{bound}(d) \ g \Downarrow_G (\text{box}(g'), v)} \quad (34)$$

$$\frac{p(g) = [g_1, g_2, \dots, g_n] \quad d \ g_i \Downarrow_G g'_i}{(p >=> d) \ g \Downarrow_G [g'_1, g'_2, \dots, g'_n]} \quad (35)$$

$$\frac{\text{intersects}(b_1, b_2) \quad e \ ((b_1, g), (b_2, s)) \Downarrow v}{\text{test}\{e\} \ ((b_1, g), (b_2, s)) \Downarrow v} \quad (36)$$

$$\frac{e \ (g_i, s) \Downarrow v_i \quad v = v_1 \oplus \dots \oplus v_n}{\text{mmrG}\{e\} \ ([g_1, \dots, g_n], s) \Downarrow v} \quad (37)$$

$$\frac{e \ (g, s_i) \Downarrow v_i \quad v = v_1 \cup \dots \cup v_n}{\text{mmrS}\{e\} \ (g, [s_1, \dots, s_n]) \Downarrow v} \quad (38)$$

$$\frac{e_1 \ (g, s) \Downarrow v}{\text{caseG}\{e_1|e_2\} \ (\text{inL}(g), s) \Downarrow v} \quad (39)$$

$$\frac{e_2 \ (g, s) \Downarrow v}{\text{caseG}\{e_1|e_2\} \ (\text{inR}(g), s) \Downarrow v} \quad (40)$$

3 Examples

We start with the source for the repeat-work raytracer.

```
buildS(1S) >>
mmrS{
  fix x.
    buildS(bound(id)) >>
    buildG(bound(id)) >>
    test{
      unboundS >>
      unboundG >>
      ifsizeG(> 1) buildG(2.GP ==> id) >> mmrG{x}
      else hit
    }
}
```

We now precompute the 2GP split.

```
buildS(1S) >>
mmrS{
  fix x.
    buildS(bound(id)) >>
    buildG(bound(id)) >>
    test{
      unboundS >>
      unboundG >>
      buildG(ifsizeG(> 1) (2.GP ==> id) else id) >>
      caseG(> 1) mmrG{x} | hit
    }
}
```


Reorder the bounding and unbounding to make the next step less daunting.

```

buildS(1S) >>
mmrS{
  fix x.
    buildS(bound(id)) >>
    buildG(bound(id)) >>
    test{
      unboundG >>
      buildG(ifsizG(> 1) (2_GP ==> id) else id) >>
      unboundS >>
      caseG(> 1) mmrG{x} | hit
    }
}

```

Pull through the bound-test-unbound (I have to show this all at once, since the intermediate stages are inexpressible in this language).

```

buildS(1S) >>
mmrS{
  fix x.
    buildS(bound(id)) >>
    buildG(bound(ifsizG(> 1) (2_GP ==> id) else id)) >>
    test{
      unboundG >>
      unboundS >>
      caseG(> 1) mmrG{x} | hit
    }
}

```

Push the unboundS through the case and into the mmrG.

```

buildS(1S) >>
mmrS{
  fix x.
    buildS(bound(id)) >>
    buildG(bound(ifsizG(> 1) (2_GP ==> id) else id)) >>
    test{
      unboundG >>
      caseG(> 1) mmrG{unboundS >> x} | (unboundS >> hit)
    }
}

```

Lift out the buildS.

```
buildS(1S) >>
mmrS{
  buildS(bound(id)) >>
  fix x.
    buildG(bound(ysizeG(> 1) (2_GP ==> id) else id)) >>
    test{
      unboundG >>
      caseG(> 1) mmrG{x} | (unboundS >> hit)
    }
}
```

Lift the buildG through the fix.

```
buildS(1S) >>
mmrS{
  buildS(bound(id)) >>
  buildG(fix z. bound(ysizeG(> 1) (2_GP ==> z) else id)) >>
  fix x.
    test{
      unboundG >>
      caseG(> 1) mmrG{x} | (unboundS >> hit)
    }
}
```

Finally list the bvh build through mmrS and we have the bvh-accelerated raytracer.

```
buildS(1S) >>
buildG(fix z. bound(ysizeG(> 1) (2_GP ==> z) else id)) >>
mmrS{
  buildS(bound(id)) >>
  fix x.
    test{
      unboundG >>
      caseG mmrG{x} | (unboundS >> hit)
    }
}
```

Now here's the dumb raytracer expressed in another language:

```

fix y.
  %G.
  fix x.
    %G(boundBox) >>
    %S(boundRay) >>
    if %GS(intersect) then
      %G(unbound) >>
      %S(unbound) >>
      if %G(sizeGT1) then
        %G(2GP) >> semimapG2(x) >> %H(closer)
      else
        %GS(hit)
    else
      %S(allMiss)

```

And the bvh-accelerated raytracer:

```

%S(1S) >>
%G(fix z. boundBox >> map×B(
  if (sizeGT1) then
    2GP >> map2(x) >> ι1
  else ι2) >>
* mapOverS * {
  %S(boundRay) >>
  fix x.
    if %GS(intersect) then
      %G(unbound) >>
      case
        (semimapG2(x) >> %H(closer))
        | (%S(unbound) >> %GS(hit))
    else
      %S(allMiss)
}

```