Status	Finished
Started	Wednesday, 21 October 2026, 9:20 PM
Completed	Wednesday, 21 October 2026, 9:23 PM
Duration	3 mins 2 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of single characters

b. a list of integers

c. str

d. a list of lines ✓

The correct answer is:
a list of lines

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. insert()

b. write() ✓

c. append()

d. read()

The correct answer is: write()

Question **3**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

- a. tell() ✓
- b. current()
- c. position()
- d. locate()

The correct answer is: tell()

Question **4**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

- a. Prints each line of the file
- b. Prints the first 10 characters of the file
- c. Prints the entire content of the file ✓
- d. Prints an error message

The correct answer is: Prints the entire content of the file

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. read(size) ✓
- b. readline()
- c. readchar()
- d. readlines()

The correct answer is: read(size)

Question **6**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. r+ ✓
b. a
c. r
d. w

The correct answer is: r+

Question **7**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

a. Deletes the file content
b. Closes the file
c. Flushes the internal buffer to the file ✓
d. Moves the file cursor to the beginning

The correct answer is: Flushes the internal buffer to the file

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

a. It reads the file and returns it as a dictionary
b. It reads the entire file and returns it as a list of lines ✓
c. It reads the entire file and returns it as a string
d. It reads a single line from the file

The correct answer is: It reads the entire file and returns it as a list of lines

Question **9**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. moves the file pointer to the end of a file

b. move the file pointer to beginning of the file

c. move the file pointer five characters ahead from the current position ✓

d. move the file pointer five characters behind from the current position

The correct answer is:
move the file pointer five characters ahead from the current position

Question **10**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlist()

b. readlines() ✓

c. read()

d. readline()

The correct answer is: readlines()

Question **11**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Write

b. Binary

c. Append

d. Read ✓

The correct answer is: Read

Question **12**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. ftell()
b. seek() ✓
c. fseek()
d. tell()

The correct answer is: seek()

Question **13**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The mode of the file
b. The size of the file
c. The encoding format of the file ✓
d. The buffer size

The correct answer is: The encoding format of the file

Question **14**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. 0
b. An empty string ✓
c. None
d. EOFError

The correct answer is: An empty string

Question **15**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a.
- Move file pointer five characters behind ahead from the end of a file.

b.
- Move file pointer five characters ahead from the current position. ✓

c. Move file pointer five characters ahead from the beginning

d.
- Move file pointer five characters behind from the current position.

The correct answer is:

- Move file pointer five characters ahead from the current position.