

```

#include <stdlib.h>

#include <GL/glut.h>

GLfloat vertices[][3] = {{-1.0,-1.0,-1.0},{1.0,-1.0,-1.0}, {1.0,1.0,-1.0}, {-1.0,1.0,-1.0},
{-1.0,-1.0,1.0}, {1.0,-1.0,1.0}, {1.0,1.0,1.0}, {-1.0,1.0,1.0}};

GLfloat normals[][3] = {{-1.0,-1.0,-1.0},{1.0,-1.0,-1.0}, {1.0,1.0,-1.0}, {-1.0,1.0,-1.0},
{-1.0,-1.0,1.0}, {1.0,-1.0,1.0}, {1.0,1.0,1.0}, {-1.0,1.0,1.0}};

GLfloat colors[][3] = {{0.0,0.0,0.0},{1.0,0.0,0.0}, {1.0,1.0,0.0}, {0.0,1.0,0.0}, {0.0,0.0,1.0},
{1.0,0.0,1.0}, {1.0,1.0,1.0}, {0.0,1.0,1.0}};

void polygon(int a, int b, int c , int d)
{
    glBegin(GL_POLYGON);
    glColor3fv(colors[a]);
    glNormal3fv(normals[a]);
    glVertex3fv(vertices[a]);
    glColor3fv(colors[b]);
    glNormal3fv(normals[b]);
    glVertex3fv(vertices[b]);
    glColor3fv(colors[c]);
    glNormal3fv(normals[c]);
    glVertex3fv(vertices[c]);
    glColor3fv(colors[d]);
    glNormal3fv(normals[d]);
    glVertex3fv(vertices[d]);
    glEnd();
}

void colorcube()
{
    polygon(0,3,2,1);
    polygon(2,3,7,6);
    polygon(0,4,7,3);
    polygon(1,2,6,5);
}

```

```

polygon(4,5,6,7);
polygon(0,1,5,4);
}

static GLfloat theta[] = {0.0,0.0,0.0};

static GLint axis = 2;

static GLdouble viewer[] = {0.0, 0.0, 5.0}; /* initial viewer location */
void display(void)
{
    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
    /* Update viewer position in modelview matrix */
    glLoadIdentity();
    gluLookAt(viewer[0],viewer[1],viewer[2], 0.0, 0.0, 0.0, 0.0, 1.0, 0.0);
    /* rotate cube */
    glRotatef(theta[0], 1.0, 0.0, 0.0);
    glRotatef(theta[1], 0.0, 1.0, 0.0);
    glRotatef(theta[2], 0.0, 0.0, 1.0);
    colorcube();
    glFlush();
    glutSwapBuffers();
}

void mouse(int btn, int state, int x, int y)
{
    if(btn==GLUT_LEFT_BUTTON && state == GLUT_DOWN) axis = 0;
    if(btn==GLUT_MIDDLE_BUTTON && state == GLUT_DOWN) axis = 1;
    if(btn==GLUT_RIGHT_BUTTON && state == GLUT_DOWN) axis = 2;
    theta[axis] += 2.0;
    if( theta[axis] > 360.0 ) theta[axis] -= 360.0;
    display();
}

void keys(unsigned char key, int x, int y)
{

```

```

/* Use x, X, y, Y, z, and Z keys to move viewer */
if(key == 'x') viewer[0]-= 1.0;
if(key == 'X') viewer[0]+= 1.0;
if(key == 'y') viewer[1]-= 1.0;
if(key == 'Y') viewer[1]+= 1.0;
if(key == 'z') viewer[2]-= 1.0;
if(key == 'Z') viewer[2]+= 1.0;
display();
}

void myReshape(int w, int h)
{
    glViewport(0, 0, w, h);
    /* Use a perspective view */
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    if(w<=h)
        glFrustum(-2.0, 2.0, -2.0*(GLfloat) h/(GLfloat) w,2.0* (GLfloat) h / (GLfloat) w,2.0, 20.0);
    else
        glFrustum(-2.0, 2.0, -2.0*(GLfloat) w/(GLfloat) h,2.0* (GLfloat) w/(GLfloat) h, 2.0, 20.0);
    /* Or we can use gluPerspective */
    /* gluPerspective(45.0, w/h, -10.0, 10.0); */
    glMatrixMode(GL_MODELVIEW);
}

void main(int argc, char **argv)
{
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGB | GLUT_DEPTH);
    glutInitWindowSize(500, 500);
    glutCreateWindow("Colorcube Viewer");
    glutReshapeFunc(myReshape);
    glutDisplayFunc(display);
}

```

```
glutMouseFunc(mouse);  
glutKeyboardFunc(keys);  
glEnable(GL_DEPTH_TEST);  
glutMainLoop();  
}
```