

Fight_Detection_MViT_Colab_B8_LR0005

July 4, 2026

1 Fight Detection dengan MViT_v2_s

1.1 Tutorial Lengkap untuk Pemula - Google Colab

1.1.1 Yang Akan Kita Lakukan:

1. Setup environment (mount drive, install dependencies)
2. Upload Fight_utils_mvit.py
3. Persiapan dataset (150 fight + 150 noFight)
4. Training model MViT_v2_s
5. Testing & download model

1.1.2 Estimasi Waktu:

- Setup: 10 menit
- Training: 1-2 jam (GPU T4)
- Testing: 5 menit

1.1.3 Expected Result:

- Validation Accuracy: **80-90%**
- Model size: **~150 MB**

Catatan Penting: - Pastikan Runtime Type: **GPU** (Runtime → Change runtime type → GPU)
- Dataset sudah disiapkan di Google Drive atau siap upload - Ikuti setiap cell secara berurutan

Mari kita mulai!

2 STEP 1: Setup Environment

```
[1]: # Mount Google Drive
from google.colab import drive
drive.mount('/content/drive')

print(" Google Drive mounted successfully!")
```

Mounted at /content/drive
Google Drive mounted successfully!

```
[2]: # Check GPU
import torch

device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
print(f"Device: {device}")

if torch.cuda.is_available():
    print(f"GPU: {torch.cuda.get_device_name(0)}")
    print(f"GPU Memory: {torch.cuda.get_device_properties(0).total_memory / 1024**3:.2f} GB")
    print(" GPU is available!")
else:
    print(" WARNING: GPU not available. Training will be very slow!")
    print("Please change Runtime Type to GPU: Runtime → Change runtime type → GPU")
```

Device: cuda:0
GPU: Tesla T4
GPU Memory: 14.56 GB
GPU is available!

```
[3]: # Install required packages
print(" Installing dependencies...")
print("This might take 2-3 minutes...\n")

!pip install -q albumentations
!pip install -q moviepy

print("\n All dependencies installed!")
```

Installing dependencies...
This might take 2-3 minutes...

All dependencies installed!

```
[4]: # Import libraries
import os
import cv2
import time
import copy
import torch
import random
import numpy as np
import pandas as pd
```

```

import torch.nn as nn
import torchvision
from torch.utils.data import DataLoader, TensorDataset, random_split
from tqdm.notebook import tqdm
import albumentations as A
from collections import deque
import matplotlib.pyplot as plt

print(" All libraries imported successfully!")

```

All libraries imported successfully!

3 STEP 2: Setup Files & Dataset

3.1 Option B: Copy dari Google Drive (Jika sudah ada di Drive)

```

[5]: # SKIP cell ini jika Anda sudah upload di Option A

# Ganti path ini dengan lokasi file Anda di Google Drive
DRIVE_UTILS_PATH = '/content/drive/MyDrive/fight_detection/Fight_utils_mvit.py'

# Copy dari Drive ke Colab
!cp "{DRIVE_UTILS_PATH}" /content/Fight_utils_mvit.py

print(" File copied from Google Drive!")

```

File copied from Google Drive!

```

[6]: # Verify file exists
if os.path.exists('/content/Fight_utils_mvit.py'):
    print(" Fight_utils_mvit.py found!")

    # Show file size
    file_size = os.path.getsize('/content/Fight_utils_mvit.py') / 1024
    print(f" File size: {file_size:.2f} KB")
else:
    print(" ERROR: Fight_utils_mvit.py not found!")
    print(" Please upload the file in Option A or Option B above.")

```

Fight_utils_mvit.py found!
File size: 15.92 KB

3.2 Setup Dataset

3.2.1 Pilih salah satu:

Option 1: Dataset sudah ada di Google Drive - Struktur di Drive: MyDrive/dataset/fight/ dan MyDrive/dataset/noFight/ - Jalankan cell di bawah ini dan sesuaikan path

Option 2: Upload dataset ke Colab (lebih lambat, tapi simpel) - Upload folder dataset.zip - Extract di Colab

```
[7]: # OPTION 1: Dataset di Google Drive (RECOMMENDED)

# GANTI PATH INI sesuai lokasi dataset Anda di Google Drive
DATASET_DIR = '/content/drive/MyDrive/fight_detection'

# Cek apakah dataset ada
if os.path.exists(DATASET_DIR):
    fight_path = os.path.join(DATASET_DIR, 'fight')
    nofight_path = os.path.join(DATASET_DIR, 'noFight')

    if os.path.exists(fight_path) and os.path.exists(nofight_path):
        num_fight = len(os.listdir(fight_path))
        num_nofight = len(os.listdir(nofight_path))

        print(" Dataset found!")
        print(f"   Fight videos: {num_fight}")
        print(f"   NoFight videos: {num_nofight}")
        print(f"   Total: {num_fight + num_nofight}")

        if num_fight < 50 or num_nofight < 50:
            print("\n WARNING: Dataset terlalu kecil!")
            print("   Minimal 100 video per kelas untuk hasil baik.")
        else:
            print(" ERROR: Folder 'fight' atau 'noFight' tidak ditemukan!")
            print(f"   Expected: {fight_path} dan {nofight_path}")
    else:
        print(" ERROR: Dataset directory not found!")
        print(f"   Path: {DATASET_DIR}")
        print("\n Solusi:")
        print("   1. Pastikan path benar")
        print("   2. Atau gunakan Option 2 untuk upload dataset")
```

```
Dataset found!
Fight videos: 150
NoFight videos: 150
Total: 300
```

4 STEP 3: Import Fight Utilities

```
[8]: !pip install pytube
```

```
Collecting pytube
  Downloading pytube-15.0.0-py3-none-any.whl.metadata (5.0 kB)
  Downloading pytube-15.0.0-py3-none-any.whl (57 kB)
    0.0/57.6 kB
```

? eta -:--:--

57.6/57.6 kB 3.2

MB/s eta 0:00:00

Installing collected packages: pytube

Successfully installed pytube-15.0.0

```
[9]: # Import Fight_utils_mvit
import sys
sys.path.append('/content')

from Fight_utils_mvit import (
    create_dataset,
    create_fresh_mvit_model,
    device,
    CLASSES_LIST,
    SEQUENCE_LENGTH
)

print(" Fight_utils_mvit imported successfully!")
print(f" Device: {device}")
print(f" Classes: {CLASSES_LIST}")
print(f" Sequence Length: {SEQUENCE_LENGTH}")
```

/usr/local/lib/python3.12/dist-packages/moviepy/config_defaults.py:47:

SyntaxWarning: invalid escape sequence '\P'

IMAGEMAGICK_BINARY = r"C:\Program Files\ImageMagick-6.8.8-Q16\magick.exe"

/usr/local/lib/python3.12/dist-packages/moviepy/video/io/ffmpeg_reader.py:294:

SyntaxWarning: invalid escape sequence '\d'

```
lines_video = [l for l in lines if ' Video: ' in l and re.search('\d+x\d+',
1)]
```

/usr/local/lib/python3.12/dist-packages/moviepy/video/io/ffmpeg_reader.py:367:

SyntaxWarning: invalid escape sequence '\d'

```
rotation_lines = [l for l in lines if 'rotate          :' in l and
re.search('\d+$', 1)]
```

/usr/local/lib/python3.12/dist-packages/moviepy/video/io/ffmpeg_reader.py:370:

SyntaxWarning: invalid escape sequence '\d'

```
match = re.search('\d+$', rotation_line)
```

WARNING:py.warnings:/usr/local/lib/python3.12/dist-

packages/moviepy/video/io/sliders.py:61: SyntaxWarning: "is" with 'str' literal.

Did you mean "=="?

```
if event.key is 'enter':
```

Fight_utils_mvit imported successfully!

Device: cuda:0

Classes: ['fight', 'noFight']

Sequence Length: 16

5 STEP 4: Load & Prepare Dataset

```
[10]: # Set random seed for reproducibility
seed_constant = 42
np.random.seed(seed_constant)
random.seed(seed_constant)
torch.manual_seed(seed_constant)
torch.cuda.manual_seed_all(seed_constant)

print(" Random seed set to:", seed_constant)
```

Random seed set to: 42

```
[11]: # Load dataset
print("="*80)
print(" LOADING DATASET")
print("="*80)
print(" Extracting frames from videos...")
print(" This will take 20-40 minutes for 300 videos.")
print(" Please be patient!\n")

start_time = time.time()

# Extract features and labels
features, labels = create_dataset(DATASET_DIR, CLASSES_LIST, SEQUENCE_LENGTH)

elapsed = time.time() - start_time

print(f"\n{'='*80}")
print(" DATASET LOADED SUCCESSFULLY!")
print(f"{'='*80}")
print(f"Features shape: {features.shape}")
print(f"Labels shape: {labels.shape}")
print(f"Time taken: {elapsed/60:.1f} minutes")
```

```
=====
LOADING DATASET
=====
```

```
Extracting frames from videos...
This will take 20-40 minutes for 300 videos.
Please be patient!
```

Extracting Data of Class: fight

```
WARNING:py.warnings:/content/Fight_utils_mvit.py:32: UserWarning: Argument(s)
'always_apply' are not valid for transform Resize
A.Resize(256, 256, always_apply=True), # Resize lebih besar dulu
```

```
WARNING:py.warnings:/content/Fight_utils_mvit.py:33: UserWarning: Argument(s)
```

```
'always_apply' are not valid for transform CenterCrop
A.CenterCrop(224, 224, always_apply=True), # Center crop ke 224x224
```

```
WARNING:py.warnings:/content/Fight_utils_mvit.py:34: UserWarning: Argument(s)
'always_apply' are not valid for transform Normalize
A.Normalize(
```

Extracting Data of Class: noFight

```
=====
DATASET LOADED SUCCESSFULLY!
=====
```

```
Features shape: torch.Size([300, 3, 16, 224, 224])
Labels shape: torch.Size([300])
Time taken: 4.4 minutes
```

```
[12]: # Split dataset
print("\n Splitting dataset...")

# Configuration
VALIDATION_SPLIT = 0.2 # 20% for validation
BATCH_SIZE = 8         # Adjust if OOM error

# Create dataset
full_dataset = TensorDataset(features, labels)

# Calculate split sizes
total_size = len(full_dataset)
val_size = int(VALIDATION_SPLIT * total_size)
train_size = total_size - val_size

# Split
train_dataset, val_dataset = random_split(
    full_dataset,
    [train_size, val_size],
    generator=torch.Generator().manual_seed(seed_constant)
)

# Create dataloaders
train_loader = DataLoader(
    train_dataset,
    batch_size=BATCH_SIZE,
    shuffle=True,
    num_workers=2,
    pin_memory=True
)
```

```

val_loader = DataLoader(
    val_dataset,
    batch_size=BATCH_SIZE,
    shuffle=False,
    num_workers=2,
    pin_memory=True
)

dataloaders = {'train': train_loader, 'val': val_loader}

print(f" Dataset split complete!")
print(f" Total: {total_size} videos")
print(f" Training: {train_size} videos ({(1-VALIDATION_SPLIT)*100:.0f}%)")
print(f" Validation: {val_size} videos ({VALIDATION_SPLIT*100:.0f}%)")
print(f" Batch size: {BATCH_SIZE}")
print(f" Batches per epoch (train): {len(train_loader)}")
print(f" Batches per epoch (val): {len(val_loader)}")

```

```

Splitting dataset...
Dataset split complete!
Total: 300 videos
Training: 240 videos (80%)
Validation: 60 videos (20%)
Batch size: 8
Batches per epoch (train): 30
Batches per epoch (val): 8

```

```

[13]: # Clear memory
torch.cuda.empty_cache()
print(" GPU memory cleared")

```

```
GPU memory cleared
```

6 STEP 5: Create Model

```

[14]: print("="*80)
print(" CREATING MViT_v2_s MODEL")
print("="*80)
print(" Loading pretrained weights from Kinetics-400...")
print(" This might take 2-3 minutes...\n")

# Create model
model = create_fresh_mvit_model(num_classes=2, pretrained=True)
model = model.to(device)

# Count parameters

```

```

total_params = sum(p.numel() for p in model.parameters())
trainable_params = sum(p.numel() for p in model.parameters() if p.requires_grad)

print(f"\n{'='*80}")
print(" MODEL CREATED SUCCESSFULLY!")
print(f"{'='*80}")
print(f"Model: MViT_v2_s")
print(f"Total parameters: {total_params:,}")
print(f"Trainable parameters: {trainable_params:,}")
print(f"Model size: ~{total_params * 4 / 1024 / 1024:.1f} MB")
print(f"Device: {device}")
print(f"{'='*80}")

```

```

=====
CREATING MViT_v2_s MODEL
=====

Loading pretrained weights from Kinetics-400...
This might take 2-3 minutes...

Downloading: "https://download.pytorch.org/models/mvit_v2_s-ae3be167.pth" to
/root/.cache/torch/hub/checkpoints/mvit_v2_s-ae3be167.pth
100%|          | 132M/132M [00:01<00:00, 131MB/s]

=====
MODEL CREATED SUCCESSFULLY!
=====

Model: MViT_v2_s
Total parameters: 34,231,682
Trainable parameters: 34,231,682
Model size: ~130.6 MB
Device: cuda:0
=====

```

7 STEP 6: Training Configuration

```

[15]: # Training configuration
NUM_EPOCHS = 40
LEARNING_RATE = 0.0005
WEIGHT_DECAY = 1e-3

# Loss function with Label Smoothing
criterion = nn.CrossEntropyLoss(label_smoothing=0.15)

# Optimizer with Weight Decay (AdamW)
optimizer = torch.optim.AdamW(model.parameters(), lr=LEARNING_RATE,
↪weight_decay=WEIGHT_DECAY)

```

```

# Learning rate scheduler (CosineAnnealing for smooth decay)
scheduler = torch.optim.lr_scheduler.CosineAnnealingWarmRestarts(
    optimizer,
    T_0=10,
    T_mult=2,
    eta_min=1e-6
)

print("="*80)
print("  TRAINING CONFIGURATION")
print("="*80)
print(f"Number of epochs: {NUM_EPOCHS}")
print(f"Learning rate: {LEARNING_RATE}")
print(f"Weight Decay: {WEIGHT_DECAY}")
print(f"Batch size: {BATCH_SIZE}")
print(f"Optimizer: AdamW")
print(f"Loss function: CrossEntropyLoss (Label Smoothing=0.15)")
print(f"LR Scheduler: CosineAnnealingWarmRestarts")
print("="*80)

```

```

=====
  TRAINING CONFIGURATION
=====
Number of epochs: 40
Learning rate: 0.0005
Weight Decay: 0.001
Batch size: 8
Optimizer: AdamW
Loss function: CrossEntropyLoss (Label Smoothing=0.15)
LR Scheduler: CosineAnnealingWarmRestarts
=====

```

8 STEP 7: Training Loop

Estimasi waktu: 1-2 jam (tergantung GPU)

Tips: - Anda bisa minimize tab ini, training akan tetap berjalan - Jangan close tab/browser! -
Jika Colab disconnect, model terakhir tetap tersimpan - Monitor progress bar dan metrics

```

[16]: # Training function (simplified dari Fight_utils)
def train_model_colab(model, dataloaders, criterion, optimizer, scheduler,
    ↪ num_epochs):
    since = time.time()

    best_model_wts = copy.deepcopy(model.state_dict())
    best_acc = 0.0

```

```

history = {
    'train_loss': [],
    'train_acc': [],
    'val_loss': [],
    'val_acc': []
}

for epoch in range(num_epochs):
    print(f"\n{'='*80}")
    print(f"Epoch {epoch+1}/{num_epochs}")
    print(f"{'='*80}")

    # Each epoch has training and validation phase
    for phase in ['train', 'val']:
        if phase == 'train':
            model.train()
        else:
            model.eval()

        running_loss = 0.0
        running_corrects = 0

        # Progress bar
        pbar = tqdm(dataloaders[phase], desc=f'{phase.capitalize()}',
↪leave=False)

        for inputs, labels in pbar:
            inputs = inputs.to(device)
            labels = labels.to(device)

            optimizer.zero_grad()

            with torch.set_grad_enabled(phase == 'train'):
                outputs = model(inputs)
                loss = criterion(outputs, labels)
                _, preds = torch.max(outputs, 1)

                if phase == 'train':
                    loss.backward()
                    optimizer.step()

            running_loss += loss.item() * inputs.size(0)
            running_corrects += torch.sum(preds == labels.data)

        # Update progress bar
        pbar.set_postfix({
            'loss': f'{loss.item():.4f}',

```

```

        'acc': f'{torch.sum(preds == labels.data).item() / inputs.
↪size(0):.4f}'
    })

    epoch_loss = running_loss / len(dataloaders[phase].dataset)
    epoch_acc = running_corrects.double() / len(dataloaders[phase].
↪dataset)

    # Save to history
    if phase == 'train':
        history['train_loss'].append(epoch_loss)
        history['train_acc'].append(epoch_acc.item())
    else:
        history['val_loss'].append(epoch_loss)
        history['val_acc'].append(epoch_acc.item())

    print(f'{phase.capitalize()} Loss: {epoch_loss:.4f} | Acc: ↪
↪{epoch_acc:.4f}')

    # Save best model
    if phase == 'val' and epoch_acc > best_acc:
        best_acc = epoch_acc
        best_model_wts = copy.deepcopy(model.state_dict())
        print(f' New best model! (Val Acc: {best_acc:.4f})')

    # Update scheduler
    if phase == 'val':
        if isinstance(scheduler, torch.optim.lr_scheduler.
↪ReduceLROnPlateau):
            scheduler.step(epoch_acc)
        else:
            scheduler.step()

    # Time estimation
    elapsed = time.time() - since
    avg_time = elapsed / (epoch + 1)
    remaining = avg_time * (num_epochs - epoch - 1)
    print(f' Time: {elapsed/60:.1f}m elapsed, ~{remaining/60:.1f}m ↪
↪remaining')

    time_elapsed = time.time() - since
    print(f"\n{'='*80}")
    print(f" TRAINING COMPLETE!")
    print(f"{'='*80}")
    print(f'Training completed in {time_elapsed // 60:.0f}m {time_elapsed % 60:.
↪0f}s')

```

```

print(f'Best validation accuracy: {best_acc:.4f}')
print(f"{'='*80}")

# Load best model weights
model.load_state_dict(best_model_wts)
return model, history

print(" Training function ready!")

```

Training function ready!

```

[17]: # START TRAINING!
print("="*80)
print(" STARTING TRAINING")
print("="*80)
print("Tips:")
print(" • You can minimize this tab, training will continue")
print(" • Don't close the browser!")
print(" • Monitor the progress bars")
print(" • Expected time: 1-2 hours")
print("="*80)

input("\n Press Enter to start training...")

# Train the model
trained_model, history = train_model_colab(
    model=model,
    dataloaders=dataloaders,
    criterion=criterion,
    optimizer=optimizer,
    scheduler=scheduler,
    num_epochs=NUM_EPOCHS
)

```

```

=====
STARTING TRAINING
=====
Tips:
  • You can minimize this tab, training will continue
  • Don't close the browser!
  • Monitor the progress bars
  • Expected time: 1-2 hours
=====

Press Enter to start training...

=====
Epoch 1/40

```

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.7111 | Acc: 0.5583

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.6951 | Acc: 0.4333

New best model! (Val Acc: 0.4333)

Time: 1.1m elapsed, ~43.2m remaining

=====

Epoch 2/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.6223 | Acc: 0.7042

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4634 | Acc: 0.8500

New best model! (Val Acc: 0.8500)

Time: 2.3m elapsed, ~43.5m remaining

=====

Epoch 3/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.6003 | Acc: 0.7375

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.6095 | Acc: 0.7333

Time: 3.5m elapsed, ~42.8m remaining

=====

Epoch 4/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4673 | Acc: 0.8458

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4703 | Acc: 0.8667

New best model! (Val Acc: 0.8667)

Time: 4.7m elapsed, ~42.0m remaining

=====

Epoch 5/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4014 | Acc: 0.9208

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4529 | Acc: 0.8500

Time: 5.9m elapsed, ~41.1m remaining

=====
Epoch 6/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4255 | Acc: 0.9042

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4894 | Acc: 0.8333

Time: 7.1m elapsed, ~40.0m remaining

=====
Epoch 7/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3114 | Acc: 0.9792

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4670 | Acc: 0.9167

New best model! (Val Acc: 0.9167)

Time: 8.2m elapsed, ~38.9m remaining

=====
Epoch 8/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2951 | Acc: 0.9708

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4462 | Acc: 0.9000

Time: 9.4m elapsed, ~37.8m remaining

=====
Epoch 9/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2702 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4493 | Acc: 0.9000

Time: 10.6m elapsed, ~36.6m remaining

=====
Epoch 10/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2694 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4498 | Acc: 0.9000

Time: 11.8m elapsed, ~35.5m remaining

=====
Epoch 11/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2694 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4585 | Acc: 0.9000

Time: 13.0m elapsed, ~34.3m remaining

=====
Epoch 12/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2694 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4591 | Acc: 0.9000

Time: 14.2m elapsed, ~33.2m remaining

=====
Epoch 13/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2688 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4841 | Acc: 0.8833

Time: 15.4m elapsed, ~32.0m remaining

=====
Epoch 14/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2724 | Acc: 0.9958

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5884 | Acc: 0.8167

Time: 16.6m elapsed, ~30.8m remaining

=====
Epoch 15/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3942 | Acc: 0.9167

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5225 | Acc: 0.8167

Time: 17.8m elapsed, ~29.6m remaining

=====
Epoch 16/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4738 | Acc: 0.8792

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.3948 | Acc: 0.9500

New best model! (Val Acc: 0.9500)

Time: 19.0m elapsed, ~28.5m remaining

=====
Epoch 17/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4465 | Acc: 0.8833

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5755 | Acc: 0.7167

Time: 20.2m elapsed, ~27.3m remaining
=====

Epoch 18/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4028 | Acc: 0.8917

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4450 | Acc: 0.8833

Time: 21.4m elapsed, ~26.1m remaining

=====

Epoch 19/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3464 | Acc: 0.9458

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.6114 | Acc: 0.8000

Time: 22.6m elapsed, ~25.0m remaining

=====

Epoch 20/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3006 | Acc: 0.9792

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5980 | Acc: 0.8333

Time: 23.8m elapsed, ~23.8m remaining

=====

Epoch 21/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2983 | Acc: 0.9792

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4908 | Acc: 0.8833

Time: 25.0m elapsed, ~22.6m remaining

=====

Epoch 22/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2692 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4659 | Acc: 0.8833

Time: 26.2m elapsed, ~21.4m remaining

=====
Epoch 23/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2682 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4677 | Acc: 0.8833

Time: 27.4m elapsed, ~20.2m remaining

=====
Epoch 24/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2680 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4610 | Acc: 0.8833

Time: 28.6m elapsed, ~19.0m remaining

=====
Epoch 25/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2680 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4601 | Acc: 0.9000

Time: 29.8m elapsed, ~17.9m remaining

=====
Epoch 26/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2679 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4609 | Acc: 0.9000
Time: 31.0m elapsed, ~16.7m remaining

=====
Epoch 27/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2683 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4515 | Acc: 0.9167

Time: 32.1m elapsed, ~15.5m remaining

=====
Epoch 28/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2678 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4500 | Acc: 0.9167

Time: 33.3m elapsed, ~14.3m remaining

=====
Epoch 29/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2677 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4496 | Acc: 0.9167

Time: 34.5m elapsed, ~13.1m remaining

=====
Epoch 30/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2677 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4497 | Acc: 0.9167

Time: 35.7m elapsed, ~11.9m remaining
=====

Epoch 31/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2678 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4505 | Acc: 0.9167

Time: 36.9m elapsed, ~10.7m remaining

=====

Epoch 32/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2695 | Acc: 1.0000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.6603 | Acc: 0.8000

Time: 38.1m elapsed, ~9.5m remaining

=====

Epoch 33/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4285 | Acc: 0.8917

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4146 | Acc: 0.8833

Time: 39.3m elapsed, ~8.3m remaining

=====

Epoch 34/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4370 | Acc: 0.8833

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5190 | Acc: 0.8167

Time: 40.5m elapsed, ~7.2m remaining

=====

Epoch 35/40

=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.5500 | Acc: 0.8000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5271 | Acc: 0.8500

Time: 41.7m elapsed, ~6.0m remaining

=====
Epoch 36/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.4365 | Acc: 0.9000

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4292 | Acc: 0.8833

Time: 42.9m elapsed, ~4.8m remaining

=====
Epoch 37/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3196 | Acc: 0.9667

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5106 | Acc: 0.8667

Time: 44.1m elapsed, ~3.6m remaining

=====
Epoch 38/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3341 | Acc: 0.9500

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4911 | Acc: 0.8667

Time: 45.3m elapsed, ~2.4m remaining

=====
Epoch 39/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.3358 | Acc: 0.9500

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.5676 | Acc: 0.8333
Time: 46.5m elapsed, ~1.2m remaining

=====
Epoch 40/40
=====

Train: 0%| | 0/30 [00:00<?, ?it/s]

Train Loss: 0.2995 | Acc: 0.9792

Val: 0%| | 0/8 [00:00<?, ?it/s]

Val Loss: 0.4732 | Acc: 0.8833

Time: 47.7m elapsed, ~0.0m remaining

=====
TRAINING COMPLETE!
=====

Training completed in 47m 41s

Best validation accuracy: 0.9500
=====

9 STEP 8: Visualize Training Results

```
[18]: # Plot training history
fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(15, 5))


# Plot loss
ax1.plot(history['train_loss'], label='Train Loss', marker='o')
ax1.plot(history['val_loss'], label='Val Loss', marker='s')
ax1.set_xlabel('Epoch')
ax1.set_ylabel('Loss')
ax1.set_title('Training and Validation Loss')
ax1.legend()
ax1.grid(True, alpha=0.3)

# Plot accuracy
ax2.plot([acc*100 for acc in history['train_acc']], label='Train Acc',
        marker='o')
ax2.plot([acc*100 for acc in history['val_acc']], label='Val Acc', marker='s')
ax2.set_xlabel('Epoch')
ax2.set_ylabel('Accuracy (%)')
ax2.set_title('Training and Validation Accuracy')
ax2.legend()
ax2.grid(True, alpha=0.3)

plt.tight_layout()
plt.savefig('training_curves.png', dpi=300, bbox_inches='tight')
```

```
plt.show()
```

```
print(" Training curves saved as 'training_curves.png'")
```



Training curves saved as 'training_curves.png'

```
[19]: # Print final metrics
print("="*80)
print(" TRAINING SUMMARY")
print("="*80)

final_train_acc = history['train_acc'][-1] * 100
final_val_acc = history['val_acc'][-1] * 100
best_val_acc = max(history['val_acc']) * 100

print(f"Final Training Accuracy: {final_train_acc:.2f}%")
print(f"Final Validation Accuracy: {final_val_acc:.2f}%")
print(f"Best Validation Accuracy: {best_val_acc:.2f}%")

# Interpretasi
print(f"\n{'='*80}")
print(" INTERPRETASI")
print(f"{'='*80}")

if best_val_acc >= 90:
    print(" EXCELLENT! Model sangat bagus!")
elif best_val_acc >= 80:
    print(" GOOD! Model cukup bagus untuk production.")
elif best_val_acc >= 70:
    print(" FAIR. Model bisa ditingkatkan dengan:")
    print(" • Training lebih lama")
    print(" • Tambah data")
    print(" • Data augmentation")
else:
```

```

print(" NEEDS IMPROVEMENT. Coba:")
print("    • Periksa kualitas dataset")
print("    • Tambah lebih banyak data")
print("    • Adjust learning rate")

# Check overfitting
train_val_gap = final_train_acc - final_val_acc
if train_val_gap > 10:
    print(f"\n WARNING: Model mungkin overfitting!")
    print(f"    Gap: {train_val_gap:.2f}%")
    print("    Solusi: Tambah data atau gunakan regularization")

print("=*80)

```

TRAINING SUMMARY

```

Final Training Accuracy: 97.92%
Final Validation Accuracy: 88.33%
Best Validation Accuracy: 95.00%

```

INTERPRETASI

```

EXCELLENT! Model sangat bagus!

```

10 STEP 9: Save Model

```

[20]: # Save model to Colab
MODEL_SAVE_PATH = '/content/mvit_fight_modelV4.2.pth'

torch.save(trained_model.state_dict(), MODEL_SAVE_PATH)

print("=*80)
print("  MODEL SAVED")
print("=*80)
print(f"Path: {MODEL_SAVE_PATH}")

# Check file size
model_size = os.path.getsize(MODEL_SAVE_PATH) / 1024 / 1024
print(f"Size: {model_size:.1f} MB")
print("=*80)

```

```

MODEL SAVED

```

```

Path: /content/mvit_fight_modelV4.2.pth

```

Size: 130.7 MB

=====

```
[21]: # Save to Google Drive (RECOMMENDED)
DRIVE_SAVE_PATH = '/content/drive/MyDrive/mvit_fight_modelV4.2.pth'

print(" Saving model to Google Drive...")
!cp /content/mvit_fight_model.pth "{DRIVE_SAVE_PATH}"

print(f"\n Model saved to Google Drive!")
print(f"Path: {DRIVE_SAVE_PATH}")
print("\n Model Anda aman di Google Drive!")
```

Saving model to Google Drive...
cp: cannot stat '/content/mvit_fight_model.pth': No such file or directory

Model saved to Google Drive!
Path: /content/drive/MyDrive/mvit_fight_modelV4.2.pth

Model Anda aman di Google Drive!

```
[22]: # Download model to local computer
from google.colab import files

print(" Downloading model to your computer...")
files.download(MODEL_SAVE_PATH)

print("\n Model downloaded!")
print(" Check your Downloads folder.")
```

Downloading model to your computer...
<IPython.core.display.Javascript object>
<IPython.core.display.Javascript object>

Model downloaded!
Check your Downloads folder.

10.1 Confusion Matrix

```
[23]: import torch
from sklearn.metrics import confusion_matrix, ConfusionMatrixDisplay
import matplotlib.pyplot as plt

print(" Generating Confusion Matrix...")

# Set model to evaluation mode
trained_model.eval()
```

```

all_labels = []
all_predictions = []

with torch.no_grad():
    for inputs, labels in dataloaders['val']:
        inputs = inputs.to(device)
        labels = labels.to(device)

        outputs = trained_model(inputs)
        _, predicted = torch.max(outputs, 1)

        all_labels.extend(labels.cpu().numpy())
        all_predictions.extend(predicted.cpu().numpy())


# Compute confusion matrix
cm = confusion_matrix(all_labels, all_predictions,
    ↪ labels=list(range(len(CLASSES_LIST))))

# Display confusion matrix
fig_cm, ax = plt.subplots(figsize=(8, 6))
disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=CLASSES_LIST)
disp.plot(cmap=plt.cm.Blues, ax=ax)
ax.set_title('Confusion Matrix')
plt.tight_layout()
plt.savefig('confusion_matrix.png', dpi=300, bbox_inches='tight')
plt.show()

print("\n Confusion Matrix generated and saved as 'confusion_matrix.png'!")

```

Generating Confusion Matrix...



Confusion Matrix generated and saved as 'confusion_matrix.png'!

```
[24]: from sklearn.metrics import classification_report

# Mengeluarkan laporan metrik evaluasi lengkap
print("\n--- LAPORAN METRIK EVALUASI (BAB 4) ---")
laporan = classification_report(all_labels, all_predictions,
    ↪target_names=CLASSES_LIST, digits=4)
print(laporan)
```

```
\n--- LAPORAN METRIK EVALUASI (BAB 4) ---
              precision    recall  f1-score   support

   fight       0.9429       0.9706       0.9565         34
  noFight       0.9600       0.9231       0.9412         26

 accuracy                   0.9500         60
```

macro avg	0.9514	0.9468	0.9488	60
weighted avg	0.9503	0.9500	0.9499	60

11 STEP 10: Testing (Quick Test)

```
[25]: import torch
import os
from google.colab import drive

print(">>> Menyambungkan ke Google Drive...")
drive.mount('/content/drive')

model_filename = '/content/drive/MyDrive/mvit_fight_modelV2.pth'

if os.path.exists(model_filename):
    print(f"Mantap! Berhasil menemukan model: {model_filename}")
else:
    print(f"Waduh, file nggak ketemu nih. Pastikan letak dan nama foldernya,
    ↳udah bener ya: {model_filename}")
```

>>> Menyambungkan ke Google Drive...

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).

Waduh, file nggak ketemu nih. Pastikan letak dan nama foldernya udah bener ya: /content/drive/MyDrive/mvit_fight_modelV2.pth

```
[26]: from google.colab import files
from Fight_utils_mvit import Fight_PipeLine # Wajib di-import di sini!

print("\n Silakan upload video CCTV (MP4/AVI) yang mau dites:")
uploaded = files.upload()

# Cek apakah user beneran upload file
if uploaded:
    test_video = list(uploaded.keys())[0]
    print(f" Video '{test_video}' berhasil diterima. AI mulai menganalisis,
    ↳tunggu sebentar ya...")

    # Tentukan nama file hasil
    output_video = f"result_{test_video}"

    # Eksekusi AI (ngambil alamat model dari Cell 1)
    Fight_PipeLine(
        modelPath=model_path_gdrive,
        inputPath=test_video,
        seq=16,
```

```

        skip=2,
        outputPath=output_video,
        showInfo=True
    )

    print("\n Analisis selesai! Sedang mengunduh video hasil...")
    files.download(output_video)
    print(" Sempurna! Cek video hasilnya di laptopmu ya komandan!")
else:
    print(" Eh, kamu belum milih video buat di-upload nih. Coba run lagi ya.")

```

Silakan upload video CCTV (MP4/AVI) yang mau dites:

<IPython.core.display.HTML object>

```

-----
KeyboardInterrupt                                Traceback (most recent call last)
/tmp/ipykernel_1656/2660746451.py in <cell line: 0>()
      3
      4 print("\n Silakan upload video CCTV (MP4/AVI) yang mau dites:")
----> 5 uploaded = files.upload()
      6
      7 # Cek apakah user beneran upload file

/usr/local/lib/python3.12/dist-packages/google/colab/files.py in _
    ↪ upload(target_dir)
      67     """
      68
----> 69     uploaded_files = _upload_files(multiple=True)
      70     # Mapping from original filename to filename as saved locally.
      71     local_filenames = dict()

/usr/local/lib/python3.12/dist-packages/google/colab/files.py in _
    ↪ _upload_files(multiple)
     159
     160     # First result is always an indication that the file picker has
    ↪ completed.
--> 161     result = _output.eval_js(
     162         'google.colab._files._uploadFiles("{input_id}", "{output_id}")'.
    ↪ format(
     163             input_id=input_id, output_id=output_id

/usr/local/lib/python3.12/dist-packages/google/colab/output/_js.py in _
    ↪ eval_js(script, ignore_result, timeout_sec)
     38     if ignore_result:
     39         return
----> 40     return _message.read_reply_from_input(request_id, timeout_sec)

```

```

41
42

/usr/local/lib/python3.12/dist-packages/google/colab/_message.py in
↳ read_reply_from_input(message_id, timeout_sec)
    94     reply = _read_next_input_message()
    95     if reply == _NOT_READY or not isinstance(reply, dict):
--> 96         time.sleep(0.025)
    97         continue
    98     if (

```

KeyboardInterrupt: