

Authority Propagation Models: PoP vs PoC and the Confused Deputy Problem

Nicola Gallo

1 December 2025

1 Model

Let P be a set of principals (e.g., U , PDF , $Storage$). Let O be a set of operations (e.g., convert, delete), and R a set of resources.

A privilege is a pair $(o, r) \in O \times R$. Each principal p has a privilege set:

$$Priv(p) \subseteq O \times R.$$

A request is a message req sent between principals and may contain a payload.

2 Confused Deputy

Definition 1 (Confused Deputy). *A confused deputy occurs when there exist principals U (user) and D (deputy) such that:*

1. $(o, r) \notin Priv(U)$,
2. $(o, r) \in Priv(D)$,
3. U sends a request req to D ,
4. as a consequence of req , D executes (o, r) .

This definition does not depend on implementation details, only on the mismatch of authority and causality.

3 Proof-of-Possession (PoP)

A token t grants a set of privileges:

$$Auth(t) \subseteq O \times R.$$

PoP Semantics: Possession implies usability: if a principal holds t , it may exercise all $(o, r) \in \text{Auth}(t)$.

PoP systems do not constrain authority by causality or provenance.

3.1 Vulnerability Condition

Assume:

$$(\text{delete}, r) \notin \text{Priv}(U) \quad (\text{H1})$$

$$(\text{delete}, r) \in \text{Priv}(PDF) \quad (\text{H2})$$

Further assume:

The payload of a request may influence control flow in PDF , including code paths that call internal privileges such as delete.

Theorem 1 (PoP admits confused deputy). *Under assumptions (H1)–(H2), there exists a request req such that PDF executes (delete, r) as a result of processing req .*

Proof. Since $(\text{delete}, r) \in \text{Priv}(PDF)$ (H2), some code path in PDF invokes $\text{Storage.delete}(r)$. Because processing is influenced by payload, there exists an adversarial payload that triggers that path. Since U lacks (delete, r) (H1), and PDF acts on behalf of U , conditions for a confused deputy are satisfied. \square

This applies to OAuth tokens and sealed capabilities: sealing protects transport, not authority semantics.

4 Proof-of-Continuity (PoC / PIC)

Execution is modeled as a causal chain of hops:

$$p_0 \rightarrow p_1 \rightarrow \cdots \rightarrow p_n,$$

with $p_0 = U$.

Each hop transfers a privilege subset:

$$\text{ops}_i \subseteq O \times R$$

and must satisfy:

$$\text{ops}_{i+1} \subseteq \text{ops}_i. \quad (\text{C1})$$

Let π be a verifiable sequence:

$$\pi = \langle (p_0, \text{ops}_0), (p_1, \text{ops}_1), \dots, (p_n, \text{ops}_n) \rangle.$$

4.1 Authorization Rule

The final service authorizes (o, r) if and only if:

$$(o, r) \in \bigcap_{i=0}^n ops_i$$

and π is valid.

Since the chain is monotonic decreasing,

$$\bigcap_{i=0}^n ops_i = ops_n.$$

Thus no hop may acquire new authority not present at the origin.

5 Safety Property

Definition 2 (Origin-bounded authority). *A model enforces origin-bounded authority if every executable privilege at hop n is a privilege originally granted by hop 0.*

Theorem 2 (PoC prevents confused deputy). *If $ops_0 = \{(convert, r)\}$ and (C1) holds for every hop, then $(delete, r)$ can never be authorized at hop n .*

Proof. Authorization requires:

$$(delete, r) \in \bigcap_{i=0}^n ops_i.$$

But $(delete, r) \notin ops_0$ and each $ops_{i+1} \subseteq ops_i$. Therefore $(delete, r) \notin ops_i$ for all i , hence not in the intersection. The request is rejected. \square

6 Discussion

PoP systems conflate authority and possession, enabling confused deputy attacks whenever privileged internal code paths exist. PIC/PoC systems propagate only non-expansive subsets of authority, ensuring that downstream services cannot perform operations not explicitly authorized at the origin.

Acknowledgments

The author used automated language assistance tools, including large language models, to help with grammar, wording, and formal phrasing. All ideas, models, proofs, and conclusions in this document are solely the responsibility of the author.