

Proof-of-Continuity: A Temporal Model for Authority Propagation in Distributed Systems and AI Agents

Nicola Gallo

8 July 2026

Abstract

Proof-of-Possession authorization models derive authority from the possession of artifacts such as tokens, credentials, or capabilities. This paper argues that possession is insufficient for discrete execution chains, whether they span multiple services or occur as separated steps within the same machine, because it does not preserve the causal relationship between the origin of a request and the authority exercised at later steps. We introduce Proof-of-Continuity as a minimal authority propagation model in which each execution step must be causally linked to the previous step and may only propagate a non-expansive subset of the authority received from the origin. Under this model, the confused deputy condition cannot be satisfied as valid model behavior: any privilege exercised at a later step must already be present in the origin authority context. This is directly relevant to distributed systems and AI agents, where executors invoke tools and downstream services while holding multiple authority sources, so that the same authority/causality mismatch recurs across service boundaries.

1 Model

We formalize the PIC (Provenance Identity Continuity) Model as follows.

Let P be a finite set of principals, O a set of operations, and R a set of resources. Define a privilege as $(o, r) \in O \times R$.

Each principal p has an associated privilege set:

$$Priv(p) \subseteq O \times R.$$

A request is a message req sent between principals and may contain a payload.

Execution is modeled as a causal chain of steps:

$$\pi = \langle (s_0, C_0), (s_1, C_1), \dots, (s_n, C_n) \rangle$$

where s_0 is the origin step and $C_i \subseteq O \times R$ is the authority context carried at step s_i .

Definition 1 (PIC Model). *A system enforces Provenance Identity Continuity if, for every execution chain π , each transition preserves causal continuity and monotonic authority restriction:*

$$C_{i+1} \subseteq C_i$$

for all i , and every privilege exercised at hop n is causally linked to the origin via a verifiable chain.

Theorem 1 (PIC Safety). *If the PIC Model holds, no execution step can exercise a privilege not present at the origin.*

Proof. By construction, $C_{i+1} \subseteq C_i$ for all i , so $C_n \subseteq C_0$. Thus, any $(o, r) \in C_n$ must also be in C_0 . Therefore, no privilege can be gained beyond the origin authority context.

2 Threat Model and Scope

We consider execution chains in which an origin request causes one or more later execution steps. Executors may be buggy, confused, or adversarially influenced through their inputs. An executor may hold multiple authority sources — ambient privileges, delegated tokens, bearer credentials, or capabilities — and may attempt to use one unrelated to the request being processed.

The adversary may influence requests, payloads, and parameters passed across the chain, and may cause an executor to select the wrong authority source. The adversary cannot forge the relationship evidence required by *PoR*, nor make a valid continuity checker accept a transition that violates monotonicity. As capability and token models assume their credentials unforgeable, we assume the relationship evidence and the authority-transition mechanism unforgeable; compromise of the validator, the cryptographic root of trust, or the initial authority bootstrap is out of scope.

3 Confused Deputy

Definition 2 (Confused Deputy). *A confused deputy occurs when there exist principals U (user) and D (deputy) and a privilege $(o, r) \in O \times R$ such that:*

1. $(o, r) \notin \text{Priv}(U)$,
2. $(o, r) \in \text{Priv}(D)$,
3. U sends a request req to D ,
4. as a consequence of req , D executes (o, r) .

This definition does not depend on implementation details, only on the mismatch of authority and causality.

Classical example. A FORTRAN compiler `FORT`, installed in the privileged directory `SYSX`, holds ambient authority to write statistics to `(SYSX)STAT`. A user invokes the compiler and provides `(SYSX)BILL` as the debugging output filename. The compiler opens the target for output using its own authority over `SYSX`, thereby overwriting `(SYSX)BILL`. The user never possessed this privilege, but the deputy exercised it as a consequence of the user's request [1].

4 Proof-of-Possession (PoP)

A token t grants a set of privileges:

$$\text{Auth}(t) \subseteq O \times R.$$

PoP Semantics. Possession implies usability: if a principal holds t , it may exercise all $(o, r) \in \text{Auth}(t)$.

PoP systems constrain authority by artifact possession, but do not, by themselves, require that the exercised authority be a causal continuation of the authority context of the request.

4.1 Authority Mixing

Assume:

$$(\text{write}, r) \notin \text{Priv}(U) \tag{H1}$$

$$(\text{write}, r) \in \text{Priv}(D) \tag{H2}$$

Here U is the user and D is a deputy.

In a possession-based model, a deputy may hold multiple authority sources: its own ambient privileges, delegated tokens, bearer credentials, or other artifacts. The model authorizes an operation by checking whether some possessed authority source grants the requested privilege.

Theorem 2 (PoP admits authority mixing). *In a possession-based model, if an executor may select authority from any artifact or ambient privilege it holds independently of the request authority context, then the confused deputy condition is admissible in the model.*

Proof. Let a request originate from an authority context that does not contain (o, r) . Let the executor hold another authority context, artifact, or ambient privilege that does contain (o, r) .

In a PoP model, authorization depends on the possession of an artifact or privilege granting (o, r) , not on whether that authority is a continuation of the request authority context. Therefore the model permits an execution in which the request causally triggers (o, r) while (o, r) is absent from the request authority context. This is exactly the confused deputy condition.

This applies to any model in which authorization is derived from possession independently of the causal lineage: JWTs, bearer credentials, and even capabilities when a held capability may be applied outside the execution that requested it. The gap is not possession itself but the absence of a temporal binding between the authority used and the execution that caused its use.

5 Proof-of-Continuity (PoC / PIC)

Execution is a causal chain:

$$s_0 \rightarrow s_1 \rightarrow \dots \rightarrow s_n.$$

Let $C_i \subseteq O \times R$ denote the authority context carried by execution step s_i .

Definition 3 (Proof of Relationship). *PoR(s_i, s_{i+1}) holds iff s_{i+1} is a valid causal continuation of s_i within the same execution lineage. PoR is a relational, single-hop property: it binds one step to its immediate predecessor.*

Definition 4 (Valid transition). *A transition from s_i to s_{i+1} is valid iff it is both causally related and non-expansive:*

$$\text{Valid}(s_i, C_i, s_{i+1}, C_{i+1}) \iff \text{PoR}(s_i, s_{i+1}) \wedge C_{i+1} \subseteq C_i.$$

The first condition proves causal relationship. The second condition proves monotonic authority restriction. Thus each hop transfers only:

$$C_{i+1} \subseteq C_i. \quad (C1)$$

Definition 5 (Proof of Continuity). *For a chain $\pi = \langle s_0, \dots, s_n \rangle$, $PoC(\pi)$ holds iff every adjacent transition is valid:*

$$PoC(\pi) \iff \bigwedge_{i=0}^{n-1} (PoR(s_i, s_{i+1}) \wedge C_{i+1} \subseteq C_i).$$

Thus continuity is the transitive composition of relationships: PoR proves a single link, PoC proves the whole lineage. Relationship is local; continuity is global.

Monotone propagation along a causal chain. Two things propagate together. First, authority attenuates monotonically: write $C_{i+1} \preceq C_i$ for authority *attenuation* — every authority at a hop is a restriction of one held at the previous hop, never an expansion. When the context is a set of atomic privileges this specializes to $C_{i+1} \subseteq C_i$, the form used in our examples. Second, the hops are bound into a single causal lineage by PoR : continuity is a property not of a hop in isolation but of the *chain*. Formally the lineage is a logical causal chain; in an implementation it need not be carried whole — it is a collection of hashes that reconstruct and verify the chain, so each hop proves its place in the lineage without transporting the entire history.

Heterogeneous operation spaces. The notation assumes a common privilege universe $O \times R$. In heterogeneous systems different hops use different vocabularies; let $O_i \times R_i$ be the universe at hop i . A transition is then governed by a policy translation

$$\mathcal{T}_{i \rightarrow i+1} : \mathcal{P}(O_i \times R_i) \rightarrow \mathcal{P}(O_{i+1} \times R_{i+1}),$$

and monotonicity becomes $C_{i+1} \subseteq \mathcal{T}_{i \rightarrow i+1}(C_i)$: the successor authority is no greater than what the predecessor permits under the local translation. We treat $\mathcal{T}$ as fixed policy input; synthesizing or verifying such translations is out of scope.

Lemma 1 (Continuity implies origin binding). *If $PoC(\pi)$ holds, then s_n is causally linked to s_0 through a verifiable relational chain and $C_n \subseteq C_0$.*

Proof. Each $PoR(s_i, s_{i+1})$ links consecutive steps; their composition links s_n to s_0 . Non-expansiveness at each hop gives $C_n \subseteq \dots \subseteq C_0$.

We state the scope explicitly: this paper models the continuity invariant; the concrete (e.g. cryptographic) construction of PoR is out of scope and is realized by a companion enforcement architecture. As capability and token models assume their credentials unforgeable, we assume the lineage is unforgeable.

5.1 Authorization Rule

(o, r) is authorized at the final hop iff:

$$(o, r) \in \bigcap_{i=0}^n C_i.$$

Since the chain is monotonic decreasing:

$$C_n \subseteq C_{n-1} \subseteq \dots \subseteq C_0,$$

we have:

$$\bigcap_{i=0}^n C_i = C_n.$$

Thus no hop may acquire authority not already present at the origin, and any authority dropped at some hop j is lost irreversibly: by monotonicity it cannot reappear at any later hop.

5.2 The Ontological Shift: Possession vs Continuity

Possession- and capability-based models [2, 3] answer a *spatial* question: does an actor hold authority over an object? Authority is a point in $O \times R$. This model is atemporal: it has no axis on which to record the execution that led to an action.

Proof-of-Relationship supplies the missing axis: it binds an execution step to its causal predecessor. Proof-of-Continuity is built on it — continuity is the transitive composition of relationships — and combines two conditions: monotone restriction of permissions ($C_{i+1} \subseteq C_i$) and causal continuity, via PoR , of the execution that carries them.

Authority therefore no longer lives in $O \times R$ alone but in $O \times R \times \mathcal{L}$, where $\mathcal{L}$ is the causal lineage of the execution. Concretely, $\mathcal{L}$ is the set of finite linear causal lineages: a lineage is a sequence $\ell = \langle s_0 \prec s_1 \prec \dots \prec s_n \rangle$,

where $\prec$ denotes causal precedence, so each event is an occurrence of a privilege within a particular lineage. Two actions identical in possession — same principal, same token, same privilege — may be distinct in continuity, because they descend from different causes. A request to *pay 100*, issued once by the user and once by a replay, is indistinguishable under possession, yet the two are distinct executions: one continues an authorizing lineage, the other continues none. Possession is the projection onto $O \times R$ that forgets the lineage axis.

In the projection language this is the *temporal reading* of the confused deputy of Definition 2: an action spatially valid but temporally invalid — the deputy holds (o, r) , yet $(o, r) \notin C_0$ for the request that caused it — a collision under the projection that forgets $\mathcal{L}$, two distinct executions that possession cannot tell apart. Section 6 gives the operational characterization (the *open passthrough*), which refines Definition 2 with designation.

Relation to capabilities. Capabilities solve the spatial question, and they do more: by fusing designation and authority in the act of invocation, a capability binds authority to a single causal step. In our terms this is *single-hop continuity* — a Proof-of-Relationship. The classical confused deputy is thereby ruled out by capabilities, not merely reduced. What *capability-as-possession* lacks — a held capability applied without occurrence binding — is the extension of that binding across a chain: it may still be exercised outside the lineage that requested it, and in that use falls into lineage-invariant possession. Proof-of-Continuity is exactly this extension, the transitive composition of the single-hop binding across the whole execution. Capability invocation can be viewed as a one-hop instance of the continuity discipline; PIC generalizes this discipline across multi-hop execution. The temporal dimension is not an optional stronger check: it is a dimension that possession alone cannot encode.

5.3 Projection: Lineage-Invariant Possession Cannot Individuate Occurrences

We make the projection precise. An *event* is an occurrence exercising a privilege within a lineage,

$$e = (o, r, \ell) \in E := O \times R \times \mathcal{L},$$

and $p : E \rightarrow O \times R$, $p(o, r, \ell) = (o, r)$, is the projection that forgets the lineage.

Definition 6 (Possession policy). *An authorization policy $A : E \rightarrow \{0, 1\}$ is possession-based iff it is invariant under lineage: it factors through p , i.e. there exists $\bar{A} : O \times R \rightarrow \{0, 1\}$ with $A = \bar{A} \circ p$. Equivalently, $A(o, r, \ell) = A(o, r, \ell')$ for all $\ell, \ell' \in \mathcal{L}$.*

Theorem 3 (Lineage-invariant policies cannot individuate occurrences). *Let $e = (o, r, \ell)$ and $e' = (o, r, \ell')$ be two events with the same privilege but distinct lineage, $p(e) = p(e')$ and $\ell \neq \ell'$. Then every possession-based policy satisfies $A(e) = A(e')$.*

Proof. $A = \bar{A} \circ p$ and $p(e) = p(e')$, hence $A(e) = \bar{A}(p(e)) = \bar{A}(p(e')) = A(e')$.

The confused deputy and the replay are two instances of the same forbidden pair: events sharing (o, r) but differing in lineage, one of which must be authorized and the other denied. In the confused deputy one lineage originates from a context holding (o, r) and the other does not; in a replay one lineage continues an authorizing request and the other continues none. By the theorem, *no* lineage-invariant possession-based policy can separate them.

Theorem 4 (Any resolution reintroduces continuity). *A policy A authorizes e and denies e' , with $p(e) = p(e')$ and $\ell \neq \ell'$, only if A is not lineage-invariant; that is, A must read some function $g : \mathcal{L} \rightarrow X$ of the lineage that is non-constant on the fiber $p^{-1}(o, r)$.*

Proof. If A were lineage-invariant it would factor through p and give $A(e) = A(e')$ by the previous theorem, contradicting $A(e) \neq A(e')$. Hence A depends on the lineage coordinate: some $g(\ell)$ distinguishes e from e' .

Such a g is exactly a continuity mechanism — a proof-of-relationship extract of the lineage. The mitigations deployed within possession-based systems (nonces, idempotency keys, timestamps, audience and context binding) are concrete instances of g : they resolve the confused deputy or the replay only by reintroducing lineage information — that is, continuity — into the decision. Whether the lineage is carried alongside the request or embedded inside the artifact is immaterial: a token that encodes a nonce or a causal context makes A depend on ℓ and is therefore continuity-aware by definition, not possession-based. The distinction is not where the information lives but whether the decision reads it. Possession does not fail for lack of engineering; by the first theorem it is structurally unable to individuate occurrences, and every working fix is lineage-sensitive — continuity-aware — rather than possession-based.

Why the possession model is representative. A bearer token is lineage-invariant by construction: a JWT asserts that “the holder may read,” not the causal chain that led to its use; the decision reads (o, r) and the token’s validity, never ℓ . Such systems often work not because they encode continuity explicitly, but because a perimeter supplies part of it implicitly — mutual TLS, network boundaries, and transport-inferred delegation often stand in for the missing lineage. Once the perimeter dissolves — zero-trust deployments, multi-organisation chains on the public internet, and autonomous AI agents calling tools and services — lineage-invariance becomes visible as a vulnerability at the second hop. The definition of a possession policy above therefore describes deployed systems, not a caricature of them.

6 Safety Property

Definition 7 (Origin-bounded authority). *A model enforces origin-bounded authority if every executable privilege at hop n was originally granted at hop 0.*

We refine Definition 2 to separate legitimate delegation from the confused deputy. The distinguishing variable is not the authority source but whether the action’s target is designated by the request and whether the requester was entitled to bring it about.

Definition 8 (Authority to cause). *The origin context C_0 records the authority the requester is entitled to cause, not only to perform directly. A later action belongs to the requester’s lineage iff it realizes an authority in C_0 ; otherwise it is the deputy’s own action, rooted in a distinct origin (the deputy itself) and unconstrained by C_0 .*

Definition 9 (Open passthrough). *A deputy is an open passthrough when, as a consequence of a request, it applies authority to a target designated by that request for an action the requester was not entitled to cause: $(o, r) \notin C_0$ yet (o, r) executes because of the request. This is exactly the confused deputy.*

These separate three cases. (i) A deputy’s own housekeeping — the compiler writing its statistics file — is rooted in the deputy as origin and is unconstrained by C_0 . (ii) Legitimate delegation — a payment gateway moving funds because the user was entitled to cause the payment — realizes an authority in C_0 and is a valid continuation, even though the user does not directly hold the banking authority. (iii) The confused deputy — writing a user-designated file the user could not cause — is an open passthrough, the

one case the model forbids. The relevant question is not whether the origin could perform the downstream operation directly, but whether the origin was authorized to *cause* it within this lineage. When successive services use different operation spaces, this is mediated by the policy translation $\mathcal{T}$ introduced above, whose synthesis and verification are left to future work.

Example. If $C_0 = \{(\text{convert}, r)\}$, then (write, r) can never be authorized within the same execution chain: $(\text{write}, r) \notin C_0$ and $C_{i+1} \subseteq C_i$ at every transition, so $(\text{write}, r) \notin C_n$.

7 Impossibility of the Confused Deputy

The confused deputy condition requires an authority mismatch: a privilege absent from the authority context of the request is nevertheless exercised as a consequence of that request.

This is the paper’s second impossibility result. Section 5.3 shows that possession *cannot* individuate occurrences; here we show the dual: under continuity the confused deputy is *not a state the model can represent*. The condition is unsatisfiable within any valid PIC execution — an impossibility by construction, at the level of valid model behavior.

Theorem 5 (Confused deputy is impossible under PIC). *In any system satisfying PIC monotonicity $C_{i+1} \subseteq C_i$ and origin-bounded authority $C_n \subseteq C_0$, the confused deputy conditions cannot be jointly satisfied as valid behavior within the model.*

Proof. The confused deputy condition requires:

$$(o, r) \notin C_0 \quad \text{and} \quad (o, r) \in C_k \text{ for some } k > 0.$$

But PIC enforces:

$$C_k \subseteq C_0 \quad \forall k.$$

Thus if $(o, r) \notin C_0$, it cannot appear in any C_k . The privilege mismatch required for a confused deputy is impossible within a valid PIC execution.

Interpretation. Authority in PIC is not something that a subject merely *has*; it is a continuity property of the execution chain. Since no hop may introduce or reinterpret authority absent at the origin, a confused-deputy execution may still be attempted physically, but it cannot be accepted as valid behavior within the PIC model.

8 Discussion

PoP systems conflate authority and possession, enabling authority mixing across execution contexts. PIC/PoC systems instead propagate only non-expansive subsets of authority along a causally verified execution chain.

Proof of Possession proves artifact control. Proof of Relationship proves execution relationship. Proof of Continuity proves authority continuation.

Design space. The temporal binding may be realized in two ways: embedded *inside* the authority itself, as attenuated and context-bound capabilities, or maintained *alongside* it as an explicit continuity proof. PIC takes the latter position, treating continuity as a first-class property of the execution chain; the two approaches are complementary rather than exclusive.

The resulting security invariant is simple: no downstream service can perform, as part of a valid execution chain, an operation that was not authorized at the origin.

Application to AI agents. For the purposes of authority propagation, AI agents can be modeled as autonomous distributed systems; we name them explicitly because the temporal gap is most acute there, but the model treats them as a special case of distributed execution. An agent executes a chain of steps — planning, tool invocations, and calls to downstream services — while holding multiple authority sources at once: its own service credentials, delegated user tokens, and per-tool scopes. The classical local-filename designation reappears as an agent-influenced parameter: a tenant id, document id, role ARN, queue message, cache key, or downstream request target. When the caller can influence this target and the agent satisfies it using authority from a different context, the result is the distributed analogue of the confused deputy. PIC binds each tool call and downstream request to the causal lineage of the request that triggered it, so an agent cannot apply authority that does not belong to the execution that caused the action. For example, an agent asked to summarize a document that contains an indirect prompt injection — one instructing it to delete files, exfiltrate secrets, or invoke an administrative API — may attempt those actions; under PoC they are valid only if the origin authority context contains the corresponding privileges. If the origin authorizes only $(\text{summarize}, d)$, then (delete, r) or $(\text{exfiltrate}, r)$ cannot be valid continuations of that request.

Related Work

The confused deputy problem was introduced by Hardy [1]. Capability-based access control [2] and the analysis of the confused deputy under capabilities [3] address the spatial dimension of authority — whether an actor holds authority over an object. This paper isolates the orthogonal temporal dimension: whether the authority used belongs to the execution that caused the action. It focuses narrowly on the confused deputy as a mismatch between authority and causality, and compares possession-based authority propagation with provenance-continuity-based authority propagation.

The closest prior work is history-based access control [4], where the authority available to a computation depends on the history of what has executed. We share the premise that authority is a function of execution rather than of static possession. Unlike a retrospective check over past callers (as in stack inspection), PoC is a forward propagation discipline: each hop must be causally related to its predecessor and must not expand the authority it received, including across asynchronous and cross-boundary steps. The contribution here is orthogonal and more specific: we frame the dependence as a *dimension* $\mathcal{L}$ orthogonal to the privilege (o, r) , prove that possession (any policy invariant under $\mathcal{L}$) cannot individuate occurrences, and show that the confused deputy and the replay are the same collision under the projection that forgets $\mathcal{L}$ — so that possession-based mitigations that distinguish such cases must become lineage-sensitive, hence continuity-aware. The object-capability literature [5] analyses the confused deputy as a separation of designation from authority, which capabilities reunify; this is the spatial resolution. Our impossibility result adds the temporal axis: even a correctly designated capability, treated as possession, cannot separate two occurrences that differ only in lineage.

Bearer tokens, macaroons, and proof-of-possession bindings. The OAuth 2.0 framework [6, 7] issues bearer tokens whose authorization decision reads the token and (o, r) , never the lineage: they are lineage-invariant, and thus subject to the first theorem. Macaroons [8] add *caveats* that only attenuate and chain them cryptographically — precisely our monotone attenuation $C_{i+1} \preceq C_i$ along a chain — yet a macaroon remains a bearer credential: absent a caveat that binds the request context, it can be presented outside the lineage that produced it. DPoP [9] and Token Binding [10] bind a token to a key or transport channel, which is exactly a function g of the occurrence in the sense of Theorem 4. The unifying observation is that these mechanisms defeat replay or cross-context misuse precisely to the

extent that a caveat or binding makes the decision read ℓ — that is, they reintroduce continuity. They are therefore continuity-aware mechanisms in the sense of this model — reading the lineage coordinate at a single hop or through context binding — rather than purely lineage-invariant possession mechanisms; PIC makes the same lineage dimension global and explicit. Such mechanisms strengthen possession but do not by themselves establish global continuity.

The PIC model is developed independently in [11], where Provenance Identity Continuity is introduced as a general model for distributed execution systems. The present paper extends an earlier version [12], refining it with the relationship/continuity distinction and the spatial/temporal analysis of authority.

9 Limitations and Future Work

This paper presents a minimal linear model of Proof-of-Continuity; several issues are intentionally left outside its scope. First, revocation is not treated as a retroactive operation on an already issued lineage: a practical system must decide whether revocation blocks only future transitions, invalidates outstanding continuations, or triggers lineage-wide cancellation. Second, the model is linear; forks, joins, fan-out, fan-in, and DAG-shaped executions require a partial-order generalization of $\mathcal{L}$. Third, the construction of *PoR* is abstract: concrete implementations may use signatures, hash chains, verifiable credentials, secure channels, trusted execution environments, or tamper-evident logs, with implementation-dependent security and performance. Fourth, naive lineage validation may cost work proportional to chain length; checkpoints, summarized proofs, or accumulator-style constructions can reduce it. Finally, heterogeneous systems require policy translations $\mathcal{T}$ between local vocabularies, whose synthesis, verification, and governance we leave to future work.

10 Conclusion

This paper introduced Proof-of-Continuity as a minimal temporal model for authority propagation. The core distinction is between possession, which proves control over an authority artifact; relationship, which proves causal linkage between adjacent execution steps; and continuity, which proves that authority has propagated without expansion across the whole lineage. The main result is that lineage-invariant possession cannot distinguish occur-

rences that share the same privilege but arise from different causes; conversely, under Proof-of-Continuity a privilege absent from the origin authority context cannot appear later in the same valid execution chain. The confused deputy condition is therefore not accepted as valid model behavior — it is precisely the authority/causality mismatch that continuity rules out.

Acknowledgments

Automated language-assistance tools were used only to speed up drafting and to improve the fluency of the writing; the ideas, design, and formulation originate entirely with the author, and these tools contributed no conceptual content.

References

- [1] N. Hardy. The Confused Deputy: Or Why Capabilities Might Have Been Invented. *ACM SIGOPS Operating Systems Review*, 22(4):36–38, 1988.
- [2] J. B. Dennis and E. C. Van Horn. Programming Semantics for Multiprogrammed Computations. *Communications of the ACM*, 9(3):143–155, 1966.
- [3] M. S. Miller, K.-P. Yee, and J. S. Shapiro. Capability Myths Demolished. Technical Report SRL2003-02, Systems Research Laboratory, Johns Hopkins University, 2003.
- [4] M. Abadi and C. Fournet. Access Control Based on Execution History. In *Proceedings of the Network and Distributed System Security Symposium (NDSS)*, 2003.
- [5] M. S. Miller. Robust Composition: Towards a Unified Approach to Access Control and Concurrency Control. PhD thesis, Johns Hopkins University, Baltimore, MD, USA, 2006.
- [6] D. Hardt, editor. The OAuth 2.0 Authorization Framework. RFC 6749, Internet Engineering Task Force, October 2012.
- [7] M. Jones and D. Hardt. The OAuth 2.0 Authorization Framework: Bearer Token Usage. RFC 6750, Internet Engineering Task Force, October 2012.

- [8] A. Birgisson, J. G. Politz, Ú. Erlingsson, A. Taly, M. Vrabie, and M. Lentczner. Macaroons: Cookies with Contextual Caveats for Decentralized Authorization in the Cloud. In *Proceedings of the Network and Distributed System Security Symposium (NDSS)*, 2014.
- [9] D. Fett, B. Campbell, J. Bradley, T. Lodderstedt, M. B. Jones, and D. Waite. OAuth 2.0 Demonstrating Proof of Possession (DPoP). RFC 9449, Internet Engineering Task Force, September 2023.
- [10] A. Popov, M. Nyström, D. Balfanz, and J. Hodges. The Token Binding Protocol Version 1.0. RFC 8471, Internet Engineering Task Force, October 2018.
- [11] N. Gallo. PIC Model — Provenance Identity Continuity for Distributed Execution Systems. Zenodo, 2025. <https://zenodo.org/records/17777421>.
- [12] N. Gallo. Authority Propagation Models: PoP vs PoC and the Confused Deputy Problem. Zenodo, 2025. <https://doi.org/10.5281/zenodo.17833000>.