

CAHP-1.5HP

Features

- Unique heat exchanger design, heat pump water temperature to 65°C
- Energy saving, fast heating, electric back up and standard modes for choosing
- Smart control to avoid cold water mixing
- LCD display
- R134a green refrigerant
- Integrate design for outdoor installation
- Available in 300 & 450 Litre storage

Wired Remote Control

Convenience to access your water heater with Wired Touch Control.



- Two Operation Mode could be set by controller.
High Demand Mode:
Water heater uses heat pump and electric heating when the working condition is in heat pump operation range, otherwise water heater only uses electric heating.
Efficiency Mode:
Water heater only uses heat pump heating when the working condition is in heat pump operation range, otherwise water heater changes to electric heating automatically.
- Display current status and error information.
- Circulation pump control mode.
Smart Mode:
According to water temperature, ambient temperature and other conditions, calculate automatically to control water pump running hour and interval hour, save electricity intelligently.
Fixed Mode:
Manual input water pump running hour and interval hour.
- LCD Display Panel
- Children lock can prevent child from changing water heater settings.
- 2 section timing heating.

Technical Specification

Model			CAHP1.5DI-80-6-W	CAHP1.5DI-120-6-W	CAHP1.5DI-120-12-W
Model Type		/	Outdoor integrated heat pump water heater		
HP rated input power		W	875		
HP Rated heating capacity		W	3680		
COP		W/W	4.2		
Electrical heating element		W	6000	6000	12000
Maximum Operation	400V / 3N / 50Hz	A	/	/	37.5
Current	230V / 1N / 50Hz	A	38.7	38.7	71.9
Refrigerant		/	R134a		
Refrigerant charge quantity		g	940		
Tank capacity		L	300	455	455
Net Weight		Kg	161	194	194
Operation Weight		Kg	461	649	649
Water Temp in efficiency mode		°C	65		
Water temperature range		°C	37~75		
Ambient temperature range		°C	-7~43		
Max Noise		dB (A)	58		
Compressor		dB	Rotary type		
Demison (LxWxH) mm		dB (A)	910x610x1700	1012x713x1700	1012x713x1700
Anode		/	Aluminum Rod		
Control Mode		/	Led wire Display (Standard 10m, Optional Maxium 30 m)		
Operation Mode		/	Efficiency, High Demand, Standard		
Other Control Functions		/	Timer, Fault Alarming, Water pump controlling, AES HP		
Power Supply Specifications		/	230V~50Hz	230V~50Hz	400V 3N~50Hz
Connection Size ~ Inlet / Outlet / T&P Valve		/	NPT 3/4 (Female Thread)		

