

HPI Series

Features

- Heat pump water temperature 55°C,
Max water temperature 75°C
- Heat pump input 460w, COP 3.8
- Two elements back up for quick recovery
- Patented AES energy saving system
- Timer setting
- Remote control
- PS safety system
- R134a Green refrigerant

Technical Specification

Model name	Unit	HPI-40C1.0AE	HPI-50C1.0AE
Rated volume	L	150	180
Voltage/Frequency	V/Hz	220V/50Hz	220V/50Hz
Rated power input	W	470	470
Rated heating capacity	W	1800	1800
COP		3.8	3.8
Refrigerant		R134a	R134a
Heating element	W	3000	3000
Max. current of quick heating	A	13.6	13.6
Out put water temperature range	°C	35~75°C	35~75°C
Ambient temperature range	°C	-7~43°C	-7~43°C
Max. Tank operating pressure	Bar	10	10
Max. Operation noise	dB	40	40
Compressor type		Rotary	Rotary
Product dimensions (Height)	mm	1660	1850
Product dimensions (Diameter)	mm	520	520
Net weight	Kg	87	92
Water connection size		NPT3/4	NPT3/4



Energy Saving Heating:

The New generation water heater extracting heat from the atmosphere and using it for heating water.

Max:

MAX function for more hot water output, therefore better bathing experience.

AES (adaptive energy-saving system):

AES feature adopts heating cycle automatically, which will facilitate water usage and save energy by minimizing thermal loss.

Hot water amount display:

Indicates the amount of hot water available in the tank.

Intelligent defrosting:

The automatic intelligent defrost function solves the problems like freezing of exchanger, frosting and resumes the system to operate efficiently.

Wired remote controller:

The controller and the unit are to be installed separately for clear view sight and convenient operation.

Glass-lined special protective tank:

Patented glass-lined protection by A. O. Smith for better tank life.

Anode rod protection:

A powerful steel-core-anode rod to protect tank and prolonged service life of the heat pump water heater.

High efficiency Energy Saving Insulation:

A polyurethane foam insulating layer reduces heat loss effectively.

Wired Touch Control

Convenience to access your water heater with Wired Touch Control.



- 1 Power ON/OFF button:**
Press Power ON/OFF button, the heater will be power-on. Setting temp and actual temp will be displayed a few seconds later.
- 2 Instant Heating button:**
Users can select instant heating by pressing this button at all times and the water heater starts electrical heating immediately to reach the preset temperature. The heating is just one time.
- 3 Increase/Decrease button:**
Press the Increase/Decrease button again to make the preset temperature increase or decrease by 1. And adjusting clock, timer also.
- 4 Program button:**
Program is to set up clock, and timing for heating. Two timers is available.
- 5 AES button:**
AES feature adopts heating cycles automatically, which will facilitate water usage and save energy by minimizing thermal loss.
- 6 Mode button:**
Change mode of Efficiency or Hybrid Turbo by touch Mode button.
- 7 Indicators:**
This indicates the water heater is working in which mode, AES, timer, etc.,
- 8 Digital Indicators:**
This indicates the water heater is working temperature, clock, timer setting, etc.,
- 9 Heating Indicator:**
Indicator glows when the heating is in progress.
- 10 Display of hot water:**
Five lighting blocks display the hot water distribution of different levels in the water tank of the water heater.
- 11 Circulation Pump:**
Controls the building Re-circulation pump (sold separately)

