Player Ratings App — Setup & Deployment Guide

How It Works

- **Public view** → `yoursite.vercel.app` — parents/learners see cards (view-only)
- **Admin view** → `yoursite.vercel.app/admin/your-secret-key` — coaches can add, edit, delete players
- **Firebase** stores all data — changes by coaches appear instantly for everyone

---

STEP 1: Set Up Firebase (5 minutes)

1. Go to https://console.firebase.google.com
2. Click **"Create a project"** → name it `player-ratings` → click Continue
3. Disable Google Analytics (not needed) → click **Create Project**
4. Once created, click the **web icon** `</>` to add a web app
5. Name it `player-ratings-web` → click **Register app**
6. You'll see a config block like this — **copy it and save it**:

```
apiKey: "AIzaSy...",
authDomain: "player-ratings-XXXXX.firebaseapp.com",
projectId: "player-ratings-XXXXX",
storageBucket: "player-ratings-XXXXX.appspot.com",
messagingSenderId: "123456789",
appId: "1:123456789:web:abcdef"
```

7. In the left sidebar, click **Build** → **Firestore Database**
8. Click **Create database** → select **Start in test mode** → pick a location → click **Enable**

> **Important:** Test mode allows open access for 30 days. After launch, update Firestore rules (see Step 5).

STEP 2: Create the Project (10 minutes)

Open your terminal and run these commands:

```bash
npm create vite@latest player-ratings -- --template react
cd player-ratings
npm install firebase react-router-dom
```

Now **delete everything inside** `src/` and create these files:

File: `src/main.jsx`

```jsx
import React from 'react'
import ReactDOM from 'react-dom/client'
import { BrowserRouter } from 'react-router-dom'
import App from './App'

ReactDOM.createRoot(document.getElementById('root')).render(
  <React.StrictMode>
    <BrowserRouter>
      <App />
    </BrowserRouter>
  </React.StrictMode>
)
```

File: `src/App.jsx`

```jsx
import { Routes, Route } from 'react-router-dom'
import PublicView from './pages/PublicView'
import AdminView from './pages/AdminView'

export default function App() {
  return (
    <Routes>
      <Route path="/" element={<PublicView />} />
      <Route path="/admin/:secretKey" element={<AdminView />} />
    </Routes>
  )
}
```

File: `src/firebase.js`

```js
import { initializeApp } from 'firebase/app'
import { getFirestore, collection, getDocs, doc, setDoc, deleteDoc, onSnapshot } from 'firebase/firestore'

// 🔥 PASTE YOUR FIREBASE CONFIG HERE
const firebaseConfig = {
  apiKey: "YOUR_API_KEY",
  authDomain: "YOUR_PROJECT.firebaseapp.com",
  projectId: "YOUR_PROJECT_ID",
  storageBucket: "YOUR_PROJECT.appspot.com",
  messagingSenderId: "YOUR_SENDER_ID",
  appId: "YOUR_APP_ID"
}

const app = initializeApp(firebaseConfig)
const db = getFirestore(app)
const playersRef = collection(db, 'players')

// 🔑 SET YOUR SECRET ADMIN KEY HERE
export const ADMIN_SECRET = 'coach2024secret'

export async function savePlayer(player) {
  await setDoc(doc(db, 'players', player.id), player)
}

export async function removePlayer(id) {
  await deleteDoc(doc(db, 'players', id))
}

export function subscribePlayers(callback) {
  return onSnapshot(playersRef, (snapshot) => {
    const players = snapshot.docs.map(d => ({ id: d.id, ...d.data() }))
    callback(players)
  })
}
```

File: `src/utils.js`

js

```js
export const ATTRS = [
  { key: "firstTouch", label: "First Touch", cat: "tec" },
  { key: "dribbling", label: "Dribbling", cat: "tec" },
  { key: "ballProtection", label: "Ball Protection", cat: "tec" },
  { key: "balance", label: "Balance", cat: "tec" },
  { key: "passAccuracy", label: "Passing Accuracy", cat: "pas" },
  { key: "shootingTechnique", label: "Shooting Technique", cat: "att" },
  { key: "weakFoot", label: "Weak Foot", cat: "att" },
  { key: "position", label: "Position", cat: "att" },
  { key: "tackling", label: "Tackling", cat: "def" },
  { key: "speed", label: "Speed", cat: "phy" },
  { key: "agility", label: "Agility", cat: "phy" },
  { key: "strength", label: "Strength", cat: "phy" },
  { key: "stamina", label: "Stamina", cat: "phy" },
  { key: "decisionMaking", label: "Decision Making", cat: "men" },
  { key: "communication", label: "Communication", cat: "men" },
  { key: "workRate", label: "Work Rate", cat: "men" },
  { key: "coachability", label: "Coachability", cat: "men" },
  { key: "discipline", label: "Discipline", cat: "men" },
  { key: "leadershipPotential", label: "Leadership Potential", cat: "men" },
]

export const CAT_FORMULAS = {
  tec: { label: "TEC", full: "Technical", keys: ["firstTouch","dribbling","ballProtection","balance"] },
  pas: { label: "PAS", full: "Passing", keys: ["passAccuracy","firstTouch","decisionMaking"] },
  att: { label: "ATT", full: "Attacking", keys: ["shootingTechnique","weakFoot","position"] },
  phy: { label: "PHY", full: "Physical", keys: ["speed","agility","strength","stamina"] },
  def: { label: "DEF", full: "Defense", keys: ["tackling","ballProtection","strength"] },
  men: { label: "MEN", full: "Mental", keys: ["decisionMaking","communication","workRate","coachability","discipline","lea
}

export const CAT_ORDER = ["tec","pas","att","phy","def","men"]
export const CAT_LABELS = CAT_ORDER.map(c => CAT_FORMULAS[c].label)

export function calcCategories(attrs) {
  const cats = {}
  for (const c of CAT_ORDER) {
    const vals = CAT_FORMULAS[c].keys.map(k => attrs[k] || 0)
    cats[c] = vals.reduce((a, b) => a + b, 0) / vals.length
  }
  return cats
}

export function calcOverall(attrs) {
  const vals = ATTRS.map(a => attrs[a.key] || 0)
  return vals.reduce((a, b) => a + b, 0) / vals.length
}
```

```
export function getRatingColor(v) {
  if (v >= 80) return "#2ecc40"
  if (v >= 70) return "#7bc74d"
  if (v >= 60) return "#e8b930"
  if (v >= 50) return "#e67e22"
  return "#e74c3c"
}

export function getOvrBg(v) {
  if (v >= 75) return "linear-gradient(135deg,#1a6b1a,#2ecc40)"
  if (v >= 65) return "linear-gradient(135deg,#3a7a1a,#7bc74d)"
  if (v >= 55) return "linear-gradient(135deg,#8a6b00,#e8b930)"
  if (v >= 45) return "linear-gradient(135deg,#8a4500,#e67e22)"
  return "linear-gradient(135deg,#8a1a1a,#e74c3c)"
}
```

File: `src/components/RadarChart.jsx`

jsx

```jsx
import { CAT_ORDER, CAT_LABELS } from '../utils'

export default function RadarChart({ cats, size = 200 }) {
  const cx = size/2, cy = size/2, r = size*0.37, n = 6
  const step = (2*Math.PI)/n, start = -Math.PI/2
  const pt = (i, v) => {
    const a = start + i*step, d = (v/100)*r
    return [cx+d*Math.cos(a), cy+d*Math.sin(a)]
  }
  const vals = CAT_ORDER.map(c => cats[c])
  const poly = vals.map((v,i) => pt(i,v).join(",")).join(" ")

  return (
    <svg width={size} height={size} viewBox={`0 0 ${size} ${size}`}>
      {[20,40,60,80,100].map(lv => (
        <polygon key={lv}
          points={Array.from({length:n},(_,i)=>pt(i,lv).join(",")).join(" ")}
          fill="none" stroke="rgba(255,255,255,0.1)" strokeWidth="1"/>
      ))}
      {Array.from({length:n},(_,i)=>{
        const [x,y]=pt(i,100)
        return <line key={i} x1={cx} y1={cy} x2={x} y2={y}
          stroke="rgba(255,255,255,0.07)" strokeWidth="1"/>
      })}
      <polygon points={poly} fill="rgba(46,204,64,0.25)"
        stroke="#2ecc40" strokeWidth="2"/>
      {vals.map((v,i)=>{
        const[x,y]=pt(i,v)
        return <circle key={i} cx={x} cy={y} r="3"
          fill="#2ecc40" stroke="#fff" strokeWidth="1"/>
      })}
      {Array.from({length:n},(_,i)=>{
        const[x,y]=pt(i,115)
        return <text key={i} x={x} y={y} textAnchor="middle"
          dominantBaseline="central" fontSize="9" fontWeight="700"
          fill="rgba(255,255,255,0.6)" fontFamily="system-ui">
          {CAT_LABELS[i]}
        </text>
      })}
    </svg>
  )
}
```

File: `src/components/PlayerCard.jsx`

jsx

```jsx
import RadarChart from './RadarChart'
import { calcCategories, calcOverall, getRatingColor, getOvrBg,
        CAT_ORDER, CAT_LABELS } from '../utils'

export default function PlayerCard({ player, rank, isAdmin, onEdit, onDelete }) {
  const cats = calcCategories(player)
  const ovr = calcOverall(player)

  return (
    <div style={{
      background:"linear-gradient(145deg,#1a1a2e,#16213e,#0f3460)",
      borderRadius:14, width:270, overflow:"hidden",
      boxShadow:"0 6px 24px rgba(0,0,0,0.4)",
      border:"1px solid rgba(255,255,255,0.08)",
      display:"flex", flexDirection:"column", alignItems:"center",
      position:"relative"
    }}>
      {isAdmin && (
        <div style={{position:"absolute",top:8,right:8,display:"flex",gap:4}}>
          <button onClick={()=>onEdit(player)} style={{
            background:"rgba(255,255,255,0.1)", border:"none",
            borderRadius:6, width:28, height:28, cursor:"pointer",
            color:"#fff", fontSize:13, display:"flex",
            alignItems:"center", justifyContent:"center"
          }}>✏️</button>
          <button onClick={()=>onDelete(player.id)} style={{
            background:"rgba(255,60,60,0.15)", border:"none",
            borderRadius:6, width:28, height:28, cursor:"pointer",
            color:"#e74c3c", fontSize:13, display:"flex",
            alignItems:"center", justifyContent:"center"
          }}>✕</button>
        </div>
      )}

      <div style={{
        width:"100%", padding:"14px 16px 8px",
        display:"flex", alignItems:"center", gap:12,
        borderBottom:"1px solid rgba(255,255,255,0.06)"
      }}>
        <div style={{
          width:50, height:50, borderRadius:10, background:getOvrBg(ovr),
          display:"flex", alignItems:"center", justifyContent:"center",
          fontSize:21, fontWeight:800, color:"#fff", fontFamily:"system-ui",
          boxShadow:"0 2px 8px rgba(0,0,0,0.3)", flexShrink:0
        }}>{Math.round(ovr)}</div>
        <div>
          <div style={{color:"#fff",fontSize:17,fontWeight:700,
```

```
        fontFamily:"system-ui"}}>{player.name}</div>
        <div style={{color:"rgba(255,255,255,0.35)",fontSize:10,
        fontWeight:600,fontFamily:"system-ui",letterSpacing:1.5}}>
        #{rank} OVERALL
        </div>
      </div>
    </div>

    <RadarChart cats={cats} size={195}/>

    <div style={{
      width:"100%", padding:"0 14px 12px",
      display:"grid", gridTemplateColumns:"1fr 1fr 1fr", gap:"5px 8px"
    }}>
      {CAT_ORDER.map((c,i)=>(
        <div key={c} style={{display:"flex",alignItems:"center",gap:5}}>
          <span style={{fontSize:15,fontWeight:800,
            color:getRatingColor(cats[c]),fontFamily:"system-ui",
            minWidth:22}}>{Math.round(cats[c])}</span>
          <span style={{fontSize:8,fontWeight:600,
            color:"rgba(255,255,255,0.4)",fontFamily:"system-ui",
            letterSpacing:.8}}>{CAT_LABELS[i]}</span>
        </div>
      ))}
    </div>
  </div>
)
}
```

File: `src/components/Modal.jsx`

jsx

```jsx
import { useState } from 'react'
import { ATTRS, CAT_ORDER, CAT_FORMULAS, calcCategories, calcOverall,
        getRatingColor, getOvrBg } from '../utils'

function AttrSlider({ attr, value, onChange }) {
  const color = getRatingColor(value)
  return (
    <div style={{display:"flex",alignItems:"center",gap:8,padding:"3px 0"}}>
      <span style={{fontSize:11,fontWeight:600,color:"rgba(255,255,255,0.6)",
        fontFamily:"system-ui",width:130,flexShrink:0}}>{attr.label}</span>
      <input type="range" min={0} max={99} value={value}
        onChange={e=>onChange(parseInt(e.target.value))}
        style={{flex:1,accentColor:color,height:4,cursor:"pointer"}}/>
      <input type="number" min={0} max={99} value={value}
        onChange={e=>{
          const v=Math.max(0,Math.min(99,parseInt(e.target.value)||0))
          onChange(v)
        }}
        style={{width:42,background:"rgba(255,255,255,0.08)",
          border:"1px solid rgba(255,255,255,0.15)",borderRadius:6,
          color:color,fontSize:14,fontWeight:700,fontFamily:"system-ui",
          textAlign:"center",padding:"4px 2px",outline:"none"}}/>
    </div>
  )
}

export default function Modal({ player, onSave, onClose, isNew }) {
  const [name, setName] = useState(player?.name || "")
  const [attrs, setAttrs] = useState(() => {
    const a = {}
    ATTRS.forEach(at => a[at.key] = player?.[at.key] ?? 50)
    return a
  })
  const setAttr = (k, v) => setAttrs(prev => ({...prev, [k]: v}))
  const cats = calcCategories(attrs)
  const ovr = calcOverall(attrs)
  const groups = { tec:[], pas:[], att:[], phy:[], def:[], men:[] }
  ATTRS.forEach(a => groups[a.cat].push(a))

  return (
    <div style={{position:"fixed",inset:0,background:"rgba(0,0,0,0.7)",
      backdropFilter:"blur(4px)",display:"flex",alignItems:"center",
      justifyContent:"center",zIndex:999,padding:16}}
      onClick={onClose}>
      <div onClick={e=>e.stopPropagation()} style={{
        background:"linear-gradient(145deg,#1a1a2e,#16213e)",
        borderRadius:16,width:"100%",maxWidth:720,maxHeight:"90vh",
```

```
  overflow:"auto",boxShadow:"0 16px 64px rgba(0,0,0,0.6)",
  border:"1px solid rgba(255,255,255,0.1)"
}}>
  <div style={{padding:"20px 24px 12px",
    borderBottom:"1px solid rgba(255,255,255,0.08)",
    display:"flex",alignItems:"center",justifyContent:"space-between",
    flexWrap:"wrap",gap:12
  }}>
    <div style={{display:"flex",alignItems:"center",gap:14}}>
      <div style={{width:48,height:48,borderRadius:10,
        background:getOvrBg(ovr),display:"flex",alignItems:"center",
        justifyContent:"center",fontSize:20,fontWeight:800,
        color:"#fff",fontFamily:"system-ui"}}>{Math.round(ovr)}</div>
      <div>
        <div style={{color:"rgba(255,255,255,0.4)",fontSize:10,
          fontWeight:600,letterSpacing:1,marginBottom:4}}>
          {isNew?"ADD NEW LEARNER":"EDIT LEARNER"}
        </div>
        <input value={name} onChange={e=>setName(e.target.value)}
          placeholder="Player name..."
          style={{background:"rgba(255,255,255,0.06)",
            border:"1px solid rgba(255,255,255,0.15)",borderRadius:8,
            padding:"8px 12px",color:"#fff",fontSize:16,fontWeight:700,
            fontFamily:"system-ui",outline:"none",width:200}}/>
      </div>
    </div>
    <div style={{display:"flex",gap:8}}>
      <button onClick={onClose} style={{
        background:"rgba(255,255,255,0.08)",
        border:"1px solid rgba(255,255,255,0.12)",borderRadius:8,
        padding:"8px 16px",color:"rgba(255,255,255,0.6)",
        fontSize:13,fontWeight:600,cursor:"pointer"
      }}>Cancel</button>
      <button onClick={()=>{
        if(!name.trim()) return
        onSave({...player,...attrs,name:name.trim(),
          id: player?.id || Date.now().toString()})
      }} style={{
        background:"linear-gradient(135deg,#1a6b1a,#2ecc40)",
        border:"none",borderRadius:8,padding:"8px 20px",
        color:"#fff",fontSize:13,fontWeight:700,cursor:"pointer",
        opacity:name.trim()?1:0.4
      }}>{isNew?"Add Learner":"Save Changes"}</button>
    </div>
  </div>

  <div style={{padding:"12px 24px 8px",display:"flex",
    flexWrap:"wrap",gap:8,
    borderBottom:"1px solid rgba(255,255,255,0.06)"}}>
    {CAT_ORDER.map(c=>(
```

```
          <div key={c} style={{background:"rgba(255,255,255,0.04)",
            borderRadius:8,padding:"6px 12px",display:"flex",
            alignItems:"center",gap:6}}>
            <span style={{fontSize:15,fontWeight:800,
              color:getRatingColor(cats[c])}}>{Math.round(cats[c])}</span>
            <span style={{fontSize:9,fontWeight:600,
              color:"rgba(255,255,255,0.4)",letterSpacing:.5}}>
              {CAT_FORMULAS[c].full}
            </span>
          </div>
        ))}
      </div>

      <div style={{padding:"16px 24px 20px",display:"grid",
        gridTemplateColumns:"repeat(auto-fit,minmax(300px,1fr))",
        gap:"12px 32px"}}>
        {CAT_ORDER.map(c=>(
          <div key={c}>
            <div style={{fontSize:10,fontWeight:700,
              color:getRatingColor(cats[c]),letterSpacing:1.5,
              marginBottom:6,display:"flex",alignItems:"center",gap:6}}>
              <span style={{background:"rgba(255,255,255,0.06)",
                borderRadius:4,padding:"2px 6px"}}>
                {CAT_FORMULAS[c].full.toUpperCase()}
              </span>
              <span style={{color:"rgba(255,255,255,0.3)}}>
                {Math.round(cats[c])}
              </span>
            </div>
            {groups[c].map(a=>(
              <AttrSlider key={a.key} attr={a} value={attrs[a.key]}
                onChange={v=>setAttr(a.key,v)}/>
            ))}
          </div>
        ))}
      </div>
    </div>
  </div>
)
}
```

File: `src/pages/PublicView.jsx`

jsx

```jsx
import { useState, useEffect, useMemo } from 'react'
import { subscribePlayers } from '../firebase'
import { calcOverall, calcCategories, CAT_ORDER, CAT_LABELS } from '../utils'
import PlayerCard from '../components/PlayerCard'

export default function PublicView() {
  const [players, setPlayers] = useState([])
  const [sortBy, setSortBy] = useState("total")
  const [search, setSearch] = useState("")
  const [loading, setLoading] = useState(true)

  useEffect(() => {
    const unsub = subscribePlayers((data) => {
      setPlayers(data)
      setLoading(false)
    })
    return () => unsub()
  }, [])

  const enriched = useMemo(() =>
    players.map(p => ({...p, cats: calcCategories(p), total: calcOverall(p)}))
  , [players])

  const ranks = useMemo(() => {
    const s = [...enriched].sort((a,b)=>b.total-a.total)
    const m = {}
    s.forEach((p,i)=>m[p.id]=i+1)
    return m
  }, [enriched])

  const sorted = useMemo(() => {
    let list = [...enriched]
    if (search) list = list.filter(p =>
      p.name.toLowerCase().includes(search.toLowerCase()))
    if (sortBy==="total") list.sort((a,b)=>b.total-a.total)
    else list.sort((a,b)=>(b.cats[sortBy]||0)-(a.cats[sortBy]||0))
    return list
  }, [enriched, sortBy, search])

  return (
    <div style={{minHeight:"100vh",background:"#0a0a1a",
      padding:"20px 12px",fontFamily:"system-ui"}}>
      <div style={{maxWidth:1280,margin:"0 auto"}}>
        <h1 style={{color:"#fff",fontSize:26,fontWeight:800,
          textAlign:"center",margin:"0 0 2px",letterSpacing:1}}>
          PLAYER RATINGS
        </h1>
```

```
      <p style={{color:"rgba(255,255,255,0.3)",fontSize:11,
        textAlign:"center",margin:"0 0 18px",letterSpacing:2}}>
        {players.length} LEARNERS
      </p>

      <div style={{display:"flex",justifyContent:"center",gap:6,
        flexWrap:"wrap",marginBottom:20,alignItems:"center"}}>
        <input type="text" placeholder="Search..." value={search}
          onChange={e=>setSearch(e.target.value)}
          style={{background:"rgba(255,255,255,0.06)",
            border:"1px solid rgba(255,255,255,0.1)",borderRadius:8,
            padding:"7px 12px",color:"#fff",fontSize:12,outline:"none",
            width:140}}/>
        {[{key:"total",label:"OVR"},
          ...CAT_ORDER.map((c,i)=>({key:c,label:CAT_LABELS[i]}))
        ].map(o=>(
          <button key={o.key} onClick={()=>setSortBy(o.key)}
            style={{
              background:sortBy===o.key
                ?"rgba(46,204,64,0.2)":"rgba(255,255,255,0.06)",
              border:sortBy===o.key
                ?"1px solid #2ecc40":"1px solid rgba(255,255,255,0.1)",
              borderRadius:8,padding:"6px 12px",
              color:sortBy===o.key?"#2ecc40":"rgba(255,255,255,0.5)",
              fontSize:10,fontWeight:700,cursor:"pointer",letterSpacing:.8
            }}>{o.label}</button>
        ))}
      </div>

      {loading ? (
        <p style={{color:"rgba(255,255,255,0.4)",textAlign:"center",
          marginTop:60}}>Loading players...</p>
      ) : (
        <div style={{display:"flex",flexWrap:"wrap",gap:18,
          justifyContent:"center"}}>
          {sorted.map(p=>(
            <PlayerCard key={p.id} player={p} rank={ranks[p.id]}
              isAdmin={false}/>
          ))}
          {sorted.length===0 &&
            <p style={{color:"rgba(255,255,255,0.3)"}}>
              No learners found.
            </p>
          }
        </div>
      )}
    </div>
  </div>
)
}
```

File: src/pages/AdminView.jsx

jsx

```jsx
import { useState, useEffect, useMemo, useCallback } from 'react'
import { useParams, Navigate } from 'react-router-dom'
import { subscribePlayers, savePlayer, removePlayer, ADMIN_SECRET } from '../firebase'
import { calcOverall, calcCategories, CAT_ORDER, CAT_LABELS } from '../utils'
import PlayerCard from '../components/PlayerCard'
import Modal from '../components/Modal'

export default function AdminView() {
  const { secretKey } = useParams()
  const [players, setPlayers] = useState([])
  const [sortBy, setSortBy] = useState("total")
  const [search, setSearch] = useState("")
  const [modal, setModal] = useState(null)
  const [loading, setLoading] = useState(true)

  // If key doesn't match, redirect to public view
  if (secretKey !== ADMIN_SECRET) return <Navigate to="/" replace />

  useEffect(() => {
    const unsub = subscribePlayers((data) => {
      setPlayers(data)
      setLoading(false)
    })
    return () => unsub()
  }, [])

  const enriched = useMemo(() =>
    players.map(p => ({...p, cats: calcCategories(p), total: calcOverall(p)}))
  , [players])

  const ranks = useMemo(() => {
    const s = [...enriched].sort((a,b)=>b.total-a.total)
    const m = {}
    s.forEach((p,i)=>m[p.id]=i+1)
    return m
  }, [enriched])

  const sorted = useMemo(() => {
    let list = [...enriched]
    if (search) list = list.filter(p =>
      p.name.toLowerCase().includes(search.toLowerCase()))
    if (sortBy==="total") list.sort((a,b)=>b.total-a.total)
    else list.sort((a,b)=>(b.cats[sortBy]||0)-(a.cats[sortBy]||0))
    return list
  }, [enriched, sortBy, search])

  const handleSave = useCallback(async (p) => {
```

```
  await savePlayer(p)
  setModal(null)
}, [])

const handleDelete = useCallback(async (id) => {
  if (!confirm("Remove this learner?")) return
  await removePlayer(id)
}, [])

return (
  <div style={{minHeight:"100vh",background:"#0a0a1a",
    padding:"20px 12px",fontFamily:"system-ui"}}>
    <div style={{maxWidth:1280,margin:"0 auto"}}>
      <div style={{display:"flex",alignItems:"center",
        justifyContent:"center",gap:8,marginBottom:2}}>
        <h1 style={{color:"#fff",fontSize:26,fontWeight:800,
          textAlign:"center",margin:0,letterSpacing:1}}>
          PLAYER RATINGS
        </h1>
        <span style={{background:"rgba(46,204,64,0.15)",
          color:"#2ecc40",fontSize:9,fontWeight:700,
          padding:"3px 8px",borderRadius:6,letterSpacing:1}}>
          ADMIN
        </span>
      </div>
      <p style={{color:"rgba(255,255,255,0.3)",fontSize:11,
        textAlign:"center",margin:"0 0 18px",letterSpacing:2}}>
        {players.length} LEARNERS • EDIT MODE
      </p>

      <div style={{display:"flex",justifyContent:"center",gap:6,
        flexWrap:"wrap",marginBottom:20,alignItems:"center"}}>
        <input type="text" placeholder="Search..." value={search}
          onChange={e=>setSearch(e.target.value)}
          style={{background:"rgba(255,255,255,0.06)",
            border:"1px solid rgba(255,255,255,0.1)",borderRadius:8,
            padding:"7px 12px",color:"#fff",fontSize:12,outline:"none",
            width:140}}/>
        {[{key:"total",label:"OVR"},
          ...CAT_ORDER.map((c,i)=>({key:c,label:CAT_LABELS[i]}))
        ].map(o=>(
          <button key={o.key} onClick={()=>setSortBy(o.key)}
            style={{
              background:sortBy===o.key
                ?"rgba(46,204,64,0.2)":"rgba(255,255,255,0.06)",
              border:sortBy===o.key
                ?"1px solid #2ecc40":"1px solid rgba(255,255,255,0.1)",
              borderRadius:8,padding:"6px 12px",
              color:sortBy===o.key?"#2ecc40":"rgba(255,255,255,0.5)",
              fontSize:10,fontWeight:700,cursor:"pointer",letterSpacing:.8
```

```
          }}>{o.label}</button>
        ))}
        <button onClick={()=>setModal({isNew:true,player:null})}
          style={{background:"linear-gradient(135deg,#1a6b1a,#2ecc40)",
            border:"none",borderRadius:8,padding:"7px 16px",color:"#fff",
            fontSize:11,fontWeight:700,cursor:"pointer",letterSpacing:.5,
            marginLeft:4}}>
          + ADD LEARNER
        </button>
      </div>

      {loading ? (
        <p style={{color:"rgba(255,255,255,0.4)",textAlign:"center",
          marginTop:60}}>Loading players...</p>
      ) : (
        <div style={{display:"flex",flexWrap:"wrap",gap:18,
          justifyContent:"center"}}>
          {sorted.map(p=>(
            <PlayerCard key={p.id} player={p} rank={ranks[p.id]}
              isAdmin={true} onEdit={pl=>setModal({isNew:false,player:pl})}
              onDelete={handleDelete}/>
          ))}
          {sorted.length===0 &&
            <p style={{color:"rgba(255,255,255,0.3)"}}>
              No learners found.
            </p>
          }
        </div>
      )}
    </div>
    {modal && <Modal player={modal.player} isNew={modal.isNew}
      onSave={handleSave} onClose={()=>setModal(null)}/>}
  </div>
)
}
```

File: index.html (replace the default one)

```html
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Player Ratings</title>
    <style>
      * { margin: 0; padding: 0; box-sizing: border-box; }
      body { background: #0a0a1a; }
    </style>
  </head>
  <body>
    <div id="root"></div>
    <script type="module" src="/src/main.jsx"></script>
  </body>
</html>
```

STEP 3: Configure Your Secrets

Open `src/firebase.js` and:

1. **Paste your Firebase config** (from Step 1) replacing the placeholder
2. **Change the admin secret key** — replace `coach2024secret` with your own secret phrase (no spaces, e.g., `myteam2024admin`)

STEP 4: Deploy to Vercel (5 minutes)

First, push to GitHub:

```bash
# In the project folder
git init
git add .
git commit -m "Initial commit"
```

Go to github.com/new, create a new repo called `player-ratings` (private recommended), then:

```bash
git remote add origin https://github.com/YOUR_USERNAME/player-ratings.git
git branch -M main
git push -u origin main
```

Then deploy on Vercel:

1. Go to vercel.com → Sign up with GitHub
2. Click **"Add New Project"** → Import your `player-ratings` repo
3. Framework: **Vite** (should auto-detect)
4. Click **Deploy**
5. Wait ~60 seconds — you'll get a URL like `player-ratings-abc.vercel.app`

Share these links:

Who	Link
Parents & Learners	`https://player-ratings-abc.vercel.app`
Coaches (admin)	`https://player-ratings-abc.vercel.app/admin/coach2024secret`

STEP 5: Secure Firebase (do this after testing)

Go back to Firebase Console → Firestore → **Rules** tab, and replace with:

```
rules_version = '2';
service cloud.firestore {
  match /databases/{database}/documents {
    match /players/{playerId} {
      allow read: if true;
      allow write: if true;
    }
  }
}
```

> This keeps it open for now. For tighter security later, you can add Firebase Auth and restrict writes to authenticated coaches only.

STEP 6: Load Your Existing Players

The first time you visit the admin URL, the database will be empty. You'll need to add each player using the + **ADD LEARNER** button.

Alternatively, ask me and I can generate a one-time Firebase import script to bulk-load all 15 players from your spreadsheet!

Quick Reference

Task	How
Add a player	Admin URL → + ADD LEARNER
Edit ratings	Admin URL → click ✏️ on card
Delete a player	Admin URL → click ✕ on card
Change admin password	Edit `ADMIN_SECRET` in `src/firebase.js` → push to GitHub → auto-redeploys
Custom domain	Vercel dashboard → Settings → Domains