


# A Refined Mean Field Approximation for Synchronous Population Processes

Nicolas Gast

Inria, Grenoble, France (joint work with Diego Latella and Mieke Massink, CNR/ISTI  
(Italy))


MAMA Workshop, 2018

# How to characterize emerging behavior starting from a stochastic model of interacting objects?



Evacuation


Thanks to the law of large numbers : Some systems simplify as they grow




Applications :

- Communication protocols (MPTCP, Simgrid)
- Mean field games (Adversarial classification)
- Performance of load balancing / caching algorithms
- Stochastic approximation / learning
- Theoretical biology

We can study large systems. What about moderate sizes?




We can study large systems. What about moderate sizes?



For many systems, asymptotically:

$$Perf(N) \approx Perf(\infty) + \frac{1}{N} V$$

We can study large systems. What about moderate sizes?



For many systems, asymptotically:

$$Perf(N) \approx Perf(\infty) + \frac{1}{N} V$$

Mean field approximation

*Refined* mean field approximation

# Outline

- 1 Mean field approximations of synchronous populations
- 2 The refined mean field
- 3 Does it always work?
- 4 Conclusion and recap

# Outline

- 1 Mean field approximations of synchronous populations
- 2 The refined mean field
- 3 Does it always work?
- 4 Conclusion and recap



## Discrete-time mean field models

Population of  $N$  objects (discrete time, discrete space).

$X_i(t)$  = fraction of object in state  $i$  at time  $t$

# Discrete-time mean field models

Population of  $N$  objects (discrete time, discrete space).

$X_i(t)$  = fraction of object in state  $i$  at time  $t$

There are two cases:

- **Asynchronous case** (BLB08,K81) – One (or a few) objects change state at each time step. (see talk at SIGMETRICS)
  - ▶ Continuous-time mean field approximation
- **Synchronous case** (LB+07) – All object simultaneously change state ([this talk](#)).
  - ▶ Discrete-time mean field approximation

**BLB08** Michel Benaïm, Jean-Yves Le Boudec: A class of mean field interaction models for computer and communication systems. Perform. Eval. 2008

**K81** Thomas G. Kurtz : Approximation of Population Processes. 1981

**LB+07** Jean-Yves Le Boudec, David D. McDonald, Jochen Munding: A Generic Mean Field Convergence Result for Systems

## Our synchronous model is similar to the one of [LB+07]

At each time step : all objects perform an independent transition :

$$K_{ij}(x) = \mathbf{P} [\text{An object in state } i \text{ changes to state } j \mid X(t) = x].$$

The mean field approximation is given by :


$$\mu(t+1) = \mu(t)K(\mu(t)) =: \Phi_1(\mu(t))$$

The mean field approximation is asymptotically exact (LB+07) :

$$X(t) = \mu(t) + o_{N \rightarrow \infty}(1).$$


## Example : a simple infection model (SEIR model)

Evolution of one individual:




## Example : a simple infection model (SEIR model)

Evolution of one individual:




We plot  $\mathbb{E}[X_S(t)]$  as a function of time :




$N = 1000$

## Example : a simple infection model (SEIR model)


Evolution of one individual:



We plot  $\mathbb{E}[X_S(t)]$  as a function of time :




$N = 1000$




$N = 10$

## Example : a simple infection model (SEIR model)


Evolution of one individual:



We plot  $\mathbb{E}[X_S(t)]$  as a function of time :



$N = 1000$



$N = 10$

# Outline

- 1 Mean field approximations of synchronous populations
- 2 The refined mean field**
- 3 Does it always work?
- 4 Conclusion and recap



## First result : transient regime

We assume that  $\Phi_1 : x \mapsto xK(x)$  is twice differentiable and we define

$$A(t) = (D\Phi_1)(\mu(t)) \text{ and } B(t) = (D^2\Phi_1)(\mu(t))$$

$$\Gamma_{jk}(x) = \sum_{i=1}^n x_i K_{ij}(x) (\mathbf{1}_{j=k} - K_{ik}(x))$$

Let  $V(0) = 0$ ,  $W(0) = 0$  and

$$\begin{aligned} V(t+1) &= A(t)V(t) + \frac{1}{2}B(t) \cdot W(t) \\ W(t+1) &= \Gamma(\mu(t)) + A(t)W(t)A(t)^T. \end{aligned} \tag{1}$$

### Theorem (Transient Regime)

For any time  $t$  :  $\mathbb{E}[X(t)] = \mu(t) + \frac{1}{N}V(t) + o(1/N)$ .

## Second result : steady-state

We assume that in addition, the mean field approximation has a unique fixed point that is exponentially stable :  $|\Phi_t(m) - \pi| \leq ae^{-bt}$ .


## Second result : steady-state

We assume that in addition, the mean field approximation has a unique fixed point that is exponentially stable :  $|\Phi_t(m) - \pi| \leq ae^{-bt}$ .

### Theorem

*If the mean field approximation has a unique exponentially stable fixed point, then the previous theorem holds uniformly in time.*

*In particular in steady state:  $\mathbb{E}[X] = \pi + \frac{1}{N} \left( \lim_{t \rightarrow \infty} V(t) \right) + o(1/N)$ .*



Refined m.f.  $\mu(t) + \frac{V_t}{10}$

Mean field  $\mu(t)$


## Second result : steady-state

We assume that in addition, the mean field approximation has a unique fixed point that is exponentially stable :  $|\Phi_t(m) - \pi| \leq ae^{-bt}$ .

### Theorem

*If the mean field approximation has a unique exponentially stable fixed point, then the previous theorem holds uniformly in time.*

*In particular in steady state:  $\mathbb{E}[X] = \pi + \frac{1}{N} \left( \lim_{t \rightarrow \infty} V(t) \right) + o(1/N)$ .*



Refined m.f.  $\mu(t) + \frac{V_t}{20}$

Mean field  $\mu(t)$

## Where does the $O(1/N)$ -term come from?

The mean field approximation is  $\mu(t+1) = \mu(t)K(\mu(t))$  with  $\mu(0) = M(0)$ .

$$\mathbb{E}[X(t+1) \mid X(t) = \mu(t)] = \mu(t)K(\mu(t)) = \mu(t+1)$$

Hence :

$$\mathbb{E}[X(t+1)] = \mathbb{E}[X(t)K(X(t))]$$

## Where does the $O(1/N)$ -term come from?

The mean field approximation is  $\mu(t+1)=\mu(t)K(\mu(t))$  with  $\mu(0)=M(0)$ .

$$\mathbb{E}[X(t+1) \mid X(t) = \mu(t)] = \mu(t)K(\mu(t)) = \mu(t+1)$$

Hence :

$$\mathbb{E}[X(t+1)] = \mathbb{E}[X(t)K(X(t))] \approx \mathbb{E}[X(t)] K(\mathbb{E}[X(t)]) \quad \text{Mean field approx.}$$

Now, in addition :

$$\text{cov}(X(t), X(t) \mid X(t) = \mu(t)) = \frac{1}{N} \Gamma(\mu(t)).$$

The refined mean field arises when the  $1/N$ -term is taken into account.

# Outline

- 1 Mean field approximations of synchronous populations
- 2 The refined mean field
- 3 Does it always work?
- 4 Conclusion and recap



## Positive side

Many models satisfy the assumptions (see paper).

- Refined model is easy to compute (linear algebra)
- It improves the accuracy for not so large values of  $N$ .




## Limit of the approach on an example




- There is a unique fixed point  $\pi$ .
- It is an attractor *iff*  $\alpha \leq 0.75$ .
- It is exponentially stable *iff*  $\alpha < 0.75$ .

## Example (continued) : numerical illustration




$N = 10$

$a = 0.6$  (exponentially stable)




$a = 0.75$  (not exp. stable).

## Example (continued) : numerical illustration




$N = 10$

$a = 0.6$  (exponentially stable)



$a = 0.75$  (not exp. stable).


## Example (continued) : numerical illustration



$N = 10$

$a = 0.6$  (exponentially stable)


**WORKS** uniformly in  $t$



$a = 0.75$  (not exp. stable).

**Does not work** for  $t \gg N$


## Example (continued) : numerical illustration



$N = 30$

$a = 0.6$  (exponentially stable)

**WORKS** uniformly in  $t$



$a = 0.75$  (not exp. stable).

**Does not work** for  $t \gg N$

# Outline

- 1 Mean field approximations of synchronous populations
- 2 The refined mean field
- 3 Does it always work?
- 4 Conclusion and recap

# Recap

- ① The traditional mean field approximation considers

$$X(t) \approx \mu(t),$$

where  $\mu(t) = \lim_{N \rightarrow \infty} X(t)$ .

- ② Our approach : we focus on  $\mathbb{E}[X(t)]$  and we show that there exists  $V(t)$  such that :

$$\mathbb{E}[X(t)] = \underbrace{\mu(t) + \frac{V(t)}{N}}_{\text{Refined approximation}} + o(1/N)$$

It also works for  $\mathbb{E}[h(X(t))]$ .

- ③  $V(t)$  is easy to evaluate and for small  $N$  the refined approximation greatly improves the accuracy compared to the classical mean field approximation.

## To go further :

It also works for continuous time models (e.g.: two-choice), see SIGMETRICS paper.

### Future work:

- Find a relevant model (more general?) of synchronous population.
- Find guidelines where the method is applicable or not (example : Non-exponentially stable systems)

### Main references :

- [A Refined Mean Field Approximation of Synchronous Discrete-Time Population Models](#) by Gast, Latella and Massink. To appear in *Performance Evaluation*.  
Paper is reproducible : [https://github.com/ngast/RefinedMeanField\\_SynchronousPopulation](https://github.com/ngast/RefinedMeanField_SynchronousPopulation)
- [A Refined Mean Field Approximation](#) by Gast and Van Houdt. To appear in SIGMETRICS 2018 <https://hal.inria.fr/hal-01622054/>  
[https://github.com/ngast/rmf\\_tool/](https://github.com/ngast/rmf_tool/)