

NG CORE 100

TECHNICAL SPECIFICATION



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

**Tractor Mounted Core Drilling rig capable to drill 300 m of NQ
High speed top drive rotary head.**

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

Application	Surface Exploration
Capacity	NQ : 300 m HQ : 200 m PQ : 100 m
Drilling Angle	90° - 45° (Optional)
Prime Mover	Rig hydraulic system is powered from tractor engine.
Platform Structure	Heavy C-section welded steel structures fitted with tractor chasses.
Mast Assembly	Strong structural steel twin tubular box type construction, Foldable mast Rotary Head Travel : 3500 mm Rod handling : 3 m Rod pull out : 6 m
Mast Raising Cylinder	PVT LTD Mast is raised and lowered by dual hydraulic cylinder.
Mast Dumping	Mast is provided with a dumping arrangement for angle drilling (only available with added cost).
Feed System	Single hydraulic cylinder with 1:3 ratio Pull Up Force : 6800 kgf Pull Down Force : 2500 kgf Pull Up Speed : 27 m/min Pull Down Speed : 45 m/min

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Rotary Head Assembly (Top Head Drive)

Floating spindle driven by a hydraulic motor omt 200. Drill head has a slide-out arrangement for hoisting.

Torque: 0-803 N-m
Speed : 0-428 rpm

Torque: 0-3074 N-m
Speed : 0-112 rpm

Floating Spindle Stroke

65 mm

Hydraulic System

2 x Fixed displacement pump for Rotation, Feed, Winch & Water pump
1 x Fixed displacement pump for Auxiliary & Hydraulic oil cooler

Maximum System Pressure : 2755 psi (190 bar)

Hydraulic Oil Cooler : 70 gpm

Hydraulic Tank Capacity : 300 L

Control Panel

Centralized control panel is at the rear left end of equipment for convenient view of drill table provided with all necessary gauges, control system.

Foot Clamp

Manually operated Rod clamp has gripping range of PQ, HQ and NQ sizes

Levelling Jacks

4 x Hydraulic levelling jacks are provided for quick setting and levelling of drill rig. Locking check valves for safety with adequate capacity to withstand loads.

Main Hoist

Capacity: 3 ton Line Speed: 35 m/min Wire rope thickness: 14 mm Wire rope length: 30 m

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Water Pump

Hydraulic operated triplex mud pump with necessary fittings, pressure regulator, flow regulator, and suction filter are provided

Maximum Flow : 80 lpm

Maximum Pressure : 750 psi

3" X 3" Heavy Duty Centrifugal Pump.- Hydraulic Operated.
1500-3000 RPM.

Wire line winch

Capacity: 1 ton

Line Speed: 100 m/min

Wire rope thickness: 6 mm

Wire rope length: 400 m

Break out wrench

Hydraulic operated BOW system with double-acting cylinder and pipe wrench.

Additional Fitments

Lights For Night Operations.

PVT LTD

Mounting Option

Trolley / Skid / Tractor

**Combinations will vary according to our Design feasibility's*

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





BOOK NOW



**Scan this QR Code or
Click Here for Testing Video**



+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

