

NGCORE 50

TECHNICAL SPECIFICATION



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

150 meter drilling depth capacity (capable to work in sand, clay, black soil and boulder formation).

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

Application	WaterWell Drilling, Rotary, Dry Piling , Geo-Technical Drilling, Core Drilling
Capacity	150 Meter depth @ Upto 600MM diameter. 50 Meter depth @ NX HX PX Sizes.
Operation	Hydra-Mech, Top Drive.
Mast	26 Feet Strudy Structural main 6"x3" Tubuler Mast welded with MS Polished Bar and 20mm Plates, support Structure 4"x2" Heavy pipes. Hydraulically Operated actuator fitted with 3:1 Ratio Travelling Pulleys 16mm wire Rope.
Chesses	Trolley made with 7x3 C-Chanel Fitted with support chanel - 3x1.5. 4 Nos of Stabilizer Jacks. Trolley with 2 Tyres. Towing Hook.
Rotary Head	Heavy Duty Spur Gear Box CR535 Material Gear Thickness 60mm Fitted with 50mm Polished Kelly Bar Mechanically Operated with Man Make Halical Baver Crown Pinion Drive.
Prime Mover	Tata Engine 1210 Refurbished. with Radiator Assembly, Panel & Battery.
Winch	2 Tonns Hydraulic Winch Capable of Lowering PVC, Cement, MS Pipes & GI Pipes.
Hydraulic Pump	39/18 Litters Reputed Make

+91 91732 03112



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Hy. System

Jacks :-

- Feed : 1 Nos.
- Stabilizers : 4 Nos.
- MRC : 2 Nos.
- Breakout : 1 Nos.

Pump : Dual Circuit with Auto feed, Manual Over Drive
Oil Tank : 200 Ltrs.

Generator

200 AMP With A/C Power (Not Included in this Quote)

Lowering Capacity

8 Tons, 10 Feet Casing Handling.

**Combinations will vary according to our Design feasibility's*





BOOK NOW



+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

