

NGDP 15

TECHNICAL SPECIFICATION



PVT LTD

**Fuel efficient
Low maintenance**

**Easy to operate
Low operating cost**

**Tractor Mounted Dry Piling Rig Capable to Drill 22 feet up to 20" Diameter
Heavy Duty Dry Piling Rig**

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Application	Dry piling
Capacity	22 Feet in dual stroke 12 Feet in single stroke Drilling Diameter : up to 20"
Prime Mover	Tractor Power Take Off
Platform Structure	Heavy duty 7X3 "C" Channel Fitted with Tractor
Mast Assembly	Sturdy Structural 6X3 main channel with 3X(1.5) support channel fitted with pulley and wire rope system powered by hydraulic jack. Hydraulic Stroke : 13 Feet
Mast Raising Cylinder	Mast is raised and lowered by single hydraulic cylinder.
Hydraulic System	Single Circuit. Hy. Jack : 4 LVL - 1 MRC - 1 Feed.
Rotary Head	60mm Spur Gear fitted with mast driven by 50mm kelly and Maan make Crown-Pinion.

**Combinations will vary according to our Design feasibility's*

Click on the icon for link.



Website



Working Video



Instagram

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

