

TECHNICAL SPECIFICATION

NGDP 60



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

**TRACTOR MOUNTED DRY+ WET PILLING MACHINE
CAPABLE OF DRILLING 700mm DIA DRY PILING UPTO 18MTR**

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

APPLICATION	DRY PILLING, WET PILLING, WATERWELL DRILLING
CAPACITY	DRY PILLING: DIA UPTO 700MM UP AND DEPTH UPTO 18 METER WET PILLING: DIA UPTO 1200MM AND DEPTH UPTO 50 METER (WATER PILE) WATERWELL : DIA UPTO 600MM AND DEPTH UPTO 150 METER.
MAST (WITH HYDRAULIC LIFTING & LOWERING SYSTEM)	HEIGHT (27 FEET) STURDY STRUCTURAL MADE WITH MS C CHANNEL 7X3 WITH SUPPORT CHANNEL 4X2, WELDED WITH POLISH BAR AND HEAVY DUTY PLATES STROKE 23 FEET
PLATFORM	NG STD RIG CHESSES FITTED WITH THE TRACTOR 7X3 C CHANNEL WELDED WITH BASE PLATES WITH TRACTOR
HYDRAULICS	Control valve: 2 x 180 ltrs (2sp) walvoil make 1 x 80 ltrs (6sp) walvoil make CIRCUIT: DUAL CYCLE Hydraulic hoses: parker/gets. PTO Over Drive Gear Box FITTED WITH HYDRAULIC PUMPS: 2 NOS 45 GPM VALJAN HYDRAULICS JACKS: 4 NOS STABILIZERS 70MM/100MM 2 NOS MRC 50MM/80MM 1 NOS FEED 80MM/140MM HYDRAULIC OIL TANK : 400 LTR HYDRAULIC OIL : 350ltr
Rotary Head	HEAVY DUTY PISTON MOTOR 1500CC DIRECT DRIVE
GEAR BOXES	Single motor ROTARY HEAD: NG MAKE heavy duty TRAVELLING 1:3 WITH 16MM SINGLE ROW WIRE ROPE PTO: NG MAKE HEAVY DUTY FOR DUAL OR TRIPLE PUMP SETUP. 100MM GEARS

*Combinations will vary according to our Design feasibility's

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



BOOK NOW



Scan this QR Code or Click Here
for Working Video

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

