

TECHNICAL SPECIFICATION

NGDTH 50

Multi-Purpose Rig



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

165 Meter IN DTH UPTO 200MM (Capable to work in All Type of Formation)

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Application	DTH, Rotary, Dry Pile, Odex
Capacity	700MM IN DRY UPTO 18MTR 600MM IN ROTARY UPTO 200 MTR 200MM IN DTH UPTO 165MTR 155MM IN DTH UPTO 200MTR 125MM IN ODEX UPTO 130 MTR (Capable to Work in All type of Formation)
Mast (With hydraulic lifting & lowering system)	STURDY STRUCTURAL MADE WITH MS C CHANNEL 7X3 WITH SUPPORT CHANNEL 4X2 WELDED WITH POLISH BAR AND HEAVY DUTY PLATES ROD HANDLING CAPACITY 20 FEET
PLATFORM:	NG STD RIG CHESSES FITTED WITH THE TRACTOR 7X3 C CHANNEL
HYDRAULICS	Control valve: 2x 180 ltrs walvoil make , 1 x 80 ltrs walvoil make Dual CIRCUIT : Hydraulic hoses: parker/gets Triple PUMP :- 38 GPM Gear pump, 38 GPM+ 17 GPM (VALJAN MAKE) STABILIZERS: 4 NOS COVERED IN MS TELESCOPIC STRUCTURE OTHER: MRCX2, FEEDX1, BREAK OUTX1 HYDRAULIC MOTOR: OMV400/ OMT500 FOR ROTARY HEAD DUAL OMT315 ROTARY HEAD OPTIONAL OMS100 FOR CENTRIFUGAL PUMP
GEAR BOXES	Dual motor ROTARY HEAD: NG MAKE 315 motor COMPATABILITY 100MM GEARS OMT 315 dual motors PTO: NG MAKE HEAVY DUTY FOR DUAL OR TRIPLE PUMP SETUP. 100MM GEARS

*Combinations will vary according to our Design feasibility's

+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





Scan the QR Code. or click Here
for Working Video

BOOK NOW



+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

