

NGDTH 30

TECHNICAL SPECIFICATION



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

165MM IN DTH UPTO 100 METER CAPABLE TO WORK IN ANY TYPES OF FORMATION

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 92271 66343

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

Application	DTH DRY PILLING, DTH WATERWELL
Capacity	165mm in DTH upto 100 Meter. (with suitable air compressor) 200mm in DTH upto 60 Meter. (with suitable air compressor) 300mm in DTH upto 20 Meter. (with suitable air compressor)
Mast (With hydraulic lifting & lowering system)	Sturdy Structural Made With Ms C Channel 6x3 With Support Channel 4x2 Welded With Polish Bar And Heavy Duty Plates. Rod Handling Capacity : 15 Feet.
Machine Platform	NGE STD Rig Chasses Fitted With The Tractor 7x3 C Channel
Hydraulics	Mono Circuit :- Dual Pump 50 Gpm+ 17 Gpm (Valjan Make) Stabilizers : 4 Nos Covered In Ms Telescopic Structure Other : MRC CY. X 2, FEED CY. X 1, BREAK OUT CY. X 1 Hydraulic Motor : OMT500 or OMV400 For Rotary Head.
Gear Boxex	Rotary Head: NGE Make 500 Motor Compatibility 100mm Gears. PTO: NGE Make Heavy Duty For Dual or Triple Pump Setup. 100mm Gears.
Drilling System	Fully Hydraulic

**Combinations will vary according to our Design feasibility's*

+91 92271 66343



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





Scan QR Code
or Click here for video



+91 91732 03112



info@ngedrill.com



Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

