

NGDR 3000

TECHNICAL SPECIFICATION



- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

1500 Meter Drilling depth capacity (capable to work in sand, clay, black soil , Hard Rock, Boulder or any Types of formation).

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91063 60907

info@ngedrill.com

C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.

Application	Water Well Drilling, Direct Rotary, DTH
Capacity	1500 meter @ 12 ¼" Dia. (320mm) 1200 meter @ 17 ½" Dia. (480mm) 800 meter @ 20" Dia. (500mm) 600 meter @ 24" Dia. (600mm) 300 meter @ 28" Dia. (700mm) capable to work in all types of formation).
Mast (With hydraulic lifting & lowering system)	17 meter length, 4" x 4" ID, Schedule 40 pipe. (Round / Square pipes). 8 mm+ wall thickness. With heavy duty Support pipes and cross supports. Lifting Pulley 11 nos. (Cross-over pulley placement for saving time in changing the drill rods and ease of installing the casings). Gross load capacity: 130,000 kg. Hook load capacity on main travelling 8 sheaves+ fast line: 100,000 kg. Hook load capacity :secondary travelling 4 sheaves+fast line: 78,000 kg.
Machine Platform	12 meter length & width 2.4 meter Trailer Comes With 3.5" king pin, 10 Tiers (leaf Suspension) With air-brakes MS chuckle plate flooring & Main 'C' channel 600mm x 150mm Stability and vibrations control becomes easy with the heaviest platform provided in water well drilling industry.
MUD PUMP	7" x 10" RECIPROCATING Dual acting duplex mudpump fitted with saparate 6 speed gear box and 6 sheave v belt pulley drive.
Water Pump	Triplex Plunger Pump - 200 LPM Dth water injection Foam pump for Sticky clay formations 4x4 Centrifugal Pump for mud mixing.

+91 91063 60907



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



Winch(Draw works)

2 NOS of 28" Diameter of draw works driven by crown pinion heavy-duty shaft drive. Set of 20 Nos of friction facings having 20" of clutch diameter, 7 INCH BELT BREAKS ON EACH DRUMS
(AIR VANTILATED BREAKS)

Prime Mover

Ashok Leyland Deck engine 320 bhp. fitted with ZF 9 speed pneumatic gear box. (brand new 2026)

Power take off with 1 input 7 output with eccentric adjustable heavy-duty triplex chain. 3 of 7 outputs are joint with gear boxes for the optimum performance and speed.
These gearbox are been made with the heavy-duty 1.25" triplex chain and sprockets. Eccentrics are for the adjustment of the chains for long duration of the chains and sprockets.

Rotary Table

Hexagonal floating spindle for 7 ¼ ".
Hexagonal key spindle for rotating the Kelley,
5 ½" of Kelley spindle made by forged EN9 material heat treated,
Easy installation of the drill rods of 3 1/2 " API standard connections 3 1/2" IF (M/F) connections OD 128mm.

Retractable and removable for lowering of the casing pipes.
Hydraulic movement facility, dual jack.

Steel Wire Rope

For main Drum: 24 mm thickness steel core. (6X36)
For Rod line Pulling drum: 24 mm thickness steel core. (6X36)

Drilling Platform

N.G standard made with MS checkered plate of 6 mm thickness,
Plate form for operator with lights and driller seat.
3 sided expandable for easy handling of the drilling operations.
Back platform easy to assemble for welding the casing pipes directly on the machine platform.

Traveling

For Drilling Lifting: 4 nos. Pulley
: 8 sheave + 1 fast line sheave.
For Auxiliary Pulling : 3 nos. pulley
: 6 sheave + 1 fast line sheave.

Kelly	HEXAGONAL Kelly: 5.5" x 14 Meter length.
Generator	400 AMP. Suitable for 4mm of welding electrodes. Single phase power output for Grinding and lighter applications.
Water Swivel	NG make heavy duty joint with travelling and Kelley. 100,000Kgs. 500 PSI
Machine Leveling System	Hydraulic Jack (04 nos.), Length 60" comes with the brackets adjustable stops at every inches.
Paint job	Industrial Epoxy paint, color choice on customer.
Lights	On the plate form, On the mast, At the drilling hole, under the platform.

One Stop Drilling Solution

NGE Drillsol
PVT. LTD.

**Combinations will vary according to our Design feasibility's*

+91 91063 60907



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.



ACCESSORIES PROVIDED WITH MACHINE FREE OF COST		
1	SPANNERS FOR MUD PUMP	3 NOS
2	SPANNERS FOR DRILL RODS	4 NOS
3	DRILLING BED	1 SET
4	DRILLING BED SLIPS	2 SET
5	HOISTING PLUG FOR THE DRILL RODS	1 NOS
6	DRILLER SEAT	1 NOS
7	RIG SPANNER SET BOX	1 SET
8	RIG SPANNER SET FIX	1 SET
9	RIG SPANNER SET RING	1 SET
10	DRAG BITS 12", 14", 16", 18" EACH	4 NOS
11	KELLEY PIN (THREAD PROTRACTOR)	2 NOS
12	RUBBER GLANDS FOR WATER SWIVEL	100 NOS
13	RUBBER GLANDS FOR MUD PUMP	1 SET
14	MUD HOSE R2	1 SET
15	MUD HOSE PU 4"	1 SET
16	MUD HOSE PU 3"	1 SET
17	MUD HOSE PU 2"	1 SET
18	FOOT VALVE	1 NOS
19	BREAK OUT CYLINDER	1 SET

+91 91063 60907



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





+91 91063 60907



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
 Bypass Highway, Mehsana - 384002.

