

NGDTH 600 R

TECHNICAL SPECIFICATION



One Stop Drilling Solution

NGE Drillsol

- ☐ Fuel efficient
- ☐ Low maintenance

- ☐ Easy to operate
- ☐ Low operating cost

500 Meter Drilling Depth Capacity (capable to work in all types of formation).

Note: The images provided here are for reference only and do not depict the exact specification outlined in this document.

+91 91732 03112



info@ngedrill.com



C/O NG ENGINEERING, Sr. No. 553, Opp. Guru 308,
Bypass Highway, Mehsana - 384002.





Application	Rotary Water Well Drilling / DTH / Cathodic Protection / Monitoring Holes Irrigation.
Capacity	700 Meter @ 6.5" Dia. 500 Meter @ {17 (1/2) }" rotary Capable to work in Boulder, Mix, Hard Rock & Sandy Formation.
Mast Assembly	11 Meters Sturdy Structural Tubular Mast Mains : 200mm x 100mm x 8mm Wall Thickness. Welded with 125mm x 70mm x 6mm Tubular Supports. Full Polished Bar for Easy Sliding. Lifting Sheave : 4 Sheave Pull Up Capacity : 50,000 Kgs. Pull Down Capacity : 15,000 Kgs. Hydraulic Dumping
Machine Platform	Length : 8 Meters main "C" Channel 10"X4" & support Channel 5"X 3". MS checkered plate of 6 mm thickness flooring NG std machine platefor with expandable side walks
Rotary Head	Cast iron Body Reduction gear box with oil bath top entry air swivel, top entry mud swivel and botom entry mud swivel spindle 110mm with 6 5/8" connection SMS - OMV 400 Dual Motors. Torque: 15,000 Nm.
Prime Mover	Deck Engine 320hp ashok layland engine Fitted with 4 Pump SMS Power Take Off Device.
Steel Wire Rope	20 mm 6X36 Steel Core
Drilling Bed	NGE Standard (DTHR) (3 Sheaves.)
Mounting	Sino 6X6 HOWO (LHD)

Hydraulic System

Rotary Head with OMT-400 motors.
Water Injection Pump : 100 LPM Capacity.
Hydraulic Circuit with efficient Hydraulic Cooler.
2X Variable pumps A10 variants bosch/rexroth for feed and rotation
1X Fix A2FM variant for mud pump
2x Gear/Van pumps for smaller operations
140mm Bore size Telescopic Box Type Stabilizers : 4 Nos.
180mm Bore Size Feed Cylinder : 1 Nos.
140mm Mast Raise Cylinder : 1 Nos
500 Ltrs. Capacity Hydraulic Tank : 1 Nos.
All Rubber Hoses are Parker / Gates Make.

Mud Pump

7X10 Reciprocating Mud Pump
Hydraulic Motor Driven heavy duty piston motor 1200/1500cc

Air Compressor

Atlas COPCO 1350 CFM (425 PSI) 30 BAR

Airline Lubricator

Tank Capacity: 15 Ltrs
Pressure: 40 Bar.

Whinch Capacity

2 Tons rotating type

Generator

400 AMP. Suitable for 4mm of welding electrodes.
Single phase power output for Grinding and lighter applications.

Machine Leveling System

Hydraulic Jack (04 nos.),
Length 40" with retaining valves.

Paint job

polyurethane paint, color choice on customer.

Lights

On the plate form, On the mast, At the drilling hole, under the platform.