

Rational OpenCog Controlled Agent


Nil Geisweiller, Hedra Yusuf


Artificial General Intelligence 2023 (AGI-23)



SingularityNET









Cognitive Schematic


$$\bullet \text{ Context} \wedge \text{Action} \rightsquigarrow^T \text{Goal}$$

$$C_1 \mathbin{\small\wedge}^{T_1} \dots \mathbin{\small\wedge}^{T_{i-1}} C_i \mathbin{\small\wedge} A_i \mathbin{\small\wedge}^{T_i} \dots \mathbin{\small\wedge}^{T_j} A_j \rightsquigarrow^{T_i + \dots + T_{j+1}} G$$







$$[C_1 \wedge^{T_1} \dots \wedge^{T_{i-1}} C_i](t) = \text{True} \mid \text{False}$$




$$[C_1 \wedge^{T_1} \dots \wedge^{T_{i-1}} C_i](t) = \text{True} \mid \text{False} \\ \mapsto \text{Dist}(\text{Bool})$$



$$\begin{aligned}
 [C_1 \neg^{T_1} \dots \neg^{T_{i-1}} C_i](t) &= \text{True} \mid \text{False} \\
 &\mapsto \text{Dist}(\text{Bool}) \\
 &\mapsto \text{Dist}(\text{Dist}(\text{Bool}))
 \end{aligned}$$




$$C \wedge A_1 \nearrow^{T_1} A_2 \nearrow^{T_2} A_3 \rightsquigarrow^{T_1+T_2+T_3} G$$




$$C \wedge A_1 \wedge^{T_1} A_2 \wedge^{T_2} A_3 \rightsquigarrow^{T_1+T_2+T_3} G$$

$$C \wedge A_1 \wedge^{T_1} A_2 \wedge^{T_2} A_3 \rightsquigarrow^{T_2+T_3} G$$



Example: Collect Diamonds



Actions

- get(key)
- go(house)
- collect(diamond)

Percepts

- outside(house)
- inside(house)
- hold(key)
- next(door)
- reward(1)
- reward(0)

Example: Collect Diamonds



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$

$\text{hold}(\text{key}) \wedge \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^2 \text{reward}(1)$



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$

$\text{hold}(\text{key}) \wedge \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^2 \text{reward}(1)$



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$

$\text{hold}(\text{key}) \wedge \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^2 \text{reward}(1)$

$\text{inside}(\text{house}) \wedge \text{collect}(\text{diamond}) \rightsquigarrow^1 \text{reward}(1)$



Example: Collect Diamonds

$\text{outside}(\text{house}) \wedge \text{get}(\text{key}) \nearrow^1 \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^3 \text{reward}(1)$

$\text{hold}(\text{key}) \wedge \text{go}(\text{house}) \nearrow^1 \text{collect}(\text{diamond}) \rightsquigarrow^2 \text{reward}(1)$

$\text{inside}(\text{house}) \wedge \text{collect}(\text{diamond}) \rightsquigarrow^1 \text{reward}(1)$



The Paradox of Choice

Many applicable schemata

$$\begin{array}{ccc}
 C_1 \wedge A_1 \rightsquigarrow^{T_1} G & \stackrel{m}{=} & TV_1 \\
 \vdots & & \\
 C_{9999} \wedge A_{9999} \rightsquigarrow^{T_{9999}} G & \stackrel{m}{=} & TV_{9999}
 \end{array}$$

The Paradox of Choice

Many applicable schemata

$$\begin{array}{ccc}
 C_1 \wedge A_1 \rightsquigarrow^{T_1} G & \stackrel{m}{=} & TV_1 \\
 \vdots & & \\
 C_{9999} \wedge A_{9999} \rightsquigarrow^{T_{9999}} G & \stackrel{m}{=} & TV_{9999}
 \end{array}$$

Some contradicting each other

$$\begin{array}{ccc}
 C_1 \wedge A \rightsquigarrow^{T_1} G & \stackrel{m}{=} & \langle 0.9 \ 0.5 \rangle \\
 C_2 \wedge A \rightsquigarrow^{T_1} G & \stackrel{m}{=} & \langle 0.1 \ 0.5 \rangle
 \end{array}$$

The Paradox of Choice

Many applicable schemata

$$\begin{array}{ccc}
 C_1 \wedge A_1 \rightsquigarrow^{T_1} G & \stackrel{m}{=} & TV_1 \\
 \vdots & & \\
 C_{9999} \wedge A_{9999} \rightsquigarrow^{T_{9999}} G & \stackrel{m}{=} & TV_{9999}
 \end{array}$$

Some contradicting each other

$$\begin{array}{ccc}
 C_1 \wedge A \rightsquigarrow^{T_1} G & \stackrel{m}{=} & \langle 0.9 \ 0.5 \rangle \\
 C_2 \wedge A \rightsquigarrow^{T_1} G & \stackrel{m}{=} & \langle 0.1 \ 0.5 \rangle
 \end{array}$$

With different risk/reward profiles

$$\begin{array}{ccc}
 C_1 \wedge A_1 \rightsquigarrow^{T_1} G & \stackrel{m}{=} & \langle 0.9 \ 0.1 \rangle \\
 C_2 \wedge A_2 \rightsquigarrow^{T_2} G & \stackrel{m}{=} & \langle 0.6 \ 0.9 \rangle
 \end{array}$$

Balancing exploitation and exploration

Solomonoff-ish Induction
+
Thompson Sampling

Balancing exploitation and exploration

Solomonoff-ish Induction ↘

+

Thompson Sampling ↙

Second Order Mixture


Balancing exploitation and exploration

Solomonoff-ish Induction ↘


+

Thompson Sampling ↙

Second Order Mixture



Learning Schemata



Pattern Mining
+
Temporal Reasoning

Pattern Mining Schemata

<i>Time</i>	<i>Event</i>
⋮	⋮
10	<i>reward(0)</i>
10	<i>outside(house)</i>
10	<i>hold(key)</i>
10	<i>go(house)</i>
11	<i>inside(house)</i>
11	<i>go(diamond)</i>
11	<i>reward(0)</i>
12	<i>reward(1)</i>
⋮	⋮

$$hold(key) \wedge go(house) \rightsquigarrow^1 inside(house) \stackrel{m}{=} \langle 0.833, 0.007 \rangle$$

Reasoning Schemata


$$\begin{array}{c}
 \frac{\text{outside}(\text{house}) \wedge \text{go}(\text{key}) \rightsquigarrow^1 \text{outside}(\text{house}) \quad \text{outside}(\text{house}) \wedge \text{go}(\text{key}) \rightsquigarrow^1 \text{hold}(\text{key})}{\text{outside}(\text{house}) \wedge \text{go}(\text{key}) \rightsquigarrow^1 \text{outside}(\text{house}) \wedge \text{hold}(\text{key})} \text{ (CC)} \\
 \frac{\text{outside}(\text{house}) \wedge \text{go}(\text{key}) \rightsquigarrow^1 \text{outside}(\text{house}) \wedge \text{hold}(\text{key}) \quad \text{outside}(\text{house}) \wedge \text{hold}(\text{key}) \wedge \text{go}(\text{house}) \rightsquigarrow^1 \text{inside}(\text{house})}{\text{outside}(\text{house}) \wedge \text{go}(\text{key}) \wedge^1 \text{go}(\text{house}) \rightsquigarrow^2 \text{inside}(\text{house})} \text{ (PD)}
 \end{array}$$

Reasoning Schemata

$$\begin{array}{c}
 \frac{\text{outside(house)} \wedge \text{go(key)} \rightsquigarrow^1 \text{outside(house)} \quad \text{outside(house)} \wedge \text{go(key)} \rightsquigarrow^1 \text{hold(key)}}{\text{outside(house)} \wedge \text{go(key)} \rightsquigarrow^1 \text{outside(house)} \wedge \text{hold(key)}} \text{ (CC)} \\
 \frac{\text{outside(house)} \wedge \text{go(key)} \rightsquigarrow^1 \text{outside(house)} \wedge \text{hold(key)} \quad \text{outside(house)} \wedge \text{hold(key)} \wedge \text{go(house)} \rightsquigarrow^1 \text{inside(house)}}{\text{outside(house)} \wedge \text{go(key)} \wedge^1 \text{go(house)} \rightsquigarrow^2 \text{inside(house)}} \text{ (PD)}
 \end{array}$$

⋮

$$\text{outside(house)} \wedge \text{go(key)} \wedge^1 \text{go(house)} \wedge^1 \text{go(diamond)} \rightsquigarrow^3 \text{reward}(1) \models \langle 0.833, 0.005 \rangle$$



Timestamped Recorded Events:

Time	Event	Evaluation
⋮	⋮	⋮
10	<i>reward(0)</i>	<i>reward(0)(10) = True</i>
10	<i>outside(house)</i>	<i>outside(house)(10) = True</i>
10	<i>hold(key)</i>	<i>hold(key)(10) = True</i>
10	<i>go(house)</i>	<i>go(house)(10) = True</i>
11	<i>inside(house)</i>	<i>inside(house)(11) = True</i>
11	<i>go(diamond)</i>	<i>go(diamond)(11) = True</i>
11	<i>reward(0)</i>	<i>reward(0)(11) = True</i>
12	<i>reward(1)</i>	<i>reward(1)(12) = True</i>
⋮	⋮	⋮

Future Work

- Attention Allocation
- Concept creation and schematization
- Plan in the inner world